

## MATERIAL SAFETY DATA SHEET

EW CANDEEZ ASSORTED COLORS

Printed: 02/27/09

----- HMIS CODES -----  
 Hazard Rating: Health 3  
 Least --> Greatest Flammability 3  
 0 --> 4 Reactivity 1  
 Personal Protection J

Manufacturer: THE EASTWOOD COMPANY  
 263 SHOEMAKER ROAD  
 POTTSTOWN, PA 19464  
 Phone: 800-345-1178

EMERGENCY TELEPHONE: 800-424-9300

## SECTION I: PRODUCT IDENTIFICATION

Product Code: 51540ZPA, 51541ZPA, 51542ZPA, 51543ZPA, 51544ZPA, 51545ZPA,  
 51546ZPA, 51547ZPA, 51548ZPA, 51549ZPA, 51678ZPA  
 Product Name: EW CANDEEZ ASSORTED COLORS  
 Product(s): POLYURETHANE  
 Product Class: ENAMEL  
 CAS Number: N/A

## SECTION IIA: HAZARDOUS INGREDIENTS

(To Nearest 05%)

INGREDIENT	CAS Number	51549ZPA 51678ZPA		51540ZPA	51541ZPA	51542ZPA	LEL % (V)	Vapor Pressure
		% by Wt.	% by Vol.	% by Weight	% by Volume			
1. ACRYLIC	N/A	59.50	54.45	59.50	54.45	54.45	1.0	7.00
2. AROMATIC HYDROCARBON	64742-94-5	1.00	1.05	1.00	1.05	1.05	1.0	.50
3. ACETONE	67-64-1	6.45	7.80	6.45	7.80	7.80	1.0	186.00
4. DIACETONE ALCOHOL	123-42-2	8.35	8.30	8.35	8.30	8.30	1.8	1.00
5. METHYL AMYL KETONE	110-43-0	17.70	20.75	17.70	20.75	20.75	1.0	2.14
6. HIGH FLASH NAPHTHA	64742-95-6	6.65	7.25	6.65	7.25	7.25	.5	2.70
7. ALUMINUM PASTE	N/A	2.00	1.50					1.00

NA = Not Applicable; NE = Not Established

## SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

Ingr. #	----OSHA PEL's-----			-----ACGIH TLV's-----		
	OSHA ppm	OSHA mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
1.	100.000	NA	100.000	NA	NA	NA
2.	10.000	NA	10.000	NA	15.000	NA
3.	100.000	NA	100.000	NA	NA	NA
4.	50.000	NA	50.000	NA	75.000	NA
5.	100.000	NA	100.000	NA	100.000	NA
OSHA: Na						
6.	100.000	305.000	100.000	305.000	150.000	450.000
7.	100.000	10.000	100.000	100.000		

NA = Not Applicable; NE = Not Established

## SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 275.00 - 288.00 Pounds per Gallon: 7.97  
 Vapor Density: HEAVIER THAN AIR Evaporation Rate: SLOWER THAN ETHER  
 Solubility in Water: NIL

## MATERIAL SAFETY DATA SHEET

EW CANDEEZ ASSORTED COLORS

Printed: 02/27/09

Volatiles (%)	by Weight		by Volume
	Total	64.04	71.08
Exempt VOC	6.44	7.78	
Non-exempt	57.60	63.30	

VOC wt/gal: 4.98 lbs non-exempt solvent per adjusted gallon

Appearance: LIQUID, ASSORTED COLORS

## SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:

OSHA: FLAMMABLE DOT: FLAMMABLE

Flash Point: 77.00 (Method: Scc)

UEL: NA

Extinguishing Media: CO2/FOAM

Unusual Fire and Explosion Hazards

ISOLATE FROM ALL SOURCES OF HEAT, SPARKS, OPEN FLAMES AND STATIC ELECTRICITY  
VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL AND IGNITE.

Special Firefighting Procedures

FIGHT AS VOLATILE LIQUID FIRE. FIRE FIGHTERS SHOULD WEAR SELF CONTAINED  
BREATHING APPARATUS. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.  
IRRITATING TOXIC GASES PRESENT IN COMBUSTION PRODUCTS

## SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

ACUTE INHALATION: IRRITATION OF THE NOSE, THROAT AND EYES, DIZZINESS, WEAKNESS,  
FATIGUE, NAUSEA, HEADACHE, POSSIBLY NARCOSIS AND ASPHYXIATION. MAY BE  
ACCOMPANIED BY COUGHING, CHOKING OR LABORED BREATHING. ASTHMA-LIKE BREATHING  
MAY BE DELAYED REACTION. VAPOR, SPRAY MIST OR LIQUID CAUSES SKIN AND EYE  
IRRITATION. PERSONS WITH PREEXISTING, NONSPECIFIC BRONCHIAL HYPERREACTIVITY  
CAN RESPOND TO CONCENTRATIONS BELOW THE TLV WITH SIMILAR SYMPTOMS AS WELL  
AS ASTHMA ATTACK. EXPOSURE WELL ABOVE TLV MAY LEAD TO BRONCHITIS,  
BRONCHIAL SPASM AND PULMONARY EDEMA [FLUID ON LUNGS] THESE EFFECTS ARE  
USUALLY REVERSABLE. CHEMICAL OR HYPERSENSITIVE PNEUMONITIS, WITH FLU  
LIKE SYMPTOMS [FEVER, CHILLS] HAS ALSO BEEN REPORTED. THESE SYMPTOMS CAN BE  
DELAYED UP TO SEVERAL HOURS AFTER EXPOSURE.CHRONIC INHALATION: AS A RESULT OF PREVIOUS REPEATED OVEREXPOSURES OR  
A SINGLE LARGE DOSE, CERTAIN INDIVIDUALS DEVELOP ISOCYANATE SENSITIZATION  
(CHEMICAL ASTHMA) WHICH WILL CAUSE THEM TO REACT TO A LATER EXPOSURE TO  
ISOCYANATES AT LEVELS WELL BELOW TLV. THESE SYMPTOMS WHICH CAN INCLUDE CHEST  
TIGHTNESS, WHEEZING, COUGH, SHORTNESS OF BREATH OR ASTHMA ATTACK, COULD BE  
IMMEDIATE OR DELAYED UP TO SEVERAL HOURS. OVEREXPOSURE TO ISOCYANATES HAS ALSO  
BEEN REPORTED TO CAUSE LUNG DAMAGE WHICH MAY BE PERMANENT.ACUTE SKIN CONTACT: ISOCYANATES REACT WITH SKIN PROTEIN AND MOISTURE  
AND CAN CAUSE IRRITATION WHICH MAY INCLUDE THE FOLLOWING SYMPTOMS:  
REDDENING, SWELLING, RASH, SCALING OR BLISTERING. CURED MATERIAL IS  
DIFFICULT TO REMOVE.

CHRONIC SKIN CONTACT: PROLONGED CONTACT CAN CAUSE REDDENING, SWELLING,

## MATERIAL SAFETY DATA SHEET

EW CANDEEZ ASSORTED COLORS

Printed: 02/27/09

RASH, SCALING, BLISTERING, AND IN SOME CASES, SKIN SENSITIZATION. INDIVIDUALS WHO HAVE SKIN SENSITIZATION CAN DEVELOP THESE SYMPTOMS FROM CONTACT WITH LIQUID OR VAPORS.

ACUTE EYE CONTACT: LIQUID, AEROSOLS OR VAPORS ARE IRRITATING AND CAN CAUSE TEARING, REDDENING AND SWELLING. IF LEFT UNTREATED, CORNEAL DAMAGE CAN OCCUR AND INJURY IS SLOW TO HEAL. HOWEVER, DAMAGE IS USUALLY REVERSIBLE.

ACUTE INGESTION: CAN RESULT IN IRRITATION AND CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

BRONCHIAL SPASM AND PULMONARY EDEMA[FLUID IN LUNGS] THESE EFFECTS ARE USUALLY REVERSABLE. THESE SYMPTOMS CAN BE DELAYED UP TO SEVERAL HOURS AFTER EXPOSURE.

DISCOMFORT BY DEFATTING ACTION.

CHRONIC INHALATION: ISOCYANATES CAN CAUSE LUNG SENSITIZATION. ALLERGIC RESPIRATORY REACTION MAY OCCUR IN SENSITIZED INDIVIDUALS WHEN EXPOSURE TO TDI IS BELOW THE TLV. CAN CAUSE LUNG INJURY. PROLONGED OR REPEATED CONTACT WITH SKIN CAN CAUSE DERMATITIS AND POSSIBLY SKIN SENSITIZATION

ACUTE INHALATION: THIS SOLVENT IS A CENTRAL NERVOUS SYSTEM DEPRESSANT. INHALATION CAN CAUSE IRRITATION OF THE RESPIRATORY SYSTEM, DIZZINESS, NAUSEA, LIGHTHEADEDNESS, HEADACHE, LOSS OF COORDINATION AND EQUILIBRIUM, UNCONSCIOUSNESS, POSSIBLE CENTRAL NERVOUS SYSTEM DAMAGE AND EVEN DEATH.

EYE/SKIN: LIQUID IN THE EYE CAN RESULT IN DISCOMFORT, PAIN AND IRRITATION. REPEATED CONTACT WITH SKIN CAN CAUSE IRRITATION AND DERMATITIS.

CHRONIC: THIS SOLVENT HAS BEEN STUDIED FOR CANCER POTENTIAL. THERE IS NO EVIDENCE THAT IT CAUSES AN INCREASED CANCER INCIDENCE.

INGESTION: SWALLOWING MAY RESULT IN IRRITATION OF THE MOUTH AND GI TRACT. VOMITING AND SUBSEQUENT ASPIRATION INTO LUNGS MAY LEAD TO CHEMICAL PNEUMONIA AND PULMONARY EDEMA.

REPRODUCTIVE: NO ADVERSE FINDINGS RELATIVE TO REPRODUCTIVE TOXICITY WERE OBSERVED FOLLOWING EXPOSURES BELOW 3000 PPM IN RATS OR RABBITS

Medical Conditions Prone to Aggravation by Exposure  
ASTHMA, HEART CONDITIONS, PULMONARY CONDITIONS SKIN SENSITIVITY

## MATERIAL SAFETY DATA SHEET

EW CANDEEZ ASSORTED COLORS

Printed: 02/27/09

Primary Routes of Entry into the Body, and Effects  
SKIN, EYES, MOUTH, LUNGS

## EMERGENCY FIRST-AID PROCEDURES

REMOVE PATIENT TO FRESH AIR. REMOVE SATURATED CLOTHING AND WASH SKIN THOROUGHLY. FLUSH EYES WITH CLEAN WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. WASH CLOTHING BEFORE REUSE.

FIRST AID FOR EYES: FLUSH WITH COPIOUS AMOUNT OF WATER, PREFERABLY LUKEWARM WATER FOR AT LEAST 15 MINUTES, HOLDING EYELIDS OPEN ALL THE TIME. REFER INDIVIDUAL TO PHYSICIAN OR OPHTHALMOLOGIST FOR IMMEDIATE FOLLOW-UP.

FIRST AIR FOR SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED SKIN THOROUGHLY WITH SOAP AND WATER. WASH CONTAMINATED CLOTHING THOROUGHLY BEFORE REUSE. FOR SEVERE EXPOSURES, GET UNDER SAFETY SHOWER AFTER REMOVING CLOTHING, THEN GET MEDICAL ATTENTION. FOR LESSER EXPOSURES, SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS AFTER THE AREA IS WASHED.

FIRST AIR FOR INHALATION: MOVE TO AN AREA FREE FROM RISK OF FURTHER EXPOSURE. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. OBTAIN MEDICAL ATTENTION. ASTHMATIC-TYPE SYMPTOMS MAY DEVELOP AND MAY BE IMMEDIATE OR DELAYED UP TO SEVERAL HOURS. CONSULT PHYSICIAN SHOULD THIS OCCUR.

FIRST AIR FOR INGESTION: DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CONSULT PHYSICIAN.

NOTE TO PHYSICIAN: EYES: STAIN FOR EVIDENCE OF CORNEAL INJURY.

IF CORNEA IS BURNED, INSTILL ANTIBIOTIC STEROID PREPARATION FREQUENTLY.

WORKPLACE VAPORS HAVE PRODUCED REVERSIBLE CORNEAL EPITHELIAL EDEMA

IMPAIRING VISION. SKIN: THIS COMPOUND IS A KNOWN SKIN SENSITIZER. TREAT

SYMPTOMATICALLY AS FOR CONTACT DERMATITIS OR THERMAL BURNS. IF BURNED,

TREAT AS THERMAL BURN. INGESTION: TREAT SYMPTOMATICALLY. THERE IS NO

SPECIFIC ANTIDOTE. INDUCING VOMITING IS CONTRAINDICATED BECAUSE OF THE

IRRITATING NATURE OF THIS COMPOUND. RESPIRATORY: THIS COMPOUND IS A

KNOWN PULMONARY SENSITIZER. TREATMENT IS ESSENTIALLY SYMPTOMATIC. AN

INDIVIDUAL HAVING A SKIN OR PULMONARY SENSITIZATION REACTION TO THIS

MATERIAL SHOULD BE REMOVED FROM EXPOSURE TO ANY ISOCYANATE.

## SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization MAY OCCUR.

Hazardous Decomposition Products

CARBON MONOXIDE, CARBON DIOXIDE, AND POSSIBLY OXIDES OF NITROGEN.

Conditions to Avoid

SPARKS, OPEN FLAMES HEAT

Incompatibilities (Materials to Avoid)

AVOID CONTACT WITH STRONG OXIDIZING AGENTS WATER BASES ALCOHOL AND AMINES

## MATERIAL SAFETY DATA SHEET

EW CANDEEZ ASSORTED COLORS

Printed: 02/27/09

## SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled  
REMOVE SOURCES OF IGNITION. PROVIDE VENTILATION AND OR RESPIRATORY PROTECTION.  
LARGE SPILLS MAY BE PICKED UP WITH NONSPARKING TOOLS, SMALL SPILLS  
WITH ABSORBENT MATERIAL.

Waste Disposal Methods  
IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

## SECTION VIII: SAFE HANDLING AND USE INFORMATION

## Respiratory Protection

CONCENTRATIONS GREATER THAN THE TLV CAN OCCUR WHEN MDI IS SPRAYED, HEATED OR USED IN A POORLY VENTILATED AREA. IN SUCH CASES, OR WHENEVER CONCENTRATIONS OF MDI EXCEED THE TLV, RESPIRATORY PROTECTION MUST BE WORN. A POSITIVE PRESSURE, SUPPLIED-AIR RESPIRATOR OR A SELF-CONTAINED BREATHING APPARATUS IS RECOMMENDED. IN SITUATIONS WHERE MDI IS NOT SPRAYED, HEATED OR USED IN A POORLY VENTILATED AREA, AND A SUPPLIED-AIR OR SELF-CONTAINED BREATHING APPARATUS IS UNAVAILABLE OR ITS USE IMPRACTICAL, AT LEAST AN AIR-PURIFYING RESPIRATOR EQUIPPED WITH AN ORGANIC VAPOR CARTRIDGE AND PARTICULATE PRE-FILTERS MUST BE WORN. HOWEVER THIS SHOULD BE PERMITTED ONLY FOR SHORT PERIODS OF TIME (LESS THAN ONE HOUR) AT RELATIVELY LOW CONCENTRATIONS (AT OR NEAR THE TLV). HOWEVER, DUE TO THE POOR WARNING PROPERTIES OF MDI, PROPER FIT AND TIMELY REPLACEMENT OF FILTER ELEMENTS MUST BE ENSURED. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134). USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR, TC19C NIOSH

## Ventilation

EXPLOSION PROOF USE ONLY WITH ADEQUATE VENTILATION  
KEEP UNPROTECTED PERSONEL AWAY FROM SPRAY AREA

## Protective Gloves

YES

## Eye Protection

YES

## Other Protective Equipment

WASH STATION AND SAFETY SHOWERS SHOULD BE AVAILABLE

MATERIAL SAFETY DATA SHEET

EW CANDEEZ ASSORTED COLORS

Printed: 02/27/09

Hygienic Practices

WASH THOROUGHLY AFTER USE. PERSONS WITH PREEXISTING SKIN DISORDERS MAY BE MORE SUSCEPTABLE TO THE EFFECTS OF THIS PRODUCT

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing

STORE AWAY FROM HEAT, SPARKS AND OPEN FLAMES.

Other Precautions

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE HAS BEEN FOUND TO CAUSE ANEMIA, LIVER ABNORMALITIES, KIDNEY DAMAGE EYE DAMAGE AND CARDIAC ABNORMALITY.

XYLENE, ETHYL BENZENE AND TOLUENE DIISOCYANATE ARE REGULATED BY SECTION 313 OF SARA, TITLE III.

WARNING! This product contains chemical substance(s) known to the state of California to cause cancer and birth defects or other reproductive harm.

DISCLAIMER: THE INFORMATION AND RECOMENDATIONS SET FORTH HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THIS DATE. EASTWOOD MAKES NO REPRESENTATION AS TO THE COMPLETENESS OR ACCURACY THEREOF. INFORMATION IS SUPPLIED UNDER THE CONDITION THAT THE RECIPIENT WILL MAKE HIS OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR INTENDED PURPOSE, PRIOR TO USE.

END OF MSDS