

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016

Revision 2

Page 1 of 8

SECTION 1 - IDENTIFICATION

Product Identifier

Product Name *Wrinkle Paint Black - 10014Z*

Other Means of Identification *None*

Recommended Use and Restrictions on Use

Recommended Use *Interior or exterior use for wrinkle finish*

Restrictions on Use *None Identified*

**24 hr Emergency
Phone Number**

800-424-9300

SUPPLIER DETAILS	
Name	<i>The Eastwood Company</i>
Address	<i>263 Shoemaker Road Pottstown PA 19464</i>
Phone Number	<i>800-343-9353</i>
Fax Number	<i>610-323-6268</i>

SECTION 2 - HAZARD(S) IDENTIFICATION

Hazard Classification

HEALTH HAZARDS				PHYSICAL HAZARDS			
Acute Tox. Oral	<input type="text" value="4"/>	Mutagenicity	<input type="text"/>	Unstable Explosive	<input type="text"/>	Refrigerated Liq. Gas	<input type="text"/>
Acute Tox. Skin	<input type="text"/>	Carcinogenicity	<input type="text" value="2"/>	Explosive	<input type="text"/>	Flammable Liquid	<input type="text"/>
Acute Tox. Inhalation	<input type="text"/>	Tox. to Reproduction	<input type="text" value="2"/>	Flammable Gas	<input type="text"/>	Flammable Solid	<input type="text"/>
Skin Irritation	<input type="text" value="2"/>	STOT SE	<input type="text" value="3"/>	Aerosol	<input type="text" value="1"/>	Self-Reactive Sub.	<input type="text"/>
Eye Irritation	<input type="text" value="2"/>	STOT RE	<input type="text" value="2"/>	Oxidizing Gas	<input type="text"/>	Pyrophoric Liquid	<input type="text"/>
Resp. Sensitization	<input type="text"/>	Aspiration Hazard	<input type="text" value="1"/>	Gas Under Pressure	<input type="text" value="X"/>	Self-Heating Substance	<input type="text"/>
Skin Sensitization	<input type="text"/>		<input type="text"/>	ENVIRONMENTAL HAZARDS (GHS Rev 3 Only)			
	<input type="text"/>		<input type="text"/>	Aquatic Acute	<input type="text"/>	Aquatic Chronic	<input type="text"/>
	<input type="text"/>		<input type="text"/>			Ozone Depleting	<input type="text"/>

Signal Word

Danger

Hazard Pictograms



Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

General

Keep out of reach of children.

Prevention

Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection.

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016

Revision 2

Page 2 of 8

Response	<i>If exposed, concerned or feel unwell: Call a doctor. IF SWALLOWED: Immediately call a POISON CENTER. Rinse mouth. Do NOT Induce vomiting. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
Storage	<i>Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.</i>
Disposal	<i>Dispose of contents/container in accordance with local regulations.</i>
Hazards Not Otherwise Classified	<i>None identified.</i>
Unknown Acute Toxicity	<i>28.2 % by wt</i>

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	% WT RANGE*
1	Propane	0000074-98-6	15 - 40
2	Acetone	0000067-64-1	10 - 30
3	Toluene	0000108-88-3	10 - 30
4	V M & P Naphtha	0064742-89-8	7 - 13
5	Butyl Cellosolve	0000111-76-2	1 - 5
6	Stoddard Solvent	0008052-41-3	1 - 5
7	Carbon Black	0001333-86-4	1 - 5
8	Xylene	0001330-20-7	0.1 - 1

* Exact percentages of composition withheld as trade secret

SECTION 4 - FIRST AID MEASURES

Description of First-Aid Measures

General	<i>If exposed or concerned seek medical advice/attention.</i>
Eye Contact	<i>Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.</i>
Skin Contact	<i>Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.</i>
Ingestion	<i>Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.</i>
Inhalation	<i>Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.</i>
First-Aid Responder Protection	<i>Wear adequate personal protective equipment based on the nature and severity of the emergency.</i>

Most Important Symptoms and Effects, Both Acute and Delayed

Eye Contact	<i>Liquid contact may cause pain along with moderate eye irritation.</i>
Skin Contact	<i>Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.</i>
Ingestion	<i>Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.</i>
Inhalation	<i>Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.</i>

Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	<i>Stoddard Solvent sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmia in individuals exposed. Use of sympathomimetic drugs should be avoided. If ingested, the material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left later lateral decubitus position.</i>
Specific Treatments/Antidotes	<i>No information available.</i>
Immediate Medical Attention	<i>No information available.</i>

SECTION 5 - FIRE-FIGHTING MEASURES**Extinguishing Media**

Suitable Extinguishing Media Water, CO₂, dry chemical, or universal aqueous film forming foam

Unsuitable Extinguishing Media Water jet

Specific Hazards Arising from the Chemical or Mixture

Decomposition Products Oxides of carbon (CO, CO₂), smoke, and/or vapors

Hazards from the Product CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapours heavier than air may spread along the ground and travel to an ignition source.

Advice for Firefighters

Protective Actions Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.

Protective Equipment As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES**Personal Precautions, Protective Equipment and Emergency Procedures**

For Non-Emergency Personnel No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.

For Emergency Responders Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.

Environmental Precautions

Precautions Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Containment Procedures Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.

Cleanup Procedures Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

Other Information Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.

Prohibited Materials Combustible absorbent material such as sawdust, use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE**Precautions for Safe Handling**

General Handling Precautions KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.

Hygiene Recommendations Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

Conditions for Safe Storage Including Any Incompatibilities

Storage Requirements Storage of individual cans should be done in an area below 50 °C (122 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.

Incompatibilities Segregate storage away from materials indicated in Section 10

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016
Revision 2
Page 4 of 8

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

ID	PEL	OSHA STEL	CEILING	IDLH	REL NIOSH	STEL	CEILING	TLV	ACGIH STEL	CEILING	AIHA WEEK
1	1000 ppm	—	—	—	1000 ppm	—	—	—	—	—	—
2	1000 ppm	—	—	25000 ppm	250 ppm	—	—	250 ppm	500 ppm	—	—
3	200 ppm	—	300 ppm	500 ppm	100 ppm	150 ppm	—	50 ppm	150 ppm	—	—
5	50 ppm	—	—	700 ppm	5 ppm	—	—	20 ppm	—	—	—
6	500 pp,	—	—	20000 mg/m3	350 mg/m3	—	18000 mg/m3	100 ppm	—	—	—
7	3.5 mg/m3	—	—	1750 mg/m3	3.5 mg/m3	—	—	3 mg/m3	—	—	—
8	100 ppm	—	—	900 ppm	100 ppm	150 ppm	—	100 ppm	150 ppm	—	—

Biological Exposure Indices

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
2	Acetone in urine	End of shift	50 mg/L	Ns
3	o-Cresol in urine	End of shift	0.5 mg/L	B
5	Butoxyacetic acid (BAA) in urine	End of shift	200 g/g creatinine	—
8	Methylhippuric acids in urine	End of shift	1.5 g/g creatinine	—

Other Control Parameters

Not Available

Appropriate Engineering Control

Engineering Measures

Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

Individual Protection Measures

Hygiene Considerations

Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.

Thermal Protection

This product does not present a thermal hazard.

Respiratory Protection

An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

Skin Protection

For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

Eye/Face Protection

Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

Other Protective Equipment

Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Properties

Boiling Point	> 56.1 °C (133.0 °F)	Melting / Freezing Point	> -95.3 °C (-139.6 °F)
Flash Point, Liquid	> -17.0 °C (1.4 °F)	Flash Point, Propellant	-104.4 °C (-156.0 °F)
Explosive Limits	0.90% - 36.00%	Autoignition Temperature, Liquid	465.0 °C (869.0 °F)
Flammability	Extremely Flammable Aerosol	Relative Density (H2O = 1)	0.763 g/cc
Molecular Weight	Not Available	Weight	6.370 lbs/gal
Vapor Pressure	108.00 psig	pH	Not Available
Vapor Density	3.100 g/cc Maximum	Evaporation Rate	Not Available
Form	Pressurized Product	Partition Coefficient	Not Available
Viscosity	Not Available	Refractive Index	Not Available
Odor Threshold	Not Available	Heat of Combustion (ΔHc)	Not Available

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016
Revision 2
Page 5 of 8

Odor	Paint Like	Water Solubility	Not Available
Appearance / Color	Black dull coating	Decomposition Temperature	Not Available

Air Quality Properties

Percent Volatile	71% Wt (81% Vol) Max	VOC Regulatory	4.039 lbs/gal (484.027 g/L)
Percent VOC	53% Wt (63% Vol) Max	VOC Actual	3.319 lbs/gal (397.617 g/L)
Percent HAP	14% Wt (12% Vol) Max	HAP Content	0.854 lbs/gal (102.273 g/L)
Solids/Non Volatile Content	30% Wt (20% Vol) Max	Maximum Incremental Reactivity	0.973 g O3/g
Global Warming Potential	1.266		

SECTION 10 - STABILITY AND REACTIVITY

Reactivity No specific test data related to reactivity is available for this product or its ingredients.

Chemical Stability This product is stable.

Hazardous Reactions Under normal conditions of storage and use, hazardous reactions are not expected to occur.

Conditions to Avoid Keep away from heat, sparks, flame, and red hot metal.

Material Incompatibility Acids, Activated Carbon, Alkalis, Bases, Dichlorohydrantion, Halogens, Hexachloromelamine, Hydrogen Peroxide, Isoprene, Nitric Acid, Nitrogen Tetroxide, Silver Perchlorate, Strong Oxidizing Agents, Strong Reducing Agents, Sulfur Dichloride, Tetranitromethane, Trichloromelamine, Uranium Hexafluoride

Decomposition Productions Oxides of Carbon, Acetic Acid, Formaldehyde fumes, Hydrogen Peroxide, Methanol, Peroxides may be formed depending on fire conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity Estimates (mixture)

Oral LD₅₀	1689 mg/kg
Dermal LD₅₀	6349 mg/kg
Inhalation LC₅₀	1467 mg/L 4-hour

Acute Toxicity on Ingredients

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
1	—	—	—	—	658 mg/L	4h	rat
2	5800 mg/kg	rat	20000 mg/kg	rabbit	50100 mg/m3	8h	rat
3	636 mg/kg	rat	12124 mg/kg	rabbit	49000 mg/m3	4h	rat
4	5000 mg/kg	rat	3000 mg/Kg	rabbit	3400 ppm	4h	rat
5	1400 mg/kg	guinea pig	>2000 mg/kg	guinea pig	2211 mg/m3	4h	rat
6	>5000 mg/kg	rat	>3000 mg/kg	rabbit	>5500 mg/m3	4h	rat
7	>15400 mg/kg	rat	>3000 mg/kg	rabbit	6750 mg/m3	4h	rat
8	4300 mg/kg	rat	4500 mg/kg	rabbit	6700 ppm	4h	rat

Health Hazard Classification

Skin Corrosion / Irritation	Category 2
Eye Damage / Irritation	Category 2
Respiratory Irritation	Classification criteria not met
Respiratory / Skin Sensitization	Classification criteria not met
Germ Cell Mutagenicity	Classification criteria not met
Reproductive Toxicity	Category 2
STOT - Single Exposure	Category 3
STOT - Repeated Exposure	Category 2

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016

Revision 2

Page 6 of 8

Aspiration Hazard
Carcinogen Data
Category 1

ID	Calif Prop-65	OSHA	NIOSH	ACGIH	NTP	IARC
5	No	-	-	A3	-	-
7	Yes	-	App A & C	A3	-	2B

Information on the Likely Routes of Exposure
Routes of Exposure

Skin contact, skin absorption, eye contact, inhalation

Information on Physical, Chemical and Toxicological Effects
Symptoms of Exposure

Abdominal Cramps, Asphyxia, Central Nervous System Depression, Chemical Pneumonitis, Confusion, Cough, Dermatitis, Dizziness, Drowsiness, Excitation, Skin Irritation, Staggering Gait, Throat Irritation, Upper Respiratory System Irritation, Vomiting

Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure
Delayed Effects

No known delayed effects.

Immediate Effects

No known immediate effects.

Chronic Effects

Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal. Stoddard Solvent when ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Reports of chronic poisoning from Toluene describe anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Exposure may affect a developing fetus.

Medical Conditions Aggravated

May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

Target Organs

Bladder, Blood, Central Nervous System, Eyes, Gastrointestinal Tract, Kidneys, Liver, Lymphoid System, Respiratory System, Skin

SECTION 12 - ECOLOGICAL INFORMATION

Acute Aquatic Toxicity

ID	TYPE	FISH VALUE	PERIOD	TYPE	INVERTEBRATES VALUE	PERIOD	TYPE	AQUATIC PLANTS VALUE	PERIOD	TYPE	MICROORGANISMS VALUE	PERIOD
2	LC50	5540 mg/L	96h	LC50	8800 mg/L	48h	NOEC	530 mg/L	8d	EC5	1700 mg/L	16h
3	LC50	5.8 mg/L	96h	EC50	6 mg/L	48h	IC50	12 mg/L	72h	EC50	20 mg/L	30m
5	LC50	1474 mg/L	96h	EC50	1550 mg/L	48h	LOEC	900 mg/L	7d	EC5	911 mg/L	48h
7	NOEC	1000 mg/L	96h	EC50	>5600 mg/L	24h	-	-	-	EC0	400 mg/L	3h
8	LC50	26.7 mg/L	96h	LC50	14 mg/L	24h	-	-	-	-	-	-

Ecological Data

ID	PERSISTENCE	PERSISTENCE AND DEGRADABILITY BOD	COD	ThOD	BIOACCUMULATIVE POTENTIAL Pow / Kow	BCF	MOBILITY Koc
1	-	-	-	-	2.36 log Pow	1.47log BCF	2.36 log Koc
2	90.9% / 28 days	1.85 mg/g / 5d	2.07 mg/g	2.21 mg/g	-0.24 log Pow	0.69 BCF	1.26 log Koc
3	86% / 20 days	2.15 mg/g	2.52 mg/g	3.13 mg/g	2.65 Pow	1.57 log BCF	2.15 log Koc
4	95% / 28 days	-	-	-	2.1 log Pow	-	-
5	90.4% / 28 days	-	-	-	0.81 log Pow	0.5 log BCF	-
6	-	-	-	-	3.16 log Kow	-	-
7	-	5 mg/L	-	-	1.09 log Pow	0.599 log BCF	1.99 log Koc
8	-	0.64 mg/L	-	2410 mg/g	3.271 log Pow	1.57 log BCF	3.156 log Koc

Other Adverse Effects

No additional information available.

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016

Revision 2

Page 7 of 8

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal

Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal of Packaging

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

Landfill Precautions

Not available

Incineration Precautions

**** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE ****

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information

UN Number
Proper Shipping Name
Hazard Class(es)
Packaging Group
Marine Pollutant
Hazard Label(s)

Ground Transportation (DOT)

UN1950

Aerosols, Limited Quantity

2.1

—

No



Air Transportation (IATA)

UN1950

Aerosols, Flammable, Limited Quantity

2.1

—

No



Ocean Transportation (IMDG)


UN1950

Aerosols, Limited Quantity

2.1

—

No



SECTION 15 - REGULATORY INFORMATION

Federal Regulations

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT HAP	CLEAN AIR ACT SOCMI	CLEAN WATER ACT
1	Yes	—	—	—	—	Yes	—	—	—	—	—	—	—
2	Yes	—	U002	5000	—	Yes	—	Yes	—	—	—	—	—
3	Yes	—	U220	1000	13%	Yes	—	Yes	Yes	—	Yes	Yes	1000 (PP)
4	Yes	—	—	—	—	—	—	Yes	—	—	—	—	—
5	Yes	—	—	—	—	—	—	Yes	—	—	—	—	—
6	Yes	—	—	—	—	—	—	Yes	—	—	—	—	—
7	Yes	—	—	—	—	—	—	—	—	—	—	—	—
8	Yes	—	U239	100	<1%	Yes	—	Yes	—	—	Yes	Yes	100

State Regulations

ID	CA P-65	DE RQ	MA RTK CODES	ME TYPE	ME RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
1	—	1000	2,4,5,6	—	—	AP	—	—	—	—	—	—	Yes	1000 ppm	—	—
2	—	5000	2,4,5,6 F8 F9	—	20000	AON	—	—	—	5000	1	—	Yes-E	750 ppm	—	—
3	D	1000	2,4,5,6 F7 F8 F9	—	2000	ANO	1	1	—	1000	1	—	Yes-E	100 ppm	A	—
5	—	—	2,4,6 F8	—	—	AO	—	—	—	—	—	—	Yes	25 ppm	A	—
6	—	—	2,4	—	—	ANO	—	—	—	—	—	—	Yes	100 ppm	A	—
7	C	—	2,4 F5	—	—	ANOR	—	—	—	—	—	—	Yes	3.5 mg/m3	A	—
8	—	100	2,4 F8 F9	—	2000	ANO	1	—	—	1000	1	—	Yes-E	100 ppm	A	—

California Prop 65: Warning! This product contains chemicals (Ethyl Benzene Cas# 100-41-4, 0.0924% and Methanol Cas#67-56-1, 0.0616%) known in the State of California to cause cancer, birth defects or other reproductive harm.

SAFETY DATA SHEET

Wrinkle Paint Black

June 8, 2016

Revision 2

Page 8 of 8

SECTION 16 - OTHER INFORMATION

SDS Revision History

Revision 2, 06/08/2016, Updated to GHS Version 3 Format.

SDS Compliance

This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department.

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.