Printing date 08/28/2009

Reviewed on 08/28/2009

Printing date 08/28/2009	Reviewed on 08/28/2009
1 Identification of substar	nce
Trade name:	BRAKE CALIPER COATING
Product codes:	
	10033Z
Manufacturered for:	The Easthill Group Dba The Eastwood Company
	263 Shoemaker Road
	Pottstown, PA 19464
	USA and Canada: 800-345-1178 Outside USA: (610)-323-2200
Emergency information:	Chem-Trec 1-800-434-9300
2 Composition/Data on co	omponents
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.
Dangerous components:	
67-64-1 Acetone	20.51%
74-98-6 propane	18.95%
108-88-3 Toluene	15.54%
106-97-8 n-butane 2807-30-9 Glycol Ether EP	11.13% 5.08%
1330-20-7 xylene (mix)	4.23%
	7.2070
3 Hazards identification	
Hazard description:	A Harmful
Hazard description:	Extremely flammable
Discrete al des serves	
Physical dangers:	Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
	Has narcotizing effect.
	Extremely flammable.
	Irritating to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	Keep out of the reach of children.
Effects of chronic	
overexposure:	May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be
	harmful or fatal.
NFPA ratings (0 - 4):	Health = 1
	Fire = 4 Reactivity = 3
HMIS-ratings (0 - 4):	Health= 1
0 ()	Fire= 4
	Physical Hazard= 3
4 Eirot aid magaures	
4 First aid measures After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult
After swallowing:	a doctor. Contact physician or poison control center.
After swallowing:	
5 Fire fighting measures	
Extinguishing agents:	CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant
Extinguishing agents.	foam.
Protective equipment:	No special measures required.
6 Accidental release meas	sures
Personal safety:	Wear protective equipment. Keep unprotected persons away.
Environmental safety: Clean-up/collection:	Do not allow product to reach sewage systems or ground water. Ensure adequate ventilation.
	בחסערים מעפיעומוס עבוונומנוטה.
7 Handling and storage	
Fire/explosion protection:	Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic
	discharges.
Storage requirements:	Observe pressurized container storage regulations. Consult with your local authorities.
	USA

(Contd. on page 2)

Printing date 08/28/2009

Trade name: BRAKE CALIPER COATING

Reviewed on 08/28/2009

(Contd. of page 1)

	(contra. of page
8 Exposure controls and	nersonal protection:
	lues that require monitoring at the workplace:
67-64-1 Acetone	
PEL 2400 mg/m ³ , 1000 pp	m
REL 590 mg/m ³ , 250 ppm	
TLV Short-term value: 178 Long-term value: 118	
BEI	
74-98-6 propane	
PEL 1800 mg/m ³ , 1000 pp	m
REL 1800 mg/m ³ , 1000 pp TLV Varies mg/m ³ , 1000 p	m ma
108-88-3 Toluene	pm
PEL Short-term value: C 3	00; 500* ppm
Long-term value: 200	ppm - abit
*10-min peak per 8-hi REL Short-term value: 560	shin) mg/m ³ , 150 ppm
Long-term value: 375	mg/m ³ , 100 ppm
TLV 75 mg/m ³ , 20 ppm	
106-97-8 n-butane	
REL 1900 mg/m ³ , 800 ppm TLV Varies mg/m ³ , 1000 p	ı om
1330-20-7 xylene (mix)	<u>r</u>
PEL 435 mg/m ³ , 100 ppm	
REL Short-term value: 655	
Long-term value: 435 TLV Short-term value: 651	mg/m ³ , 100 ppm mg/m ³ 150 ppm
Long-term value: 434	mg/m ³ , 100 ppm
BEI	
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cas where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If y
	suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Protective gloves. The glove material has to be impermeable and resistant to the substance. No glo
Eye protection:	recommendation can be given. Tightly sealed goggles
9 Physical and chemical	properties:
General Information:	
Odor:	Aromatic
Boiling point:	-44°C
Flash point:	-19°C
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 1.
	degrees fahrenheit.
Lower Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density at 20°C:	0.77084 g/cm ³
Specific Gravity:	Between 0.77 and 0.85 (Water equals 1.00)
VOC content:	554.9 g/l / 4.63 lb/gl
VOC content (less exemp MIR Value:	t solvents): 57.6 % 1.53
Solids content:	21.9 %
	21.0 /0
0 Stability and reactivity:	
Conditions to avoid:	Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Hazardous Reactions:	No dangerous reactions known.
	ion:
1 Toxicological information	
Skin effects:	No irritant effect.

Printing date 08/28/2009

Trade name: BRAKE CALIPER COATING

Reviewed on 08/28/2009

	(Contd. of page
Ecological information Other information: Acquatic toxicity:	This product does not contain any chlorofluorocarbons (CFC's) or chlorinated solvents. Hazardous for water, do not empty into drains.
Disposal considerations	
· · · · · · · · · · · · · · · · · · ·	, ose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or comp
Partially empty cans must be	disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation:	Completely empty can's should be recycled.
Transport information:	
Hazard class:	2.1
Identification number:	N/A
Label ADR/RID/TDG class:	2.1+8 2 5FC Gases
UN-Number:	1950
IMDG Class:	2.1
Packaging group: EMS Number:	II F-D,S-U
Marine pollutant:	No
ICAO/IATA Class:	2.1
Propper shipping name:	Aerosols, Flammable
	Consumer Commodity ORM-D
Regulations	
	ely hazardous substances):
None of the ingredients in thi	
SARA Section 313 (Specified	c toxic chemical listings):
108-88-3 Toluene	
1330-20-7 xylene (mix)	
TSCA:	All ingredients are listed.
CPSC:	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
	hemicals known to cause cancer:
100-41-4 ethyl benzene 1333-86-4 Carbon black	
California Proposition 65	
chemicals known to cause	
developmental toxicity:	108-88-3 Toluene
CANADIAN	
ENVIRONMENTAL PROTECTION ACT:	All hazardous ingredients for this product appear on the Canadian Domestice Substance List.
EPA:	A= Known human carcinogen B= Probable human carcinogen
	C= Possible human carcinogen
	D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence
	carcinogenicity (or no data is available). I: 'Data are inadequate for an assessment of human carcinogeni potential.'
	II: 'Inadequate information to assess carcinogenic potential.'
67-64-1 Acetone	
108-88-3 Toluene	
1330-20-7 xylene (mix)	
IARC:	Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence carcinogenicity.
	Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.
108-88-3 Toluene	
14807-96-6 Talc (Mg3H2(Si	O3)4)
1330-20-7 xylene (mix)	
ACGIH:	A1-designates a confirmed human carcinogen.
	A2-designates a suspected human carcinogen.
	A3-designates an animal carcinogen. A4-designates "not classifiable as a human carcinogen".
67-64-1 Acetone	
108-88-3 Toluene	
14807-96-6 Talc (Mg3H2(Si	
1330-20-7 xylene (mix)	
NIOSH:	The following substances are regulated in the United States with reference to occupational expos
	limits:
1333-86-4 Carbon black	
	(Contd. on pay

Printing date 08/28/2009

Reviewed on 08/28/2009

3		
Trade name: BRAKE CALIPER COATING		
	(Contd. of page 3)	
Risk phrases:	Extremely flammable. Irritating to eyes.	
	Harmful: danger of serious damage to health by prolonged exposure through inhalation.	
Safety phrases:	Keep out of the reach of children. Do not breathe gas/fumes/vapour/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.	
16 Other information		
This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Contact: Regulatory Affairs		
Abbreviations and acronyms:	GHS: Globally Harmonized System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) PP: Severe Marine Pollutant P: Marine Pollutant HMIS: Hazardous Materials Identification System (USA) ISO: International Organization for Standardization EPA: Environmental Protection Agency IARC: International Agency for the Research of Cancer NIOSH: National Institute for Occupational Safety and Health TSCA: Toxic Substances Control Act CPSC: Consumer Product Safety Commission	