

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

## 1 Identification of substance

**Trade name:** ENGINE PAINT FORD DARK BLUE

**Product code:** 10059Z

**Manufactured For:** The Easthill Group dba/ The Eastwood Company  
263 Shoemaker Road  
Pottstown, PA 19464  
USA & Canada: 800-345-1178 Outside USA: (610) 323-2200

**Emergency information:** Chem-Trec 800-424-9300

## 2 Composition/Data on components

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

67-64-1	Acetone	38.61%
74-98-6	propane	15.76%
108-88-3	Toluene	12.12%
106-97-8	n-butane	9.25%
107-87-9	Methyl Propyl Ketone	3.99%
2807-30-9	Glycol Ether EP	1.58%

## 3 Hazards identification

**Hazard description:**   Harmful  
Extremely flammable

**Physical dangers:** Extremely flammable.  
Irritating to eyes.  
Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
Keep out of the reach of children.

**Effects of chronic overexposure:** May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

**NFPA ratings (scale 0 - 4):** Health = 1  
Fire = 4  
Reactivity = 3

**HMIS-ratings (scale 0 - 4):** Health= 1  
Fire= 4  
Physical Hazard= 3

## 4 First aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.

**After eye contact:** Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Contact physician or poison control center.

## 5 Fire fighting measures

**Extinguishing agents:** CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

**Protective equipment:** No special measures required.

## 6 Accidental release measures

**Personal safety precautions:** Wear protective equipment. Keep unprotected persons away.

**Environmental safety precautions:** Do not allow product to reach sewage systems or ground water.

**Measures for cleaning/collecting:** Ensure adequate ventilation.

## 7 Handling and storage

**Fire/explosion protection:** Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

(Contd. on page 2)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

**Trade name: ENGINE PAINT FORD DARK BLUE****Storage requirements:** Observe pressurized container storage regulations. Consult with your local authorities.

(Contd. of page 1)

**8 Exposure controls and personal protection:****Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**

PEL	2400 mg/m <sup>3</sup> , 1000 ppm
REL	590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1782 mg/m <sup>3</sup> , 750 ppm
	Long-term value: 1188 mg/m <sup>3</sup> , 500 ppm
BEI	

**74-98-6 propane**

PEL	1800 mg/m <sup>3</sup> , 1000 ppm
REL	1800 mg/m <sup>3</sup> , 1000 ppm
TLV	Varies mg/m <sup>3</sup> , 1000 ppm

**108-88-3 Toluene**

PEL	Short-term value: C 300; 500* ppm
	Long-term value: 200 ppm
	*10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	75 mg/m <sup>3</sup> , 20 ppm

**106-97-8 n-butane**

REL	1900 mg/m <sup>3</sup> , 800 ppm
TLV	Varies mg/m <sup>3</sup> , 1000 ppm

**107-87-9 Methyl Propyl Ketone**

PEL	700 mg/m <sup>3</sup> , 200 ppm
REL	530 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

**Protective hygienic measures:**

Keep away from foodstuffs and animal feed. Wash hands after use.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. Please consult an authority on chemical hygiene monitoring if you suspect overexposure conditions exist and need a specific recommendation on proper ventilation techniques and personal protection.

**Protection of hands:**

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties:****General Information:**

<b>Odor:</b>	Aromatic
<b>Boiling point/Boiling range:</b>	-44°C

<b>Flash point:</b>	-19°C
---------------------	-------

<b>Ignition temperature:</b>	365°C
------------------------------	-------

<b>Auto igniting:</b>	Product is not self-igniting.
-----------------------	-------------------------------

<b>Danger of explosion:</b>	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.
-----------------------------	---

<b>Lower Explosion Limit:</b>	In use, may form flammable/explosive vapour-air mixture.
-------------------------------	--

<b>Upper Explosion Limit:</b>	1.7 Vol %
-------------------------------	-----------

<b>Vapor Pressure:</b>	10.9 Vol %
------------------------	------------

<b>Density at 20°C:</b>	40 PSI, 2750 hPa
-------------------------	------------------

<b>Specific Gravity:</b>	0.75515 g/cm <sup>3</sup>
--------------------------	---------------------------

<b>VOC content:</b>	Between 0.77 and 0.85 (Water equals 1.00)
---------------------	---

<b>VOC content (less exempt solvents):</b>	532.9 g/l / 4.45 lb/gl
--	------------------------

<b>MIR value:</b>	44.6 %
-------------------	--------

<b>MIR Value:</b>	44.6 %
-------------------	--------

(Contd. on page 3)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

Trade name: ENGINE PAINT FORD DARK BLUE

(Contd. of page 2)

Solids content: 16.3 %

**10 Stability and reactivity:****Conditions to be avoided:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.**Possibility of Hazardous****Reactions:** No dangerous reactions known.**11 Toxicological information:****Primary effect on the skin:** No irritant effect.**Primary effect on the eye:** Irritating effect.**Sensitization:** No sensitizing effects known.**Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

**12 Ecological information****Other information:** This product does not contain any chloroflourocarbons (CFC's), chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.**Acquatic toxicity:** Hazardous for water, do not empty into drains.**13 Disposal considerations****DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.**Recommendation:** Completely empty cans should be recycled.**14 Transport information:**

**Hazard class:** 2.1  
**Identification number:** N/A  
**Label:** 2.1  
**ADR/RID class:** 2 5F Gases  
**UN-Number:** 1950  
**IMDG Class:** 2.1  
**Packaging group:** II  
**EMS Number:** F-D,S-U  
**Marine pollutant:** No  
**ICAO/IATA Class:** 2.1  
**Proper shipping name:** Aerosols, Flammable  
 Consumer Commodity ORM-D

**15 Regulations****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

108-88-3 Toluene

**TSCA (Toxic Substances****Control Act):** All ingredients are listed.**PROPOSITION 65 Chemicals known to cause cancer:**

100-41-4 ethyl benzene

**PROPOSITION 65****Chemicals known to cause developmental toxicity:****EPA:** 108-88-3 Toluene A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1 Acetone

I

108-88-3 Toluene

II

(Contd. on page 4)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

**Trade name: ENGINE PAINT FORD DARK BLUE****IARC:**

(Contd. of page 3)  
Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.  
Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3 Toluene

3

**ACGIH TLVs:**

A1-designates a confirmed human carcinogen.  
A2-designates a suspected human carcinogen.  
A3-designates an animal carcinogen.  
A4-designates "not classifiable as a human carcinogen".

67-64-1 Acetone

A4

108-88-3 Toluene

A4

**NIOSH:**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

**Risk phrases:**

Extremely flammable.  
Irritating to eyes.  
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

**Safety phrases:**

Keep out of the reach of children.  
Keep in a cool place.  
Keep container in a well-ventilated place.  
Keep away from food, drink and animal feedingstuffs.  
Keep away from sources of ignition - No smoking.  
Do not breathe gas/fumes/vapour/spray.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point  
Wear suitable protective clothing and gloves.  
If swallowed, seek medical advice immediately and show this container or label.  
Use only in well-ventilated areas.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:**

Regulatory Affairs

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
VOC: Volatile Organic Compounds (USA, EU)

USA