



DO THE JOB RIGHT.®

ALUMA BLAST®

ALUMINUM REPLICATION COATING



- Fresh-Cast Aluminum Look
- Protects From Corrosion
- Maximum Temperature 300°F



Scan for product info

DANGER: EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION.

Read Cautions on Back Panel.

Net Wt. 12 oz. / 340 grams

10109Z

EASTWOOD ALUMA BLAST® is formulated to capture the look and texture of cast aluminum. Using Aluma Blast provides you a protective and super-durable finish that will resist temperatures up to 300°F. Aluma Blast is ideal for alternators, transmissions and so much more.

APPLICATION – NOT FOR USE ON INTERNAL ENGINE SURFACES!

NOTE: Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).

1. Use Eastwood's PRE Painting Prep (10041Z) to clean surface of dirt, grease, loose paint, rust and wax. Ensure surface is dry after cleaning.
2. Sand with 220-320 grit sandpaper. Wipe or blow off surface and re-clean. 3. Mask off adjacent areas not to be coated to protect them from overspray. 4. Point opening of spray button toward object holding can approximately 6-8" from surface to be coated.
5. Press spray button firmly. Use steady, even strokes while spraying. 6. Apply light "mist" coats, allowing 5-10 minutes between coats. Several thin coats give a better finish than one heavy coat. 7. If clogging develops, remove spray button with a twisting motion and clean with a compliant solvent. DO NOT stick pin or other object into can. Gently replace spray button with a twisting motion with top of can and spray button opening pointed away from you. 8. After each use, turn can upside down and spray several seconds to clear head.

CONTAINS (CAS No.): propane (74-98-6), toluene (108-88-3), acetone (67-64-1), alkylid resin, n-butyl acetate (123-86-4), pentan-2-one (107-87-9), aluminium (7429-90-5), ethyl 3-ethoxypropionate (763-69-9), heavy naphtha (64742-48-9), talc (14807-96-6), precipitated Silica (Silica-Amorphous) (112926-00-8), 4-methylpentan-2-one (108-10-1), stoddard solvent (8052-41-3), 2-butanone oxime (96-29-7).



This product is not for sale to the general public and should be applied by professionally trained personnel using proper equipment.
DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONS: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames or hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Do not breathe dust, fume, gas, mist, vapors, spray. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, eye protection and face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

RESPONSE: If exposed or concerned: Get medical advice or attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor or physician. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). Take off contaminated clothing and wash before reuse. If eye irritation persists: Get medical advice or attention. Get medical advice or attention if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse.

STORAGE: Store locked up. Keep cool. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C -122°F. Keep container tightly closed. **DISPOSAL:** Dispose of contents and container in accordance with local, regional, national, and international regulations.

Safety data sheet available on request. **KEEP OUT OF REACH OF CHILDREN.**



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464 USA: 1-800-345-1178
Canada: 1-800-820-9042 International: (610) 323-2200
www.eastwood.com © Copyright 2016 Easthill Group, Inc. Made in USA



6 07174 10123 8