

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

1 Identification of substance

Trade name: OLDS METALLIC BLUE
Product codes: 10123Z
Manufactured for: The Easthill Group
 DbA The Eastwood Company
 263 Shoemaker Road
 Pottstown, PA 19464
 USA and Canada: 800-345-1178
 Outside USA: (610)-323-2200
Emergency information: Chem-Trec 1-800-434-9300

2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|-----------|-------------------------------|--------|
| 67-64-1 | Acetone | 30.38% |
| 74-98-6 | propane | 18.89% |
| 106-97-8 | n-butane | 11.1% |
| 108-88-3 | Toluene | 10.14% |
| 1330-20-7 | xylene (mix) | 9.86% |
| 100-41-4 | ethyl benzene | 2.46% |
| 2807-30-9 | Glycol Ether EP | 1.52% |
| 7429-90-5 | aluminium powder (stabilised) | 1.3% |

3 Hazards identification

Hazard description:   Harmful
Extremely flammable

Physical dangers: Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
 Has narcotizing effect.
 Extremely flammable.
 Irritating to eyes and skin.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Keep out of the reach of children.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4): Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (0 - 4): Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Immediately wash with water and soap and rinse thoroughly.
After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
Protective equipment: No special measures required.

6 Accidental release measures

Personal safety: Wear protective equipment. Keep unprotected persons away.
Environmental safety: Do not allow product to reach sewage systems or ground water.
Clean-up/collection: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.
Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

Trade name: OLDS METALLIC BLUE

(Contd. of page 1)

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm
 REL 590 mg/m³, 250 ppm
 TLV Short-term value: 1782 mg/m³, 750 ppm
 Long-term value: 1188 mg/m³, 500 ppm
 BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
 REL 1800 mg/m³, 1000 ppm
 TLV Varies mg/m³, 1000 ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
 TLV Varies mg/m³, 1000 ppm

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm
 Long-term value: 200 ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV 75 mg/m³, 20 ppm

1330-20-7 xylene (mix)

PEL 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

100-41-4 ethyl benzene

PEL 435 mg/m³, 100 ppm
 REL Short-term value: 545 mg/m³, 125 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 543 mg/m³, 125 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

7429-90-5 aluminium powder (stabilised)

PEL 15* 5** mg/m³
 Metal dust *total dust **respirable fraction
 REL 10* 5** mg/m³
 Metal dust *total dust **respirable fraction
 TLV 1* mg/m³
 *as respirable fraction

Additional information: The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. However, a two year rat and mouse gavage study by the National Toxicology Program on mixed xylene isomers including 17% ethylbenzene showed no evidence of carcinogenicity.

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties:

General Information:

Odor: Aromatic

Boiling point: -44°C

Flash point: -19°C

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor Pressure: 40 PSI, 2750 hPa

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

Trade name: OLDS METALLIC BLUE

(Contd. of page 2)

Density:
Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)
VOC content: 895.6 g/l / 7.47 lb/gl
VOC content (less exempt solvents): 55.2 %
Solids content: 14.4 %

10 Stability and reactivity:

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Hazardous Reactions: No dangerous reactions known.

11 Toxicological information:

Skin effects: Irritant to skin and mucous membranes.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Other information: This product does not contain any chlorofluorocarbons (CFC's) or chlorinated solvents.
Aquatic toxicity: Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information:

Hazard class: 2.1
Identification number: N/A
Label: 2.1
ADR/RID/TDG class: 2 5F Gases
UN-Number: 1950
IMDG Class: 2
Packaging group: II
EMS Number: F-D,S-U
Marine pollutant: No
ICAO/IATA Class: 2.1
Proper shipping name: Aerosols, Flammable
 Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

| | |
|-----------|-------------------------------|
| 108-88-3 | Toluene |
| 1330-20-7 | xylene (mix) |
| 100-41-4 | ethyl benzene |
| 7429-90-5 | aluminium powder (stabilised) |

TSCA: All ingredients are listed.**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

| | |
|-----------|---------------|
| 100-41-4 | ethyl benzene |
| 1333-86-4 | Carbon black |

California Proposition 65 chemicals known to cause developmental toxicity: 108-88-3 Toluene

CANADIAN

ENVIRONMENTAL PROTECTION ACT:

Canadian WHMIS:

EPA:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

D2A

A= Known human carcinogen

B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

I: 'Data are inadequate for an assessment of human carcinogeni potential.'

II: 'Inadequate information to assess carcinogenic potential.'

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

Trade name: OLDS METALLIC BLUE

(Contd. of page 3)

| | | |
|-----------|---------------|----|
| 67-64-1 | Acetone | I |
| 108-88-3 | Toluene | II |
| 1330-20-7 | xylene (mix) | I |
| 100-41-4 | ethyl benzene | D |

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

| | | |
|-----------|---------------|----|
| 108-88-3 | Toluene | 3 |
| 1330-20-7 | xylene (mix) | 3 |
| 100-41-4 | ethyl benzene | 2B |

ACGIH: A1-designates a confirmed human carcinogen.
A2-designates a suspected human carcinogen.
A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

| | | |
|-----------|-------------------------------|----|
| 67-64-1 | Acetone | A4 |
| 108-88-3 | Toluene | A4 |
| 1330-20-7 | xylene (mix) | A4 |
| 100-41-4 | ethyl benzene | A3 |
| 7429-90-5 | aluminium powder (stabilised) | A4 |

NIOSH: The following substances are regulated in the United States with reference to occupational exposure limits:

| | |
|-----------|--------------|
| 1333-86-4 | Carbon black |
|-----------|--------------|

Risk phrases: Extremely flammable.
Irritating to eyes and skin.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety phrases: Keep out of the reach of children.
Do not breathe gas/fumes/vapour/spray.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
Wear suitable protective clothing and gloves.
If swallowed, seek medical advice immediately and show this container or label.
Use only in well-ventilated areas.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
VOC: Volatile Organic Compounds (USA, EU)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
PP: Severe Marine Pollutant
P: Marine Pollutant
HMIS: Hazardous Materials Identification System (USA)
ISO: International Organization for Standardization
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission

USA