Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

Printing date 08/28/2009	Reviewed on 08/28/2009
1 Identification of substar	1Ce
Trade name:	OLDS BRONZE
Product codes:	10124Z
Manufacturered for:	The Easthill Group
	Dba The Eastwood Company
	263 Shoemaker Road
	Pottstown, PA 19464 USA and Canada: 800-345-1178
	Outside USA: (610)-323-2200
Emergency information:	Chem-Trec 1-800-434-9300
2 Composition/Data on co	umponents
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.
	This product is a mixture of the substances listed below with normazardous additions.
Dangerous components:	
67-64-1 Acetone	31.43%
74-98-6 propane	18.8%
106-97-8 n-butane	11.04%
108-88-3 Toluene	10.07%
1330-20-7 xylene (mix)	9.82%
100-41-4 ethyl benzene	2.45%
7440-50-8 Copper Powder	1.6%
2807-30-9 Glycol Ether EP	1.5%
3 Hazards identification	
Hazard description:	A Harmful
Hazaru description.	Extremely flammable
Physical dangers:	Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and
	flame.
	Has narcotizing effect. Extremely flammable.
	Irritating to eyes.
	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	Keep out of the reach of children.
Effects of chronic	
overexposure:	May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be
	harmful or fatal.
NFPA ratings (0 - 4):	Health = 1
	Fire = 4
	Reactivity = 3
HMIS-ratings (0 - 4):	Health= 1
	Fire= 4 Physical Hazard= 3
4 First sid was seen	
4 First aid measures	
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact: After eye contact:	Remove contaminated clothing. Wash exposed area with soap and water. Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult
Aller eye contact.	a doctor.
After swallowing:	Contact physician or poison control center.
5 Fire fighting measures	
Extinguishing agents:	CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant
Extinguishing agents.	foam.
Protective equipment:	No special measures required.
- •	· · · · · · · · · · · · · · · · · · ·
6 Accidental release meas	Sures
Personal safety:	Wear protective equipment. Keep unprotected persons away.
Environmental safety:	Do not allow product to reach sewage systems or ground water.
Clean-up/collection:	Ensure adequate ventilation.
•	
7 Handling and storage	
Fire/explosion protection:	Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic
	discharges.
Storage requirements:	Observe pressurized container storage regulations. Consult with your local authorities.
	USAUUSA _UUSAUUS
	(Contd. on page 2)

Material Safety Data Sheet acc. to ISO/DIS 11014

Reviewed on 08/28/2009

(Contd. of page 1)

Trade name: OLDS BRONZE

Printing date 08/28/2009

	(contraction of page 1)
8 Exposure controls and	personal protection:
	lues that require monitoring at the workplace:
67-64-1 Acetone	
PEL 2400 mg/m ³ , 1000 pp	m
REL 590 mg/m ³ , 250 ppm	
TLV Short-term value: 178	2 mg/m³, 750 ppm
Long-term value: 118	8 mg/m³, 500 ppm
BEI	
74-98-6 propane PEL 1800 mg/m ³ , 1000 pp	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
REL 1800 mg/m ³ , 1000 pp	m
TLV Varies mg/m ³ , 1000 p	pm
106-97-8 n-butane	Г
REL 1900 mg/m ³ , 800 ppm	۱
TLV Varies mg/m ³ , 1000 p	pm
108-88-3 Toluene	
PEL Short-term value: C 3	
Long-term value: 200 *10-min peak per 8-hr	ppm · shift
REL Short-term value: 560	mg/m ³ , 150 ppm
Long-term value: 375	mg/m³, 100 ppm
TLV 75 mg/m ³ , 20 ppm	
1330-20-7 xylene (mix)	
PEL 435 mg/m ³ , 100 ppm	mg/m3 150 ppm
REL Short-term value: 655 Long-term value: 435	mg/m², 150 ppm mg/m³ 100 nnm
TLV Short-term value: 651	mg/m ³ , 150 ppm
Long-term value: 434	mg/m³, 100 ppm
BEI	
100-41-4 ethyl benzene	
PEL 435 mg/m ³ , 100 ppm REL Short-term value: 545	mg/m3 125 ppm
Long-term value: 435	mg/m ³ , 100 ppm
TLV Short-term value: 543	mg/m ³ , 125 ppm
Long-term value: 434	mg/m³, 100 ppm
BEI	The International Amenay for Descende on Concer has evaluated athellograms and electified it as a
Additional information:	The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen based on sufficient evidence for carcinogenicity in experimental animals, but
	inadequate evidence for cancer in exposed humans. However, a two year rat and mouse gavage study
	by the National Toxicology Program on mixed xylene isomers including 17% ethylbenzene showed no
Hygionia protoction	evidence of carcinogenicity. Keep away from foodstuffs and animal feed. Wash hands after use.
Hygienic protection: Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases
Breating equipment.	where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you
	suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove
Eye protection:	recommendation can be given. Tightly sealed goggles
Lye protection.	
0 Physical and chamical	nronartiaci
9 Physical and chemical General Information:	pi operates.
Odor:	Aromatic
Boiling point:	-44°C
Flash point:	-19°C
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120
	degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	
Specific Gravity:	Between 0.77 and 0.85 (Water equals 1.00)
VOC content:	898.8 g/l / 7.50 lb/gl
VOC content (less exemp	
Solids content:	14.3 %

Printing date 08/28/2009

Skin effects:

Eye effects:

Sensitization:

Hazard class:

UN-Number:

IMDG Class:

15 Regulations

TSCA:

CPSC:

CANADIAN

EPA:

Label

Page 3/4

Material Safety Data Sheet acc. to ISO/DIS 11014 Reviewed on 08/28/2009 Trade name: OLDS BRONZE (Contd. of page 2) 10 Stability and reactivity: Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures. Hazardous Reactions: No dangerous reactions known. 11 Toxicological information: No irritant effect. Irritating effect. No sensitizing effects known. **12 Ecological information** Other information: This product does not contain any chlorofluorocarbons (CFC's) or chlorinated solvents. Acquatic toxicity: Hazardous for water, do not empty into drains. 13 Disposal considerations DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. Completely empty cans should be recycled. **Recommendation:** 14 Transport information: 2.1 Identification number: N/A 2.1 2 ADR/RID/TDG class: 5F Gases 1950 2.1 Packaging group: 11 F-D,S-U EMS Number: Marine pollutant: Yes Symbol (fish and tree) ICAO/IATA Class: 2.1 Propper shipping name: Aerosols, Flammable Consumer Commodity ORM-D SARA Section 355 (extremely hazardous substances): None of the ingredients in this product are listed. SARA Section 313 (Specific toxic chemical listings): 108-88-3 Toluene 1330-20-7 xylene (mix) 100-41-4 ethyl benzene 7440-50-8 Copper Powder All ingredients are listed. This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. California Proposition 65 chemicals known to cause cancer: 100-41-4 ethyl benzene California Proposition 65 chemicals known to cause developmental toxicity: 108-88-3 Toluene **ENVIRONMENTAL** PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List. **Canadian WHMIS:** D2A A= Known human carcinogen B= Probable human carcinogen C= Possible human carcinogen D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

'Data are inadequate for an assessment of human carcinogeni potential.' ŀ

11:	'Inadequate information to assess	carcinogenic notential '	

		Acetone	<u> </u>
ſ	108-88-3		I
		xylene (mix)	
Г		ethyl benzene	D
	7440-50-8	Copper Powder	D
			(Contd. on page 4) USA
			054

USA

Printing date 08/28/2009

Material Safety Data Sheet acc. to ISO/DIS 11014 Reviewed on 08/28/2009

IARC:	(Contd. of pag Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence carcinogenicity. Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.
108-88-3 Toluene	3
1330-20-7 xylene (mix)	3
100-41-4 ethyl benzene	2
ACGIH:	A1-designates a confirmed human carcinogen. A2-designates a suspected human carcinogen. A3-designates an animal carcinogen. A4-designates "not classifiable as a human carcinogen".
67-64-1 Acetone	A
108-88-3 Toluene	A
1330-20-7 xylene (mix)	A
100-41-4 ethyl benzene	A second
NIOSH:	The following substances are regulated in the United States with reference to occupational exposi- limits:
The following substances	are regulated in the United States with reference to occupational exposure limits:
Risk phrases:	Extremely flammable. Irritating to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Safety phrases:	Keep out of the reach of children. Do not breathe gas/fumes/vapour/spray. Do not empty into drains, dispose of this material and its container at hazardous or special wa collection point
	Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.
Other information	Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.
	Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label.