

Casturced DO THE JOB RIGHT.

Safety Data Sheet acc. GHS

Printing date 01/17/2017

Reviewed on 01/17/2017

1 Identification

. Product identifier

. Trade name RAL 7042 SM GL

. Article number: 10152 Manufacturer/Supplier:

The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

Phone: 800-343-9353

Emergency Telephone number: 24/7 - 800-424-9300

2 Hazard(s) identification

. Classification of the substance or mixture						
GHS08 I	Health hazard					
Muta. 1B	H340 May cause genetic defects.					
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.					
	GHS05 Corrosion Eye Dam. 1 H318 Causes serious eye damage.					
	H317 May cause an allergic skin reaction.					
. Label elements . GHS label eleme The product is	classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US					

DO THE JOB RIGHT.

Safety Data Sheet acc. GHS

Printing date 01/17/2017

Trade name RAL 7042 SM GL


. Hazard pictograms



- . Signal word Danger
- . Hazard-determining components of labeling: 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione . Hazard statements Causes serious eye damage. May cause an allergic skin reaction. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure. May form combustible dust concentrations in air. . Precautionary statements Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention if you feel unwell. IF ON SKIN: Wash with plenty of water. Store locked up. Dispose of contents/container in accordance with local/regional/national/international
- . Classification system
- . NFPA ratings (scale 0-4)



HMIS-RATINGS (SCALE 0 - 4)



- . Other hazards
- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.

3 Composition/information on ingredients

. Chemical characterization: Mixtures

. Description: Mixture consisting of the following components with harmless additives.


. Hazardous ingredients:

7727-43-7 barium sulphate, natural

- US ·

(Contd. of page 1)

Reviewed on 01/17/2017





Safety Data Sheet acc. GHS

Reviewed on 01/17/2017

Printing date 01/17/2017

Trade name RAL 7042 SM GL

	(Cont	d. of page 2)
13463-67-7	titanium dioxide	2.5-10%
2451-62-9	1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione Acute Tox. 3, H301; Acute Tox. 3, H331; Muta. 1B, H340; STOT RE 2, H373; Eye Dam. 1, H318; Skin Sens. 1, H317	2.5-10%
1332-58-7	kaolin	< 2.5%
. Additional	information For the wording of the listed hazard phrases refer to sec	tion 16.

4 First-aid measures

. Description of first aid measures

. General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- . After inhalation Supply fresh air and call for doctor for safety reasons. In case of unconsciousness bring patient into stable side position for transport.
- . After skin contact Instantly wash with water and soap and rinse thoroughly.
- . After eye contact Rinse opened eye for several minutes under running water.
- . After swallowing Instantly call for doctor.
- . Information for doctor
- . Most important symptoms and effects, both acute and delayed No further relevant information available.
- . Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- . Extinguishing media
- . Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcoholresistant foam.
- . Special hazards arising from the substance or mixture No further relevant information available.
- . Advice for firefighters
- . Protective equipment: Put on breathing apparatus.

6 Accidental release measures

- . Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Avoid causing dust.
- . Environmental precautions: Do not allow product to reach sewage system or water bodies.
- . Methods and material for containment and cleaning up: Collect mechanically.
- Ensure adequate ventilation.

. Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

. Protective Action Criteria for Chemicals

. PAC-1:		
7727-43-7	barium sulphate, natural	15 mg/m3
13463-67-7	titanium dioxide	30 mg/m3
7631-86-9	silicon dioxide, chemically prepared	18 mg/m3
1344-28-1	aluminium oxide	15 mg/m3
112926-00-8	Silicon dioxide	18 mg/m3
9002-88-4	Ethene, homopolymer	16 mg/m3
		(Contd. on page 4)



Safety Data Sheet acc. GHS

Printing date 01/17/2017

Reviewed on 01/17/2017

Trade name RAL 7042 SM GL

1314-23-4 zirconium dioxide 14 mg/m3 1333-86-4 carbon black 9 mg/m3 14808-60-7 quartz (SiO2) 0.075 mg/m3 20344-49-4 iron hydroxide oxide 24 mg/m3 . PAC-2:			(Contd. of page 3)		
1333-86-4 carbon black 9 mg/m3 14808-60-7 quartz (SiO2) 0.075 mg/m3 20344-49-4 iron hydroxide oxide 24 mg/m3 . PAC-2: 7727-43-7 barium sulphate, natural 170 mg/m3 13463-67-7 titanium dioxide 330 mg/m3 7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 1313-86-4 carbon black 99 mg/m3 1333-86-4 carbon black 99 mg/m3 1333-86-4 carbon black 99 mg/m3 13463-67-7 titanium dioxide 260 mg/m3 1333-86-4 carbon black 99 mg/m3 1344-23-4 zirconium dioxide 260 mg/m3 1333-86-4 carbon black 99 mg/m3 13463-67-7 titanium sulphate, natural 990 mg/m3 1344-28-1 aluminium oxide 2,000 mg/m3 1344-28-1 aluminium oxide 1,000 mg/m3 1344-28-4 aluminium oxide	-		45 mg/m3		
14808-60-7 quartz (SiO2) 0.075 mg/m3 20344-49-4 iron hydroxide oxide 24 mg/m3 . PAC-2: 7727-43-7 barium sulphate, natural 170 mg/m3 13463-67-7 titanium dioxide 330 mg/m3 7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 13133-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 1344-28-1 12926-00-8 Silicon dioxide, chemically prepared 4,500 mg/m3 13463-67-7 titanium oxide 990 mg/m3 132926-00-8 Silicon di					
20344-49-4 iron hydroxide oxide 24 mg/m3 . PAC-2: 170 mg/m3 13463-67-7 titanium dioxide 330 mg/m3 7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 1314-23-4 zirconium dioxide 210 mg/m3 1314-23-4 zirconium dioxide 99 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1313-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 132926-00-8 Silicon dioxide 1,200 mg/m3 112926-00-8 Silicon dioxide 1,200 mg			-		
. PAC-2: 7727-43-7 barium sulphate, natural 170 mg/m3 13463-67-7 titanium dioxide 330 mg/m3 7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1313-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 13463-67-7 titanium dioxide 990 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 132926-00-8 Silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 1,200 mg/m3 132926-00-8 Silicon dioxide 1,200 mg/m3 1312926-00-8 Silicon dioxide 1	14808-60-7		2		
7727-43-7 barium sulphate, natural 170 mg/m3 13463-67-7 titanium dioxide 330 mg/m3 7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 1314-23-4 zirconium dioxide 210 mg/m3 1314-23-4 zirconium dioxide 99 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 13463-67-7 titanium dioxide 1,000 mg/m3 13462-60-8 silicon dioxide, chemically prepared 4,500 mg/m3 13462-60-7 silicon dioxide, chemically prepared 1,200 mg/m3 13462-60-8 silicon dioxide 1,000 mg/m3 1314-23-4 aluminium oxide 1,000 mg/m3 1314-	20344-49-4	iron hydroxide oxide	24 mg/m3		
13463-67-7 titanium dioxide 330 mg/m3 7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 1314-23-4 zirconium dioxide 210 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1333-86-4 carbon black 99 mg/m3 13463-67-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 990 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 112926-00-8 Silicon dioxide 1,000 mg/m3 112926-00-8 Silicon dioxide 1,300 mg/m3 112926-00-8 Silicon dioxide 1,000 mg/m3 11314-23-4 zirconium dioxide <th>. PAC-2:</th> <td></td> <td></td>	. PAC-2:				
7631-86-9 silicon dioxide, chemically prepared 740 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1333-86-4 carbon black 99 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 2000 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 1344-28-1 aluminium oxide 2,000 mg/m3 1344-28-1 silicon dioxide, chemically prepared 4,500 mg/m3 13463-67-7 titanium dioxide 990 mg/m3 13462-60-8 silicon dioxide, chemically prepared 4,500 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 112926-00-8 Silicon dioxide 1,300 mg/m3 112926-00-8 Silicon dioxide 1,300 mg/m3 112926-00-8 Silicon dioxide 1,300 mg/m3 112926-00-8 Sili	7727-43-7	barium sulphate, natural	170 mg/m3		
1344-28-1 aluminium oxide 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1334-23-4 zirconium dioxide 110 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 112926-00-8 silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 silicon dioxide 680 mg/m3 112926-00-8 silicon dioxide 590 mg/m3 112926-00-8 silicon dioxide 590	13463-67-7	titanium dioxide	330 mg/m3		
112926-00-8 Silicon dioxide 200 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 .PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 13463-67-7 titanium dioxide 990 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 silicon dioxide, chemically prepared 4,500 mg/m3 112926-00-8 silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	7631-86-9	silicon dioxide, chemically prepared	740 mg/m3		
9002-88-4 Ethene, homopolymer 170 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 112926-00-8 silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 590 mg/m3 1314-23-4 zirconium dioxide 590 mg/m3 1333-86-4 carbon black 590 mg/m3	1344-28-1	aluminium oxide	170 mg/m3		
471-34-1 calcium carbonate 210 mg/m3 1314-23-4 zirconium dioxide 110 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 200 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1314-23-4 zirconium dioxide 590 mg/m3 1333-86-4 carbon black 590 mg/m3	112926-00-8	Silicon dioxide	200 mg/m3		
1314-23-4 zirconium dioxide 110 mg/m3 1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide, chemically prepared 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 1314-23-4 zirconium dioxide 1,300 mg/m3 1314-23-4 zirconium dioxide 590 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	9002-88-4	Ethene, homopolymer	170 mg/m3		
1333-86-4 carbon black 99 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	471-34-1	calcium carbonate	210 mg/m3		
14808-60-7 quartz (SiO2) 33 mg/m3 20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	1314-23-4	zirconium dioxide	110 mg/m3		
20344-49-4 iron hydroxide oxide 260 mg/m3 . PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	1333-86-4	1333-86-4 carbon black			
. PAC-3: 7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	14808-60-7	14808-60-7 quartz (SiO2)			
7727-43-7 barium sulphate, natural 990 mg/m3 13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	20344-49-4 iron hydroxide oxide				
13463-67-7 titanium dioxide 2,000 mg/m3 7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	. PAC-3:				
7631-86-9 silicon dioxide, chemically prepared 4,500 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	7727-43-7	barium sulphate, natural	990 mg/m3		
1344-28-1 aluminium oxide 990 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	13463-67-7	titanium dioxide	2,000 mg/m3		
112926-00-8 Silicon dioxide 1,200 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m3		
9002-88-4 Ethene, homopolymer 1,000 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	1344-28-1	aluminium oxide	990 mg/m3		
471-34-1 calcium carbonate 1,300 mg/m3 1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	112926-00-8	Silicon dioxide	1,200 mg/m3		
1314-23-4 zirconium dioxide 680 mg/m3 1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	9002-88-4	Ethene, homopolymer	1,000 mg/m3		
1333-86-4 carbon black 590 mg/m3 14808-60-7 quartz (SiO2) 200 mg/m3	471-34-1	calcium carbonate	1,300 mg/m3		
14808-60-7 quartz (SiO2) 200 mg/m3	1314-23-4	1314-23-4 zirconium dioxide 6			
	1333-86-4	1333-86-4 carbon black .			
20344 - 49 - 4 iron hydroxide oxide	14808-60-7 quartz (SiO2) 200				
	20344-49-4	iron hydroxide oxide	1,600 mg/m3		

7 Handling and storage

. Handling

. Precautions for safe handling

No special measures required. Thorough dedusting. Keep containers tightly sealed. Ensure good ventilation/exhaustion at the workplace. Open and handle container with care. . Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep breathing equipment ready. Dust can combine with air to form an explosive mixture.

- . Conditions for safe storage, including any incompatibilities . Storage
- . Requirements to be met by storerooms and containers: Store only in the original container. Static charges may build up in the powder
- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep container tightly sealed.

Eastwood) DO THE JOB RIGHT.

Safety Data Sheet acc. GHS

Printing date 01/17/2017

Trade name RAL 7042 SM GL

. Specific end use(s) No further relevant information available.

(Contd. of page 4)

8 Exposure controls/personal protection

Components wit	h critical values that require monitoring at the workplace:
-	um sulphate, natural
PEL (U.S.A)	Long-term value: 15* 5** mg/m ³
	*total dust **respirable fraction
REL (U.S.A)	Long-term value: 10* 5** mg/m ³
	*total dust **respirable fraction
TLV (U.S.A)	Long-term value: 5* mg/m³ *inhalable fraction; E
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m ³
. ,	total dust
LMPE (Mexico)	Long-term value: 10 mg/m³
13463-67-7 tit	anium dioxide
PEL (U.S.A)	Long-term value: 15* mg/m³ *total dust
REL (U.S.A)	See Pocket Guide App. A
TLV (U.S.A)	Long-term value: 10 mg/m³ withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m ³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m³ A4
2451-62-9 1,3,	5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione
TLV (U.S.A)	Long-term value: 0.05 mg/m³
EL (Canada)	Long-term value: 0.05 mg/m³ R; S
EV (Canada)	Long-term value: 0.05 mg/m³
LMPE (Mexico)	Long-term value: 0.05 mg/m³
1332-58-7 kaol	in
PEL (U.S.A)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (U.S.A)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (U.S.A)	Long-term value: 2* mg/m ³ E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m ³
EV (Canada)	Long-term value: 2(D) mg/m³ respirable
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable

. Exposure controls

.



Reviewed on 01/17/2017



Safety Data Sheet acc. GHS

Printing date 01/17/2017

Trade name RAL 7042 SM GL

. Personal protective equipment . General protective and hygienic measures Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Store protective clothing separately.

. Breathing equipment:



In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

. Protection of hands:



Protective gloves.

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.





Safety Glasses

. Body protection: Protective work clothing.

9 Physical and Chemical Properties

. Information on basic physical and chemi . General Information	cal properties
. Appearance:	
Form:	Solid
Colour:	According to Trade Name
. Smell:	Characteristic
. Odor threshold:	Not determined
. pH-value:	Not applicable
. Change in condition	
Melting point/Melting range:	> 50 C / 120F
Boiling point/Boiling range:	Not applicable
. Flash point:	Not applicable
. Inflammability (solid, gaseous)	Not determined
. Ignition temperature:	
Decomposition temperature:	Not determined
. Self-inflammability:	Product is not selfigniting.
. Danger of explosion:	Product is not explosive. However, formation of explosive air/dust mixtures is possible
. Critical values for explosion:	
Lower:	Not determined.
	(Contd. on page 7)
	US

(Contd. of page 5)

Reviewed on 01/17/2017



Printing date 01/17/2017

Trade name RAL 7042 SM GL

		(Contd. of page 6)
Upper:	Not determined.	
. Steam pressure:	Not applicable.	
. Density (Specific gravity) at 20 °C (68 °F) . Relative density . Vapor density . Evaporation rate	1.6 g/cm ³ (13.352 lbs/gal) Not determined. Not applicable. Not applicable.	
. Solubility in / Miscibility with Water:	Unsoluble	
. Partition coefficient (n-octanol/water):	Not determined.	
. Viscosity: dynamic: kinematic:	Not applicable. Not applicable.	
. Solvent content: Organic solvents:	0.0 %	
Solids content:	100.0 %	

Solids content: . Other information

10 Stability and Reactivity

. Reactivity No further relevant information available.

- . Chemical stability
- . Conditions to be avoided: No decomposition if used according to specifications.
- . Possibility of hazardous reactions No dangerous reactions known
- . Conditions to avoid No further relevant information available.
- . Incompatible materials: No further relevant information available.
- . Hazardous decomposition products: In case of fire: CO, CO2, NOx

11 Toxicological Information

. Information on toxicological effects

- . Acute toxicity:
- . LD/LC50 values that are relevant for classification:

2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione

Oral	LD50	188-1450 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	0.309-0.650 mg/l (rat)

. Primary irritant effect:

- . on the skin: No irritant effect.
- . on the eye: No irritant effect.
- . Sensitization: Sensitization possible by skin contact.
- . Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Irritant

Harmful

The product can cause inheritable damage.

. Carcinogenic categories

. IARC (International Agency for Research on Cancer)				
13463-67-7	7-7 titanium dioxide 2			
7631-86-9	silicon dioxide, chemically prepared	3		
112926-00-8	Silicon dioxide	3		
9002-88-4	Ethene, homopolymer	3		
1333-86-4	carbon black	2B		
	(Contd. on	bage 8)		

Reviewed on 01/17/2017

No further relevant information available.



Reviewed on 01/17/2017

Eastwood) DO THE JOB RIGHT.

Safety Data Sheet

acc. GHS

Printing date 01/17/2017

Trade name RAL 7042 SM GL

	(C	ontd. of page 7)
14808-60-7	quartz (SiO2)	1
. NTP (Nationa	al Toxicology Program)	
14808-60-7	quartz (SiO2)	K
. OSHA-Ca (Oco	cupational Safety & Health Administration)	
None of the	ingredients is listed.	

12 Ecological information

. Toxicity

- . Aquatic toxicity: No further relevant information available.
- . Persistence and degradability No further relevant information available.
- . Behaviour in environmental systems:
- . Bioaccumulative potential No further relevant information available.
- . Mobility in soil No further relevant information available.
- . Additional ecological information:
- . General notes:

Water danger class 3 (Self-assessment): extremely hazardous for water. Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.


Danger to drinking water if even extremely small quantities leak into soil.

- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . **vPvB:** Not applicable.
- . Other adverse effects No further relevant information available.

13 Disposal considerations

. Waste treatment methods

. Recommendation



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

. Uncleaned packagings:

. Recommendation: Disposal must be made according to official regulations.

14	Transport information		
	UN-Number	n/a	
	UN proper shipping name	n/a	
	Transport hazard class(es)		
	DOT, IMDG, IATA		
	Class	Not regulated.	
	Packing group	n/a	
	Environmental hazards:		
	Marine pollutant:	No	
	Transport in bulk according to Annex II of		
	MARPOL73/78 and the IBC Code	Not applicable.	
		1 1	(Contd. on page 9)



Safety Data Sheet acc. GHS

Printing date 01/17/2017

Trade name RAL 7042 SM GL

Reviewed on 01/17/2017

(Contd. of page 8)

15 Regulatory information

. Safety, health and environmental regulations/legislation specific for the substance or mixture

. SARA (Superfund Amendments and Reauthorization Act):

•	Section	355	(Extremly	hazardous	substances):
					-

None of the ingredients is listed.

. Section 313 (Specific toxic chemical listings):

7727-43-7 barium sulphate, natural

1344-28-1 aluminium oxide

. TSCA (Toxic Substances Control Act):

All ingredients are listed.

. Proposition 65:

. Chemicals known to cause cancer:

13463-67-7 titanium dioxide

. Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

. Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

. Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

. Cancerogenity categories

. EPA (Environmental Protection Agency)			
7727-43-7	barium sulphate, natural D, CBD(inh), NL(ora		cal)
. TLV (Threshold Limit Value established by ACGIH)			
13463-67-7	titanium dioxide		A4
1332-58-7	kaolin		Α4
1344-28-1	aluminium oxide		A4
1314-23-4	zirconium dioxide		A4
1333-86-4	carbon black		Α4
14808-60-7	quartz (SiO2)		A2
. NIOSH-Ca (National Institute for Occupational Safety and Health)			
13463-67-7	titanium dioxide		
1333-86-4	carbon black		
14808-60-7	quartz (SiO2)		

. GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



. Signal word Danger

. Hazard-determining components of labeling:

1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione

. Hazard statements Causes serious eye damage. May cause an allergic skin reaction. May cause genetic defects.



(Contd. of page 9)

US

Easturced DO THE JOB RIGHT.

Safety Data Sheet

acc. GHS

Printing date 01/17/2017

Reviewed on 01/17/2017

Trade name RAL 7042 SM GL

May cause damage to organs through prolonged or repeated exposure. May form combustible dust concentrations in air. . Precautionary statements Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention if you feel unwell. IF ON SKIN: Wash with plenty of water. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H301 Toxic if swallowed. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H340 May cause genetic defects. H373 May cause damage to organs through prolonged or repeated exposure. . Date of preparation / last revision 01/17/2017 / -. Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 3: Acute toxicity - Category 3 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 1B: Germ cell mutagenicity - Category 1B STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 . * Data compared to the previous version altered.