

SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 1 of 9

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Manufacturer Product Number : E7301CT
Supplier Product Numbers : 10175Z

1.2 Other Means Of Identification

Other Identifiers : Not Applicable

1.3 Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against

Recommended Use : High temperature coating
Restrictions On Use : None Identified

1.4 Supplier Details

Company Name : The Easthill Group, Inc./The Eastwood Company
Address : 263 Shoemaker Road,
Pottstown, PA 19464 - United States
Phone Number : 800-343-9353
Fax Number : 610-323-6268
Email :
Website :

1.5 24 Hr Emergency Phone Number

Emergency Number : 800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification Of The Substance Or Mixture

Flammable Liquids, Category 2 : Highly flammable liquid and vapour
Serious Eye Damage/Eye Irritation, Category 2a : Causes serious eye irritation
Specific Target Organ Toxicity — Single Exposure, Category 1 : Causes damage to organs
Specific Target Organ Toxicity — Single Exposure, Category 3, Narcosis : May cause drowsiness or dizziness

2.2 Label Elements

Hazard Pictograms :



Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to organs.

SAFETY DATA SHEET

High Temp Coating Matte Silver

Precautionary Statements

: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe fumes. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed: Call a poison center/doctor. Call doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use water, CO₂, dry chemical, or universal aqueous film forming foam to extinguish. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container to local regulations.

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown Acute Toxicity

2.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance

Not Applicable

3.2 Mixture

Ingredient	Cas Number	%	Classification*
Acetone	67-64-1	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Methyl Acetate	79-20-9	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Propylene Glycol Monomethyl Ether Acetate	108-65-6	1 - 5	Flam. Liq. 3, H226
Methanol	67-56-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 1, H370

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 - FIRST-AID MEASURES

4.1 Description Of First-Aid Measures

General Measures

: IF exposed or concerned: Get medical advice/attention.

Eye Contact

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

: Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.

Ingestion

: Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.

Inhalation

: Remove the victim into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.

First-Aid Responder Protection

: Wear adequate personal protective equipment based on the nature and severity of the emergency.



SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 3 of 9

4.2 Most Important Symptoms And Effects, Both Acute And Delayed

Eye Contact	: Eye irritation.
Skin Contact	: Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking skin. May cause more severe response if confined to skin.
Ingestion	: May cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary oedema.
Inhalation	: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.

4.3 Indication Of Immediate Medical Attention And Special Treatment

Notes To Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Immediate Medical Attention	: No Information Available.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

5.2 Specific Hazards Arising From The Chemical Or Mixture

Decomposition Products	: Decomposition products may include: oxides of carbon, smoke, vapors.
Hazards From The Product	: CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to ignition an source.

5.3 Special Protective Actions For Fire-Fighters

Protective Actions	: Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
Protective Equipment	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment And Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Responders	: Use personal protection as recommended in Section 8.

6.2 Environmental Precautions

Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
-------------	---

6.3 Methods And Materials For Containment And Cleaning Up

Containment Procedures	: Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
Cleanup Procedures	: Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information	: The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
Prohibited Materials	: Use of equipment that may cause sparking.

SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 4 of 9

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions For Safe Handling

- General Handling Precautions** : *KEEP OUT OF THE REACH OF CHILDREN. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.*
- Hygiene Recommendations** : *Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.*

7.2 Conditions For Safe Storage Including Any Incompatibilities

- Storage Requirements** : *Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.*
- Incompatibilities** : *Segregate storage away from materials indicated in Section 10.*

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m ³)	1200 mg/m ³
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m ³)	1780 mg/m ³
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
BEI	Acetone in urine, End of shift (Ns)	25 mg/l
Methyl Acetate (79-20-9)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	610 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	US IDLH (ppm)	3100 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	610 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	760 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
California	California PEL (TWA) (mg/m ³)	610 mg/m ³
California	California PEL (TWA) (ppm)	200 ppm
California	California PEL (STEL) (mg/m ³)	760 mg/m ³
California	California PEL (STEL) (ppm)	250 ppm
Propylene Glycol Monomethyl Ether Acetate (108-65-6)		
California	California PEL (TWA) (mg/m ³)	541 mg/m ³
California	California PEL (TWA) (ppm)	100 ppm
Not applicable		
Methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm



SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 5 of 9

Methanol (67-56-1)

ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
California	California PEL (TWA) (mg/m ³)	260 mg/m ³
California	California PEL (TWA) (ppm)	200 ppm
California	California PEL (STEL) (mg/m ³)	325 mg/m ³
California	California PEL (STEL) (ppm)	250 ppm
California	California PEL (Ceiling) (ppm)	1000 ppm
BEI	Methanol in Urine, End of shift (B,Ns)	15 mg/l

8.2 Exposure Controls

Engineering Measures	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
Respiratory Protection	: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.
Skin Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed.
Eye/Face Protection	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling.
Other Protective Equipment	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 55.00 °C	Melting / Freezing Point	Not Available
Flash Point, Liquid	> -17.20 °C		
Explosive Limits	LEL: 1.00 UEL: 16.00 vol %	Autoignition Temperature, Liquid	Not Available
Flammability	Flammable Liquid	Density	1.040 g/cm ³
Molecular Weight	Not Available	Weight	8.679 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical Form	Liquid	Heat Of Combustion	Not Available
Odor	Paint-like	Water Solubility	Not Available
Appearance / Color	Silver	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	44.20 % wt	VOC Regulatory	109.82 g/L (0.92 lbs/gal)
Percent VOC	5.20 % wt	VOC Actual	54.08 g/L (0.45 lbs/gal)
Percent HAP	2.60 % wt	HAP Content	27.04 g/L (0.23 lbs/gal)
Global Warming Potential	0.26 GWP	Maximum Incremental Reactivity	0.2210 g O ₃ /g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY



SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 6 of 9

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Stability : This product is stable.

10.3 Possibility Of Hazardous Reactions

Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions To Avoid

Conditions : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

10.5 Incompatible Materials

Incompatibilities : Strong Oxidizing Agents, Alkali Metals, Strong Acids, Potassium t-Butoxide, Hydrogen Peroxide.

10.6 Hazardous Decomposition Products

Products : Oxides of carbon, Formaldehyde, Methanol, Acetic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1.1 Information On Toxicological Effects

Acetone (67-64-1)

LD50 Oral (Rat)	5800 mg/kg (ECHA)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (Lit.)

Methyl Acetate (79-20-9)

LD50 Oral (Rat)	6970 mg/kg (Lit.)
LD50 Dermal (Rabbit)	> 5000 mg/kg (RTECS)
LC50 Inhalation (Rat)	16000 - 32000 (ChemInfo)

Propylene Glycol Monomethyl Ether Acetate (108-65-6)

LD50 Oral (Rat)	8532 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 5000 mg/kg bodyweight (RTECS)
LC50 Inhalation (Rat)	5250 ppm/4h (ChemInfo)

Methanol (67-56-1)

LD50 Oral (Rat)	5850 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	15800 mg/kg (RTECS)
LC50 Inhalation (Rat)	131.25 mg/l/4h (ECHA)
LC50 Inhalation (Rat)	64000 ppm/4h (ChemInfo)

11.1.2 Health Hazard Classification

Skin Corrosion/Irritation	: Not classified
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory Or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Not classified
Stot-Single Exposure	: Causes damage to organs. May cause drowsiness or dizziness.
Stot-Repeated Exposure	: Not classified
Aspiration Hazard	: Not classified
Carcinogen Data	: None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 7 of 9

11.1.3 Information On The Likely Routes Of Exposure

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.

11.1.4 Symptoms Related To The Physical, Chemical And Toxicological Characteristics

Symptoms of Exposure : Eye Irritation, Nose Irritation, Throat Irritation, Skin Irritation, Headache, Dizziness, Nausea, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Optical Nerve Damage, Chest Tightness.

11.1.5 Delayed And Immediate Effects And Also Chronic Effects From Short And Long Term Exposure

Delayed Effects : No known delayed effects.
Immediate Effects : No known immediate effects.
Chronic Effects : Methyl alcohol may be fatal or cause blindness if swallowed.
Target Organs : Central Nervous System, Eyes, Gastrointestinal Tract, Respiratory System, Skin.
Medical Conditions Aggravated : None identified.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Acetone (67-64-1)	
LC50 fish 1	5540 mg/l 96h, Rainbow Trout (Lit.)
EC50 Daphnia 1	12600 mg/l 48h, Water Flea (Lit.)
Methyl Acetate (79-20-9)	
LC50 fish 1	250 - 350 mg/l Zebra Fish - 96hr
EC50 Daphnia 1	1026.7 mg/l Water Flea - 48hr
Propylene Glycol Monomethyl Ether Acetate (108-65-6)	
LC50 fish 1	100 - 180 ml/l Rainbow Trout - 96hr
EC50 Daphnia 1	373 mg/l Water Flea - 48hr
Methanol (67-56-1)	
LC50 fish 1	15400 mg/l Bluegill Sunfish - 96h
EC50 Daphnia 1	> 10000 mg/l Water Flea - 48hr
EC50 other aquatic organisms 1	22000 mg/l Freshwater Algae - 96hr

12.2 Ecological Properties

Acetone (67-64-1)	
Persistence and degradability	Biodegradability >90% / 28 days.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.20 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 days; Literature study)
BCF fish 1	0.69 (BCF)
BCF other aquatic organisms 1	3 (BCF; BCFWIN)
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.
Methyl Acetate (79-20-9)	
Persistence and degradability	Biodegradability 70% / 28 days.
Chemical oxygen demand (COD)	1511.8 mg/g
ThOD	1510 mg/g
BCF fish 1	< 1 (BCF)
Log Pow	0.18
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.68
Propylene Glycol Monomethyl Ether Acetate (108-65-6)	
Persistence and degradability	Biodegradability 100% / 8 days.
Biochemical oxygen demand (BOD)	330 mg/g

SAFETY DATA SHEET

High Temp Coating Matte Silver

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 8 of 9

Propylene Glycol Monomethyl Ether Acetate (108-65-6)

Chemical oxygen demand (COD)	1740 mg/g
ThOD	1820 mg/g
Log Pow	0.56
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Log Koc	0.36

Methanol (67-56-1)





Persistence and degradability	Biodegradability 72% / 5 days.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.5 g O ₂ /g substance
BOD (% of ThOD)	0.8 (Literature study)
BCF fish 1	< 10 (BCF; 72 h; <i>Leuciscus idus</i>)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.44

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.
Incineration Precautions	: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information	Ground Transportation (DOT)	Air Transportation (IATA)	Ocean Transportation (IMDG)
Identification Number	UN1263	UN1263	UN1263
Proper Shipping Name	Paint, Limited Quantity	Paint, Limited Quantity	Paint, Limited Quantity
Hazard Class(es)	3	3	3
Packaging Group	II	II	II
Limited Quantity	Yes 	Yes 	Yes 
Marine Pollutant	No	No	No
Hazard Labels		3 - Flammable liquid 	

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

TSCA Inventory	: All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory
-----------------------	---



SAFETY DATA SHEET

Print Date: 08/10/2016
Revision Date: 08/09/2016
Version: 3.0 (EN)
Page 9 of 9

High Temp Coating Matte Silver

SARA 313 Reporting

: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methanol	CAS No 67-56-1	1 - 5%
----------	----------------	--------

Applicable Federal Regulations

: One or more ingredients are regulated by other Federal Regulations.

Acetone (67-64-1)		
CERCLA RQ	5000 lb	

Methanol (67-56-1)		
CERCLA RQ	5000 lb	

15.2 State Regulations

California Proposition 65

: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Methanol (67-56-1)		
Developmental Toxicity	Yes	

State Right-to-Know Lists

: The following ingredients appear on one or more state Right-to-Know lists.

Acetone (67-64-1)		
U.S. - Massachusetts - Right To Know List		
U.S. - New Jersey - Right to Know Hazardous Substance List		
U.S. - Pennsylvania - RTK (Right to Know) List		

Methyl Acetate (79-20-9)		
U.S. - New Jersey - Right to Know Hazardous Substance List		

Methanol (67-56-1)		
U.S. - New Jersey - Right to Know Hazardous Substance List		
U.S. - Pennsylvania - RTK (Right to Know) List		

SECTION 16 - OTHER INFORMATION

SDS Compliance

: This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at msds@chem-pak.com.
OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200
Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

Disclaimer Of Liability

: The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist

Full text of H-statements

H Code	H Phrase
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H311	Toxic in contact with skin
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs