Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

Printing date 08/28/2009	Reviewed on 08/28/2009
1 Identification of substa	nce
Trade name:	CARB RENEW BRONZE
Product codes:	10179Z
Manufacturered for:	The Easthill Group
	Dba The Eastwood Company
	263 Shoemaker Road Pottstown, PA 19464
	USA and Canada: 800-345-1178
	Outside USA: (610)-323-2200
Emergency information:	Chem-Trec 1-800-434-9300
2 Composition/Data on co	omponente
Chemical Description:	This product is a mixture of the substances listed below with nonhazardous additions.
Dangerous components: 67-64-1 Acetone	28.19%
74-98-6 propane	18.79%
108-88-3 Toluene	13.8%
106-97-8 n-butane	11.04%
2807-30-9 Glycol Ether EP	
1330-20-7 xylene (mix)	3.33%
	5.5570
3 Hazards identification	
Hazard description:	A Harmful
nazaru uescription.	Extremely flammable
Physical dangers:	Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and
	flame.
	Has narcotizing effect.
	Extremely flammable. Irritating to eyes.
	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
	Keep out of the reach of children.
Effects of chronic	
overexposure:	May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be
	harmful or fatal.
NFPA ratings (0 - 4):	Health = 1
	Fire = 4
HMIS-ratings (0 - 4):	Reactivity = 3 Health= 1
11013-1atings (0 - 4).	Fire= 4
	Physical Hazard= 3
4 First aid measures	Oursele frank nie annault dastanie and af annalaiste
After inhalation: After skin contact:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult
•	a doctor.
After swallowing:	Contact physician or poison control center.
5 Fire fighting measures	
Extinguishing agents:	CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
Protective equipment:	No special measures required.
6 Accidental release mea	sures
Personal safety:	Wear protective equipment. Keep unprotected persons away.
Environmental safety:	Do not allow product to reach sewage systems or ground water.
Clean-up/collection:	Ensure adequate ventilation.
7 Llendling and store w	
7 Handling and storage	
7 Handling and storage Fire/explosion protection:	
	 Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges. Observe pressurized container storage regulations. Consult with your local authorities.

(Contd. on page 2)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009

Trade name: CARB RENEW BRONZE

Reviewed on 08/28/2009

	(Contd. of page 1
8 Exposure controls and	personal protection:
	alues that require monitoring at the workplace:
67-64-1 Acetone	
PEL 2400 mg/m ³ , 1000 pp REL 590 mg/m ³ , 250 ppm	m
TLV Short-term value: 178	32 mg/m³, 750 ppm
Long-term value: 118	8 mg/m³, 500 ppm
BEI 74-98-6 propane	
PEL 1800 mg/m ³ , 1000 pp	
REL 1800 mg/m ³ , 1000 pp	m
TLV Varies mg/m ³ , 1000 p	pm
PEL Short-term value: C 3	
Long-term value: 200	ppm
*10-min peak per 8-hi	r shift
REL Short-term value: 560 Long-term value: 375	/ mg/m³, 150 ppm mg/m³ 100 ppm
TLV 75 mg/m ³ , 20 ppm	
106-97-8 n-butane	
REL 1900 mg/m ³ , 800 ppm	
TLV Varies mg/m³, 1000 p 1330-20-7 xylene (mix)	pin
PEL 435 mg/m ³ , 100 ppm	
REL Short-term value: 655	5 mg/m³, 150 ppm
Long-term value: 435	mg/m³, 100 ppm
TLV Short-term value: 651 Long-term value: 434	mg/m ³ , 150 ppm mg/m ³ 100 ppm
BEI	
Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In case
	where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If yo suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Protective gloves. The glove material has to be impermeable and resistant to the substance. No glov
Eye protection:	recommendation can be given. Tightly sealed goggles
9 Physical and chemical	properties:
General Information:	•••
Odor:	Aromatic
Boiling point:	-44°C
Flash point:	-19°C
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 12
	degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density:	
Specific Gravity:	Between 0.77 and 0.85 (Water equals 1.00)
VOC content:	834.8 g/l / 6.97 lb/gl
VOC content (less exemp	•
Solids content:	17.2 %
10 Stability and reactivity	
10 Stability and reactivity: Conditions to avoid:	
Hazardous Reactions:	Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures. No dangerous reactions known.
11 Toxicological informat	ion:
Skin effects:	No irritant effect.
Eye effects:	Irritating effect.
Sensitization:	No sensitizing effects known.
12 Ecological information	
12 Ecological information Other information:	This product does not contain any chlorofluorocarbons (CFC's) or chlorinated solvents.

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009

Reviewed on 08/28/2009

nting date 08/28/2009	Reviewed on 08/2	28/2005
ade name: CARB RENEW BR	ONZE	
	(Contd. of	page 2
Acquatic toxicity:	Hazardous for water, do not empty into drains.	
3 Disposal consideration	e	
		t
DISPOSAL METHOD: DIS	pose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or con e disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.	npact
Recommendation:	Completely empty cans should be recycled.	
Recommendation.		
4 Transport information:		
Hazard class:	2.1	
Identification number:	N/A	
Label	2.1	
ADR/RID/TDG class:	2 5TF Gases	
UN-Number:	1950	
IMDG Class:	2	
Packaging group: EMS Number:	ll F-D,S-U	
Marine pollutant:	No	
ICAO/IATA Class:	2.1	
Propper shipping name:	Aerosols, Flammable	
	Consumer Commodity ORM-D	
5 Regulations		
	nely hazardous substances):	
None of the ingredients in the		
	ic toxic chemical listings):	
108-88-3 Toluene		
1330-20-7 xylene (mix)		
TSCA:	All ingredients are listed.	
CPSC:	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.	
	chemicals known to cause cancer:	
100-41-4 ethyl benzene		
California Proposition 65		
chemicals known to caus developmental toxicity:	e 108-88-3 Toluene	
CANADIAN	100-00-3 Toluene	
ENVIRONMENTAL		
PROTECTION ACT:	All hazardous ingredients for this product appear on the Canadian Domestice Substance List.	
EPA:	A= Known human carcinogen B= Probable human carcinogen	
	C= Possible human carcinogen	
	D= Not classifiable as to human carcinogenicity: Inadequate human and animal eviden	ce o
	carcinogenicity (or no data is available).	
	 Data are inadequate for an assessment of human carcinogeni potential.' Inadequate information to assess carcinogenic potential.' 	
67-64-1 Acetone	II: 'Inadequate information to assess carcinogenic potential.'	
108-88-3 Toluene		
1330-20-7 xylene (mix)		
IARC:	Group 2B: The ingredient is possibly carcinogenic to humans. There is limited eviden	Ce of
	carcinogenicity.	
	Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.	
108-88-3 Toluene		3
14807-96-6 Talc (Mg3H2(S	SiO3)4)	3
1330-20-7 xylene (mix)		3
ACGIH:	A1-designates a confirmed human carcinogen.	
	A2-designates a suspected human carcinogen.	
	A3-designates an animal carcinogen. A4-designates "not classifiable as a human carcinogen".	
67-64-1 Acetone	איז עסטאומנסי ווטי טמסטוומטוב מס מ וועווומוו טמוטווטעכוו .	A4
108-88-3 Toluene		A4
14807-96-6 Talc (Mg3H2(S	Si(C3)4)	A4
1330-20-7 xylene (mix)	ודןסטת	A4 A4
NIOSH:	The following substances are regulated in the United States with reference to occupational exp	
	The following substances are regulated in the onliced states with reference to occupational exp	Joure
	limits:	
The following substances a		

Risk phrases: Extremely flammable

Extremely flammable. Irritating to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

(Contd. on page 4) USA

Page 4/4

USA

Reviewed on 08/28/2009

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009

Trade name: CARB RENEW BRONZE (Contd. of page 3) Safety phrases: Keep out of the reach of children. Do not breathe gas/fumes/vapour/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas. **16 Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Contact: **Regulatory Affairs** Abbreviations and GHS: Globally Harmonized System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) PP: Severe Marine Pollutant P: Marine Pollutant HMIS: Hazardous Materials Identification System (USA) acronyms: P: Marine Pollutant HMIS: Hazardous Materials Identification System (USA) ISO: International Organization for Standardization EPA: Environmental Protection Agency IARC: International Agency for the Research of Cancer NIOSH: National Institute for Occupational Safety and Health TSCA: Toxic Substances Control Act CPSC: Consumer Product Safety Commission