# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009 Reviewed on 08/28/2009

#### 1 Identification of substance

Trade name: **CARB RENEW SILVER** 

**Product codes:** 10187Z

Manufacturered for: The Easthill Group

Dba The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464 USA and Canada: 800-345-1178 Outside USA: (610)-323-2200

Chem-Trec 1-800-434-9300 **Emergency information:** 

## 2 Composition/Data on components

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous	s components:	
	Acetone	28.19%
74-98-6	propane	18.79%
108-88-3	Toluene	13.8%
106-97-8		11.04%
	Glycol Ether EP	4.52%
1330-20-7	xylene (mix)	3.33%

## 3 Hazards identification

Hazard description:

Harmful

Extremely flammable

**Physical dangers:** Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and

Has narcotizing effect. Extremely flammable. Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Keep out of the reach of children.

Effects of chronic

overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

Health = NFPA ratings (0 - 4):

Fire = Reactivity = 3

HMIS-ratings (0 - 4): Health=

Fire= Physical Hazard= 3

## 4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult

a doctor.

After swallowing: Contact physician or poison control center.

## 5 Fire fighting measures

**Extinguishing agents:** CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam.

**Protective equipment:** No special measures required.

#### 6 Accidental release measures

Personal safety: Wear protective equipment. Keep unprotected persons away. Do not allow product to reach sewage systems or ground water. Environmental safety:

Clean-up/collection: Ensure adequate ventilation.

### 7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

(Contd. on page 2)

USA

## **Material Safety Data Sheet** acc. to ISO/DIS 11014

Printing date 08/28/2009 Reviewed on 08/28/2009

Trade name: CARB RENEW SILVER

(Contd. of page 1)

## 8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL | 2400 mg/m³, 1000 ppm REL | 590 mg/m³, 250 ppm

Short-term value: 1782 mg/m³, 750 ppm Long-term value: 1188 mg/m³, 500 ppm

BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm REL 1800 mg/m³, 1000 ppm TLV Varies mg/m³, 1000 ppm

108-88-3 Toluene

Short-term value: C 300; 500\* ppm PEL Long-term value: 200 ppm

10-min peak per 8-hr shift

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm

75 mg/m³, 20 ppm 106-97-8 n-butane

REL 1900 mg/m<sup>3</sup>, 800 ppm

TLV Varies mg/m³, 1000 ppm

1330-20-7 xylene (mix)

PEL 435 mg/m<sup>3</sup>, 100 ppm

Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm Short-term value: 651 mg/m³, 150 ppm REL TLV

Long-term value: 434 mg/m³, 100 ppm

BEI

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases

where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Hand protection:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove

recommendation can be given.

Eye protection: Tightly sealed goggles

## 9 Physical and chemical properties:

**General Information:** 

Odor: Aromatic **Boiling point:** -44°C -19°C Flash point:

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120

degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % **Upper Explosion Limit:** 10.9 Vol % Vapor Pressure: 40 PSI, 2750 hPa

Density:

**Specific Gravity:** Between 0.77 and 0.85 (Water equals 1.00)

VOC content: 834.8 g/l / 6.97 lb/gl

VOC content (less exempt solvents): 53.7 % Solids content: 17.2 %

# 10 Stability and reactivity:

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

**Hazardous Reactions:** No dangerous reactions known.

# 11 Toxicological information:

Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

## 12 Ecological information

Other information: This product does not contain any chlorofluorocarbons (CFC's) or chlorinated solvents.

(Contd. on page 3)

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009 Reviewed on 08/28/2009

Trade name: CARB RENEW SILVER

Acquatic toxicity: Hazardous for water, do not empty into drains. (Contd. of page 2)

## 13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty can's should be recycled. Recommendation:

### 14 Transport information:

**Hazard class:** 2.1 Identification number: N/A 2.1 2 Label

ADR/RID/TDG class: 5TF Gases

**UN-Number:** 1950 **IMDG Class:** 2 Packaging group: Ш **EMS Number:** F-D,S-U Marine pollutant: No ICAO/IATA Class: 2.1

Aerosols, Flammable Propper shipping name:

Consumer Commodity ORM-D

### 15 Regulations

# SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

# SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene 1330-20-7 xylene (mix)

TSCA: All ingredients are listed.

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. CPSC:

# California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene California Proposition 65

chemicals known to cause

developmental toxicity: 108-88-3 Toluene

CANADIAN **ENVIRONMENTAL** 

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

EPA:

A= Known human carcinogen B= Probable human carcinogen C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of

carcinogenicity (or no data is available).

'Data are inadequate for an assessment of human carcinogeni potential.'

'Inadequate information to assess carcinogenic potential.

67-64-1	etone I	
108-88-3	uene II	٦
1330-20-7	ene (mix)	٦

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of

carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	Toluene	3
14807-96-6	Talc (Mg3H2(SiO3)4)	3
1330-20-7	xylene (mix)	3

ACGIH: A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1		A4
108-88-3	Toluene	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
1330-20-7	xylene (mix)	A4

NIOSH: The following substances are regulated in the United States with reference to occupational exposure

The following substances are regulated in the United States with reference to occupational exposure limits:

Risk phrases: Extremely flammable.

Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

(Contd. on page 4)

(Contd. of page 3)

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 08/28/2009 Reviewed on 08/28/2009

Trade name: CARB RENEW SILVER

Safety phrases: Keep out of the reach of children.

Do not breathe gas/fumes/vapour/spray.

Do not empty into drains, dispose of this material and its container at hazardous or special waste

collection point

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and

acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) PP: Severe Marine Pollutant P: Marine Pollutant

P: Marine Pollutant
HMIS: Hazardous Materials Identification System (USA)
ISO: International Organization for Standardization
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission

USA