

#### **Material Safety Data Sheet** acc. to ISO/DIS 11014

Reviewed on 05/06/2009 Printing date 05/06/2009

# 1 Identification of substance

Trade name:

DETAIL CLEAR

Product code:

The Easthill Group Dba/The Eastwood Company

Manufacturer/Supplier:

263 Shoemaker Road Pottstown, PA 19464 USA & Canada: 800-345-1178 Outside USA: 610-323-2200

**Emergency information:** 

Emergency contact: Chem-Trec: 800-424-9300

#### 2 Composition/Data on components

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous	angerous components:		
67-64-1	Acetone	21.7%	
74-98-6	propane	15.68%	
110-19-0	isobutyl acetate	14.16%	
108-88-3	Toluene	12.94%	
2807-30-9	Glycol Ether EP	10.25%	
106-97-8	n-butane	9.21%	
1330-20-7	xylene (mix)	1.35%	

## 3 Hazards identification

Hazard description:



Harmful

Extremely flammable

Physical dangers:

Extremely flammable.

Irritating to eyes. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Keep out of the reach of children.

Effects of chronic

overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage

kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

NFPA ratings (scale 0 - 4): Health =

Fire =

HMIS-ratings (scale 0 - 4): Health=

Reactivity = 3Fire=

Physical Hazard=

#### 4 First aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist,

consult a doctor.

After swallowing:

Contact physician or poison control center.

#### 5 Fire fighting measures

**Extinguishing agents:** 

CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam.

Protective equipment: No special measures required.

# 6 Accidental release measures

Personal safety

precautions:

Wear protective equipment. Keep unprotected persons away.

**Environmental safety** 

precautions:

Do not allow product to reach sewage systems or ground water.

Measures for cleaning/

collecting: Ensure adequate ventilation.

# 7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic

discharges.

(Contd. on page 2)



# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 05/06/2009 Reviewed on 05/06/2009

Trade name: DETAIL CLEAR

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

(Contd. of page 1)

ponents with limit values that require monitoring at the workplace:
-1 Acetone
2400 mg/m³, 1000 ppm 590 mg/m³, 250 ppm Short-term value: 1782 mg/m³, 750 ppm Long-term value: 1188 mg/m³, 500 ppm BEI
3-6 propane
1800 mg/m³, 1000 ppm 1800 mg/m³, 1000 ppm Varies mg/m³, 1000 ppm
9-0 isobutyl acetate
700 mg/m³, 150 ppm 700 mg/m³, 150 ppm 713 mg/m³, 150 ppm
8-3 Toluene
Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm 75 mg/m³, 20 ppm
7-8 n-butane
1900 mg/m³, 800 ppm Varies mg/m³, 1000 ppm
20-7 xylene (mix)
435 mg/m³, 100 ppm Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm

Protective hygienic

measures:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. Please consult an authority on chemical hygeine monitoring if you suspect overexposure conditions exist and

need a specific recommendation on proper ventilation techniques and personal protection.

Protection of hands:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove

recommendation can be given.

Eye protection:

Tightly sealed goggles

# 9 Physical and chemical properties:

General Information:

Odor:

Aromatic -44°C

Boiling point/Boiling range:

-19°C

Flash point:

-19°C

Ignition temperature:
Auto igniting:

230°C

\_\_\_\_\_

Product is not self-igniting.

Danger of explosion:

Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120

degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: Upper Explosion Limit:

1.7 Vol % 23.3 Vol %

Vapor Pressure:

40 PSI, 2750 hPa

Density at 20°C:

0.75778 g/cm<sup>3</sup>

(Contd. on page 3)

(Contd. of page 2)



#### Material Safety Data Sheet acc. to ISO/DIS 11014

Reviewed on 05/06/2009 Printing date 05/06/2009

Trade name: DETAIL CLEAR

Between 0.77 and 0.85 (Water equals 1.00) Specific Gravity:

628.7 g/l / 5.25 lb/gl VOC content:

VOC content (less exempt solvents): 65.7 % MIR value: 65.7 % MIR Value: 1.41 12.6 % Solids content:

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Possibility of Hazardous

Reactions:

No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect. Primary effect on the eye: Irritating effect.

Sensitization:

No sensitizing effects known.

Additional toxicological

information:

The product shows the following dangers according to internally approved calculation methods for

preparations:

12 Ecological information

Other information:

This product does not contain any chlorofluorocarbons (CFC's) or chlorinated solvents.

Acquatic toxicity: Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact.

Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:

Completely empty cans should be recycled.

14 Transport information:

Hazard class: 2.1 Identification number: N/A

Label

2.1+8 2 5FC Gases

F-D,S-U

No

2.1

ADR/RID class: 1950 **UN-Number:** IMDG Class: 2.1

Packaging group: EMS Number: Marine pollutant:

ICAO/IATA Class: Propper shipping name:

Aerosols, Flammable

Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed

SARA Section 313 (Specific toxic chemical listings):

108-88-3 | Toluene

Control Act):

1330-20-7 xylene (mix)

TSCA (Toxic Substances

All ingredients are listed.

**CPSC** (Consumer Product

This product is regulated by 16 CFR 1303. It complies with this regulation and does not contain more than 90 ppm of lead.

PROPOSITION 65 Chemicals known to cause cancer:

100-41-4 ethyl benzene

Safety Commission):

(Contd. on page 4)



#### **Material Safety Data Sheet** acc. to ISO/DIS 11014

Reviewed on 05/06/2009 Printing date 05/06/2009

Trade name: DETAIL CLEAR

(Contd. of page 3)

**PROPOSITION 65** 

Chemicals known to cause

developmental toxicity:

108-88-3 Toluene

CANADIAN

PROTECTION ACT:

**ENVIRONMENTAL** 

EPA:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. B= Probable human carcinogen A= Known human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of

carcinogenicity (or no data is available).

	67-64-1	Acetone	I
	110-19-0	isobutyl acetate	D
ı	108-88-3	Toluene	II
ſ	1330-20-7		I

IARC:

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of

carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	Coluene	3
1330-20-7 x	rylene (mix)	3

**ACGIH TLVs:** 

A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.
A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
110-19-0	isobutyl acetate	A4
108-88-3	Toluene	A4
1330-20-7	xylene (mix)	A4

#### NIOSH:

None of the ingredients is listed.

Risk phrases:

Extremely flammable.

Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety phrases:

Keep out of the reach of children.

Keep in a cool place.

Keep container in a well-ventilated place.

Keep away from food, drink and animal feedingstuffs. Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Do not empty into drains, dispose of this material and its container at hazardous or special waste

collection point

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact:

**Řegulatory** Affairs

Abbreviations and

acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

VOC: Volatile Organic Compounds (USA, EÙ)

USA