

**EASTWOOD ZINC PHOSPHATE** duplicates the original appearance of Zinc Phosphate plating. This charcoal gray OEM plating was used on tie rods, center links, spindles, hood hinges and latches as well as sway bars and shifter and carb linkages. Formulated to match the exact appearance of Zinc Phosphate plating in a very durable enamel coating. Resists temperatures up to 300°F, covers up to 6 sq. ft. 4-8% gloss.

**DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT**

1. Surface must be clean and dry before painting. Use Eastwood's PRE Painting Prep to remove grease and oil. For maximum protection, prepare bare metal with primer before top coating. For best results, use when can is between 70°F and 90°F (21°C and 32°C).
2. SHAKE CAN VIGOROUSLY for at least one minute before and occasionally during use. Use several light coats from a distance of 8-10 inches.
3. DO NOT insert any object into can opening. Discard empty can in trash pick-up. DO NOT incinerate or compact.

**IMPORTANT:** To prevent clogging, after each use, invert the can and spray a few short blasts to clear the valve.

**CONTAINS:** Ethyl Acetate (CAS #141-78-6), (Propane (CAS #74-98-6), Acetone (CAS #67-64-1), Carbon Black (CAS #1333-86-4) and Ethyl Benzene (CAS #100-41-4). 54% of the ingredients have an unknown acute toxicity.

**DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

**PRECAUTIONARY STATEMENTS:** Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: do not pierce or burn, even after use. Avoid breathing spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/120°F. Dispose of contents and container in accordance with applicable regulations.

**FIRST AID:** If exposed, concerned or feel unwell: Call a physician. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.




**WARNING: Cancer –**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**VOC CONTENT –** EFI Max MIR 1.20  
**KEEP OUT OF REACH OF CHILDREN**

Only in the event of a chemical emergency involving a spill, leaks, fire, or exposure call Chemtrec toll-free day or night:  
1-800-424-9300 International call collect: (202) 483-7616


Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464  
1-800-343-9353 [www.eastwood.com](http://www.eastwood.com)

© Copyright 2018 Easthill Group, Inc. Made in USA Label #10281ZL 2/18 Rev 1



**DO THE JOB RIGHT.®**

# ZINC PHOSPHATE



- Correct Duplication of OEM Zinc Phosphate Plating
- Temperature Rated to 300°F
- Resists Fading, Chipping and Ultraviolet Rays



Scan for product info

**DANGER: CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. EYE IRRITANT.**  
Read Precautions On Rear Panel Before Use.

Net wt. 12 oz. / 340 grams

10281Z