

MATERIAL SAFETY DATA SHEET

Page 1 of 5
Diamond Clear Satin PS
Part No. 10283ZP Liquid
Revision 1 ~ January 31, 2006

EMERGENCY OVERVIEW

FLAMMABLE LIQUID. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL. INGESTION MAY BE HARMFUL OR FATAL.

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED FOR:	<i>The Easthill Group dba/ The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464 USA & Canada: 800-345-1178 Outside USA: (610) 323-2200</i>	SUPPLIER:	<i>The Easthill Group, Inc. 263 Shoemaker Road Pottstown PA 19464 USA</i>
INFORMATION:		INFORMATION:	610-323-2200
EMERGENCY:	<i>Chem-Trec 800-424-9300</i>	EMERGENCY:	
PRODUCT IDENTIFIER:	10283ZP	SUPPLIER NUMBER:	10283ZP
PRODUCT DESCRIPTION:	<i>Diamond Clear Satin for Painted Surfaces</i>		
PRODUCT TYPE:	<i>Liquid</i>	REVISION NUMBER:	1
CAS NUMBER:	<i>Mixture</i>	REVISION DATE:	<i>January 31, 2006</i>
		PRINT DATE:	<i>January 31, 2006</i>

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	OSHA PEL	NIOSH REL	ACGIH PEL	IDLH	% WT
<i>Light Aliphatic Petroleum Solvent Naphtha</i>	064742-89-8	N/E	N/E	N/E	N/E	20-30
<i>Xylene</i>	001330-20-7	100 ppm	100 ppm	100 ppm	900 ppm	10-20
<i>Ligroine</i>	008032-32-4	N/E	350 mg/m3	300 ppm	N/E	10-20

See Section 11 for LD50 and LC50 Species/Route Information. See Section 15 for Symbol Letters and R Phases.

SECTION 3 HAZARD IDENTIFICATION

ROUTES OF ENTRY:

Skin Contact	T	Skin Absorption	T	Eye Contact	T	Inhalation	T	Ingestion	T
--------------	----------	-----------------	----------	-------------	----------	------------	----------	-----------	----------

EFFECTS OF ACUTE EXPOSURE

EYE: *Liquid contact may cause pain along with moderate eye irritation which may be slow to heal. Vapors may cause irritation.*

SKIN: *Prolonged or repeated exposure may cause skin irritation, even a burn. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin. Extensive skin contact may cause an intense burning sensation followed by a cold, numb feeling which will subside after contact.*

INGESTION: *Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps.*

INHALATION: *Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death.*

OTHER HEALTH HAZARD DATA

EFFECTS OF CHRONIC EXPOSURE: *Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.*

MEDICAL CONDITIONS AGGRAVATED: *May aggravate personnel with pre-existing disorders associated with any of the Target Organs.*

PRIMARY HAZARDS: *Sensory Irritation (xylene, ethyl benzene, butyl acetate), Neuropathy (n-hexane), Narcosis (toluene)*

CARCINOGEN DATA: *Ethyl Benzene, a component of Xylene, is listed with IARC as Class 2B (possible human carcinogen) and with ACGIH as A3 (confirmed animal carcinogen with unknown relevance to humans). Ethyl Benzene is also listed with the State of California as a carcinogen.*

Ligroine is classified as a Category 2 carcinogen by the European Union although it is not listed with any other agency.

CALIFORNIA PROP-65 WARNING: *This product contains substances known to the State of California to cause cancer.*

TARGET ORGANS: *Eyes, skin, respiratory system, central nervous system*

MATERIAL SAFETY DATA SHEET

Page 2 of 5
Diamond Clear Satin PS
Part No. 10283ZP Liquid
Revision 1 ~ January 31, 2006

OSHA HAZARD CLASSIFICATIONS

HEALTH HAZARD CLASSIFICATION				PHYSICAL HAZARD CLASSIFICATION			
Irritant	T	Sensitizer	<input type="checkbox"/>	Combustible	<input type="checkbox"/>	Explosive	<input type="checkbox"/>
Toxic	T	Highly Toxic	<input type="checkbox"/>	Flammable	T	Oxidizer	<input type="checkbox"/>
Corrosive	<input type="checkbox"/>	Carcinogenic	<input type="checkbox"/>	Compressed Gas	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>
						Pyrophoric	<input type="checkbox"/>
						Water Reactive	<input type="checkbox"/>
						Unstable	<input type="checkbox"/>

SECTION 4 FIRST AID MEASURES

INGESTION: *Should actual ingestion occur, do not induce vomiting! Drink a glass of water or milk to dilute. Contact a physician. Never give anything by mouth to an unconscious person.*

SKIN: *Remove with soap and water. Consult a physician if irritation continues.*

EYE: *Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician.*

INHALATION: *Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult doctor if symptoms persist or if unconscious.*

NOTES TO PHYSICIAN: *Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias (irregular beating) in persons exposed to high concentrations of n-Hexane. If used, monitor heart activity closely.*

SECTION 5 FIRE FIGHTING MEASURES

CONDITIONS OF FLAMMABILITY: *Heat, sparks, flame, red hot metal*

SUITABLE MEANS OF EXTINCTION: *Water, CO₂, dry chemical, or universal aqueous film forming foam.*

UNSUITABLE EXTINGUISHING MEDIA: *N/Av*

FLASH POINT AND METHOD OF DETERMINATION: *N/A*

FLAMMABLE LIMITS: *Lower (LEL): N/A @ 25 C Upper (UEL): N/A @ 25 C*

AUTOIGNITION TEMPERATURE: *N/D*

HAZARDOUS COMBUSTION PRODUCTS: *Oxides of carbon*

EXPLOSION DATA - SENSITIVITY TO MECHANICAL IMPACT: *N/Av*

EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE: *N/Av*

SPECIAL FIRE FIGHTING PROCEDURES: *Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure. Firemen should wear self-contained breathing apparatus.*

SPECIAL FIRE AND EXPLOSION HAZARDS: *N/D*

SECTION 6 ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: *Eliminate ignition sources. Handling equipment must be grounded to prevent sparking. Evacuate hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so.*

SPILL CLEANUP: *Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain all water run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand, or other suitable material. Do not use combustible materials such as sawdust. Place in approved safety containers for proper disposal.*

REPORTING REQUIREMENTS: *Comply with all applicable governing agencies.*

SECTION 7 HANDLING AND STORAGE

EMPTY CONTAINER WARNING: *Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. Empty drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.*

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES: *Since this product is a mixture, an exposure value is not available. In determination of any exposure procedures, protection, or testing, use the lowest rated ingredient from Section 2.*

ENGINEERING CONTROLS: *Ensure air contamination is below that of the lowest PEL rated ingredient from Section 2.*

EYE PROTECTION: *Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling.*

MATERIAL SAFETY DATA SHEET

Page 3 of 5
Diamond Clear Satin PS
Part No. 10283ZP Liquid
Revision 1 ~ January 31, 2006

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

RESPIRATORY PROTECTION: Not normally required. If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/D	MELTING/FREEZING POINT: . . . N/D
SPECIFIC GRAVITY (H₂O=1): . . . 0.838 g/cc	COEFF. OF WATER/OIL DIST.: . . N/D
VAPOR PRESSURE: N/D	pH: N/D
VAPOR DENSITY: N/D	EVAPORATION RATE: N/D
PHYSICAL STATE: Liquid	WATER SOLUBILITY: N/D
PERCENT VOLATILE: 80% Wt (82% Vol) Max	VOLATILITY: 5.356 lbs/gal (0.643 g/cc)
PERCENT VOC: 80% Wt (82% Vol) Max	MIR VALUE: 2.216
VISCOSITY: N/D	ODOR THRESHOLD: N/D
APPEARANCE: Clear Coating	ODOR: Paint-like

SECTION 10 STABILITY AND REACTIVITY

CONDITIONS OF INSTABILITY: N/Av

MATERIAL INCOMPATIBILITY: Strong oxidizers, nitrates, alkalis, acids

CONDITIONS OF REACTIVITY: Heat, sparks, flame, red hot metal

DECOMPOSITION PRODUCTS: Oxides of carbon

STABILITY: Stable

HAZARD POLYMERIZATION: Not expected to occur

SECTION 11 TOXICOLOGICAL INFORMATION

LD50 AND LC50 SPECIES/ROUTE INFORMATION:

INGREDIENT	ORAL LD50	DERMAL LD50	INHALATION LC50
Light Aliphatic Petroleum Solvent Naphtha	N/Av	N/Av	N/Av
Xylene	2840 mg/kg, rat	4500 mg/kg, rabbit	6300 mg/l /4hr, rat
Ligroine	N/Av	N/Av	3400 ppm /4hr, rat

IRRITANCY OF PRODUCT: The following ingredients are considered Skin Irritants: Xylene

SENSITIZATION TO PRODUCT: N/Av

REPRODUCTIVE TOXICITY: . . . N/Av

TERATOGENICITY: N/Av

MUTAGENICITY: N/Av

SYNERGISTIC PRODUCTS: . . . N/Av

SECTION 12 ECOLOGICAL INFORMATION

ECOTOXICITY:

INGREDIENT	FISH LC50	DAPHNIA EC50	ALGAL IC50	BACTERIAL EC50
Light Aliphatic Petroleum Solvent Naphtha	N/Av	N/Av	N/Av	N/Av
Xylene	14 mg/l /96 hr	165 mg/l /24 hr	N/Av	N/Av
Ligroine	N/Av	N/Av	N/Av	N/Av

OTHER ECOLOGIC DATA: Do not allow to enter waters, waste water, or soil. N-Hexane is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment

EFFECT ON THE OZONE LAYER: This product does not contain any ozone depleting ingredients.

SECTION 13 DISPOSAL CONSIDERATIONS

WASTE MANAGEMENT INFORMATION: Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

MATERIAL SAFETY DATA SHEET

Diamond Clear Satin PS
Part No. 10283ZP Liquid
Revision 1 ~ January 31, 2006

SECTION 14 TRANSPORTATION INFORMATION

DOT SHIPPING INFORMATION (United States)

PROPER SHIPPING NAME: . Consumer Commodity
HAZARD CLASS: ORM-D
PACKAGING GROUP: None
UN or ID NUMBER: None

TDG SHIPPING INFORMATION (Canada)

PROPER SHIPPING NAME: . Paint Related Material
HAZARD CLASS: 3
PACKAGING GROUP: II
UN or ID NUMBER: UN1263

IMDG SHIPPING INFORMATION (International Ocean)

PROPER SHIPPING NAME: . Paint Related Material
CLASS: 3
PACKAGING GROUP: II
SUBSIDIARY RISK(S): -
UN or ID NUMBER: UN1263
PACKING INSTRUCTIONS: . P001
EmS NO.: F-E, S-E
STOWAGE: Category B
MFAG NO.: 310,313

ICAO/IATA SHIPPING INFORMATION (International Air)

PROPER SHIPPING NAME: Consumer Commodity
HAZARD CLASS: 9
PACKAGING GROUP: None
UN or ID NUMBER: ID8000

ADR SHIPPING INFORMATION (European Union)

PROPER SHIPPING NAME: Paint Related Material
ADR CLASS: 3
PACKAGING GROUP: II
UN or ID NUMBER: UN1263
CLASSIFICATION CODE: . F1
HAZARD ID NO.: 33

NMFC DESCRIPTION (United States)

ITEM DESCRIPTION: Paint Related Material
ITEM NO.: 149980 Sub 3
CLASS: 55

NORTH AMERICAN EMERGENCY RESPONSE GUIDE

ID NUMBER: 1593
GUIDE NUMBER: 160

SECTION 15 REGULATORY INFORMATION

UNITED STATES - FEDERAL:

INGREDIENT	CAS NO	TSCA	RCRA	CERCLA	SARA 313	CAA	CWA
Light Aliphatic Petroleum Solvent Naphtha	64742-89-8	T					
Xylene	1330-20-7	T	U239	100#	16 %	XOV	100#
Ligroine	8032-32-4	T					

UNITED STATES - STATES:

INGREDIENT	CA	DE	FL	MA	PA	MN	NJ	NY	WA
Light Aliphatic Petroleum Solvent Naphtha									
Xylene	C*	T	T	2,4 F8 F9	E	ANO	T	T	T
Ligroine									

* CA-Xylene is not listed but contains Ethyl Benzene which is.

CANADA:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.


All of the components in this product are listed on the Domestic Substances List (DSL).

WHMIS Classification: B2, D2A, D2B


EUROPEAN UNION:

INGREDIENT	EINECS	SYMBOL	RISK PHRASES	SAFETY PHRASES
Light Aliphatic Petroleum Solvent Naphtha	265-192-2			2-23-24-62
Xylene	215-535-7	F Xn	10-20/21-38	2-25
Ligroine	232-453-7	T Xn	45-65	45-53

SECTION 16 OTHER INFORMATION



Canadian Hazard Symbols



European Hazard Symbols

MATERIAL SAFETY DATA SHEET

Page 5 of 5
Diamond Clear Satin PS
Part No. 10283ZP Liquid
Revision 1 ~ January 31, 2006

HMIS and NFPA RATINGS:

	HEALTH	FLAMMABILITY	REACTIVITY	SPECIAL
HMIS RATING	3	3	0	X
NFPA RATING	3	3	0	-

R and S PHASES (European Union):

CODE	RISK or SAFETY PHRASE
R10	Flammable
R20/21	Harmful by inhalation and in contact with skin
R38	Irritating to skin
R45	May cause cancer
R65	Harmful: may cause lung damage if swallowed
S2	Keep out of the reach of children
S23	Do not breathe fumes
S24/25	Avoid contact with skin and eyes
S45	In case of accident or if you feel unwell, seek medical advice immediately
S53	Avoid exposure – obtain special instructions before use
S62	If swallowed do not induce vomiting: seek medical advise immediately

DISCLAIMER OF LIABILITY:

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular purpose.

REVISIONS:

Revision 1 - 06/27/2006 Original