

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

### SECTION 1 - IDENTIFICATION

#### 1.1 Product Identifier

Product Name : Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

Supplier Product Numbers : 10300Z

#### 1.2 Other Means Of Identification

Other Identifiers : Not Available

#### 1.3 Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against

Recommended Use : Rust preventative

Restrictions On Use : None Identified

#### 1.4 Supplier Details

	Supplier Details
Company Name	The Easthill Group, Inc./The Eastwood Company
Address	263 Shoemaker Road, Pottstown, PA 19464 - United States
Phone Number	800-343-9353
Website	www.eastwood.com

#### 1.5 24 Hr Emergency Phone Number

Emergency Number : 800-424-9300 ChemTrec

### SECTION 2 - HAZARDS IDENTIFICATION

#### 2.1 Classification Of The Substance Or Mixture

Flammable Aerosols, Category 1 : Extremely flammable aerosol

Gases Under Pressure : Dissolved Gas : Contains gas under pressure; may explode if heated

Serious Eye Damage/Eye Irritation, Category 2a : Causes serious eye irritation

Reproductive Toxicity, Category 2 : Suspected of damaging fertility or the unborn child

Specific Target Organ Toxicity — Single Exposure, Category 3, Narcosis : May cause drowsiness or dizziness

Specific Target Organ Toxicity — Repeated Exposure, Category 2 : May cause damage to organs through prolonged or repeated exposure

#### 2.2 Label Elements

Hazard Pictograms :



GHS02



GHS04



GHS07



GHS08

Signal Word : Danger

Hazard Statements : Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

**Part No. 10300Z**

Print Date: 11/02/2016

Revision Date: 11/02/2016

Version: 3.0 (EN)

Page 2 of 10

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

**Precautionary Statements**

: Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call physician if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to local regulations.

### 2.3 Other Hazards Which Do Not Result In Classification

**Hazards Not Otherwise Classified** : None Identified.

### 2.4 Unknown Acute Toxicity

41.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

41.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

6.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substance

Not Applicable

### 3.2 Mixture

Ingredient	Cas Number	%	Classification*
Acetone	67-64-1	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Light Aromatic Solvent Naphtha	64742-95-6	5 - 10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Acute 3, H402
Propane	74-98-6	5 - 10	Flam. Gas 1, H220 Dissolved gas, H280
Toluene	108-88-3	1 - 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Heavy Aromatic Solvent Naphtha	64742-94-5	1 - 5	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4 - FIRST-AID MEASURES

### 4.1 Description Of First-Aid Measures

**General Measures**

: IF exposed or concerned: Get medical advice/attention.

**Eye Contact**

: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Skin Contact**

: Wash skin with plenty of water.

**Ingestion**

: Call a poison center or a doctor if you feel unwell.

**Inhalation**

: Remove person to fresh air and keep comfortable for breathing.

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

**First-Aid Responder Protection** : *Wear adequate personal protective equipment based on the nature and severity of the emergency.*

### 4.2 Most Important Symptoms And Effects, Both Acute And Delayed

- Eye Contact** : *Eye irritation.*
- Skin Contact** : *Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking skin. May cause more severe response if confined to skin.*
- Ingestion** : *Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.*
- Inhalation** : *Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.*

### 4.3 Indication Of Immediate Medical Attention And Special Treatment

- Notes To Physician** : *Treat symptomatically.*
- Specific Treatments/Antidotes** : *No Information Available.*
- Immediate Medical Attention** : *No Information Available.*

## SECTION 5 - FIRE-FIGHTING MEASURES

### 5.1 Suitable Extinguishing Media

- Extinguishing Media** : *Water, carbon dioxide, dry chemical, universal aqueous film forming foam.*
- Unsuitable Media** : *Water jet.*

### 5.2 Specific Hazards Arising From The Chemical Or Mixture

- Decomposition Products** : *Decomposition products may include: oxides of carbon, smoke, vapors.*
- Hazards From The Product** : *Extremely flammable. Contents under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to ignition an source.*

### 5.3 Special Protective Actions For Fire-Fighters

- Protective Actions** : *Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.*
- Protective Equipment** : *Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.*

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment And Emergency Procedures

- For Non-Emergency Personnel** : *No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.*
- For Emergency Responders** : *Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.*

### 6.2 Environmental Precautions

- Precautions** : *Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.*

### 6.3 Methods And Materials For Containment And Cleaning Up

- Containment Procedures** : *Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.*

# SAFETY DATA SHEET

**Eastwood Diamond Clear DTM  
and Painted Surfaces Aerosol**

- Cleanup Procedures** : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

**SECTION 7 - HANDLING AND STORAGE**
**7.1 Precautions For Safe Handling**

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

**7.2 Conditions For Safe Storage Including Any Incompatibilities**

- Storage Requirements** : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.
- NFPA 30B Classification** : This product is classified as a Level 3 Aerosol per NFPA 30B.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**
**8.1 Control Parameters**

<b>Propane (74-98-6)</b>		
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	1000 ppm
<b>Toluene (108-88-3)</b>		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (ppm)	200
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
NIOSH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	10 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	150 ppm
California	California PEL (Ceiling) (ppm)	500 ppm
BEI	Toluene in blood, Prior to last shift of workweek	0.02 mg/l

# SAFETY DATA SHEET

**Eastwood Diamond Clear DTM  
and Painted Surfaces Aerosol**

<b>Toluene (108-88-3)</b>		
BEI	Toluene in urine, End of shift	0.03 mg/l
BEI	o-Cresol in urine (with hydrolysis), End of shift (B)	0.3 mg/g creatinine
<b>Light Aromatic Solvent Naphtha (64742-95-6)</b>		
Not applicable		
<b>Acetone (67-64-1)</b>		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
BEI	Acetone in urine, End of shift (Ns)	25 mg/l
<b>Heavy Aromatic Solvent Naphtha (64742-94-5)</b>		
OSHA	OSHA PEL (TWA) (ppm)	500 ppm

## 8.2 Exposure Controls

<b>Engineering Measures</b>	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
<b>Respiratory Protection</b>	: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.
<b>Skin Protection</b>	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
<b>Eye/Face Protection</b>	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
<b>Other Protective Equipment</b>	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Physical Properties

<b>Boiling Point</b>	> 56.10 °C	<b>Melting / Freezing Point</b>	> -95.30 °C
<b>Flash Point, Liquid</b>	> -17.00 °C	<b>Flash Point, Propellant</b>	-104.40 °C
<b>Explosive Limits</b>	LEL: 0.90 UEL: 13.00 vol %	<b>Autoignition Temperature, Liquid</b>	465.00 °C
<b>Flammability</b>	Extremely Flammable Aerosol	<b>Density</b>	0.766 g/cm <sup>3</sup>
<b>Molecular Weight</b>	Not Available	<b>Weight</b>	6.392 lbs/gal
<b>Vapor Pressure</b>	Not Available	<b>pH</b>	Not Available
<b>Vapor Density</b>	Not Available	<b>Evaporation Rate (nBAC=1)</b>	Not Available
<b>Viscosity</b>	Not Available	<b>Partition Coefficient</b>	Not Available
<b>Odor Threshold</b>	Not Available	<b>Refractive Index</b>	Not Available
<b>Physical Form</b>	Pressurized Product	<b>Heat Of Combustion</b>	Not Available

# SAFETY DATA SHEET

**Part No. 10300Z**

Print Date: 11/02/2016

Revision Date: 11/02/2016

Version: 3.0 (EN)

Page 6 of 10

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

Odor	Paint-like	Water Solubility	Not Available
Appearance / Color	Clear, Colorless	Decomposition Temperature	Not Available

### 9.2 Environmental Properties

Percent Volatile	93.28 % wt	VOC Regulatory	740.20 g/L (6.18 lbs/gal)
Percent VOC	50.63 % wt	VOC Actual	387.84 g/L (3.24 lbs/gal)
Percent HAP	5.00 % wt	HAP Content	38.30 g/L (0.32 lbs/gal)
Global Warming Potential	0.51 GWP	Maximum Incremental Reactivity	1.4890 g O3/g
Ozone Depletion Potential	0.00 ODP		

## SECTION 10 - STABILITY AND REACTIVITY

### 10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

### 10.2 Chemical Stability

Stability : This product is stable.

### 10.3 Possibility Of Hazardous Reactions

Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

### 10.4 Conditions To Avoid

Conditions : Other Ignition Sources, Temperatures above 140°F (60°C), Hot Surfaces, Heat, Flames, Sparks.

### 10.5 Incompatible Materials

Incompatibilities : Strong Oxidizing Agents, Strong Acids.

### 10.6 Hazardous Decomposition Products

Products : None identified.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### 11.1.1 Information On Toxicological Effects

Propane (74-98-6)	
LC50 Inhalation (Rat)	658 mg/l/4h (Lit.)
Toluene (108-88-3)	
LD50 Oral (Rat)	> 2000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	12124 mg/kg (IUCLID)
LC50 Inhalation (Rat)	> 20 mg/l/4h (Rat; Literature study)
Light Aromatic Solvent Naphtha (64742-95-6)	
LD50 Oral (Rat)	8400 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 3160 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	3670 ppm/4h (Lit.)
Acetone (67-64-1)	
LD50 Oral (Rat)	5800 mg/kg (ECHA)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (Lit.)
Heavy Aromatic Solvent Naphtha (64742-94-5)	
LD50 Oral (Rat)	> 5000 mg/kg (External SDS)
LD50 Dermal (Rabbit)	> 2000 ml/kg (External SDS)
LC50 Inhalation (Rat)	5100 mg/m <sup>3</sup> (External SDS)

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

### 11.1.2 Health Hazard Classification

Skin Corrosion/Irritation	: Not classified
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory Or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
Stot-Single Exposure	: May cause drowsiness or dizziness.
Stot-Repeated Exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration Hazard	: Not classified
Carcinogen Data	: None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

### 11.1.3 Information On The Likely Routes Of Exposure

Routes Of Exposure : Eye Contact, Skin Contact, Inhalation.

### 11.1.4 Symptoms Related To The Physical, Chemical And Toxicological Characteristics

Symptoms of Exposure : Confusion, Dizziness.

### 11.1.5 Delayed And Immediate Effects And Also Chronic Effects From Short And Long Term Exposure

Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: No chronic effects identified.
Target Organs	: Central Nervous System.
Medical Conditions Aggravated	: None identified.

## SECTION 12 - ECOLOGICAL INFORMATION

### 12.1 Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

<b>Toluene (108-88-3)</b>	
LC50 fish 1	5.8 mg/l Rainbow Trout - 96hr
LC50 other aquatic organisms 1	10 mg/l Green Algae - 72hr
EC50 Daphnia 1	6 mg/l Water Flea - 48hr
<b>Light Aromatic Solvent Naphtha (64742-95-6)</b>	
LC50 fish 1	18 mg/l (LC50)
EC50 Daphnia 1	21 mg/l (EC50)
<b>Acetone (67-64-1)</b>	
LC50 fish 1	5540 mg/l 96h, Rainbow Trout (Lit.)
EC50 Daphnia 1	12600 mg/l 48h, Water Flea (Lit.)
<b>Heavy Aromatic Solvent Naphtha (64742-94-5)</b>	
LC50 fish 1	7.9 mg/l Fathead Minnow - 96h
EC50 Daphnia 1	8.6 mg/l Water Flea - 48hr

### 12.2 Ecological Properties

<b>Propane (74-98-6)</b>	
Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
BCF fish 1	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

# SAFETY DATA SHEET

**Part No. 10300Z**

Print Date: 11/02/2016

Revision Date: 11/02/2016

Version: 3.0 (EN)

Page 8 of 10

**Eastwood Diamond Clear DTM  
and Painted Surfaces Aerosol**
**Toluene (108-88-3)**

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.52 g O <sub>2</sub> /g substance
ThOD	3.13 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.69
BCF fish 2	90 (BCF; 72 h; <i>Leuciscus idus</i> ; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

**Light Aromatic Solvent Naphtha (64742-95-6)**

Persistence and degradability	Readily biodegradable in water.
Log Pow	> 3

**Acetone (67-64-1)**





Persistence and degradability	Biodegradability 90% / 28 days.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.20 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.872 (20 days; Literature study)
BCF fish 1	0.69 (BCF)
BCF other aquatic organisms 1	3 (BCF; BCFWIN)
Log Pow	-0.24 (Test data)
Bioaccumulative potential	Not bioaccumulative.

## SECTION 13 - DISPOSAL CONSIDERATIONS

### 13.1 Waste Treatment Methods

- Waste Disposal** : Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
- Waste Disposal Of Packaging** : In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.
- Landfill Precautions** : Not Available.
- Incineration Precautions** : **\*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*.**

## SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information	Ground Transportation (DOT)	Air Transportation (IATA)	Ocean Transportation (IMDG)
Identification Number	UN1950	UN1950	UN1950
Proper Shipping Name	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
Hazard Class(es)	2.1	2.1	2.1
Packaging Group	None	None	None
Limited Quantity	Yes 	Yes 	Yes 
Marine Pollutant	No	No	No
Hazard Labels		2.1 - Flammable gas 	



# SAFETY DATA SHEET

**Part No. 10300Z**

Print Date: 11/02/2016

Revision Date: 11/02/2016

Version: 3.0 (EN)

Page 9 of 10

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

### SECTION 15 - REGULATORY INFORMATION

#### 15.1 Federal Regulations

**Trace Ingredient Disclosure** : This product is using this ingredient at a trace amount. This ingredient is known to the State of California to cause cancer.

*Ethyl Benzene Cas# 100-41-4 -- 0.0291% -- Cancer*

**TSCA Inventory** : All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

**SARA 313 Reporting** : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS No 108-88-3	1 - 5%
Xylene	CAS No 1330-20-7	< 1%
Ethyl Benzene	CAS No 100-41-4	< 1%

**Applicable Federal Regulations** : One or more ingredients are regulated by other Federal Regulations.

#### **Toluene (108-88-3)**

CERCLA RQ 1000 lb

#### **Acetone (67-64-1)**

CERCLA RQ 5000 lb

#### 15.2 State Regulations

**California Proposition 65** : This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

#### **Toluene (108-88-3)**

Developmental Toxicity	Yes
Non-significant risk level (NSRL)	7000

**State Right-to-Know Lists** : The following ingredients appear on one or more state Right-to-Know lists.

#### **Dimethyl Ether (115-10-6)**

U.S. - New Jersey - Right to Know Hazardous Substance List

#### **Propane (74-98-6)**

U.S. - New Jersey - Right to Know Hazardous Substance List

#### **Toluene (108-88-3)**

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### **Acetone (67-64-1)**

U.S. - Massachusetts - Right To Know List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - RTK (Right to Know) List

#### **2-Phenoxyethanol (122-99-6)**

U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16 - OTHER INFORMATION

**SDS Compliance** : This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at [msds@chem-pak.com](mailto:msds@chem-pak.com).

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

**Disclaimer Of Liability** : The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from

# SAFETY DATA SHEET

**Part No. 10300Z**

Print Date: 11/02/2016

Revision Date: 11/02/2016

Version: 3.0 (EN)

Page 10 of 10

## Eastwood Diamond Clear DTM and Painted Surfaces Aerosol

*use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist*

**Full text of H-statements**

H Code	H Phrase
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life