



Printing Date: 07-Feb-08

Revision Date:

08-Mar-06

# 1. IDENTIFICATION OF SUBSTANCE

• Product description:

Powder Coating

Trade Name:

**Epoxy** 

Manufactured For:

The Easthill Group Dba/The Eastwood Company

263 Shoemaker Road Pottstown,PA 19464 USA & Canada: 800-345-1178

Outside USA: 610-323-2200

Emergency contact: Chem-Trec: 800-424-9300

#### 2. HAZARDOUS INGREDIENTS

### • Chemical characterization

• Description:

Product is a mixture of hazardous and non-hazardous ingredients compounded in a polymer

Hazardous components:	CAS#	PEL-OSHA	TLV-ACGIH	Conc. [%]
Diglycidyl Ether of Bisphenol A	25036-25-3	N/E	N/E	30-60
Eutomer 500MH	54553-90-1	N/E	N/E	5-10
Titanium dioxide	13463-67-7	15 mg/m³	10 mg/m <sup>3</sup>	5-10

### 3. POTENTIAL HEALTH EFFECTS

Information pertaining to particular danger for man and environment

Harmful by inhalation and if swallowed.

Classification system

Classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data

NFPA ratings (scale 0-4)

Health

Health Fire

Reactivity 0

Effects of overexposure to:

Diglycidyl Ether of Bisphenol A

Caution! May cause irritation and sensitization!

Eutomer 500MH

May be harmful by inhalation, ingestion, or skin absorption. Material is irritating to the

eyes, skin, mucous membranes and upper respiratory tract. Irritant!

Titanium dioxide

Skin irritant, Inhalation effects similar to effects of inert nuisance dust, Dust can cause

lung irritation. An experimental carcinogen, neoplastigen and tumorigen.

### 4. FIRST AID MEASURES

After inhalation

Supply fresh air and to be sure call for a doctor

After skin contact

Generally the product does not irritate the skin, wash skin with mild soap and water.

After eye contact

Rinse opened eye for several minutes under running water

• After swallowing

Rinse mouth out and then drink plenty of water. If symptoms persist consult doctor



08-Mar-06 Printing Date: 07-Feb-08 Revision Date:

# 5. FIRE FIGHTING MEASURES

# Suitable extinguishing agents

Use CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

#### Protective equipment

Wear self-contained respiratory device

## 6. ACCIDENTAL RELEASE MEASURES

### Person-related safety precautions

Ensure adequate ventilation

#### Measures for environmental protection

Do not allow to enter sewer/surface or ground water

#### Measures for cleaning/collecting

Pick up mechanically. Dispose contaminated material as waste according to item 13

#### 7. HANDLING AND STORAGE

#### · Handling

Information for safe handling

Prevent formation of dust Ensure good ventilation/exhaustion at the workplace

Information about protection against explosions and fires –

Dust can combine with air to form an explosive mixture

#### Storage

#### Requirements to be met by storerooms and receptacles

Store in cool, dry place, in tightly closed container Storage temperature not to exceed 25°C/77°F to ensure product quality. Shelf life of the product at that temperature up to 2 years, after that the performance of the product will deteriorate Protect from heat and direct sunlight. Protect from humidity and water

Information about storage in one common storage facility

Not required

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Additional information about design of technical systems

No further data; see item 7

Components with limited values that require monitoring at the workplace

Titanium dioxide

#### Personal protective equipment

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. The usual. Precautionary measures for handling chemicals should be followed

#### • General protective and hygienic measures

Inhalation:

It is recommended to use MSHA approved respirator when handling powders. Powders are

considered nuisance dust.

Skin contact:

Avoid skin contact, use long sleeved shirts and impermeable gloves at a minimum when handling powders. TYVEK full body suits or equivalent are recommended for heavy exposure. Be sure to launder contaminated clothing before reuse. Wash skin with mild soap

and water if contact occurs. If symptoms develop, consult with a physician.

Eye protection: Require the use of safety goggles with side shields. Powder particles can be abrasive on the cornea. In case of eye contact flush with plenty of fresh water. If irritation develops consult

with a physician

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Solid, finely divided powder

Colour

According to product specifications

07-Feb-08



Printing Date: 07-Feb-08 Revision Date: 08-Mar-06

Odour
 Nearly odourless

• Change in condition

Melting point/range 70-80°C/158-176°F
 Boiling point/range Not applicable

• Flash point Not applicable

• Auto igniting Product is not self-igniting

Danger of explosion
 Product does not normally present an explosive hazard. However, dust can combine with air to form an explosive mixture if it comes in contact with a source of ignition.

LOWER EXPLOSION LIMIT: 15 g/m3 UPPER EXPLOSION LIMIT: 50 g/m3

• **Density:** 1.2 g/cm 3 - 1.7 g/cm 3

• Solubility in/miscibility with water

Not miscible or difficult to mix

**Solvent content** Organic solvents – 0.0%

Solids content - 100%

### 10. STABILITY AND REACTIVITY

Product Stability:

No decomposition if used according to specifications

Thermal decomposition/conditions to be avoided:

Decomposition at high temperatures may yield Carbon Dioxide, Carbon Monoxide, Nitrous Oxides and other hazardous gases.

- Dangerous Reactions:
- Dangerous products of decompoition:

### 11. TOXICOLOGICAL INFORMATION

Primary irritant effect

On the skin – Powder can be irritating through mechanical action, also has a drying effect. On the eye – Powder can be irritating through mechanical action, can cause abrasion on the cornea.

Sensitization

Sensitization possible through inhalation and skin contact

Additional toxicological information

The product shows the following danger according to internally approved calculation methods for preparationsHarmful

## 12. ECOLOGICAL INFORMATION

General notes

Water hazard class 1 (self-assessment): slightly hazardous for water

### 13. DISPOSAL CONSIDERATIONS

- · Product
- Recommendations

Dispose of in accordance with Federal, State, and local regulations.

- · Uncleaned packaging
- Recommendations

Dispose of in accordance with Federal, State, and local regulations.

# 14. TRANSPORTATION INFORMATION

- · DOT regulations
- Hazard class

07-Feb-08





Printing Date: 07-Feb-08 Revision Date: 08-Mar-06

# Maritime transportation IMDG

Marine pollutant

No

# 15. REGULATIONS

# Product related hazard information

he product has been classified and marked in accordance with directives on hazardous materials

### Hazard symbols

Harmful

# Hazard-determining components of labeling

#### Risk phrases

Harmful by inhalation and if swallowed May cause sensitization by inhalation and skin contact

### Safety phrases

Keep out of the reach of children

Keep container dry

Keep container in a well ventilated place

Keep away from food, drink, and animal feed

Do not breathe gas/fumes/vapour/spray

If swallowed, seek medical advise immediately and show this container or label

#### 16. OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Powder may contain crystalline silica as quartz (maximum 0.04%). Crystalline is an experimental carcinogen, tumerogen and neoplastigen. It is listed by the Toxicology Program, International Agency for Research on Cancer, and is listed pursuant to California's Safe Drinking Water and Toxic Enforcement Act (1986) as a human carcinogen.