

Printing date 04/18/2016 Reviewed on 04/18/2016

1 Identification

- . Product identifier
- . Trade name RAL 7024 SM GL
- . Article number: 10308
- . Application of the substance / the mixture Powder coating material
- . Manufacturer/Supplier:

The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

Phone: 800-343-9353

Emergency Telephone number: 24/7 - 800-424-9300

2 Hazard(s) identification

. Classification of the substance or mixture



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated

exposure.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Combustible Dust May form combustible dust concentrations in air.

- . Label elements
- . GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). $({\tt Contd.\ on\ page\ 2})$



Printing date 04/18/2016

Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 1)

. Hazard pictograms







GHS05

GHS07

. Signal word Danger

. Hazard-determining components of labeling:

1, 3, 5-tris (oxiranylmethyl) -1, 3, 5-triazine-2, 4, 6 (1H, 3H, 5H) -trione

. Hazard statements

Causes serious eye damage.

May cause an allergic skin reaction.

May cause genetic defects.

May cause damage to organs through prolonged or repeated exposure.

May form combustible dust concentrations in air.

. Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Wear eye protection / face protection.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- . Classification system
- . NFPA ratings (scale 0-4)



Health = 2Fire = 1Reactivity = 1

. HMIS-RATINGS (SCALE 0 - 4)



Health = *1Fire = 1Reactivity = 1

- . Other hazards
- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . **vPvB**: Not applicable.

3 Composition/information on ingredients

- . Chemical characterization: Mixtures
- . Description: Mixture consisting of the following components with harmless additives.



Safety Data Sheet

acc. GHS

Printing date 04/18/2016

Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 2)

. Hazardous ingredients:		
7727-43-7	barium sulphate, natural	25-50%
2451-62-9	1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione Acute Tox. 3, H301; Acute Tox. 3, H331; Muta. 1B, H340; STOT RE 2, H373; Eye Dam. 1, H318; Skin Sens. 1, H317	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
1332-58-7	kaolin	< 2.5%
1309-37-1	diiron trioxide	< 2.5%

. Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- . Description of first aid measures
- . General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- . After inhalation
 - Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- . After skin contact Instantly wash with water and soap and rinse thoroughly.
- . After eye contact Rinse opened eye for several minutes under running water.
- . After swallowing Instantly call for doctor.
- . Information for doctor
- . Most important symptoms and effects, both acute and delayed

No further relevant information available.

. Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- . Extinguishing media
- . Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

. Special hazards arising from the substance or mixture

No further relevant information available.

- . Advice for firefighters
- . Protective equipment: Put on breathing apparatus.

6 Accidental release measures

. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid causing dust.

- . Environmental precautions: Do not allow product to reach sewage system or water bodies.
- . Methods and material for containment and cleaning up:

Collect mechanically.

Ensure adequate ventilation.

. Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

7 Handling and storage

- . Handling
- . Precautions for safe handling

No special measures required. Thorough dedusting.



Printing date 04/18/2016

Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 3)

Keep containers tightly sealed. Ensure good ventilation/exhaustion at the workplace. Open and handle container with care.

. Information about protection against explosions and fires:





Keep ignition sources away - Do not smoke.

Keep breathing equipment ready.

Dust can combine with air to form an explosive mixture.

- . Conditions for safe storage, including any incompatibilities
- . Storage
- . Requirements to be met by storerooms and containers:

Store only in the original container.

Static charges may build up in the powder

- . Information about storage in one common storage facility: Not required.
- . Further information about storage conditions: Keep container tightly sealed.
- . Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- . Additional information about design of technical systems: No further data; see item 7.
- . Control parameters

. Components wit	h critical values that require monitoring at the workplace:
7727-43-7 bari	um sulphate, natural
PEL (U.S.A)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (U.S.A)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (U.S.A)	Long-term value: 5* mg/m³ *inhalable fraction; E
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction
EV (Canada)	Long-term value: 10 mg/m³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m³
2451-62-9 1,3,	5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione
TLV (U.S.A)	Long-term value: 0.05 mg/m³
EL (Canada)	Long-term value: 0.05 mg/m³ R; S
EV (Canada)	Long-term value: 0.05 mg/m³
LMPE (Mexico)	Long-term value: 0.05 mg/m³
13463-67-7 tit	anium dioxide
PEL (U.S.A)	Long-term value: 15* mg/m³ *total dust
REL (U.S.A)	See Pocket Guide App. A
TLV (U.S.A)	Long-term value: 10 mg/m³ withdrawn from NIC
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B
EV (Canada)	Long-term value: 10 mg/m³ total dust
LMPE (Mexico)	Long-term value: 10 mg/m³ A4
	(Contd. on page 5)

(Contd. on page 5)



Printing date 04/18/2016 Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 4)

	(Conta. of page 4
1332-58-7 kaol	in
PEL (U.S.A)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (U.S.A)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (U.S.A)	Long-term value: 2* mg/m³ E; as respirable fraction
EL (Canada)	Long-term value: 2 mg/m³
EV (Canada)	Long-term value: 2(D) mg/m³ respirable
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable
1309-37-1 diir	on trioxide
PEL (U.S.A)	Long-term value: 10* 15** 5*** mg/m³ *Fume; Rouge: **Total dust, ***respirable
REL (U.S.A)	Long-term value: 5 mg/m³ Dust & fume, as Fe
TLV (U.S.A)	Long-term value: 5* mg/m³ *as respirable fraction
EL (Canada)	Short-term value: 10** mg/m³ Long-term value: 5* 10*** 3**** mg/m³ *dust & fume**fume; Rouge: ***total dust***resp.
EV (Canada)	Long-term value: 5* 10** mg/m³ *respirable, including Rouge;**total dust
LMPE (Mexico)	Long-term value: 5* mg/m³ A4, *fracción respirable

. Additional information:

The lists that were valid during the compilation were used as basis.

- . Exposure controls
- . Personal protective equipment
- . General protective and hygienic measures

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work. Store protective clothing separately.

. Breathing equipment:



In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Protection of hands:



Protective gloves.

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Printing date 04/18/2016 Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 5)

. Eye protection:



Safety Glasses

. Body protection: Protective work clothing.

9 Physical and Chemical Properties

. Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Solid

Colour: According to Trade Name

. Change in condition

Melting point/Melting range: > 50 C / 120F
Boiling point/Boiling range: Not applicable

Flash point: Not applicable

Inflammability (solid, gaseous) Not determined

. Ignition temperature:

Decomposition temperature: Not determined

. Self-inflammability: Product is not selfigniting.

. Danger of explosion: Product is not explosive. However,

formation of explosive $\operatorname{air}/\operatorname{dust}$ mixtures is

possible

. Critical values for explosion:

Lower: Not determined.
Upper: Not determined.

Steam pressure: Not applicable.

. Density (Specific gravity) at 20 °C (68 °F) 1.57 g/cm³ (13.102 lbs/gal)

Relative density
Vapor density
Evaporation rate
Not determined.
Not applicable.
Not applicable.

. Solubility in / Miscibility with

Water: Unsoluble

. Partition coefficient (n-octanol/water): Not determined.

. Viscosity:

dynamic: Not applicable.
kinematic: Not applicable.

. Solvent content:

Organic solvents: 0.0 %
Solids content: 100.0 %

. Other information No further relevant information available.

10 Stability and Reactivity

- . Reactivity No further relevant information available.
- . Chemical stability
- . Conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)



Printing date 04/18/2016 Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 6)

- . Possibility of hazardous reactions No dangerous reactions known
- . Conditions to avoid No further relevant information available.
- . Incompatible materials: No further relevant information available.
- . Hazardous decomposition products: In case of fire: CO, CO2, NOx

11 Toxicological Information

- . Information on toxicological effects
- . Acute toxicity:

. LD/LC50 values that are relevant for classification:			
2451-62-9 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione			
Oral	LD50	188-1450 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	0.309-0.650 mg/l (rat)	

- . Primary irritant effect:
- . on the skin: N/A
- . Sensitization: Sensitization possible by skin contact.
- . Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Irritant

The product can cause inheritable damage.

. Carcinogenic categories

. IARC (International Agency for Research on Cancer)		
13463-67-7	titanium dioxide	2B
1309-37-1	diiron trioxide	3
1333-86-4	carbon black	2B
9002-88-4	Ethene, homopolymer	3
112926-00-8	Silicon dioxide	3
7631-86-9	silicon dioxide, chemically prepared	3
14808-60-7	quartz (SiO2)	1
. NTP (Nationa	l Toxicology Program)	
14808-60-7	14808-60-7 quartz (SiO2) K	
. OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

* | 12 Ecological information

- . Toxicity
- . Aquatic toxicity: No further relevant information available.
- . Persistence and degradability No further relevant information available.
- . Behaviour in environmental systems:
- . Bioaccumulative potential No further relevant information available.
- . Mobility in soil No further relevant information available.
- . Additional ecological information:
- . General notes:

Water danger class 3 (Self-assessment): extremely hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into soil.

- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . vPvB: Not applicable.

(Contd. on page 8)



Printing date 04/18/2016 Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 7)

. Other adverse effects No further relevant information available.

13 Disposal considerations

- . Waste treatment methods
- . Recommendation





Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- . Uncleaned packagings:
- . Recommendation: Disposal must be made according to official regulations.

14 Transport information

. UN-Number

. ADR N/A
. UN proper shipping name n/a

. Transport hazard class(es)

. DOT, IMDG, IATA

. Class Not regulated.

. Packing group N/A

. Environmental hazards:

. Marine pollutant: No

. Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

- . Safety, health and environmental regulations/legislation specific for the substance or mixture
- . SARA (Superfund Amendments and Reauthorization Act):

. Section 35	55 (Extremly hazardous substances):		
None of th	None of the ingredients is listed.		
. Section 31	. Section 313 (Specific toxic chemical listings):		
7727-43-7	barium sulphate, natural		
1344-28-1	aluminium oxide		
147-14-8	C T Pigment Blue 15		

. TSCA (Toxic Substances Control Act):

All ingredients are listed.

. Proposition 65:

. Chemicals k	nown to cause cancer:
13463-67-7	titanium dioxide
1333-86-4	carbon black

. Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

. Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

. Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)



Printing date 04/18/2016 Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 8)

. Cancerogenity categories

. EPA (Enviro	nmental Protection Agency)	
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
. TLV (Thresh	old Limit Value established by ACGIH)	
13463-67-7	titanium dioxide	A4
1332-58-7	kaolin	A4
1309-37-1	diiron trioxide	A4
1333-86-4	carbon black	A4
1344-28-1	aluminium oxide	A4
1314-23-4	zirconium dioxide	A4
14808-60-7	quartz (SiO2)	A2
. NIOSH-Ca (N	Mational Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide	
1333-86-4	carbon black	
14808-60-7	quartz (SiO2)	

. GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

. Hazard pictograms





GHS07



. Signal word Danger

. Hazard-determining components of labeling:

1, 3, 5-tris(oxiranylmethyl)-1, 3, 5-triazine-2, 4, 6(1H, 3H, 5H)-trione

. Hazard statements

Causes serious eye damage.

May cause an allergic skin reaction.

May cause genetic defects.

May cause damage to organs through prolonged or repeated exposure.

May form combustible dust concentrations in air.

. Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Wear eye protection / face protection.

Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If exposed or concerned: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

IF ON SKIN: Wash with plenty of water.

Store locked up.

 ${\it Dispose of contents/container in accordance with local/regional/national/international regulations.}$

. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)



Printing date 04/18/2016 Reviewed on 04/18/2016

Trade name RAL 7024 SM GL

(Contd. of page 9)

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Relevant phrases

H301 Toxic if swallowed.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H340 May cause genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure.

. Date of preparation / last revision 04/18/2016 / -

. Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 3: Acute toxicity, Hazard Category 3 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

. * Data compared to the previous version altered.

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1