



Printing Date: 08-May-07

Revision Date: 08-Mar-06

**1. IDENTIFICATION OF SUBSTANCE**

- Product description:** Powder Coating  
**Manufactured For:**  
**The Easthill Group DbA/The Eastwood Company**  
263 Shoemaker Road  
Pottstown, PA 19464  
USA & Canada: 800-345-1178  
Outside USA: 610-323-2200  
**Emergency contact: Chem-Trec: 800-424-9300**

**2. HAZARDOUS INGREDIENTS**

- Chemical characterization**

- Description:**

Product is a mixture of hazardous and non-hazardous ingredients compounded in a polymer

Hazardous components:	CAS#	PEL-OSHA	TLV-ACGIH	Conc. [%]
Aluminum	7429-90-5	15/5 mg/m <sup>3</sup>	10/5 mg/m <sup>3</sup>	1 - 5
Barium Sulfate	7727-43-7	15/5 mg/m <sup>3</sup>	10/5 mg/m <sup>3</sup>	10 - 30
Diglycidyl Ether of Bisphenol A	25036-25-3	N/E	N/E	10 - 30
Oleic acid	112-80-1	N/E	N/E	1 - 5
Titanium dioxide	13463-67-7	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>	1 - 5

**3. POTENTIAL HEALTH EFFECTS**

- Information pertaining to particular danger for man and environment**

Harmful by inhalation and if swallowed.

- Classification system**

Classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data

**NFPA ratings (scale 0-4)****Health** 1**Fire** 1**Reactivity** 0

- Effects of overexposure to:**

Aluminum	TLV and PEL are for Total dust/Respirable fraction. Warning! Flammable solid. Water-Reactive. Air sensitive. May cause eye and skin irritation. May cause respiratory and digestive tract irritation. May cause lung damage. May ignite or explode on contact with moist air. May cause bone marrow damage. Reacts violently and/or explosively with water, steam or moisture. Target Organs: Lungs, bone marrow.
Barium Sulfate	TLV and PEL are for Total dust/Respirable fraction. May cause mechanical irritation of eyes or in great concentration overloading of the respiratory system. Lungs may be affected by repeated or prolonged exposure to dust particles, resulting in baritosis (a form of benign pneumoconiosis). Reacts violently with aluminium powder.
Diglycidyl Ether of Bisphenol A	Caution! May cause irritation and sensitization!
Oleic acid	Caution! This is expected to be a low hazard for usual industrial handling. May cause eye and skin irritation. May cause respiratory and digestive tract irritation. Good laboratory procedures are recommended when handling this compound.
Titanium dioxide	Skin irritant. Inhalation effects similar to effects of inert nuisance dust. Dust can cause lung irritation. An experimental carcinogen, neoplastigen and tumorigen.

**4. FIRST AID MEASURES**

- After inhalation**

Supply fresh air and to be sure call for a doctor.

08-May-07



Printing Date: 08-May-07

Revision Date: 08-Mar-06

- **After skin contact**  
Generally the product does not irritate the skin, wash skin with mild soap and water.
- **After eye contact**  
Rinse opened eye for several minutes under running water
- **After swallowing**  
Rinse mouth out and then drink plenty of water. If symptoms persist consult doctor

**5. FIRE FIGHTING MEASURES**

- **Suitable extinguishing agents**  
Use CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Protective equipment**  
Wear self-contained respiratory device

**6. ACCIDENTAL RELEASE MEASURES**

- **Person-related safety precautions**  
Ensure adequate ventilation
- **Measures for environmental protection**  
Do not allow to enter sewer/surface or ground water
- **Measures for cleaning/collecting**  
Pick up mechanically. Dispose contaminated material as waste according to item 13

**7. HANDLING AND STORAGE**

- **Handling**
  - **Information for safe handling**  
Prevent formation of dust Ensure good ventilation/exhaustion at the workplace
  - **Information about protection against explosions and fires –**  
Dust can combine with air to form an explosive mixture
- **Storage**
  - **Requirements to be met by storerooms and receptacles**  
Store in cool, dry place, in tightly closed container. Storage temperature not to exceed 25°C/77°F to ensure product quality. Shelf life of the product at that temperature up to 2 years, after that the performance of the product will deteriorate. Protect from heat and direct sunlight. Protect from humidity and water
  - **Information about storage in one common storage facility**  
Not required

**8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

- **Additional information about design of technical systems**  
No further data; see item 7
- **Components with limited values that require monitoring at the workplace**  
Aluminum  
Barium Sulfate  
Titanium dioxide
- **Personal protective equipment**  
Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. The usual precautionary measures for handling chemicals should be followed
- **General protective and hygienic measures**
  - **Inhalation:** It is recommended to use MSHA approved respirator when handling powders. Powders are considered nuisance dust.
  - **Skin contact:** Avoid skin contact, use long sleeved shirts and impermeable gloves at a minimum when

08-May-07



Printing Date: 08-May-07

Revision Date: 08-Mar-06

- handling powders. TYVEK full body suits or equivalent are recommended for heavy exposure. Be sure to launder contaminated clothing before reuse. Wash skin with mild soap and water if contact occurs. If symptoms develop, consult with a physician.
- **Eye protection:** Require the use of safety goggles with side shields. Powder particles can be abrasive on the cornea. In case of eye contact flush with plenty of fresh water. If irritation develops consult with a physician

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- **Form** Solid, finely divided powder
- **Colour** According to product specifications
- **Odour** Nearly odourless
- **Change in condition**
- **Melting point/range** 70-80°C/158-176°F
- **Boiling point/range** Not applicable
- **Flash point** Not applicable
- **Auto igniting** Product is not self-igniting
- **Danger of explosion** Product does not normally present an explosive hazard. However, dust can combine with air to form an explosive mixture if it comes in contact with a source of ignition.  
LOWER EXPLOSION LIMIT: 15 g/m3  
UPPER EXPLOSION LIMIT: 50 g/m3
- **Density:** 1.2 g/cm3 – 1.7g/cm3
- **Solubility in/miscibility with water**  
Not miscible or difficult to mix
- **Solvent content** Organic solvents – 0.0%  
Solids content – 100%

## 10. STABILITY AND REACTIVITY

- **Product Stability:**  
No decomposition if used according to specifications
- **Thermal decomposition/conditions to be avoided:**  
Decomposition at high temperatures may yield Carbon Dioxide, Carbon Monoxide, Nitrous Oxides and other hazardous gases.
- **Dangerous Reactions:**
- **Dangerous products of decomposition:**

## 11. TOXICOLOGICAL INFORMATION

- **Primary irritant effect**  
On the skin – Powder can be irritating through mechanical action, also has a drying effect.  
On the eye – Powder can be irritating through mechanical action, can cause abrasion on the cornea.
- **Sensitization**  
Sensitization possible through skin contact
- **Additional toxicological information**  
The product shows the following danger according to internally approved calculation methods for preparations:  
Harmful

## 12. ECOLOGICAL INFORMATION

- **General notes**  
Water hazard class 1 (self-assessment): slightly hazardous for water



Printing Date: 08-May-07

Revision Date: 08-Mar-06

**13. DISPOSAL CONSIDERATIONS**

- **Product**
- **Recommendations**  
Dispose of in accordance with Federal, State, and local regulations.
- **Uncleaned packaging**
- **Recommendations**  
Dispose of in accordance with Federal, State, and local regulations.

**14. TRANSPORTATION INFORMATION**

- **DOT regulations**
- **Hazard class**  
Non Regulated
- **Maritime transportation IMDG**
- **Marine pollutant**  
No

**15. REGULATIONS**

- **Product related hazard information**  
the product has been classified and marked in accordance with directives on hazardous materials
- **Hazard symbols**  
Harmful
- **Hazard-determining components of labeling**
- **Risk phrases**  
Harmful by inhalation and if swallowed  
May cause sensitization by skin contact
- **Safety phrases**  
Keep out of the reach of children  
Keep container dry  
Keep container in a well ventilated place  
Keep away from food, drink, and animal feed  
Do not breathe gas/fumes/vapour/spray  
If swallowed, seek medical advice immediately and show this container or label

**16. OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.