

Printing date 05/24/2017 Reviewed on 05/24/2017

1 Identification

. Product identifier

. Trade name GREY METALLIC MET HGL

. Article number: 10341

. Application of the substance / the mixture Powder coating material

. Manufacturer/Supplier:

The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

Phone: 800-343-9353

Emergency Telephone number: 24/7 - 800-424-

- . Informing department: Product Safety Department
- . Emergency telephone number: 24/7:1-800-255-3924; International:+01 or +001-813-248-0585

2 Hazard(s) identification

. Classification of the substance or mixture

Combustible Dust May form combustible dust concentrations in air.

- . Label elements
- . GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- . Hazard pictograms Void
- . Signal word Warning
- . Hazard statements

May form combustible dust concentrations in air.

- . Classification system
- . NFPA ratings (scale 0-4)



Health = 1
Fire = 1
Reactivity = 1

. HMIS-RATINGS (SCALE 0 - 4)



Health = 1
Fire = 1
Reactivity = 1

- . Other hazards
- . Results of PBT and vPvB assessment
- . PBT: Not applicable.



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

(Contd. of page 1)

. vPvB: Not applicable.

3 Composition/information on ingredients

- . Chemical characterization: Mixtures
- . Description: Mixture consisting of the following components with harmless additives.

	. Hazardous	ingredients:	
Ī	7727-43-7	barium sulphate, natural	10-25%
Ī	1332-58-7	kaolin	< 2.5%

. Additional information For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- . Description of first aid measures
- . General information No special measures required.
- . After inhalation Supply fresh air; consult doctor in case of symptoms.
- . After skin contact Instantly wash with water and soap and rinse thoroughly.
- . After eye contact Rinse opened eye for several minutes under running water.
- . After swallowing In case of persistent symptoms consult doctor.
- . Information for doctor
- . Most important symptoms and effects, both acute and delayed

No further relevant information available.

. Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- . Extinguishing media
- . Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

. Special hazards arising from the substance or mixture

No further relevant information available.

- . Advice for firefighters
- . Protective equipment: No special measures required.

6 Accidental release measures

. Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Avoid causing dust.

- . Environmental precautions: Do not allow product to reach sewage system or water bodies.
- . Methods and material for containment and cleaning up: Collect mechanically.
- . Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

. Protective Action Criteria for Chemicals

. PAC-1:		
25036-25-3	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	12 mg/m3
7727-43-7	barium sulphate, natural	15 mg/m3
1333-86-4	carbon black	9 mg/m3
9002-88-4	Ethene, homopolymer	16 mg/m3
112926-00-8	Silicon dioxide	18 mg/m3
471-34-1	calcium carbonate	45 mg/m3
		(Contd. on page 3)



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

112945-52-5 Silica, amorphous fumed 18 mg/m3 14808-60-7 quartz (SiO2) 0.075 mg/m3 PAC-2: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 130 mg/m3 7727-43-7 barium sulphate, natural 170 mg/m3 1333-86-4 carbon black 99 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 790 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3			(Contd. of page 2)
### PAC-2: 25036-25-3	1344-28-1	aluminium oxide	15 mg/m3
### PAC-2: 25036-25-3	112945-52-5	Silica, amorphous fumed	18 mg/m3
25036-25-3	14808-60-7	quartz (SiO2)	0.075 mg/m3
methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 170 mg/m3 7727-43-7 barium sulphate, natural 170 mg/m3 1333-86-4 carbon black 99 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 . PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	. PAC-2:		
1333-86-4 carbon black 99 mg/m3 9002-88-4 Ethene, homopolymer 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	25036-25-3		130 mg/m3
9002-88-4 Ethene, homopolymer 170 mg/m3 112926-00-8 Silicon dioxide 200 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis[oxirane] 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	7727-43-7	barium sulphate, natural	170 mg/m3
112926-00-8 Silicon dioxide 200 mg/m3 471-34-1 calcium carbonate 210 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 790 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	1333-86-4	carbon black	99 mg/m3
471-34-1 calcium carbonate 210 mg/m3 1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 . PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 790 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	9002-88-4	Ethene, homopolymer	170 mg/m3
1344-28-1 aluminium oxide 170 mg/m3 112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 790 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	112926-00-8	Silicon dioxide	200 mg/m3
112945-52-5 Silica, amorphous fumed 100 mg/m3 14808-60-7 quartz (SiO2) 33 mg/m3 . PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 790 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	471-34-1	calcium carbonate	210 mg/m3
14808-60-7 quartz (SiO2) 33 mg/m3 . PAC-3: 25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 790 mg/m3 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	1344-28-1	aluminium oxide	170 mg/m3
. PAC-3: 25036-25-3	112945-52-5	Silica, amorphous fumed	100 mg/m3
25036-25-3 Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	14808-60-7	quartz (SiO2)	33 mg/m3
methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] 7727-43-7 barium sulphate, natural 990 mg/m3 1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	. PAC-3:		
1333-86-4 carbon black 590 mg/m3 9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	25036-25-3		790 mg/m3
9002-88-4 Ethene, homopolymer 1,000 mg/m3 112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	7727-43-7	barium sulphate, natural	990 mg/m3
112926-00-8 Silicon dioxide 1,200 mg/m3 471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	1333-86-4	carbon black	590 mg/m3
471-34-1 calcium carbonate 1,300 mg/m3 1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	9002-88-4	Ethene, homopolymer	1,000 mg/m3
1344-28-1 aluminium oxide 990 mg/m3 112945-52-5 Silica, amorphous fumed 630 mg/m3	112926-00-8	Silicon dioxide	1,200 mg/m3
112945-52-5 Silica, amorphous fumed 630 mg/m3	471-34-1	calcium carbonate	1,300 mg/m3
	1344-28-1	aluminium oxide	1
14808-60-7 quartz (SiO2) 200 mg/m3	112945-52-5	Silica, amorphous fumed	630 mg/m3
	14808-60-7	quartz (SiO2)	200 mg/m3

7 Handling and storage

- . Handling
- . Precautions for safe handling No special measures required.
- . Information about protection against explosions and fires:





Keep ignition sources away - Do not smoke.

Dust can combine with air to form an explosive mixture.

- . Conditions for safe storage, including any incompatibilities
- . Storage
- . Requirements to be met by storerooms and containers:

Store only in the original container. Static charges may build up in the powder

. Information about storage in one common storage facility: Not required.

- . Further information about storage conditions: None.
- . Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

. Additional information about design of technical systems: No further data; see item 7. (Contd. on page 4)

- US -



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

(Contd. of page 3)

. Control parameters

Components with critical values that require monitoring at the workplace: 7727-43-7 barium sulphate, natural		
PEL (U.S.A)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (U.S.A)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (U.S.A)	Long-term value: 5* mg/m³ *inhalable fraction; E	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
LMPE (Mexico)	Long-term value: 10 mg/m³	
1332-58-7 kaol	lin	
PEL (U.S.A)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (U.S.A)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (U.S.A)	Long-term value: 2* mg/m³ E; as respirable fraction	
EL (Canada)	Long-term value: 2 mg/m³	
EV (Canada)	Long-term value: 2(D) mg/m³ respirable	
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable	

. Additional information:

The lists that were valid during the compilation were used as basis.

- . Exposure controls .
- . Personal protective equipment
- . General protective and hygienic measures

The usual precautionary measures should be adhered to in handling the chemicals.

. Breathing equipment:



In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

. Protection of hands:



Protective gloves.

. Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

. Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

. Eye protection:



Safety Glasses



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

(Contd. of page 4)

. Body protection: Protective work clothing.

9 Physical and Chemical Properties

. Information on basic physical and chemical properties

. General Information

. Appearance:

Form: Solid

Colour: According to Trade Name

. Change in condition

Melting point/Melting range: > 50 C / 120F

Boiling point/Boiling range: > 260 °C (> 500 °F)

Not applicable

. Flash point: Not applicable
. Inflammability (solid, gaseous) Not determined

. Ignition temperature:

Decomposition temperature: Not determined

. Self-inflammability: Product is not selfigniting.

. Danger of explosion: Product is not explosive. However,

formation of explosive air/dust mixtures is

possible

. Critical values for explosion:

Lower: Not determined.
Upper: Not determined.

Steam pressure: Not applicable.

. Density (Specific gravity) at 20 °C (68 °F) 1.52 q/cm³ (12.684 lbs/qal)

Relative density
Vapor density
Evaporation rate
Not determined.
Not applicable.
Not applicable.

. Solubility in / Miscibility with

Water: Unsoluble

. Partition coefficient (n-octanol/water): Not determined.

. Viscosity:

dynamic: Not applicable.
kinematic: Not applicable.

. Solvent content:

Organic solvents: 0.0 %
Solids content: 100.0 %

. Other information No further relevant information available.

10 Stability and Reactivity

- . Reactivity No further relevant information available.
- . Chemical stability
- . Conditions to be avoided: No decomposition if used according to specifications.
- . Possibility of hazardous reactions $\ensuremath{\text{No}}$ dangerous reactions known
- . Conditions to avoid No further relevant information available.
- . Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

(Contd. of page 5)

. Hazardous decomposition products: In case of fire: CO, CO2, NOx

11 Toxicological Information

- . Information on toxicological effects
- . Acute toxicity:
- . Primary irritant effect:
- . on the skin: No irritant effect.
- . on the eye: No irritant effect.
- . Sensitization: No sensitizing effect known.
- . Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

. Carcinogenic categories

. IARC (International Agency for Research on Cancer)			
1333-86-4	carbon black	2B	
9002-88-4	Ethene, homopolymer	3	
112926-00-8	Silicon dioxide	3	
14808-60-7	quartz (SiO2)	1	
. NTP (National Toxicology Program)			
14808-60-7	14808-60-7 quartz (SiO2) K		
. OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

12 Ecological information

- . Toxicity
- . Aquatic toxicity: No further relevant information available.
- . Persistence and degradability No further relevant information available.
- . Behaviour in environmental systems:
- . Bioaccumulative potential No further relevant information available.
- . Mobility in soil No further relevant information available.
- . Additional ecological information:
- . General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

- . Results of PBT and vPvB assessment
- . PBT: Not applicable.
- . **vPvB**: Not applicable.
- . Other adverse effects ${\it No}$ further relevant information available.

13 Disposal considerations

- . Waste treatment methods
- . Recommendation Smaller quantities can be disposed with household garbage.
- . Uncleaned packagings:
- . Recommendation: Disposal must be made according to official regulations.

14 Transport information

. UN-Number	N/A
. ADR, IMDG, IATA	N/A
. UN proper shipping name	N/A
. IMDG, IATA	N/A

(Contd. on page 7)



Printing date 05/24/2017 Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

(Contd. of page 6)

. Transport hazard class(es)

. DOT, IMDG, IATA

. Class Not regulated.

. ADR
. Class N/A
. Label N/A
. Packing group N/A
. ADR, IMDG, IATA N/A

. Environmental hazards:

. Marine pollutant: No

. Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

* 15 Regulatory information

- . Safety, health and environmental regulations/legislation specific for the substance or mixture
- . SARA (Superfund Amendments and Reauthorization Act):

. Section 35	5 (Extremly hazardous substances):		
None of th	e ingredients is listed.		
	. Section 313 (Specific toxic chemical listings):		
7727-43-7	barium sulphate, natural		
7429-90-5	aluminium powder (pyrophoric)		
1344-28-1	aluminium oxide		
. TSCA (Toxi	. TSCA (Toxic Substances Control Act):		
All ingredients are listed.			

. Proposition 65:

	-1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
. Cł	hemicals known to cause cancer:
13	333-86-4 carbon black
. Cł	hemicals known to cause reproductive toxicity for females:
No	one of the ingredients is listed.
. Cł	hemicals known to cause reproductive toxicity for males:
No	one of the ingredients is listed.
. Cł	hemicals known to cause developmental toxicity:
No	one of the ingredients is listed.

. Cancerogenity categories

. EPA (Environmental Protection Agency)					
7727-43-7	barium sulphate, natural	D, CBD(inh), NL(ora	al)		
. TLV (Thresh	. TLV (Threshold Limit Value established by ACGIH)				
1332-58-7	kaolin		A4		
1333-86-4	carbon black		A4		
7429-90-5	aluminium powder (pyrophoric)		A4		
1344-28-1	aluminium oxide		A4		
14808-60-7	quartz (SiO2)		A2		
. NIOSH-Ca (National Institute for Occupational Safety and Health)					
1333-86-4	carbon black				
14808-60-7	quartz (SiO2)				

. GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- . Hazard pictograms Void
- . Signal word Warning



Printing date 05/24/2017

Reviewed on 05/24/2017

Trade name GREY METALLIC MET HGL

(Contd. of page 7)

. Hazard statements

May form combustible dust concentrations in air.

. Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Date of preparation / last revision 05/24/2017 / -

. Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
PBT: Persistent, Bioaccumulative and Toxic
VPVB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health

OSHA: Occupational Safety & Heal TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

. * Data compared to the previous version altered.

US