

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Eastwood Diamond Clear Satin for Bare Metal
Supplier Product Numbers : 10345ZP

1.2 Other Means of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Top coat used to protect and preserve metal surfaces
Restrictions on Use : None Identified

1.4 Supplier Details

Supplier Details	
Company Name	The Easthill Group, Inc./The Eastwood Company
Address	263 Shoemaker Road, Pottstown, PA 19464 - United States
Phone Number	800-343-9353
Website	www.eastwood.com

1.5 24 hr Emergency Phone Number

Emergency Number : 800-424-9300 ChemTrec

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Skin Irrit. 2	H315	Health Hazards	Skin corrosion/irritation Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Stot Se 3	H335	Health Hazards	Specific target organ toxicity (single exposure) Category 3
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3
Aquatic Acute 2	H401	Environmental Hazards	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 3	H412	Environmental Hazards	Hazardous to the aquatic environment - Chronic Hazard Category 3

2.2 Label Elements

Hazard Pictograms



GHS02



GHS07

Signal Word

Danger

Hazard Statements

H225 : Highly flammable liquid and vapour
H315 : Causes skin irritation
H319 : Causes serious eye irritation
H335 : May cause respiratory irritation
H336 : May cause drowsiness or dizziness
H401 : Toxic to aquatic life
H412 : Harmful to aquatic life with long lasting effects

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 2/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary Statements

P210 : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 : Keep container tightly closed.
P240 : Ground/Bond container and receiving equipment
P241 : Use explosion-proof electrical/ventilating/lighting equipment
P242 : Use only non-sparking tools.
P243 : Take precautionary measures against static discharge.
P261 : Avoid breathing vapors.
P264 : Wash hands thoroughly after handling.
P271 : Use only outdoors or in a well-ventilated area.
P273 : Avoid release to the environment.
P280 : Wear protective gloves and eye protection.
P303+P361+P353 : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 : If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 : Call physician if you feel unwell
P332+P313 : If skin irritation occurs: Get medical advice/attention.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P362+P364 : Take off contaminated clothing and wash it before reuse.
P370+P378 : In case of fire: Use water, CO2, dry chemical, or universal aqueous film forming foam to extinguish.
P403+P233 : Store in a well-ventilated place. Keep container tightly closed.
P235 : Keep cool.
P405 : Store locked up.
P501 : Dispose of contents/container to local regulations

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

This product does not have any ingredients with an unknown acute toxicity.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Acetone	67-64-1	>= 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
4-Chlorobenzotrifluoride	98-56-6	10 - 30	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Heavy Aromatic Solvent Naphtha	64742-94-5	1 - 5	Flam. Liq. 4, H227 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 3/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.1 Description of First-Aid Measures

General Measures	: Call a poison center or a doctor if you feel unwell.
Inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
Skin Contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Call a poison center or a doctor if you feel unwell.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Central Nervous System Depression, Confusion, Respiratory Irritation, Skin Irritation, Headache, Dizziness, Narcosis, Upper Respiratory Tract Irritation, Cough, Mucous Membrane.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Central Nervous System, Eyes, Liver, Reproductive System, Respiratory System, Skin, Kidneys.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting	: CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions	: Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel	: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

Environmental Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
---------------------------	---

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 4/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3 Methods and Materials for Containment and Cleaning up

- Containment Procedures** : Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
- Cleanup Procedures** : Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Application using Flammable and Combustible Materials is recommended.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Acetone (67-64-1)		
ACGIH	ACGIH TWA (mg/m ³)	250 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m ³)	1200 mg/m ³
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m ³)	1780 mg/m ³
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

Heavy Aromatic Solvent Naphtha (64742-94-5)

OSHA	OSHA PEL (TWA) (ppm)	500 ppm
------	----------------------	---------

8.2 Exposure Controls

- Engineering Measures** : Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
- Personal Protective Equipment**
- Eye / Face Protection** : Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
- Hand Protection** : Chemical-resistant gloves, tested according to ASTM F903-17.
- Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
- Skin and Body Protection** : For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
- Respiratory Protection** : An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.
- Compliance** : If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 5/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Protective Equipment : Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

Environmental Exposure Controls : Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 55.60 °C	Melting / Freezing Point	> -95.01 °C
Flash Point, Liquid	> -17.20 °C		
Explosive Limits	LEL: 0.00 UEL: 14.00 vol %	Autoignition Temperature, Liquid	350.00 °C
Flammability	Highly Flammable Liquid	Density	0.938 g/cm ³
Molecular Weight	Not Available	Weight	7.828 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	Not Available
Appearance / Color	Clear, Colorless	Water Solubility	Not Available
Odor	Paint-like	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	89.95 % wt	VOC Regulatory	130.33 g/L (1.09 lbs/gal)
Percent VOC	1.77 % wt	VOC Actual	16.57 g/L (0.14 lbs/gal)
Percent HAP	0.21 % wt	HAP Content	1.97 g/L (0.02 lbs/gal)
Global Warming Potential	0.32 GWP	Maximum Incremental Reactivity	0.4430 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Bases, Hydrogen Peroxide, Strong Bases, Potassium Chlorate, Organic Peroxides.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes, Formaldehyde, Methanol, Acetic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 6/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (CAS: 67-64-1 / EC: 200-662-2)

LC50 Inhalation (Rat) 76 mg/l/4h (GESTIS Substance Database)

4-Chlorobenzotrifluoride (CAS: 98-56-6 / EC: 202-681-1)

LD50 Oral (Rat) 13000 mg/kg (Hazardous Substances Data Bank)
LD50 Dermal (Rabbit) 3300 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat) 33 mg/l/4h (Hazardous Substances Data Bank)

Heavy Aromatic Solvent Naphtha (CAS: 64742-94-5 / EC: 265-198-5)

LD50 Oral (Rat) > 5000 mg/kg (External SDS)
LD50 Dermal (Rabbit) > 2000 ml/kg (External SDS)
LC50 Inhalation (Rat) 5100 mg/m³ (External SDS)

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.
Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure : See Section 4.2
Skin Corrosion/Irritation : Causes skin irritation.
Eye Damage/Irritation : Causes serious eye irritation.
Respiratory or Skin Sensitization : Not classified
Germ Cell Mutagenicity : Not classified
Reproductive Toxicity : Not classified
STOT-Single Exposure : May cause respiratory irritation. May cause drowsiness or dizziness.
STOT-Repeated Exposure : Not classified
Aspiration Hazard : Not classified
Carcinogen Data : None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

Acetone (67-64-1)

LC50 Fish 5540 mg/l Rainbow Trout - 96hr
LC50 Fish 8300 mg/l Bluegill Sunfish - 96h
EC50 Daphnia 8800 mg/l Water Flea - 48hr
Persistence and Degradability Biodegradability 90% / 28 days.
Biochemical Oxygen Demand 1.43 g O₂/g substance
Chemical Oxygen Demand 1.92 g O₂/g substance
Theoretical Oxygen Demand 2.2 g O₂/g substance
BCF Fish 0.69
BCF Other Aquatic Organisms 3
Log Pow -0.24

4-Chlorobenzotrifluoride (98-56-6)

LC50 Fish 5.6 mg/l Bluegill Sunfish - 96h
LC50 Fish 13.5 mg/l Rainbow Trout - 24hr
EC50 Daphnia 3.68 mg/l (EC50; 48 h)
Persistence and Degradability Biodegradability in water: no data available.
Log Pow 3.6
Bioaccumulative Potential Low potential for bioaccumulation (Log Kow < 4).

Heavy Aromatic Solvent Naphtha (64742-94-5)

LC50 Fish 7.9 mg/l Fathead Minnow - 96h
EC50 Daphnia 8.6 mg/l Water Flea - 48hr

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal : Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 7/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste Disposal Of Packaging

responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.

Landfill Precautions

: Not Available.

Incineration Precautions

: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1263	UN1263	UN1263

14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity

14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 3	3	3
Labels	: None	3 - Flammable liquid	None



Limited Quantity	: Yes	Yes	Yes

EmS Code	: Not Applicable	Not Applicable	F-E, S-E
----------	------------------	----------------	----------

14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Packing Group	: II	II	II

14.5 Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Marine Pollutant	: No	No	No

14.6 Special Precautions	
Precautions	: None Identified

14.7 Transport in Bulk	
Remarks	: Not applicable for product as supplied

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313 : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Xylene	CAS-No. 1330-20-7	< 1%
Toluene	CAS-No. 108-88-3	< 1%
Ethyl Benzene	CAS-No. 100-41-4	< 1%
Ethyl Acrylate	CAS-No. 140-88-5	< 1%

TSCA Section 12(b) : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 8/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CERCLA Reportable Quantity

: Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
Xylene	CAS-No. 1330-20-7	100 lb
Toluene	CAS-No. 108-88-3	1000 lb
Ethyl Benzene	CAS-No. 100-41-4	1000 lb
Ethyl Acrylate	CAS-No. 140-88-5	1000 lb

SARA Section 311/312 Hazard Classes

: Delayed (chronic) health hazard, Fire hazard, Immediate (acute) health hazard.

TSCA Inventory (United States)

: All chemical substances in this product are either listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.

15.2 State Regulations

California Proposition 65

: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Ethyl Benzene (100-41-4)	Cancer	Yes	0.0582 %
Ethyl Acrylate (140-88-5)	Cancer	Yes	%
Toluene (108-88-3)	Developmental Toxicity	Yes	0.0015 %
Toluene (108-88-3)	No significance risk level (NSRL)	7000 µg/day	
Ethyl Benzene (100-41-4)	No significance risk level (NSRL)	54 µg/day	

State Right-to-Know Lists

: The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Xylene (1330-20-7)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
2-phenoxyethanol (122-99-6)	U.S. - Pennsylvania - RTK (Right to Know) List
Toluene (108-88-3)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Ethyl Benzene (100-41-4)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Ethyl Acrylate (140-88-5)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 - OTHER INFORMATION

Indication of changes

Section	Changed item	Change
1	Supersedes	Added
1	SDS US Regulation reference	Added
1	Revision date	Modified
1	Date of issue	Modified
2.2	Precautionary statements (GHS-US)	Added
2.2	Hazard statements (GHS-US)	Added
2.3	Other hazards not contributing to the classification	Added
4	Symptoms/effects after ingestion	Added
4	Other medical advice or treatment	Added
4	Symptoms/effects after eye contact	Added
4	Symptoms/effects after skin contact	Added
4	Symptoms/effects	Added
4	Symptoms/effects after inhalation	Added
4.1	First-aid measures after ingestion	Added
4.1	First-aid measures after eye contact	Added
4.1	First-aid measures general	Added
4.1	First-aid measures after inhalation	Added
4.1	First-aid measures after skin contact	Added
8.2	Compliance	Added
8.2	Remarks	Added
8.2	Hand Protection	Added
8.2	Environmental Exposure Controls	Added
8.2	Respiratory Protection	Added
8.2	Other Protective Equipment	Added
8.2	Eye / Face Protection	Added
8.2	Skin and Body Protection	Added

SAFETY DATA SHEET

Part No. 103452P (Liquid)

Print Date: 7/27/2018
Revision Date: 7/27/2018
Supersedes Date: 11/2/2016
Issue Date: 1/31/2006
Version: 5.0 (EN)-US
Page: 9/9

Eastwood Diamond Clear Satin for Bare Metal

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2	Engineering Measures	Added
8.2	Environmental exposure controls	Added
8.2	Hand protection	Added
8.2	Appropriate engineering controls	Added
9	Relative vapor density at 20 °C	Added
9	Appearance	Added
9	Melting point	Added
9	Flash point	Added
9	Explosive limits (vol %)	Added
9	Boiling point	Added
9	Auto-ignition temperature	Added
9	Specific gravity / density	Added
10	Incompatibilities	Added
10	Prohibited Materials	Added
10	Decomposition Products due to Fire	Added
12.1	Ecology - general	Added
14	EmS Code (Column 15 in IMDG Book 2)	Added
14	User Precautions	Added
15	Select the Appropriate Proposition 65 Notice	Added
15	Display TSCA summary in 15.1	Added
15	Display SARA 313 summary in 15.1	Added
15	Display California Proposition 65 summary in 15.3	Added

Full Text of H-Statements

H Code	H Phrase
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.