

Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

This MSDS covers the following Aervoe aerosol product.

PRODUCT NAME: 10352Z - Almost Chrome Aerosol

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURED FOR: The Easthill Group dba/ The Eastwood Co.

ADDRESS: 263 Shoemaker Road, Pottstown, PA 19464

INFORMATION PHONE: USA & Canada: 800-345-1178
Outside USA: 610-323-2200

EMERGENCY PHONE: Chem-Trec 800-424-9300

DATE REVISED: December 19, 2007

REASON REVISED: Revised

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	ACGIH STEL	LD50 SPECIES & ROUTE	LC50 SPECIES & ROUTE
Hydrocarbon Propellant (CAS 68476-86-8)	30 - 60	1000 ppm	1000 ppm		N / AV	N / AV
*Hexane (CAS 110-54-3)	10 - 30	500 ppm	50 ppm (skin)		2870 mg / kg (Rat-Oral)	N / AV
p-Chlorobenzotrifluoride (98-56-6)	7 - 13	N / AV	N / AV		11500 mg / kg (Mouse-Oral) 13 g / kg (Rat-Oral)	20 g / m ³ (Mouse-Inha) 22 g / m ³ (Rat-Inha)
*Xylene (CAS 1330-20-7)	7 - 13	100 ppm	100 ppm		4300 mg / kg (Rat-Oral)	6700 ppm / 4 hr (Rat-Inha)
Zinc (CAS 7440-66-6)	1 - 2	N / AV	N / AV		N / AV	N / AV

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

NOTE: N / AP = Not Applicable N / AV = Not Available

10352Z - Almost Chrome Aerosol

25A9

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: N / AP
ODOR THRESHOLD: N / AV
EVAPORATION RATE: Faster than n-Butyl Acetate

SPECIFIC GRAVITY (H2O=1): 0.7
VAPOR DENSITY: Heavier than air
APPEARANCE AND ODOR: Opaque silver liquid with hydrocarbon odor.

COEFFICIENT OF WATER/OIL DIST: N / AV
SOLUBILITY IN WATER: Negligible

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: <0° F (-18° C) METHOD USED: Estimated FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: 0.9% UPPER: 10.5%

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Water Spray

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may rupture due to pressure build up from extreme heat or fire

SENSITIVITY TO IMPACT: Do not puncture SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

FLAMMABILITY: Yes - Flammable aerosol under conditions of sparks, flame, or hot surfaces.

SECTION V - REACTIVITY DATA

STABILITY: Stable CONDITIONS TO AVOID: Open flames, sparks, electrical arcs.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.

SKIN CONTACT: Prolonged or repeated contact may cause irritation and dermatitis.

EYE CONTACT: Painful with slight to moderate irritation.

SKIN ABSORPTION: Not likely to be absorbed in toxic amounts under normal use

INGESTION: Not likely in normal use but swallowing large amounts may be harmful.

CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA

TERATOGENICITY: Not established. MUTAGENICITY: Not established

MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION - Remove from exposure, seek medical attention if signs/symptoms persist.

SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.

EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists

INGESTION - Do NOT induce vomiting, drink plenty of water, seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store above 120° F. Do not store or use near heat, sparks or flame

OTHER PRECAUTIONS: Do not smoke while using this product. Dust from sanding the dry paint films should be treated as a nuisance dust with a TLV of 15mg/cubic meter.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator. For concentrations above the TLV (as defined in Section II), use a positive air supplied respirator.

VENTILATION: General ventilation to maintain exposure limits below TLV's as defined in Section II

PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.

EYE PROTECTION: Safety glasses or goggles.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: None

WORK / HYGIENIC PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.