

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008










1 Identification of substance

- **Product details**
- **Trade name:** Pro-Tex Tintable Truckbed Liner
- **Article number:** 10358ZP
- **Distributed by:**
The Easthill Group
dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
- **Information department:**
USA & Canada: 800-345-1178 Outside USA: 610-323-2200
- **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)	Warning:  3.2/2, 3.3/2A, 3.8/3	13 - 30%
	POLYESTER RESIN	Danger:  3.1.O/3, 3.2/2, 3.3/2A, 3.8/3	13 - 30%
	ACRYLIC RESIN	Warning:  3.2/2, 3.3/2A, 3.8/3	13 - 30%
67-64-1	acetone	Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	7 - 10%
123-86-4	n-butyl acetate	Warning:  2.6/3;  3.8/3	5 - 7%
110-43-0	heptan-2-one	Danger:  3.1.O/3, 3.1.I/4 Warning:  2.6/3	1.5 - 5%

3 Hazards identification

- **Hazard description:**



Harmful
Highly flammable

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.
Has a narcotizing effect.
Highly flammable.
Harmful if swallowed.
Irritating to eyes, respiratory system and skin.
Vapours may cause drowsiness and dizziness.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 1)

· **NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· **GHS label elements****Danger**

2.6/2 - Highly flammable liquid and vapour.

**Warning**

3.1/4 - Harmful if swallowed.

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation. May cause drowsiness or dizziness.

· **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

· **Response:**

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

Rinse mouth.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use for extinction: CO₂, powder or water spray.· **Storage:**

Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 2)

*Store in a well-ventilated place. Keep cool.**Store locked up.***· Disposal:***Dispose of contents/container in accordance with local/regional/national/international regulations.***4 First aid measures****· General information:***Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.***· After inhalation:** *In case of unconsciousness place patient stably in side position for transportation.***· After skin contact:** *Immediately wash with water and soap and rinse thoroughly.***· After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***· After swallowing:** *Immediately call a doctor.***5 Fire fighting measures****· Suitable extinguishing agents:** *CO2, sand, extinguishing powder. Do not use water.***· For safety reasons unsuitable extinguishing agents:** *Water with full jet***· Protective equipment:** *No special measures required.***6 Accidental release measures****· Person-related safety precautions:** *Wear protective equipment. Keep unprotected persons away.***· Measures for environmental protection:** *Do not allow to enter sewers/ surface or ground water.***· Measures for cleaning/collecting:***Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).**Dispose contaminated material as waste according to item 13.**Ensure adequate ventilation.**Do not flush with water or aqueous cleansing agents***7 Handling and storage****· Handling:****· Information for safe handling:***Ensure good ventilation/exhaustion at the workplace.**Prevent formation of aerosols.***· Information about protection against explosions and fires:***Keep ignition sources away - Do not smoke.**Protect against electrostatic charges.***· Storage:****· Requirements to be met by storerooms and receptacles:** *Store in a cool location.***· Information about storage in one common storage facility:** *Not required.***· Further information about storage conditions:***Keep receptacle tightly sealed.*

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 3)

Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm
	Long-term value: 1188 mg/m ³ , 500 ppm
BEI	

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm
	Long-term value: 713 mg/m ³ , 150 ppm

110-43-0 heptan-2-one

PEL	465 mg/m ³ , 100 ppm
REL	465 mg/m ³ , 100 ppm
TLV	233 mg/m ³ , 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties· **General Information**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic

· **Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** Undetermined.· **Flash point:** -15°C (5°F)· **Ignition temperature:** 370°C (698°F)· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.· **Density at 20°C (68°F):** 1.22 g/cm³· **Solubility in / Miscibility with****Water:** Not miscible or difficult to mix.· **Solvent content:****Organic solvents:** 23.4 %**VOC content:** 13.6 %
169.0 g/l / 1.41 lb/gal· **Solids content:** 76.4 %**10 Stability and reactivity**· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **Dangerous reactions** No dangerous reactions known.· **Dangerous products of decomposition:** No dangerous decomposition products known.**11 Toxicological information**· **Acute toxicity:**· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 6)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed LinerHarmful
Irritant

(Contd. of page 5)

12 Ecological information· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations· **Product:**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.**14 Transport information**· **DOT regulations:**

- **Hazard class:** 3
- **Identification number:** UN1263
- **Packing group:** II
- **Proper shipping name (technical name):** PAINT
- **Label:** 3

· **Land transport TDG (Canada) and ADR/RID (Europe):**

- **Hazard class:** 3 Flammable liquids
- **UN-Number:** 1263
- **Packaging group:** II
- **Label:** 3
- **Description of goods:** 1263 PAINT, special provision 640D

· **Maritime transport IMDG:**

- **IMDG Class:** 3
- **UN Number:** 1263

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 6)

· **Label** 3
 · **Packaging group:** II
 · **EMS Number:** F-E,S-E
 · **Marine pollutant:** No
 · **Propper shipping name:** PAINT

· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1263
 · **Label** 3
 · **Packaging group:** II
 · **Propper shipping name:** PAINT

· **UN "Model Regulation":** UN1263; PAINT; 3; II

15 Regulations

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**14807-96-6 Talc ($Mg_3H_2(SiO_3)_4$)

ACRYLIC RESIN

1330-20-7 xylene

· **TSCA (Toxic Substances Control Act):**14807-96-6 Talc ($Mg_3H_2(SiO_3)_4$)

67-64-1 acetone

123-86-4 n-butyl acetate

110-43-0 heptan-2-one

763-69-9 ethyl 3-ethoxypropionate

1330-20-7 xylene

77-58-7 dibutyltin dilaurate

111-76-2 2-butoxyethanol

· **Proposition 65**· **Chemicals known to cause cancer:**

1330-20-7 xylene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 8)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 7)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**· **EPA (Environmental Protection Agency)**

67-64-1	acetone	D
1330-20-7	xylene	D

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
1330-20-7	xylene	3
111-76-2	2-butoxyethanol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
67-64-1	acetone	A4
1330-20-7	xylene	A4
77-58-7	dibutyltin dilaurate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful
Highly flammable

· **Hazard-determining components of labelling:**

POLYESTER RESIN

· **Risk phrases:**

Highly flammable.
Harmful if swallowed.
Irritating to eyes, respiratory system and skin.
Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

Keep in a cool place.
Keep container in a well-ventilated place.
Keep away from sources of ignition - No smoking.
This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing MSDS:** Environment protection department.

(Contd. on page 9)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 04/18/2008

Reviewed on 04/18/2008

Trade name: Pro-Tex Tintable Truckbed Liner

(Contd. of page 8)

· **Contact:** Steve Gaver· **Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**RID: Reglement internationale concernent le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)**ICAO: International Civil Aviation Organization**ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**ACGIH: American Conference of Governmental Industrial Hygienists**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)*

USA