Printing date 04/18/2008 Reviewed on 04/18/2008

# 1 Identification of substance

· Product details

· Trade name: Pro-Tex Truckbed Liner System - Black

· Article number: 10359ZP

· Distributed by:

The Easthill Group dba/The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

· Information department:

USA & Canada: 800-345-1178; Outside USA: 610-323-2200

· Emergency information: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

### 2 Composition/Data on components

- · Chemical characterization
- · Description: Mixture of the substances listed below with nonhazardous additions.

_	components:		
14807-96-6	Talc (Mg3H2(SiO3)4)	Warning: 1.2/2, 3.3/2A, 3.8/3	13 - 30%
	ACRYLIC RESIN	Warning: <b>(</b> ) 3.2/2, 3.3/2A, 3.8/3	13 - 30%
	POLYESTER RESIN	Warning: <b>(</b> ) 3.2/2, 3.3/2A, 3.8/3	7 - 10%
	POLYESTER RESIN	Danger: 🔷 3.1.0/3, 3.2/2, 3.3/2A, 3.8/3	7 - 10%
67-64-1	acetone	Danger: <u> </u>	7 - 10%
123-86-4	n-butyl acetate	Warning: 🚸 2.6/3; 🕚 3.8/3	5 - 7%
110-43-0	heptan-2-one	Danger: 🔶 3.1.0/3, 3.1.1/4 Warning: 🐠 2.6/3	1.5 - 5%
108-65-6	2-methoxy-1-methylethyl acetate	Warning: 🚸 2.6/3; 🕚 3.3/2A	1.5 - 5%
1333-86-4	Carbon black	Warning: <b>(</b> ) 3.2/2, 3.3/2A, 3.8/3	1-1.5%
1330-20-7	xylene	Danger: 🔗 3.1.D/3, 3.1.I/4, 3.2/2 Warning: 🌑 2.6/3	1-1.5%

# 3 Hazards identification

· Hazard description:





Irritant Highly flammable

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines. Has a narcotizing effect.

Highly flammable.

Irritating to eyes, respiratory system and skin.

Vapours may cause drowsiness and dizziness.

(Contd. on page 2)

(Contd. of page 1)

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

#### · Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

GHS label elements



2.6/2 - Highly flammable liquid and vapour.



### Warning

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation. May cause drowsiness or dizziness.

### Warning

3.1/5 - May be harmful if swallowed.

#### · Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

### · Response:

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

If skin irritation occurs: Get medical advice/attention.

*If eye irritation persists: Get medical advice/attention.* 

Take off contaminated clothing and wash before reuse.

*In case of fire: Use for extinction: CO2, powder or water spray.* 

(Contd. on page 3)

(Contd. of page 2)

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

· Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

· Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

### 4 First aid measures

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

### 5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: No special measures required.

### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

### 7 Handling and storage

- · Handling:
- · Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

TICA.

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

(Contd. of page 3)

## 8 Exposure controls and personal protection

· Additi	onal information about design of technical systems: No further data; see item 7.	
· Comp	onents with limit values that require monitoring at the workplace:	
67-64-1 acetone		
PEL	2400 mg/m³, 1000 ppm	
REL	590 mg/m³, 250 ppm	
TLV	Short-term value: 1782 mg/m³, 750 ppm	
	Long-term value: 1188 mg/m³, 500 ppm	
	BEI	
123-8	6-4 n-butyl acetate	
PEL	710 mg/m³, 150 ppm	
REL	Short-term value: 950 mg/m³, 200 ppm	
	Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 950 mg/m³, 200 ppm	
	Long-term value: 713 mg/m³, 150 ppm	
110-4.	3-0 heptan-2-one	
PEL	465 mg/m³, 100 ppm	
REL	$465 \text{ mg/m}^3, 100 \text{ ppm}$	
TLV	$233 \text{ mg/m}^3, 50 \text{ ppm}$	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WEEL	50 ppm	
1333-	86-4 Carbon black	
PEL	$3.5 \text{ mg/m}^3$	
REL	$3.5* mg/m^3$	
	*0.1 in presence of PAHs, as PAHs; 10-hr TWA	
TLV	$3.5 \text{ mg/m}^3$	
1330-2	20-7 xylene	
PEL	435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm	
	Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: 651 mg/m³, 150 ppm	
	Long-term value: 434 mg/m³, 100 ppm	
	BEI	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

(Contd. of page 4)

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

### 9 Physical and chemical properties

· General Information	
Form: Color: Odor:	Liquid According to product specification Characteristic
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	
· Flash point:	-19°C (-2°F)
· Ignition temperature:	370°C (698°F)
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Density at 20°C (68°F):	1.23 g/cm³
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	25.8 %
VOC content:	18.0 % 186.2 g/l / 1.55 lb/gl

(Contd. on page 6)

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

(Contd. of page 5)

· Solids content: 73.8 %

### 10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition: No dangerous decomposition products known.

### 11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

# 12 Ecological information

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# 13 Disposal considerations

- · Product:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

# 14 Transport information

· DOT regulations:



· Hazard class: 3

· Identification number: UN1263 · Packing group: II

· Proper shipping name (technical name): PAINT

(Contd. on page 7)

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

(Contd. of page 6)

· Label

· Land transport TDG (Canada) and ADR/RID (Europe):



· Hazard class: 3 Flammable liquids

· UN-Number: 1263
· Packaging group: II
· Label: 3

• **Description of goods:** 1263 PAINT, special provision 640D

· Maritime transport IMDG:



IMDG Class:

UN Number:
Label
Packaging group:
EMS Number:
Marine pollutant:
Propper shipping name:

3

F-E,S-E

No
PAINT

· Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class:
UN/ID Number:
Label
Packaging group:
Propper shipping name:

· UN "Model Regulation": UN1263; PAINT; 3; II

# 15 Regulations

Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

14807-96-6 Talc (Mg3H2(SiO3)4)

ACRYLIC RESIN

1330-20-7 xylene

108-88-3 toluene

(Contd. on page 8)

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

	(Contd. of page
TSCA (Toxic Substances Control Act):	
14807-96-6 Talc (Mg3H2(SiO3)4)	
67-64-1 acetone	
123-86-4 n-butyl acetate	
110-43-0 heptan-2-one	
763-69-9 ethyl 3-ethoxypropionate	
108-65-6 2-methoxy-1-methylethyl acetate	
1333-86-4 Carbon black	
1330-20-7 xylene	
108-88-3 toluene	
77-58-7 dibutyltin dilaurate	
111-76-2 2-butoxyethanol	
Proposition 65	
Chemicals known to cause cancer:	
1333-86-4 Carbon black	
1330-20-7 xylene	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
108-88-3 toluene	
Cancerogenity categories	
EPA (Environmental Protection Agency)	
67-64-1 acetone	
1330-20-7 xylene	
108-88-3 toluene	
IARC (International Agency for Research on Cancer)	ľ
14807-96-6 Talc (Mg3H2(SiO3)4)	
1333-86-4 Carbon black	3
1330-20-7 xylene	3
108-88-3 toluene	3
111-76-2 2-butoxyethanol	3
NTP (National Toxicology Program)	
None of the ingredients is listed.	
TLV (Threshold Limit Value established by ACGIH)	
14807-96-6 Talc (Mg3H2(SiO3)4)	A
67-64-1 acetone	A
1333-86-4 Carbon black	A
1330-20-7 xylene	A
108-88-3 toluene	A
77-58-7 dibutyltin dilaurate	A

Printing date 04/18/2008 Reviewed on 04/18/2008

Trade name: Pro-Tex Truckbed Liner System - Black

(Contd. of page 8)

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### · Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

#### · Hazard symbols:

Irritant

Highly flammable

#### · Risk phrases:

Highly flammable.

Irritating to eyes, respiratory system and skin.

Vapours may cause drowsiness and dizziness.

### · Safety phrases:

Keep in a cool place.

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

This material and its container must be disposed of as hazardous waste.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Steve Gaver
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement internationale concernent le transport des merchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

USA