

EASTWOOD SATIN BLACK HIGH-TEMP COATING AEROSOL is your ideal choice when restoring or customizing exhaust manifolds and headers. Easy to apply and will provide years of durability and great looks. Its high temp properties will withstand temperatures up to 1400°F. This unique formula uses your engine's exhaust heat to cure the coating, creating a baked on, durable finish.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT

1. Make sure the surface to be painted is clean and free of greases, oils and old coatings. For best results, abrasive blast cast surfaces. Steel tube headers must be blasted or abraded with 80-120 grit sandpaper for best adhesion.
2. Final clean surface with Eastwood PRE Painting Prep (10041Z) or acetone.
3. Shake can vigorously. For best results apply at room temperature 65-85°F at 50% humidity. Apply 2-3 light coats, allowing 30-45 minutes between each coat. **NOTE:** Heavy applications may reduce service life and cause flaking.
4. Let dry for 24 hours before putting part into service. Once manifold is installed on engine, start motor and let idle for 20 minutes, this will final cure the coating. **WARNING:** Do not run motor in sealed garage, only in a well ventilated area or outdoors. The coating will emit an odor that contains potentially harmful vapors – ensure proper ventilation.

IMPORTANT: To prevent clogging, after each use, invert the can and spray a few short blasts to clear the valve.

CONTAINS: Dimethyl Ether (CAS #115-10-6), N-Butyl Acetate (CAS #123-86-4), Acetone (CAS #67-64-1), PM Acetate (CAS #108-65-6), Toluene (CAS #108-88-3) and Methyl Acetate (CAS #79-20-9). 50% of the ingredients have an unknown acute toxicity.



DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS: Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/120°F. Dispose of contents and container in accordance with applicable regulations.

FIRST AID: If exposed, concerned or feel unwell: Call a doctor. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.



WARNING: Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

VOC CONTENT: HTC Maximum MIR 1.85
KEEP OUT OF THE REACH OF CHILDREN

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night:
1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
1-800-343-9353 www.eastwood.com © Copyright 2018 Easthill Group, Inc.
Made in USA Label #10393ZL 9/18 Rev 1



DO THE JOB RIGHT.®

HIGH TEMP COATING SATIN BLACK



- Resists Heat Up To 1400°F
- Durable and Long Lasting
- Easy Spray-On Application
- Covers Approx. 8-10 sq. ft.



Scan for product info

DANGER: CONTENTS EXTREMELY FLAMMABLE
AND UNDER PRESSURE. EYE IRRITANT.
Read Precautions On Rear Panel Before Use.

Net wt. 11.75 oz. / 333.7 grams

10393Z