

Manufactured For:
 The Easthill Group
 dba/ The Eastwood Co.
 263 Shoemaker Rd.
 Pottstown, PA 19464
 USA & Canada: 1-800-345-1178
 Outside USA: (610) 323-2200

EMERGENCY NO: 800-424-9300

MATERIAL SAFETY DATA SHEET

MSDS NO:1200 STAINLESS

DATE: February 28, 2003

SECTION 1 MATERIAL IDENTIFICATION

PRODUCT NAME: SS Gray Hi-Temp Coating

GENERIC NAME OR FAMILY: Heat Resistant Paint

SHIPPING NAMES: DOT: Paint-Flammable liquid-UN1263

IATA: Restricted-Flammable liquid-UN1263

HAZARDOUS COMPONENTS OF MIXTURE	WEIGHT %	OSHA PEL (PPM)	ACGIH TLV (PPM)	CAS Number
Aromatic Petroleum Distillate	40-45	N.A.	N.A.	64742-95-6
Aliphatic Hydrocarbons	15-20	100	100PPM	8052-41-3
Aromatic Petroleum Distillates	7-12	NA	NA	64742-94-5
1,2,4- Trimethylbenzene	1-5	NA	NA	95-63-6
1,3,5-Trimethylbenzene	1-5	NA	NA	108-67-8
Xylene	1-5	100	100	1330-20-7
Isopropylbenzene	1-5	50	50	98-82-8
Manganese Ferrite Black Spinel	1-5	5 mg/cu.m	0.2mg/cu.m	68186-94-7
Titanium Dioxide	1-5	15mg/cu.m	10mg/cu.m	13463-67-7
Magnesium Silicate Hydrate	1-5	2mg/cu.m	2mg/cu.m	14807--96-6
Nickel Titanate	1-5	10mg/cu.m	10mg/cu.m	8007-18-9
Non- Hazardous	Balance			

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemical (s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of CFR 372:

Chemical Name	Max%	CAS Number
1,2,4-Trimethylbenzene	5	95-63-6
Xylene	5	1330-20-7
Cumene	5	98-82-8
Antimony compound	2	1314-60-9
Nickel compound	2	1313-99-1

SECTION 2 PHYSICAL DATA

BOILING POINT (°F): NA	SPECIFIC GRAVITY (H ₂ O = 1): NA
VAPOR PRESSURE (mm Hg.): NA	PERCENT VOLATILE BY VOLUME (%): NA
VAPOR DENSITY (AIR =1): 3.8	EVAPORATION RATE (N-Butyl Acetate = 1): NA
SOLUBILITY IN WATER: Negligible	VOLATILE ORGANIC COMPOUNDS (VOC): N.A.
APPEARANCE AND ODOR: Paint-Aromatic Naphtha odor	

SECTION 3 FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (and Method): Approx. 100°F (T.C.C.)	FLAMMABLE LIMITS	LOWER NA	UPPER NA
---	------------------	-------------	-------------

EXTINGUISHING MEDIA: Drychemical, CO₂, or universal type foam

SPECIAL FIRE FIGHTING PROCEDURES: Wear appropriate protective equipment including respiratory protection equipment to protect against possible toxic combustion or decomposition products.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This material is flammable and may be ignited by heat, flame, spark or static electricity. Closed container may explode in the heat of a fire.

SECTION 4 - REACTIVITY HAZARD DATA

<input type="checkbox"/> STABILITY: Stable	CONDITIONS TO AVOID: Not applicable
---	--

Incompatibility (Materials to Avoid): Unknown

Hazardous Decomposition Products: If heated to decomposition may emit carbon dioxide, carbon monoxide or other toxic compounds.

HAZARDOUS POLYMERIZATION: Will not occur	CONDITIONS TO AVOID: Not applicable
---	--

SECTION 5 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type): Not required with adequate ventilation.

Protective Gloves: Impermeable to paint

Eye Protection: Splash goggles

VENTILATION TO BE USED

- | | |
|--|--|
| <input type="checkbox"/> Local Exhaust | Mechanical(general): If local exhaust is not sufficient. |
| <input type="checkbox"/> Other: Respirator or air supplied equipment if exhaust is not sufficient. | |

Other Protective Clothing & Equipment: Impermeable apron or clothing is necessary.

Hygienic Work Practices: Wash hands after use of this product. Observe good personal hygienic work practices to avoid contact with skin, eyes and clothing.

SECTION 6 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY ☐ Inhalation ☐ Skin Absorption This substance has not been identified as a carcinogen by NTP, IARC or OSHA.

HEALTH HAZARDS	Acute: Skin Contact: irritation, redness. Vapors: headache, drowsiness, dizziness, loss of coordination. Chronic: Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage.
-----------------------	---

Signs & Symptoms of Exposure: Skin Contact: irritation, redness. Vapors: headache, drowsiness, dizziness, loss of coordination, nausea.

Target Organ Information: Respiratory symptoms associated with pre-existing lung disorders may be aggravated by exposure to this material. SEE HEALTH HAZARDS.

EMERGENCY FIRST AID PROCEDURES - Seek medical assistance for further treatment, observation and support if necessary.

Eye Contact: Flush eyes with water for 15 minutes. If pain or irritation persists, obtain medical attention.	Skin Contact: Wash with soap and water. If pain or irritation persists, obtain medical attention.
Inhalation: Remove to fresh air. Obtain immediate medical attention.	Ingestion: Obtain immediate medical attention.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken if Material Is Spilled or Released: Pick up in absorbent material and discard by approved procedures in compliance with Federal, State and local laws.

Waste Disposal Methods: Standard, in observance of all Federal, State and local laws concerning health and environment.

Precaution to be taken in Handling & Storage: Keep containers tightly closed and store away from possible source of ignition. Do not use near possible source of ignition.

Other Precautions and/or Special Hazards: Only use in well ventilated area.

HMIS rating: 0= Minimal hazard 1= Slight hazard 2= Moderate hazard 3= Serious hazard 4= Severe hazard

Health: 2 Flammability: 3 Reactivity: 0

This information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.