# MATERIAL SAFETY DATA SHEET

# SECTION I: PRODUCT AND COMPANY IDENTIFICATION:

Product name: 10452 - Sprayable Road Noise Barrier

Distributed by: The Easthill Group

dba/ The Eastwood Company

263 Shoemaker Road Pottstown, PA 19464

USA & Canada: 800-345-1178 Outside USA: 610-323-2200

Emergency Contact: Chem-Trec

800-424-9300

**HMIS Rating Information:** Item Numbers:

Health 1 TC/SC-12
Flammability 0 TC/SC-18
Reactivity 0 TC/SC-200

# **SECTION II: HAZARDOUS INGREDIENTS**

Ingredients	Cas#	%	LC50,ppm	LD50, mg/Kg
		weight	inhalation,rat	oral,rat
Calcium	1317-65-3	20-50	N/Av	6450
Carbonate				
Divinyl	N/Av	40-60	N/Av	N/Av
emulsion				

# SECTION III: CHEMICAL AND PHYSICAL DATA:

Chemical formulation: Mixed Products

Short description: Synthetic polymers mix, black colorant,

calcium carbonates and adherence agents.

Uses: Sound deadener, anti-chipping protection,

corrosion protection.

Form: Liquid

Color: Dark gray. Black when dried.

Odor:

Boiling point:

Specific gravity:

Solubility in water:

Viscosity:

None.

100 C

1,14 gr/ml

70%

40.000 Cp

#### **SECTION IV: FIRE AND EXPLOSIVE DATA**

Flame point: N/A
Auto-ignition point: N/A
Explosion and fire danger: None

#### **SECTION V: REACTIVITY DATA:**

Stability: Product is Stable.

Unstable at contact with: None Dangerous by-products: None

Hazardous Decomposition Products: Decomposition will release gases such as

carbon dioxide.

#### SECTION VI: HEALTH HAZARD DATA:

Routes of Entry: Inhalation, Skin contact, eye contact, ingestion.

**Inhalation**: Avoid inhalation of vapors and mist.

Skin and eyes: Avoid contact.

**Ingestion**: May cause gastrointestinal irritation, contact Physician.

**Acute Health Hazard**: Abrasiveness of filler may cause eye and skin irritation. Flush eyes with water for at least 15 min and if irritation persists get medical attention. Wash skin thoroughly with soap and water.

**Chronic effects:** Prolonged or repeated skin contact may cause drying of the skin.

# SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE.

SPILLAGE / LEAKAGE PROCEDURE: Collect spilled material with absorbent and dispose according to state or local requirements.

# **SECTION VIII: CONTROL MEASURES**

# **HEALTH PROTECTION DEVICES:**

Breath: Wear a paper mask respiratory protection.

Skin: Plastic gloves.
Eyes: Safety glasses.
Additional protection: Not needed

SPECIAL PROCEDURES:

Storage: Keep away from sources of heat.

Keep container tightly closed.

Keep from freezing.

# **DISPOSAL CONSIDERATIONS:**

Local regulations should be adhered to.

For disposal of empty containers local regulations are binding.

Product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with legal regulations. The information contained herein is intended to describe our product from the point of view of safety requirements.