

# Material Safety Data Sheet

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

**Product ID:** 10486Z  
**Product Name:** BRAKE CALIPER-DRUM PAINT PURPLE  
**Product Use:** Paint product.  
**Print date:** 23/Feb/2009  
**Revision Date:** 14/Jan/2009

**Distributed By** The Eashill Group  
dba/ The Eastwood Company  
263 Shoemaker Road  
Pottstown, PA 19464  
USA & Canada: 800-345-1178  
Outside USA: 610-323-2200

**Emergency Contact** Chem-Trec - 800-424-9300

## 2. HAZARDS IDENTIFICATION

### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

### Eye Contact:

- Severe eye irritation

### Skin Contact:

- Causes skin irritation.
- Dermatitis
- May cause defatting of the skin.
- Can be absorbed through skin.

### Ingestion:

- Irritation of the mouth, throat, and stomach.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

### Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.

**Target Organ and Other Health Effects:**

- Kidney injury may occur.
- Liver injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.
- Blood disorders

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Carcinogens:**

- Possible cancer hazard. Contains material which may cause cancer based on animal data.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>Chemical Name</b>
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	40 - 45	Acetone
PROPANE 74-98-6	15 - 20	Propane
XYLENE 1330-20-7	5 - 10	Xylenes (o-, m-, p- isomers)
BUTANE 106-97-8	5 - 10	Butane
ETHYL 3- ETHOXYPROPIONATE 763-69-9	1 - 5	Ethyl 3-ethoxypropionate
ETHYL ACETATE 141-78-6	1 - 5	Acetic acid ethyl ester
ETHYLBENZENE 100-41-4	1 - 5	Ethyl benzene
METHYL ETHYL KETONE 78-93-3	1 - 5	Methyl ethyl ketone
PROPRIETARY RESIN	1 - 5	PROPRIETARY RESIN
TITANIUM DIOXIDE 13463-67-7	.1 - 1	Titanium dioxide

If this section is blank there are no hazardous components per OSHA guidelines.

**4. FIRST AID MEASURES****Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

**5. FIRE FIGHTING MEASURES**

Flash point (Fahrenheit):	-31°F (-35°C)
Lower explosive limit:	1 %
Upper explosive limit:	13 %
Autoignition temperature:	not determined -°F (°C)
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

**7. HANDLING AND STORAGE****Precautions to be taken in handling and storage:**

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

**8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS****Personal Protective Equipment**

**Eye and face protection:**

Chemical goggles, also wear a face shield if splashing hazard exists.

**Skin protection:**

Appropriate chemical resistant gloves should be worn.

**Other Personnel Protection Data:**

To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

**Exposure Guidelines****OSHA Permissible Exposure Limits (PEL's)**

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>TWA (final)</b>	<b>Ceilings limits (final)</b>	<b>Skin designations</b>
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	40 - 45	2400 mg/m <sup>3</sup> 1000 ppm		
PROPANE 74-98-6	15 - 20	1800 mg/m <sup>3</sup> 1000 ppm		
XYLENE 1330-20-7	5 - 10	435 mg/m <sup>3</sup> 100 ppm		
ETHYL ACETATE 141-78-6	1 - 5	1400 mg/m <sup>3</sup> 400 ppm		
ETHYLBENZENE 100-41-4	1 - 5	435 mg/m <sup>3</sup> 100 ppm		
METHYL ETHYL KETONE 78-93-3	1 - 5	590 mg/m <sup>3</sup> 200 ppm		
TITANIUM DIOXIDE 13463-67-7	.1 - 1	15 mg/m <sup>3</sup> Total dust.		

**ACGIH Threshold Limit Value (TLV's)**

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>TWA</b>	<b>STEL</b>	<b>Ceiling limits</b>	<b>Skin designations</b>
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	40 - 45	500 ppm	750 ppm		
PROPANE 74-98-6	15 - 20	1000 ppm			
XYLENE 1330-20-7	5 - 10	100 ppm	150 ppm		
BUTANE 106-97-8	5 - 10	1000 ppm			
ETHYL ACETATE 141-78-6	1 - 5	400 ppm			
ETHYLBENZENE 100-41-4	1 - 5	100 ppm	125 ppm		

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
METHYL ETHYL KETONE 78-93-3	1 - 5	200 ppm	300 ppm		
TITANIUM DIOXIDE 13463-67-7	.1 - 1	10 mg/m <sup>3</sup>			

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	Aerosol
pH:	not determined
Vapor pressure:	NOT DETERMINED mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	5.0
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	6.39
Specific Gravity:	.77
Evaporation rate (butyl acetate = 1.0):	6.2
Flash point (Fahrenheit):	-31°F (-35°C)
Lower explosive limit:	1 %
Upper explosive limit:	13 %
Autoignition temperature:	not determined -°F (°C)

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Heat.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. This product contains diarylide pigments. While they are not dangerous, they are, however, susceptible to decomposition to monoazoics and dichlorobenzidine at temperatures above 200 °C. Consequently, use at temperatures above 200 °C should be avoided.

Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
----------------------------------	---

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	40 - 45	Inhalation LC50 Rat : 50100 mg/m <sup>3</sup> /8H Inhalation LC50 Mouse : 44 gm/m <sup>3</sup> /4H Oral LD50 Rat : 5800 mg/kg Oral LD50 Mouse : 3 gm/kg
XYLENE 1330-20-7	5 - 10	Inhalation LC50 Rat : 5000 ppm/4H Oral LD50 Rat : 4300 mg/kg Dermal LD50 Rabbit : >1700 mg/kg
BUTANE 106-97-8	5 - 10	Inhalation LC50 Rat : 658 gm/m <sup>3</sup> /4H Inhalation LC50 Mouse : 680 gm/m <sup>3</sup> /2H

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>NIOSH - Selected LD50s and LC50s</b>
ETHYL 3-ETHOXYPROPIONATE 763-69-9	1 - 5	Oral LD50 Rat : 5 gm/kg Dermal LD50 Rabbit : 10 mL/kg
ETHYL ACETATE 141-78-6	1 - 5	Inhalation LC50 Rat : 200 gm/m <sup>3</sup> Inhalation LC50 Mouse : 45 gm/m <sup>3</sup> /2H Oral LD50 Rat : 5620 mg/kg Oral LD50 Mouse : 4100 mg/kg Dermal LD50 Rabbit : >20 mL/kg
ETHYLBENZENE 100-41-4	1 - 5	Oral LD50 Rat : 3500 mg/kg Dermal LD50 Rabbit : 17800 uL/kg
METHYL ETHYL KETONE 78-93-3	1 - 5	Inhalation LC50 Rat : 23500 mg/m <sup>3</sup> /8H Inhalation LC50 Mouse : 32 gm/m <sup>3</sup> /4H Oral LD50 Rat : 2737 mg/kg Oral LD50 Mouse : 4050 mg/kg Dermal LD50 Rabbit : 6480 mg/kg
PROPRIETARY RESIN	1 - 5	Oral LD50 Rat : >5 gm/kg Oral LD50 Mouse : >5 gm/kg

**Mutagens/Teratogens/Carcinogens:**

Possible cancer hazard. Contains material which may cause cancer based on animal data.

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans. Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>California Prop 65 - Reproductive (Female)</b>	<b>California Prop 65 - Carcinogen</b>
ETHYLBENZENE 100-41-4	1 - 5		Listed: June 11, 2004 Carcinogenic.

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>IARC Group 1 - Human Evidence</b>	<b>IARC Group 2A - Limited Human Data</b>	<b>IARC Group 2B - Sufficient Animal Data</b>
ETHYLBENZENE 100-41-4	1 - 5			Monograph 77, 2000
TITANIUM DIOXIDE 13463-67-7	.1 - 1			2B Possible Carcinogen

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>NTP Known Carcinogens</b>	<b>NTP Suspect Carcinogens</b>	<b>NTP Evidence of Carcinogenicity</b>
ETHYLBENZENE 100-41-4	1 - 5			male rat-clear evidence; female rat-some evidence; male mice- some evidence; female mice-some evidence

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>OSHA Select Carcinogens</b>	<b>OSHA Possible Select Carcinogens</b>	<b>ACGIH Carcinogens</b>
ETHYLBENZENE 100-41-4	1 - 5			Group A3 Confirmed animal carcinogen with unknown relevance to humans.

**12. ECOLOGICAL DATA**

No information on ecology is available.

**13. DISPOSAL CONSIDERATIONS**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORTATION INFORMATION****U.S. Department of Transportation**

Proper Shipping Name: CONSUMER COMMODITY ORM-D  
UN ID Number: CONCOM

**U.S. Highway & Rail Shipments**

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

**Reportable Quantity Description:****International Air Transport Association (IATA):**

Proper Shipping Name: AEROSOLS, FLAMMABLE  
Hazard Class: 2.1  
UN ID Number: UN1950

**International Maritime Organization (IMO):**

Proper Shipping Name: AEROSOLS  
Hazard Class: 2.1  
Non-Bulk UN ID Number: UN1950

**15. REGULATORY INFORMATION****U.S. FEDERAL REGULATIONS:**

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	40 - 45			5000
XYLENE 1330-20-7	5 - 10		form R reporting required for 1.0% de minimis concentration	100
ETHYL ACETATE 141-78-6	1 - 5			5000
ETHYLBENZENE 100-41-4	1 - 5		form R reporting required for 1.0% de minimis concentration	1000
METHYL ETHYL KETONE 78-93-3	1 - 5			5000

**SARA 311/312 Hazard Class:**

Acute: yes  
Chronic: yes  
Flammability: yes  
Reactivity: no  
Sudden Pressure: yes

**U.S. STATE REGULATIONS:****Right to Know:**

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

**Pennsylvania Right To Know:**

ETHYLBENZENE	100-41-4
XYLENE	1330-20-7
DIMETHYL KETONE- EXEMPT SOLVENT	67-64-1
ETHYL 3-ETHOXYPROPIONATE	763-69-9
ETHYL ACETATE	141-78-6
PROPRIETARY RESIN	Trade Secret
METHYL ETHYL KETONE	78-93-3
PROPANE	74-98-6
BUTANE	106-97-8

**Additional Non-Hazardous Materials**

PROPRIETARY RESIN	Trade Secret
-------------------	--------------

**California Proposition 65:**

WARNING! This product contains a chemical known in the State of California to cause cancer.

**Rule 66 status of product**

Photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories****US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION****HMIS Codes**

<b>Health:</b>	2*
<b>Flammability:</b>	4
<b>Reactivity:</b>	1
<b>PPE:</b>	X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.



**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

Prepared By:	Regulatory Affairs Department
Print date:	23/Feb/2009
Revision Date:	14/Jan/2009