DIRECTIONS

- Test a small area to make sure PRE is compatible with the metal surface to be cleaned. PRE may damage uncured paints and may damage some plastics.
- 2. Wet a clean cloth with PRE or using a trigger spray bottle, spray directly onto the surface to be cleaned.
- **3.** Wipe surface with a clean cloth to remove debris. Do not reuse dirty cloths.
- **4.** On a waxed surface use PRE before any sanding is done.
- **5.** Some contaminants may require multiple applications.

DISPOSAL: All used and unused product should be disposed of in accordance local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water. For additional information, consult the Material Safety Data Sheet (MSDS) for this product.

CONTAINS: Toluene 108-88-3, Hydrotreated Light Distillate 64742-47-8, Xylene 1330-20-7, Ethyl Benzene 100-41-4.

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Toll Free Day or Night: Chemtrec 1-800-424-9300 (International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company 263 Shoemaker Road, Pottstown, PA 19464 USA: 1-800-345-1178 Canada: 1-800-820-9042 International: (610) 323-2200 www.eastwood.com

> Label #10594ZPL • Rev. 2/14 ©Copyright 2014 The Easthill Group, Inc.







DO THE JOB RIGHT.

PRE PAINTING PREP



- Removes Silicone, Wax, Polish Grease, and Dirt
- Ensures Better Paint Adhesion
- Safe for All Metal Surfaces

DANGER:

FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT.

See other cautions on side panels.

One US Gallon / 3.79 Liters



•

May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Heat or prolonged exposure to sun may cause bursting. Do not store at temperatures above 120°F.

NOTICE: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Vapors May Ignite Explosively. Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation.

Use Only With Adequate Ventilation.

Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist labels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow the Manufacturer's directions for respirator use. Close container after each use. Avoid contact with eyes, skin, and clothing.

FIRST AID: If swallowed, DO NOT induce vomiting. Call a physician immediately. If it becomes difficult to breath, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water.

KEEP OUT OF THE REACH OF CHILDREN

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects and other reproductive harm.

100% VOC



DO THE JOB RIGHT.

PRE PAINTING PREP



- Removes Silicone, Wax, Polish Grease, and Dirt
- Ensures Better Paint Adhesion
- Safe for All Metal Surfaces

DANGER:

FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT.

See other cautions on side panels.

One US Gallon / 3.79 Liters

10594 ZP







