

# SAFETY DATA SHEET

**Part No. 11173ZP (Liquid)**

 Print Date: 7/25/2018  
 Revision Date: 7/25/2018  
 Supersedes Date: 8/19/2015  
 Issue Date: 6/27/2006  
 Version: 4.0 (EN)-US  
 Page: 1/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 1 - IDENTIFICATION

#### 1.1 Product Identifier

Product Name : Eastwood Extreme Chassis Black Gloss Finish  
 Supplier Product Numbers : 11173ZP

#### 1.2 Other Means of Identification

Other Identifiers : Not Available

#### 1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Underbody coating  
 Restrictions on Use : None Identified

#### 1.4 Supplier Details

Supplier Details	
Company Name	The Easthill Group, Inc./The Eastwood Company
Address	263 Shoemaker Road, Pottstown, PA 19464 - United States
Phone Number	800-343-9353
Website	www.eastwood.com

#### 1.5 24 hr Emergency Phone Number

Emergency Number : 800-424-9300 ChemTrec

### SECTION 2 - HAZARDS IDENTIFICATION

#### 2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Skin Irrit. 2	H315	Health Hazards	Skin corrosion/irritation Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Skin Sens. 1	H317	Health Hazards	Skin sensitization, Category 1
Carc. 2	H351	Health Hazards	Carcinogenicity Category 2
Repr. 2	H361	Health Hazards	Reproductive toxicity Category 2
Stot Re 1	H372	Health Hazards	Specific target organ toxicity (repeated exposure) Category 1
Asp. Tox. 1	H304	Health Hazards	Aspiration hazard Category 1
Aquatic Acute 3	H402	Environmental Hazards	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	H412	Environmental Hazards	Hazardous to the aquatic environment - Chronic Hazard Category 3

#### 2.2 Label Elements

Hazard Pictograms



Signal Word

**Danger**

Hazard Statements

H225 : Highly flammable liquid and vapour  
 H304 : May be fatal if swallowed and enters airways  
 H315 : Causes skin irritation

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 2/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H317 : May cause an allergic skin reaction  
H319 : Causes serious eye irritation  
H351 : Suspected of causing cancer  
H361 : Suspected of damaging fertility or the unborn child  
H372 : Causes damage to organs through prolonged or repeated exposure  
H402 : Harmful to aquatic life  
H412 : Harmful to aquatic life with long lasting effects

### Precautionary Statements

P202 : Do not handle until all safety precautions have been read and understood.  
P210 : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 : Keep container tightly closed.  
P240 : Ground/Bond container and receiving equipment  
P241 : Use explosion-proof electrical/ventilating/lighting equipment  
P242 : Use only non-sparking tools.  
P243 : Take precautionary measures against static discharge.  
P260 : Do not breathe vapours.  
P264 : Wash hands thoroughly after handling.  
P270 : Do not eat, drink or smoke when using this product.  
P272 : Contaminated work clothing must not be allowed out of the workplace  
P273 : Avoid release to the environment.  
P280 : Wear protective gloves and eye protection.  
P301+P310 : If swallowed: Immediately call POISON CENTER  
P303+P361+P353 : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P305+P351+P338 : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308+P313 : If exposed or concerned: Get medical advice/attention.  
P314 : Get medical advice/attention if you feel unwell.  
P331 : Do NOT induce vomiting.  
P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 : If eye irritation persists: Get medical advice/attention.  
P362+P364 : Take off contaminated clothing and wash it before reuse.  
P370+P378 : In case of fire: Use water, CO2, dry chemical, or universal aqueous film forming foam to extinguish.  
P403+P235 : Store in a well-ventilated place. Keep cool.  
P405 : Store locked up.  
P501 : Dispose of contents/container to local regulations

### 2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

### 2.4 Unknown acute toxicity

35.62% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
35.62% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
35.62% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substance / Mixture

Substance / Mixture : Mixture

### 3.2 Composition

Substance name	CAS Number	% wt*	Classification
Mineral Spirits	64742-88-7	10 - 30	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 3/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substance name	CAS Number	% wt*	Classification
Acetone	67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
4-Chlorobenzotrifluoride	98-56-6	10 - 30	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Propylene Glycol Monomethyl Ether Acetate	108-65-6	5 - 10	Flam. Liq. 3, H226
Carbon Black	1333-86-4	1 - 5	Carc. 2, H351
Hydrotreated Heavy Petroleum Naphtha	64742-48-9	1 - 5	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Zirconium 2-Ethylhexanoate	22464-99-9	0.1 - 1	Repr. 2, H361
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	Flam. Liq. 4, H227 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4 - FIRST-AID MEASURES

### 4.1 Description of First-Aid Measures

General Measures	: Call a physician immediately.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
Skin Contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Do NOT induce vomiting. Call a physician immediately.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Lassitude (Weakness), Dermatitis, Central Nervous System Depression, Confusion, Respiratory Irritation, Skin Irritation, Headache, Dizziness, Nausea, Narcosis, Upper Respiratory Tract Irritation, Drowsiness, Vomiting, Cough, Chemical Pneumonitis (Aspiration Liquid), Mucous Membrane.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Blood, Central Nervous System, Eyes, Liver, Respiratory System, Skin, Kidneys.

### 4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

## SECTION 5 - FIRE-FIGHTING MEASURES

### 5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 4/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.2 Specific Hazards Arising from the Chemical or Mixture

- Hazardous Combustion Products** : Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
- Specific Hazards During Firefighting** : CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

### 5.3 Special Protective Actions for Fire-Fighters

- Firefighting Instructions** : Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
- Protection during Firefighting** : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- For Non-Emergency Personnel** : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
- For Emergency Personnel** : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

### 6.2 Environmental Precautions

- Environmental Precautions** : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

### 6.3 Methods and Materials for Containment and Cleaning up

- Containment Procedures** : Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
- Cleanup Procedures** : Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

## SECTION 7 - HANDLING AND STORAGE

### 7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Application using Flammable and Combustible Materials is recommended.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

### 7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control Parameters

Acetone (67-64-1)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	250 ppm
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	500 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 5/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Acetone (67-64-1)

California	California PEL (TWA) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

### Propylene Glycol Monomethyl Ether Acetate (108-65-6)

California	California PEL (TWA) (mg/m <sup>3</sup> )	541 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	100 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	811 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	150 ppm

### Carbon Black (1333-86-4)

ACGIH	ACGIH TWA (ppm)	3 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
NIOSH	US IDLH (mg/m <sup>3</sup> )	1750 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>
California	California PEL (TWA) (mg/m <sup>3</sup> )	3.5 mg/m <sup>3</sup>

### Methyl Ethyl Ketoxime (96-29-7)

AIHA	WEEL TWA (ppm)	10 ppm
------	----------------	--------

## 8.2 Exposure Controls

<b>Engineering Measures</b>	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
<b>Personal Protective Equipment</b>	
<b>Eye / Face Protection</b>	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
<b>Hand Protection</b>	: Chemical-resistant gloves, tested according to ASTM F903-17.
<b>Remarks</b>	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
<b>Skin and Body Protection</b>	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
<b>Respiratory Protection</b>	: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.
<b>Compliance</b>	: If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.
<b>Other Protective Equipment</b>	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.
<b>Environmental Exposure Controls</b>	: Avoid release to the environment.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Physical Properties

Boiling Point	> 55.60 °C	Melting / Freezing Point	> -95.40 °C
Flash Point, Liquid	> -17.20 °C		
Explosive Limits	LEL: 0.60 UEL: 13.10 vol %	Autoignition Temperature, Liquid	200.00 °C
Flammability	Highly Flammable Liquid	Density	0.944 g/cm <sup>3</sup>
Molecular Weight	Not Available	Weight	7.878 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	Not Available
Appearance / Color	Black	Water Solubility	Not Available
Odor	Paint-like	Decomposition Temperature	Not Available

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 6/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2 Environmental Properties

Percent Volatile	62.27 % wt	VOC Regulatory	425.96 g/L (3.55 lbs/gal)
Percent VOC	30.69 % wt	VOC Actual	289.69 g/L (2.42 lbs/gal)
Percent HAP	0.07 % wt	HAP Content	0.66 g/L (0.01 lbs/gal)
Global Warming Potential	0.08 GWP	Maximum Incremental Reactivity	0.6450 g O3/g
Ozone Depletion Potential	0.00 ODP		

## SECTION 10 - STABILITY AND REACTIVITY

### 10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

### 10.2 Chemical Stability

Chemical Stability : This product is stable.

### 10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

### 10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

### 10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Potassium t-Butoxide, Bases, Hydrogen Peroxide.

### 10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Unstable peroxides, Formaldehyde, Methanol, Acetic Acid.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### 11.1 Information on Toxicological Effects

#### Hydrotreated Heavy Petroleum Naphtha (CAS: 64742-48-9 / EC: 265-150-3)

LD50 Oral (Rat)	> 6000 mg/kg (RTECS)
LD50 Dermal (Rat)	> 5000 mg/kg (MERCK)
LC50 Inhalation (Rat)	8500 mg/m <sup>3</sup> (RTECS)

#### Zirconium 2-Ethylhexanoate (CAS: 22464-99-9 / EC: 245-018-1)

LD50 Oral (Rat)	> 5000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 5000 mg/kg (RTECS)
LC50 Inhalation (Rat)	> 8800 mg/m <sup>3</sup> (RTECS)

#### Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (GESTIS Substance Database)

#### 4-Chlorobenzotrifluoride (CAS: 98-56-6 / EC: 202-681-1)

LD50 Oral (Rat)	13000 mg/kg (Hazardous Substances Data Bank)
LD50 Dermal (Rabbit)	3300 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	33 mg/l/4h (Hazardous Substances Data Bank)

#### Mineral Spirits (CAS: 64742-88-7 / EC: 265-191-7)

LD50 Oral (Rat)	> 5000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	> 3000 mg/kg (Lit.)
LC50 Inhalation (Rat)	5500 ppm/4h (Lit.)

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 7/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Propylene Glycol Monomethyl Ether Acetate (CAS: 108-65-6 / EC: 203-603-9)

LD50 Oral (Rat)	10000 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	19200 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	> 5250 ppm/4h (ChemInfo)

### Carbon Black (CAS: 1333-86-4 / EC: 215-609-9)

LD50 Oral (Rat)	> 15400 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 3000 mg/kg (RTECS)
LC50 Inhalation (Rat)	27 mg/l/4h (ChemInfo)

### Methyl Ethyl Ketoxime (CAS: 96-29-7 / EC: 202-496-6)

LD50 Oral (Rat)	> 930 mg/kg (RTECS)
LD50 Dermal (Rat)	> 2000 mg/kg (RTECS)
LD50 Dermal (Rabbit)	> 1000 mg/kg body weight (RTECS)
LC50 Inhalation (Rat)	20 mg/l/4h (Lit.)

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation.
Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure	: See Section 4.2
Skin Corrosion/Irritation	: Causes skin irritation.
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: May cause an allergic skin reaction.
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
STOT-Single Exposure	: Not classified
STOT-Repeated Exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration Hazard	: May be fatal if swallowed and enters airways.
Carcinogen Data	: The following ingredients are listed as known or suspected carcinogens:

### Carbon Black (CAS: 1333-86-4 / EC: 215-609-9)

IARC group	2B - Possibly Carcinogenic to Humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans

## SECTION 12 - ECOLOGICAL INFORMATION

### 12.1 Ecotoxicity and Ecological Properties

#### Hydrotreated Heavy Petroleum Naphtha (64742-48-9)

Bioaccumulative Potential	Bioaccumable.
---------------------------	---------------

#### Acetone (67-64-1)

LC50 Fish	5540 mg/l Rainbow Trout - 96hr
LC50 Fish	8300 mg/l Bluegill Sunfish - 96h
EC50 Daphnia	8800 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 90% / 28 days.
Biochemical Oxygen Demand	1.43 g O <sub>2</sub> /g substance
Chemical Oxygen Demand	1.92 g O <sub>2</sub> /g substance
Theoretical Oxygen Demand	2.2 g O <sub>2</sub> /g substance
BCF Fish	0.69
BCF Other Aquatic Organisms	3
Log Pow	-0.24

#### 4-Chlorobenzotrifluoride (98-56-6)

LC50 Fish	5.6 mg/l Bluegill Sunfish - 96h
LC50 Fish	13.5 mg/l Rainbow Trout - 24hr
EC50 Daphnia	3.68 mg/l (EC50; 48 h)
Persistence and Degradability	Biodegradability in water: no data available.
Log Pow	3.6
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).



# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 8/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Mineral Spirits (64742-88-7)

LC50 Fish	500 mg/l 96hr
EC50 Daphnia	> 100 mg/l 48hr
Chemical Oxygen Demand	0.47 mg/g
Log Pow	3.3
Bioaccumulative Potential	No bioaccumulation data available.

### Propylene Glycol Monomethyl Ether Acetate (108-65-6)

LC50 Fish	100 ml/l Rainbow Trout - 96hr
EC50 Daphnia	373 mg/l Water Flea - 48hr
EC50 Daphnia	> 1000 mg/l Green Algae - 96hr
Persistence and Degradability	Biodegradability 81% / 28 days.
Biochemical Oxygen Demand	330 mg/g
Chemical Oxygen Demand	1740 mg/g
Theoretical Oxygen Demand	1820 mg/g
Log Pow	0.56
Log Koc	0.36

### Carbon Black (1333-86-4)

LC50 Fish	> 1000 mg/l Zebra Fish - 96hr
EC50 Daphnia	> 5600 mg/l Water Flea - 24hr
EC50 Other Aquatic Organisms	> 10000 mg/l Green Algae - 72hr
Theoretical Oxygen Demand	Not applicable
Log Pow	1.09
Bioaccumulative Potential	Not bioaccumulative.

### Methyl Ethyl Ketoxime (96-29-7)

BCF Fish	0.5-5.8,BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; Cyprinus carpio; Fresh water; Experimental value
Log Pow	0.63 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).

## SECTION 13 - DISPOSAL CONSIDERATIONS

### 13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.
Incineration Precautions	: Not Available.

## SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1263	UN1263	UN1263
14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity
14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 3	3	3
Labels	: None	3 - Flammable liquid	None



# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 9/10


## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Limited Quantity

:


Yes



Yes



Yes



EmS Code

:

Not Applicable

Not Applicable

F-E, S-E

### 14.4 Packing Group

DOT (USA)

IATA (AIR)

IMDG (OCEAN)

Packing Group

:

II

II

II

### 14.5 Environmental Hazards

DOT (USA)

IATA (AIR)

IMDG (OCEAN)

Marine Pollutant

:

No

No

No

### 14.6 Special Precautions

Precautions

:

None Identified

### 14.7 Transport in Bulk

Remarks

:

Not applicable for product as supplied

## SECTION 15 - REGULATORY INFORMATION

### 15.1 Federal Regulations

SARA Section 313

: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

1,2,4-Trimethyl Benzene	CAS-No. 95-63-6	< 1%
Methyl Isobutyl Ketone	CAS-No. 108-10-1	< 1%

TSCA Section 12(b)

: This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

CERCLA Reportable Quantity

: Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
Methyl Isobutyl Ketone	CAS-No. 108-10-1	5000 lb

SARA Section 311/312 Hazard Classes

: Fire hazard, Immediate (acute) health hazard.

TSCA Inventory (United States)

: All chemical substances in this product are either listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.

### 15.2 State Regulations

California Proposition 65

: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Carbon Black (1333-86-4)	Cancer	Yes	1.46 %
Methyl Isobutyl Ketone (108-10-1)	Cancer	Yes	0.0665 %
Methyl Isobutyl Ketone (108-10-1)	Developmental Toxicity	Yes	0.0665 %

State Right-to-Know Lists

: The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Nonane (111-84-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
2-Ethylhexanoic Acid (149-57-5)	U.S. - New Jersey - Right to Know Hazardous Substance List
1,2,4-Trimethyl Benzene (95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List

# SAFETY DATA SHEET

Part No. 111732P (Liquid)

Print Date: 7/25/2018  
Revision Date: 7/25/2018  
Supersedes Date: 8/19/2015  
Issue Date: 6/27/2006  
Version: 4.0 (EN)-US  
Page: 10/10

## Eastwood Extreme Chassis Black Gloss Finish

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	U.S. - Pennsylvania - RTK (Right to Know) List
Carbon Black (1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List
Methyl Isobutyl Ketone (108-10-1)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Dipropylene Glycol Monomethyl Ether (34590-94-8)	U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16 - OTHER INFORMATION

### Indication of changes

Section	Changed item	Change
1	SDS US Regulation reference	Added
1	Supersedes	Modified
1	Revision date	Modified
1	Date of issue	Modified
2.2	Precautionary statements (GHS-US)	Modified
2.2	Hazard statements (GHS-US)	Modified
3	Composition/Information on ingredients	Modified
4	Symptoms/effects after ingestion	Modified
4.1	First-aid measures after ingestion	Modified
4.1	First-aid measures general	Modified
8.2	Compliance	Added
8.2	Remarks	Added
8.2	Hand Protection	Added
8.2	Environmental Exposure Controls	Added
8.2	Respiratory Protection	Added
9	Relative vapor density at 20 °C	Added
9	Appearance	Added
9	Melting point	Modified
9	Flash point	Modified
9	Explosive limits (vol %)	Modified
9	Boiling point	Modified
9	Auto-ignition temperature	Modified
9	Specific gravity / density	Modified
14	User Precautions	Added
14	EmS Code (Column 15 in IMDG Book 2)	Added
15	Select the Appropriate Proposition 65 Notice	Modified

### Full Text of H-Statements

H Code	H Phrase
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

### Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.