

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 1/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Rubberized Rust Encapsulator :
Supplier Product Numbers : 11864ZP

1.2 Other Means of Identification

Other Identifiers : Not Applicable

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Automobile rust encapsulator
Restrictions on Use : None Identified

1.4 Supplier Details

Supplier Details	
Company Name	The Eastwood Company
Address	263 Shoemaker Road Pottstown, PA 19464
Phone Number	800-343-9353
Website	www.eastwood.com

1.5 24 hr Emergency Phone Number

Emergency Number : 800-424-9300 ChemTrec

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Skin Irrit. 2	H315	Health Hazards	Skin corrosion/irritation Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Repr. 2	H361	Health Hazards	Reproductive toxicity Category 2
Stot Se 3	H335	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Respiratory tract irritation
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Narcosis
Stot Re 2	H373	Health Hazards	Specific target organ toxicity (repeated exposure) Category 2
Aquatic Acute 2	H401	Environmental Hazards	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	H411	Environmental Hazards	Hazardous to the aquatic environment - Chronic Hazard Category 2

2.2 Label Elements

Hazard Pictograms



GHS02



GHS07



GHS08



GHS09

Signal Word

Danger

Hazard Statements

H225 : Highly flammable liquid and vapour
H315 : Causes skin irritation
H319 : Causes serious eye irritation

SAFETY DATA SHEET

Part No. 118642P (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 2/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary Statements	H335	: May cause respiratory irritation
	H336	: May cause drowsiness or dizziness
	H361	: Suspected of damaging fertility or the unborn child
	H373	: May cause damage to organs through prolonged or repeated exposure
	H401	: Toxic to aquatic life
	H411	: Toxic to aquatic life with long lasting effects
	P202	: Do not handle until all safety precautions have been read and understood.
	P210	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P233	: Keep container tightly closed.
	P240	: Ground/Bond container and receiving equipment
	P241	: Use explosion-proof electrical/ventilating/lighting equipment
	P242	: Use only non-sparking tools.
	P243	: Take precautionary measures against static discharge.
	P260	: Do not breathe vapors.
	P264	: Wash hands thoroughly after handling.
	P271	: Use only outdoors or in a well-ventilated area.
	P273	: Avoid release to the environment.
	P280	: Wear protective gloves and eye protection.
	P303+P361+P353	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
	P304+P340	: If inhaled: Remove person to fresh air and keep comfortable for breathing
	P305+P351+P338	: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P308+P313	: If exposed or concerned: Get medical advice/attention.
	P314	: Get medical advice/attention if you feel unwell.
	P332+P313	: If skin irritation occurs: Get medical advice/attention.
	P337+P313	: If eye irritation persists: Get medical advice/attention.
	P362+P364	: Take off contaminated clothing and wash it before reuse.
	P370+P378	: In case of fire: Use water, CO2, dry chemical, or universal aqueous film forming foam to extinguish.
	P391	: Collect spillage.
	P403+P233	: Store in a well-ventilated place. Keep container tightly closed.
	P235	: Keep cool.
	P405	: Store locked up.
	P501	: Dispose of contents/container to applicable regulations

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

47.25% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
47.25% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
49% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 3/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substance name	CAS Number	% wt*	Classification
4-Chlorobenzotrifluoride	98-56-6	30 - 60	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Toluene	108-88-3	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Propylene Carbonate	108-32-7	1 - 5	Eye Irrit. 2, H319

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

General Measures	: If exposed or concerned: Get medical advice/attention.
Inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
Skin Contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Call a poison center or a doctor if you feel unwell.
First-Aid Responder Protection	: No additional protection needs are anticipated.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Dermatitis, Confusion, Respiratory Irritation, Skin Irritation, Headache, Dizziness, Narcosis, Cough, Mucous Membrane.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: No known chronic effects.
Target Organs	: Central Nervous System, Eyes, Liver, Reproductive System, Respiratory System, Skin, Kidneys.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting	: CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 4/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3 Special Protective Actions for Fire-Fighters

- Firefighting Instructions** : Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
- Protection during Firefighting** : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- For Non-Emergency Personnel** : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
- For Emergency Personnel** : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

- Environmental Precautions** : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

6.3 Methods and Materials for Containment and Cleaning up

- Containment Procedures** : Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
- Cleanup Procedures** : Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Application using Flammable and Combustible Materials is recommended.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Toluene (108-88-3)		
ACGIH	ACGIH TWA (mg/m ³)	20 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	150 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
NIOSH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
California	California PEL (TWA) (mg/m ³)	37 mg/m ³
California	California PEL (TWA) (ppm)	10 ppm
California	California PEL (STEL) (mg/m ³)	560 mg/m ³
California	California PEL (STEL) (ppm)	150 ppm

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 5/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)

California	California PEL (Ceiling) (ppm)	500 ppm
Biological Exposure Index	Toluene in blood, Prior to last shift of workweek	0.02 mg/l
Biological Exposure Index	Toluene in urine, End of shift	0.03 mg/l
Biological Exposure Index	o-Cresol in urine (with hydrolysis), End of shift (B)	0.3 mg/g creatinine

8.2 Exposure Controls

Engineering Measures	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
Personal Protective Equipment	
Eye / Face Protection	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
Hand Protection	: Chemical-resistant gloves, tested according to ASTM F903-17.
Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
Skin and Body Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
Respiratory Protection	: Respiratory protection is not anticipated to be needed.
Compliance	: If needed, wear an appropriate NIOSH approved respirator.
Other Protective Equipment	: Not Applicable.
Environmental Exposure Controls	: Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 80.00 °C	Melting / Freezing Point	> -96.00 °C
Flash Point, Liquid	> 6.00 °C		
Explosive Limits	LEL: 0.80 UEL: 7.80 vol %	Autoignition Temperature, Liquid	> 425.00 °C
Flammability	Highly Flammable Liquid	Density	1.242 g/cm ³
Molecular Weight	Not Available	Weight	10.364 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	788.00 cSt (centistoke)	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	> 5982.10 BTU/lb
Appearance / Color	Black	Water Solubility	Not Available
Odor	Aromatic	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	52.75 % wt	VOC Regulatory	382.20 g/L (3.19 lbs/gal)
Percent VOC	21.00 % wt	VOC Actual	260.82 g/L (2.18 lbs/gal)
Percent HAP	21.00 % wt	HAP Content	260.82 g/L (2.18 lbs/gal)
Global Warming Potential	0.57 GWP	Maximum Incremental Reactivity	0.8770 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 6/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Acids, Bases, Aluminum Chloride, Acids, Chlorosulfuric Acid, Potassium Chlorate.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Acute Toxicity : None Identified

4-Chlorobenzotrifluoride (CAS: 98-56-6 / EC: 202-681-1)

LD50 Oral (Rat)	13000 mg/kg (Hazardous Substances Data Bank)
LD50 Dermal (Rabbit)	3300 mg/kg (Sigma-Aldrich)
LC50 Inhalation (Rat)	33 mg/l/4h (Hazardous Substances Data Bank)

Toluene (CAS: 108-88-3 / EC: 203-625-9)

LD50 Oral (Rat)	> 2000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	12124 mg/kg (IUCLID)
LC50 Inhalation (Rat)	> 20 mg/l/4h (Lit.)

Propylene Carbonate (CAS: 108-32-7 / EC: 203-572-1)

LD50 Oral (Rat)	> 5000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male/female, Experimental value, Oral)
LD50 Dermal (Rabbit)	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male/female, Experimental value, Dermal)
LC50 Inhalation (Rat)	(RTECS)

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.

Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure : See Section 4.2

Skin Corrosion/Irritation : Causes skin irritation.

Eye Damage/Irritation : Causes serious eye irritation.

Respiratory or Skin Sensitization : Not classified

Germ Cell Mutagenicity : Not classified

Reproductive Toxicity : Suspected of damaging fertility or the unborn child.

STOT-Single Exposure : May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-Repeated Exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard : Not classified

Carcinogen Data : None of the ingredients in the product are listed with EU, IARC, or NTP as being suspected or known carcinogen in a concentration greater than 0.1% by weight.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

4-Chlorobenzotrifluoride (98-56-6)

LC50 Fish	5.6 mg/l Bluegill Sunfish - 96h
LC50 Fish	13.5 mg/l Rainbow Trout - 24hr
EC50 Daphnia	3.68 mg/l (EC50; 48 h)
Persistence and Degradability	Biodegradability in water: no data available.



DO THE JOB RIGHT.

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018

Revision Date: 12/11/2018

Supersedes Date: 11/18/2015

Issue Date: 7/12/2012

Version: 3.0 (EN)-US

Page: 7/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4-Chlorobenzotrifluoride (98-56-6)

Log Pow	3.6
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).

Toluene (108-88-3)

LC50 Fish	5.8 mg/l Rainbow Trout - 96hr
LC50 Other Aquatic Organisms	10 mg/l Green Algae - 72hr
EC50 Daphnia	6 mg/l Water Flea - 48hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in soil.
Biochemical Oxygen Demand	2.15 g O ₂ /g substance
Chemical Oxygen Demand	2.52 g O ₂ /g substance
Theoretical Oxygen Demand	3.13 g O ₂ /g substance
Biodegradation	86 % 28 Days
Log Pow	2.73 (Experimental Value)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	2.15

Propylene Carbonate (108-32-7)

LC50 Fish	5300 mg/l (96 h, Leuciscus idus, Static system)
EC50 Daphnia	> 1000 mg/l (48 h, Daphnia magna, GLP)
Persistence and Degradability	Readily biodegradable in water.
Biochemical Oxygen Demand	0.046 g O ₂ /g substance
Chemical Oxygen Demand	1.29 g O ₂ /g substance
Log Pow	-0.48 - -0.41 (Experimental value)
Bioaccumulative Potential	Not bioaccumulative.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.
Incineration Precautions	: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1263	UN1263	UN1263
14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity	Paint Related Material, Limited Quantity
14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 3	3	3
Labels	: None	3 - Flammable liquid	None
Limited Quantity	: Yes	Yes	Yes




SAFETY DATA SHEET

Part No. 118642P (Quart)

 Print Date: 11/12/2018
 Revision Date: 12/11/2018
 Supersedes Date: 11/18/2015
 Issue Date: 7/12/2012
 Version: 3.0 (EN)-US
 Page: 8/10

Rubberized Rust Encapsulator


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



Not Applicable



Not Applicable



F-E, S-E

EmS Code

:

14.4 Packing Group

DOT (USA)
IATA (AIR)
IMDG (OCEAN)

Packing Group

:

II

II

II

14.5 Environmental Hazards

DOT (USA)
IATA (AIR)
IMDG (OCEAN)

Marine Pollutant

:

No

No

No

14.6 Special Precautions

Precautions

: None Identified

14.7 Transport in Bulk

Remarks

: Not applicable for product as supplied

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313

: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Benzene	CAS-No. 71-43-2	< 1%
Naphthalene	CAS-No. 91-20-3	< 1%
Cumene	CAS-No. 98-82-8	< 1%
Ethyl Benzene	CAS-No. 100-41-4	< 1%
Toluene	CAS-No. 108-88-3	10 - 30%

TSCA Section 12(b)

: This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

CERCLA Reportable Quantity

: Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Benzene	CAS-No. 71-43-2	10 lb
Naphthalene	CAS-No. 91-20-3	100 lb
Cumene	CAS-No. 98-82-8	5000 lb
Ethyl Benzene	CAS-No. 100-41-4	1000 lb
Toluene	CAS-No. 108-88-3	1000 lb

15.2 State Regulations

California Proposition 65

: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Benzene (71-43-2)	Cancer	Yes	0.0001 %
Naphthalene (91-20-3)	Cancer	Yes	0.0007 %
Cumene (98-82-8)	Cancer	Yes	0.0007 %
Ethyl Benzene (100-41-4)	Cancer	Yes	0.063 %
Benzene (71-43-2)	Developmental Toxicity	Yes	0.0001 %
Toluene (108-88-3)	Developmental Toxicity	Yes	20.9355 %
Ethyl Benzene (100-41-4)	No significance risk level (NSRL)	54	
Toluene (108-88-3)	No significance risk level (NSRL)	7000	

SAFETY DATA SHEET

Part No. 118642P (Quart)

Print Date: 11/12/2018
Revision Date: 12/11/2018
Supersedes Date: 11/18/2015
Issue Date: 7/12/2012
Version: 3.0 (EN)-US
Page: 9/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

State Right-to-Know Lists

: The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Benzene (71-43-2)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Naphthalene (91-20-3)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Ethyl Benzene (100-41-4)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Toluene (108-88-3)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 - OTHER INFORMATION

Indication of changes

Section	Changed item	Change
1	Revision date	Modified
1	Supersedes	Added
1	Date of issue	Modified
1	SDS US Regulation reference	Added
2.1	GHS-US classification	Modified
2.2	Precautionary statements (GHS US)	Modified
2.2	Hazard statements (GHS US)	Modified
2.2	Hazard pictograms (GHS US)	Modified
3	Composition/Information on ingredients	Modified
4	Symptoms/effects after skin contact	Modified
4	Symptoms/effects after inhalation	Modified
4	Symptoms/effects after eye contact	Modified
4	Symptoms/effects	Added
4.1	First-aid measures after ingestion	Modified
4.1	First-aid measures after skin contact	Modified
4.1	First-aid measures after inhalation	Modified
4.1	First-aid measures after eye contact	Modified
8.2	Respiratory Protection	Added
8.2	Eye / Face Protection	Modified
8.2	Skin and Body Protection	Modified
8.2	Engineering Measures	Modified
8.2	Remarks	Added
8.2	Environmental Exposure Controls	Added
8.2	Compliance	Added
8.2	Hand Protection	Added
9	Melting point	Modified
9	Boiling point	Modified
9	Auto-ignition temperature	Modified
9	Relative vapor density at 20 °C	Added
9	Flash point	Added
9	Explosive limits (vol %)	Added
9	Specific gravity / density	Added
10	Reactivity	Modified
10	Conditions to avoid	Modified
12.1	Ecology - general	Modified
13	Additional information	Added
14	User Precautions	Added
14	EmS Code (Column 15 in IMDG Book 2)	Added
15	Select the Appropriate Proposition 65 Notice	Modified

Full Text of H-Statements

H Code	H Phrase
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.



DO THE JOB RIGHT.

SAFETY DATA SHEET

Part No. 11864ZP (Quart)

Print Date: 11/12/2018

Revision Date: 12/11/2018

Supersedes Date: 11/18/2015

Issue Date: 7/12/2012

Version: 3.0 (EN)-US

Page: 10/10

Rubberized Rust Encapsulator

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations