#### PRODUCT: 12417Z EW GUIDE COAT TAN AEROSOL 12 OZ







## Section 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURED FOR ..... THE EASTHILL GROUP dba/ THE EASTWOOD COMPANY 263 SHOEMAKER ROAD POTTSTOWN, PA 19464 USA & CANADA: 800-345-1178; OUTSIDE USA: 610-323-2200 CHEM-TREC: 800-424-9300 EMERGENCY CONTACT.....

12417Z EW GUIDE COAT TAN AEROSOL 12 OZ ACRYLIC BASED COATING. NOT APPLICABLE. PRODUCT NAME.....

CHEMICAL FAMILY......MOLECULAR WEIGHT.....CHEMICAL FORMULA.....

**MIXTURE** TRADE NAMES & SYNONYMS..... 05303-14-441/5 GUIDE COAT - BEIGE 12OZ

PRODUCT USES ..... ..... COATING.

FORMULA/LAB BOOK #..... F 14-128/002-21-128.

0 41 00	001100017101//1156	DALATION INCORPIENTO
Section 02:	·COMPOSITION/INFO	DRMATION INGREDIENTS

Codion 62. Comin Controllina Orthication Incidental					
Hazardous Ingredients	%	Exposure Limit	C.A.S.#	LD/50, Route,Species	LC/50 Route,Species
ACETONE	15-40	750 ppm	67-64-1	>9750 mg/kg ORAL - RAT	>16,000 ppm (4 hr) INHAL - RAT
VM&P NAPHTHA	10-30	300 ppm	64742-89-8	NOT AVAILABLE	3400 ppm (4 hr) INHAL - RAT
TOLUENE	7-13	50 ppm	108-88-3	5000 mg/kg ORAL - RAT	8000 ppm (4 hr) INHAL - RAT
TALC (MAGNESIUM SILICATE HYDRATE)	5-10	2 mg/m 3	14807-96-6	NOT AVAILABLE	NOT AVAILABLE
TITANIUM DIOXIDE	7-13		13463-67-7	NOT AVAILABLE	NOT AVAILABLE
ISOBUTANE	5-10	1000 ppm	75-28-5	NOT APPLICABLE	142,500 ppm (4h) INHAL - RAT
PROPANE	10-30	1000 ppm	74-98-6	NOT APPLICABLE	NOT AVAILABLE

# Section 03: HAZARDS IDENTIFICATION

ROUTE OF ENTRY:

INGESTION.....

MAY CAUSE HEADACHE, NAUSEA, VOMITING AND WEAKNESS. INHALATION OF SOLVENTS MAY CAUSE IRRITATION. PROPELLANT IS A SIMPLE INHALATION.....

ASPHYXIANT.

MAY CAUSE IRRITATION.

EYE CONTACT.....SKIN ABSORPTION.... NO DATA AVAILABLE FOR THIS PRODUCT MIXTURE.

### Section 04: FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE ..... IN CASE OF EYE CONTACT, FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN, WASH THOROUGHLY WITH SOAP AND WATER. IF AFFECTED BY INHALATION OF VAPOUR OR SPRAY MIST, REMOVE TO FRESH AIR.

IF SWALLOWED; DO NOT INDUCE VOMITING, GET MEDICAL ATTENTION.

## Section 05: FIRE FIGHTING MEASURES

AUTO IGNITION TEMPERATURE (°C)..... WATER FROM FOGGING NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT BUILD-UP IF EXPOSED TO EXTREME TEMPERATURES. FULL PROTECTIVE EQUIPMENT INCLUDING SELF CONTAINED BREATHING APPARTATUS SHOULD BE WORN IN A SPECIAL PROCEDURES..... FIRE INVOLVING THIS MATERIAL. FLAMMABILITY..... **FLAMMABLE** 

IF YES, UNDER WHICH CONDITIONS?..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME UPPER FLAMMABLE LIMIT...... 12.8.

(% BY VOLUME) LOWER FLAMMABLE LIMIT...... 1. (% BY VOLUME)

**EXPLOSION DATA** 

HAZARDOUS COMBUSTION

### EW #12417Z - EW Guide Coat Tan Aerosol 12 oz MATERIAL SAFETY DATA SHEET 00007700 Page 2 PRODUCT: 12417Z EW GUIDE COAT TAN AEROSOL 12 OZ Section 05: FIRE FIGHTING MEASURES PRODUCTS..... HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS INCOMPLETE. AEROSOL FLAME PROJECTION CLASSIFIED AS: >45cm. Section 06: ACCIDENTAL RELEASE MEASURES LEAK/SPILL.... REMOVE ALL SOURCES OF IGNITION. USE AN INERT ABSORBENT MATERIAL, AND NON-SPARKING TOOLS. VENTILATE AREA. PREVENT FROM ENTERING A WATERCOURSE. Section 07: HANDLING AND STORAGE KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. ..... ENGINEERING CONTROLS..... VENTILATION - LOCAL (MECHANICAL IF USED INDOORS ON A CONTINUOUS BASIS). STORE IN A COOL, WELL VENTILATED AREA NOT TO EXCEED 50 DEG C. HANDLING PROCEDURES AND EQUIPMENT..... SYNERGISTIC MATERIALS..... NONE KNOWN. Section 08: EXPOSURE CONTROLS/PERSONAL PROTECTION GLOVES/ TYPE.....RESPIRATORY/TYPE.... WEAR CHEMICAL RESISTANT GLOVES. IF USED INDOORS ON A CONTINUOUS BASIS, USE OF A CARTRIDGE TYPE RESPIRATOR (NIOSH/MSHATC 23C OR EQUIVALENT) IS RECOMMENDED. EYE/TYPE......FOOTWEAR/TYPE..... SAFETY GLASSES. NOT NORMALLY REQUIRED. OTHER/TYPE..... NOT REQUIRED. Section 09: PHYSICAL AND CHEMICAL PROPERTIES PHYSICAL STATE..... AEROSOL. APPEARANCE..... BEIGE. KETONE @ 20 C BOILING POINT (°C)(CONC)...... 57-156. EVAPORATION RATE...... GREATER THAN 1. n-BLITYL ACETATE = 1 VAPOUR DENSITY (AIR=1)..... GREATER THAN 1. (BY WEIGHT) SOLUBILITY IN WATER g/L (20°C)...... NEGLIGIBLE. AEROSOL PERCENT VOLATILE...... 75-76. (BY WEIGHT) SPECIFIC GRAVITY (AEROSOL)........................ 0.80-0.85. Section 10: STABILITY AND REACTIVITY HAZARDOUS PRODUCTS OF HYDROCARBON FUMES AND SMOKE. CARBON MONOXIDE WHERE COMBUSTION IS DECOMPOSITION..... INCOMPLETE. CHEMICAL STABILITY: YES.. NO, WHICH CONDITIONS? UNDER NORMAL CONDITIONS. NOT APPLICABLE. COMPATIBILITY WITH OTHER SUBSTANCES: NO, WHICH ONES? STRONG OXIDIZING AGENTS. REACTIVITY CONDITIONS?.... NOT APPLICABLE. Section 11: TOXICOLOGICAL INFORMATION REPRODUCTIVE EFFECTS..... TOLUENE - PROLONGED AND REPEATED EXPOSURE OF PREGNANT ANIMALS TO TOLUENE (LEVELS GREATER THAN APPROXIMATELY 1500 ppm) HAS BEEN REPORTED TO CAUSE ADVERSE FETAL DEVELOPMENTAL EFFECTS. IRRITANCY OF MATERIAL....SENSITIZING CAPABILITY OF MATERIAL..... SKIN/EYE IRRITANT. UNKNOWN. NONE KNOWN. CARCINOGENICITY OF MATERIAL..... MUTAGENICITY.....TERATOGENICITY.....

NO INFORMATION IS AVAILABLE AND NO ADVERSE TERATOGENIC EFFECTS ARE

ANTICIPATED.