

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

1 Identification of substance

· Product details

· Trade name: **12411Z - Leather and Vinyl Paint Aerosol - Graphite**

· Article number:

17013, 17023, 17033, 17043, 17053, 17063, 17073, 17083, 17093, 17103, 17113, 17123, 17133, 17143, 17153, 17163, 17173, 17183, 17193, 17203, 17213, 17223, 17233, 17243, 17253, 17263, 17273, 17283, 17293, 17303, 17313, 17323, 17333, 17343, 17353

· Distributed By:

The Easthill Group
dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464

· Information department:

USA & Canada: 800-345-1178
Outside USA: 610-323-2200



















· Emergency information: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/Data on components

· Chemical characterization

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

67-64-1	acetone	30 - 40%
	Danger:  2.6/2	
	Warning:  3.3/2A, 3.8/3	
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
	Danger:  2.2/1;  3.5/1B, 3.6/1A	
	Warning:  2.5/C	
108-88-3	toluene	13 - 30%
	Danger:  2.6/2;  3.10/1, 3.7/2, 3.9/2	
	Warning:  3.2/2, 3.8/3	
108-10-1	4-methylpentan-2-one	1.5 - 5%
	Danger:  2.6/2	
	Warning:  3.1.1/4, 3.3/2A, 3.8/3	
110-19-0	isobutyl acetate	1.5 - 5%
	Danger:  2.6/2	
	ACRYLIC RESIN	1.5 - 5%
	Warning:  3.2/2, 3.3/2A, 3.8/3	
9004-36-8	CELLULOSE ACETATE BUTYRATE	1.5 - 5%
	Warning:  3.1.0/4, 3.2/2, 3.3/2A, 3.8/3	
78-93-3	butanone	1.5 - 5%
	Danger:  2.6/2	
	Warning:  3.3/2A, 3.8/3	
	ACRYLIC RESIN	1.5 - 5%
	Warning:  3.2/2, 3.3/2A, 3.8/3	
108-65-6	2-methoxy-1-methylethyl acetate	1.5 - 5%
	Warning:  2.6/3;  3.3/2A	

(Contd. on page 2)

USA

Material Safety Data Sheet





acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 1)

2807-30-9	2-(propyloxy)ethanol	1.5 - 5%
	Warning:  3.1.D/4, 3.3/2A	
78-83-1	butanol	1-1.5%
	Danger:  3.3/1, 3.2/2	
	Warning:  2.6/3;  3.8/3	

3 Hazards identification

· Hazard description:



Harmful
Extremely flammable

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

Has a narcotizing effect.

Extremely flammable.

Irritating to eyes and skin.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Possible risk of harm to the unborn child.

Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

91.9 % by mass of the contents are flammable

Keep out of the reach of children.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 2
Fire = 4
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2
Fire = 4
Reactivity = 0

· GHS label elements



Danger

2.3/1 - Extremely flammable aerosol.



Warning

3.7/2 - Suspected of damaging fertility or the unborn child.

3.9/2 - May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 3)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 2)

**Warning***3.2/2 - Causes skin irritation.**3.3/2A - Causes serious eye irritation.**3.8/3 - May cause drowsiness or dizziness.***• Prevention:***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Do not spray on an open flame or other ignition source.**Pressurized container: Do not pierce or burn, even after use.**Do not breathe dust/fume/gas/mist/vapours/spray.**Avoid breathing dust/fume/gas/mist/vapours/spray.**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**Use personal protective equipment as required.***• Response:***IF ON SKIN: Wash with plenty of soap and water.**IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a POISON CENTER or doctor/physician if you feel unwell.**Get medical advice/attention if you feel unwell.**Specific treatment (see on this label).**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Take off contaminated clothing and wash before reuse.***• Storage:***Store in a well-ventilated place. Keep container tightly closed.**Store locked up.**Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.***• Disposal:***Dispose of contents/container in accordance with local/regional/national/international regulations.***4 First aid measures***• After inhalation: In case of unconsciousness place patient stably in side position for transportation.**• After skin contact: Immediately wash with water and soap and rinse thoroughly.**• After eye contact:**Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.**• After swallowing: If symptoms persist consult doctor.***5 Fire fighting measures***• Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.**• For safety reasons unsuitable extinguishing agents: Water with full jet*

(Contd. on page 4)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

· **Protective equipment:** No special measures required.

(Contd. of page 3)

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
 - Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
 - Do not spray on a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Do not gas tight seal receptacle.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	2400 mg/m³, 1000 ppm
REL	590 mg/m³, 250 ppm
TLV	Short-term value: 1782 mg/m³, 750 ppm
	Long-term value: 1188 mg/m³, 500 ppm
BEI	

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 4)

108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	75 mg/m ³ , 20 ppm

108-10-1 4-methylpentan-2-one

PEL	410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: (205) NIC-123 mg/m ³ , (50) NIC-30 ppm BEI;NIC-A3

110-19-0 isobutyl acetate

PEL	700 mg/m ³ , 150 ppm
REL	700 mg/m ³ , 150 ppm
TLV	713 mg/m ³ , 150 ppm

78-93-3 butanone

PEL	590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	50 ppm
------	--------

78-83-1 butanol

PEL	300 mg/m ³ , 100 ppm
REL	150 mg/m ³ , 50 ppm
TLV	152 mg/m ³ , 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form: Aerosol
Color: According to product specification
Odor: Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: -17°C (1°F)

· **Flash point:** < -17°C (< 1°F)

· **Ignition temperature:** 405°C (761°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 13.0 Vol %

· **Vapor pressure at 20°C (68°F):** 233 hPa (175 mm Hg)

· **Density at 20°C (68°F):** 0.747 g/cm³

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents: 91.9 %

VOC content: 60.2 %

450.1 g/l / 3.76 lb/gal

· **Solids content:** 8.0 %

USA

(Contd. on page 7)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 6)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **DOT regulations:**



- **Hazard class:** 2.1

(Contd. on page 8)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 7)

- Identification number: UN1950
- Packing group: -
- Proper shipping name (technical name): AEROSOLS, flammable
- Label 2.1
- Remarks ORM-D 49CFR 173.150,156,or306

· Land transport TDG (Canada) and ADR/RID (Europe):



- Hazard class: 2 5F Gases
- UN-Number: 1950
- Packaging group: -
- Label: 2.1
- Description of goods: 1950 AEROSOLS

· Maritime transport IMDG:



- IMDG Class: 2.1
- UN Number: 1950
- Label 2.1
- Packaging group: -
- EMS Number: F-D,S-U
- Marine pollutant: No
- Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label 2.1
- Packaging group: -
- Proper shipping name: AEROSOLS, flammable

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

(Contd. on page 9)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 8)

108-10-1	4-methylpentan-2-one
78-93-3	butanone
	ACRYLIC RESIN
1330-20-7	xylene
67-56-1	methanol
100-41-4	ethylbenzene
14807-96-6	Talc (Mg3H2(SiO3)4)

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
68476-86-8	Petroleum gases, liquefied, sweetened
108-88-3	toluene
108-10-1	4-methylpentan-2-one
110-19-0	isobutyl acetate
9004-36-8	CELLULOSE ACETATE BUTYRATE
78-93-3	butanone
108-65-6	2-methoxy-1-methylethyl acetate
2807-30-9	2-(propyloxy)ethanol
78-83-1	butanol
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate
9011-05-6	Urea polymer
13463-67-7	titanium dioxide
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1330-20-7	xylene

· Proposition 65

· Chemicals known to cause cancer:

68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1330-20-7	xylene
1333-86-4	Carbon black
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
108-88-3	toluene	II
108-10-1	4-methylpentan-2-one	I
78-93-3	butanone	I

(Contd. on page 10)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 9)

1330-20-7	xylene	I
111-76-2	2-butoxyethanol	CBD
100-41-4	ethylbenzene	D

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3
111-76-2	2-butoxyethanol	3
100-41-4	ethylbenzene	2B
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
100-41-4	ethylbenzene	A3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
1333-86-4	Carbon black
67-56-1	methanol

· **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
------------	---

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful
Extremely flammable

· **Hazard-determining components of labelling:**

toluene

· **Risk phrases:**

Extremely flammable.
Irritating to eyes and skin.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Possible risk of harm to the unborn child.
Vapours may cause drowsiness and dizziness.

(Contd. on page 11)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: 12411Z - Leather and Vinyl Paint Aerosol - Graphite

(Contd. of page 10)

- **Safety phrases:**
Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
Wear suitable protective clothing and gloves.
Use only in well-ventilated areas.
This material and its container must be disposed of as hazardous waste.
- **Special labeling of certain preparations:**
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
91.9 % by mass of the contents are flammable
Keep out of the reach of children.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing MSDS:** Environment protection department.
- **Contact:** Steve Gaver
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ACGIH: American Conference of Governmental Industrial Hygienists
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent