

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Octane Boost

Product Number (s): 05077

Distributed By:

The Easthill Group
dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464

USA & Canada: 800-345-1178

Outside USA: 610-323-2200

24-Hr Emergency (CHEMTREC) (800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor: Clear amber liquid, petroleum odor

DANGER

Harmful or Fatal if Swallowed. Combustible.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE: Contact with liquid or vapor may cause mild irritation.

SKIN: May cause skin irritation with prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are repeatedly exposed.

INHALATION: Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure and death.

INGESTION: Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous system effects similar to alcohol intoxication. The major health threat of ingestion occurs from the danger of aspiration of the liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia, severe lung damage, respiratory failure and even death.

CHRONIC EFFECTS: Similar products produced skin cancer and systemic toxicity in laboratory animals following repeated applications. The significance of these results to human exposures has not been determined.

TARGET ORGANS: Central nervous system

Medical Conditions Aggravated by Exposure: skin disorders / dermatitis

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.
Kerosene	8008-20-6	80 - 90
Heavy aromatic solvent naphtha	64742-94-5	8 – 12
Methylcyclopentadienyl-manganese tricarbonyl (MMT)	12108-13-3	< 2
Naphthalene	91-20-3	1.2

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do NOT induce vomiting. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration.

Note to Physicians: Aspiration hazard. Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: As defined by OSHA, this product is a combustible liquid.

Flash Point:	127 F (TCC)	Upper Explosive Limit:	5.0
Autoignition Temperature:	410 F	Lower Explosive Limit:	0.7

Suitable Extinguishing Media: Class B fire extinguisher; dry chemical; CO₂; water spray; foam

Products of Combustion: Oxides of carbon and nitrogen

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Product Name: Octane Boost**Product Number (s): 05077**

Methods for Containment & Clean-up: Dike area to contain spill. Remove all sources of ignition. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Keep away from heat, sparks and open flame. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

Storage Procedures: Store in a cool dry area out of direct sunlight and away from sources of ignition. Keep containers closed when not in use. Store in a well ventilated area.

Aerosol Storage Level: NA

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Kerosene	NE	NE	200 (s)	NE	NE		mg/m ³
Heavy aromatic solvent naphtha	NE	NE	NE	NE	NE		
Methylcyclopentadienyl-manganese tricarbonyl (MMT)	NE	NE	0.2 (s)	NE	NE		mg/m ³
Naphthalene	10	NE	10 (s)	15 (s)	NE		ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile, neoprene or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid

Color: Clear amber

Odor: petroleum

Product Name: Octane Boost**Product Number (s): 05077**

Specific Gravity: 0.8235

Initial Boiling Point: 300 F

Freezing Point: ND

Vapor Pressure: ND

Vapor Density: > 4 (air = 1)

Evaporation Rate: < 1 (ether = 1)

Solubility: Negligible in water

pH: NA

Volatile Organic Compounds: wt %: 98.8 g/L: 813.6 lbs./gal: 6.78**Section 10: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: High temperatures, sources of ignition

Incompatible Materials: Strong oxidizers such as nitric acid and sulfuric acids, halogens, hydrogen peroxide and chlorinating agents

Hazardous Decomposition Products: Oxides of carbon and nitrogen

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

<u>Component</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Kerosene	LD50	> 2 g/kg	Dermal	Rabbit
Kerosene	LD50	> 5 g/kg	Oral	Rat
MMT	LD50	140 mg/kg	Dermal	Rabbit

CHRONIC EFFECTS

Carcinogenicity:

	<u>Component</u>	<u>Result</u>
OSHA:	Naphthalene	Hazard communication carcinogen
IARC:	Naphthalene	2B – Possibly carcinogenic to humans
NTP:	Naphthalene	Reasonably anticipated to be a human carcinogen

Mutagenicity: No information available

Other: None

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity:	This product contains components which are considered marine pollutants.
Persistence / Degradability:	No information available.
Bioaccumulation / Accumulation:	No information available.
Mobility in Environment:	No information available.

Section 13: Disposal Considerations

Disposal: This product is a RCRA hazardous waste for the characteristic of ignitability with the following potential waste codes: D001 (See 40 CFR Part 261.20 – 261.33)

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): Consumer Commodity, ORM-D

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: MMT (100 lbs); Naphthalene (100 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): MMT

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
Naphthalene (1.2%)

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Naphthalene

Product Name: Octane Boost**Product Number (s): 05077**

Consumer Product Safety Act General Conformity Certification: This product was evaluated by CRC Industries, Inc., and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location listed in Section 1 of this MSDS. The date of manufacture is stamped on the product container. No testing is required to certify compliance with the above

State RegulationsCalifornia Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: Naphthalene, Cumene

State Right to Know:

New Jersey: 8008-20-6, 12108-13-3, 91-20-3, 95-63-6
 Pennsylvania: 8008-20-6, 12108-13-3, 91-20-3, 95-63-6
 Massachusetts: 8008-20-6, 12108-13-3, 91-20-3, 95-63-6
 Rhode Island : 8008-20-6, 12108-13-3, 91-20-3, 95-63-6

Additional Regulatory Information: None

Section 16: Other Information

NFPA:	Health: 1	Flammability: 2	Reactivity: 0	
HMIS:	Health: 1	Flammability: 2	Reactivity: 0	PPE: B

Prepared By: Michelle Rudnick
 CRC #: 636H
 Revision Date: 08/13/2010

Changes since last revision: Section 15: California Prop 65 chemical added

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:	Chemical Abstract Service	NA:	Not Applicable
ppm:	Parts per Million	ND:	Not Determined
TCC:	Tag Closed Cup	NE:	Not Established
PMCC:	Pensky-Martens Closed Cup	g/L:	grams per Liter
PPE:	Personal Protection Equipment	lbs./gal:	pounds per gallon
TWA:	Time Weighted Average	STEL:	Short Term Exposure Limit
OSHA:	Occupational Safety and Health Administration		
ACGIH	American Conference of Governmental Industrial Hygienists		
NIOSH	National Institute of Occupational Safety & Health		