

MATERIAL SAFETY DATA SHEET

Distributed by:
The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200
Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 07/01/09**

| | |
|--|-----------|
| IDENTITY: (As used on label) | Synonyms: |
| Auto Air Transparent White Item # 4230 | |
| Chemical family: | Formula |
| --- | |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|------------------------|---------------|-------|-----------------|
| Proprietary Ingredient | Not specified | 75-95 | Not established |
| Methoxy 2 | 107-98-2 | <1 | 100 PPM |
| Methoxy 1 | 1589-47-5 | < .05 | 150 PPM |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Appreciable (>20%) |
| Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C |
| Vapor density: (Air=1) 6.6 |
| Specific Gravity (H₂O=1): (Water=1) 0.972 |
| Evaporation Rate: (BuAct=1): .07 |
| Appearance and Odor: Colorless liquid, combustible, sweet ether odor |
| Flash Point: 79° C / 174°F |

Volatile Organic Compound

| |
|----------------------------|
| *Paint 80%: .92 |
| **Reducer 20% : .61 |
| Combined VOC: 1.53 |

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
| Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible! |
| Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat |

REACTIVITY DATA

| |
|---|
| Stability: (X) Stable () Unstable Conditions to avoid: extreme temperatures, open flames |
| Incompatibility (materials to avoid) : strong oxidizers, strong acids |

Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

Hazardous Polymerization:

() may occur (X) will not occur **Conditions to avoid:** None

HEALTH INFORMATION

Primary Route of Exposure:

Inhalation:

Skin: X

Ingestion:

Eyes:

Carcinogen:

IARC: no

NTP: no

OSHA: no

Signs and Symptoms of Exposure:

none found

Medical Conditions Generally Aggravated by Exposure:

none found

Emergency and First Aid Procedures:

Eye Contact, remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.

Ingestion, If victim is conscious give water, *do not* induce vomiting. Call physician.

SPECIAL PROTECTION DATA

Respiratory Protection:

Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.

Ventilation:

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.

Protective Gloves:

Neoprene or rubber gloves with cuffs

Other Protective Clothing:

Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill:

COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

Storing/Handling:

Store in tightly closed containers in a cool, well-ventilated area.

Waste Disposal Method:

Sanitary landfill in accordance with local, state, and federal regulations.

Other Precautions:

None

MATERIAL SAFETY DATA SHEET

Distributed by:
The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200
Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 07/01/09**

| | |
|---|-----------|
| IDENTITY: (As used on label) | Synonyms: |
| Auto Air Transparent Yellow Item # 4231 | |
| Chemical family: | Formula |
| --- | |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|------------------------|---------------|-------|-----------------|
| Proprietary Ingredient | Not specified | 75-95 | Not established |
| Methoxy 2 | 107-98-2 | <1 | 100 PPM |
| Methoxy 1 | 1589-47-5 | < .05 | 150 PPM |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Appreciable (>20%) |
| Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C |
| Vapor density: (Air=1) 6.6 |
| Specific Gravity (H₂O=1): (Water=1) 0.972 |
| Evaporation Rate: (BuAct=1): .07 |
| Appearance and Odor: Colorless liquid, combustible, sweet ether odor |
| Flash Point: 79° C / 174°F |

Volatile Organic Compound

| |
|----------------------------|
| *Paint 80%: .92 |
| **Reducer 20% : .61 |
| Combined VOC: 1.53 |

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
| Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible! |
| Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat |

REACTIVITY DATA

| |
|---|
| Stability: (X) Stable () Unstable Conditions to avoid: extreme temperatures, open flames |
| Incompatibility (materials to avoid) : strong oxidizers, strong acids |

Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

Hazardous Polymerization:

() may occur (X) will not occur **Conditions to avoid:** None

HEALTH INFORMATION

Primary Route of Exposure:

Inhalation:

Skin: X

Ingestion:

Eyes:

Carcinogen:

IARC: no

NTP: no

OSHA: no

Signs and Symptoms of Exposure:

none found

Medical Conditions Generally Aggravated by Exposure:

none found

Emergency and First Aid Procedures:

Eye Contact, remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.

Ingestion, If victim is conscious give water, *do not* induce vomiting. Call physician.

SPECIAL PROTECTION DATA

Respiratory Protection:

Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.

Ventilation:

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.

Protective Gloves:

Neoprene or rubber gloves with cuffs

Other Protective Clothing:

Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill:

COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

Storing/Handling:

Store in tightly closed containers in a cool, well-ventilated area.

Waste Disposal Method:

Sanitary landfill in accordance with local, state, and federal regulations.

Other Precautions:

None

MATERIAL SAFETY DATA SHEET

Distributed by:
The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200
Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 07/01/09**

| | |
|---|-----------|
| IDENTITY: (As used on label) | Synonyms: |
| Auto Air Transparent Fire Red Item # 4234 | |
| Chemical family: | Formula |
| --- | |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|------------------------|---------------|-------|-----------------|
| Proprietary Ingredient | Not specified | 75-95 | Not established |
| Methoxy 2 | 107-98-2 | <1 | 100 PPM |
| Methoxy 1 | 1589-47-5 | < .05 | 150 PPM |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Appreciable (>20%) |
| Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C |
| Vapor density: (Air=1) 6.6 |
| Specific Gravity (H₂O=1): (Water=1) 0.972 |
| Evaporation Rate: (BuAct=1): .07 |
| Appearance and Odor: Colorless liquid, combustible, sweet ether odor |
| Flash Point: 79° C / 174°F |

Volatile Organic Compound

| |
|----------------------------|
| *Paint 80%: .92 |
| **Reducer 20% : .61 |
| Combined VOC: 1.53 |

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
| Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible! |
| Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat |

REACTIVITY DATA

| |
|---|
| Stability: (X) Stable () Unstable Conditions to avoid: extreme temperatures, open flames |
| Incompatibility (materials to avoid) : strong oxidizers, strong acids |

Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

Hazardous Polymerization:

() may occur (X) will not occur **Conditions to avoid:** None

HEALTH INFORMATION

Primary Route of Exposure:

Inhalation:

Skin: X

Ingestion:

Eyes:

Carcinogen:

IARC: no

NTP: no

OSHA: no

Signs and Symptoms of Exposure:

none found

Medical Conditions Generally Aggravated by Exposure:

none found

Emergency and First Aid Procedures:

Eye Contact, remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.

Ingestion, If victim is conscious give water, *do not* induce vomiting. Call physician.

SPECIAL PROTECTION DATA

Respiratory Protection:

Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.

Ventilation:

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.

Protective Gloves:

Neoprene or rubber gloves with cuffs

Other Protective Clothing:

Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill:

COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

Storing/Handling:

Store in tightly closed containers in a cool, well-ventilated area.

Waste Disposal Method:

Sanitary landfill in accordance with local, state, and federal regulations.

Other Precautions:

None

MATERIAL SAFETY DATA SHEET

Distributed by:
The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200
Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 7/01/09**

| | |
|--|-----------|
| IDENTITY: (As used on label) | Synonyms: |
| Auto Air Transparent Blue Item# 4241 | |
| Chemical family: | Formula |
| --- | |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|------------------------|---------------|-------|-----------------|
| Proprietary Ingredient | Not specified | 75-95 | Not established |
| Methoxy 2 | 107-98-2 | <1 | 100 PPM |
| Methoxy 1 | 1589-47-5 | < .05 | 150 PPM |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Appreciable (>20%) |
| Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C |
| Vapor density: (Air=1) 6.6 |
| Specific Gravity (H₂O-1): (Water=1) 0.972 |
| Evaporation Rate: (BuAct=1): .07 |
| Appearance and Odor: Colorless liquid, combustible, sweet ether odor |
| Flash Point: 79° C / 174°F |

Volatile Organic Compound

| |
|----------------------------|
| *Paint 80%: .92 |
| **Reducer 20% : .61 |
| Combined VOC: 1.53 |

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
| Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible! |
| Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat |

REACTIVITY DATA

| |
|---|
| Stability: (X) Stable () Unstable Conditions to avoid: extreme temperatures, open flames |
|---|

| |
|---|
| Incompatibility (materials to avoid) : strong oxidizers, strong acids |
| Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. |
| Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: None |

HEALTH INFORMATION

| | | | |
|--|-----------------|-------------------|-----------------|
| Primary Route of Exposure: | | | |
| Inhalation: | Skin: X | Ingestion: | Eyes: |
| Carcinogen: | IARC: no | NTP: no | OSHA: no |
| Signs and Symptoms of Exposure: none found | | | |
| Medical Conditions Generally Aggravated by Exposure: none found | | | |
| Emergency and First Aid Procedures: <u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician. | | | |

SPECIAL PROTECTION DATA

| |
|--|
| Respiratory Protection: Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator. |
| Ventilation: The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment. |
| Protective Gloves: Neoprene or rubber gloves with cuffs |
| Other Protective Clothing: Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking. |

SPILL AND LEAK PROCEDURES

| |
|--|
| Steps to be taken in case of material spill: COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway. |
| Storing/Handling: Store in tightly closed containers in a cool, well-ventilated area. |
| Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations. Other Precautions: None |

MATERIAL SAFETY DATA SHEET

Distributed by:
 The Easthill Group dba/ The Eastwood Company
 263 Shoemaker Road
 Pottstown, PA 19464
 USA & Canada: 800-345-1178
 Outside USA: 610-323-2200
 Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 7/01/09**

| | |
|---|-----------|
| IDENTITY: (As used on label) | Synonyms: |
| Auto Air Transparent Black Item# 4249 | |
| Chemical family: | Formula |
| --- | |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|------------------------|---------------|-------|-----------------|
| Proprietary Ingredient | Not specified | 75-95 | Not established |
| Methoxy 2 | 107-98-2 | <1 | 100 PPM |
| Methoxy 1 | 1589-47-5 | < .05 | 150 PPM |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Appreciable (>20%) |
| Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C |
| Vapor density: (Air=1) 6.6 |
| Specific Gravity (H₂O-1): (Water=1) 0.972 |
| Evaporation Rate: (BuAct=1): .07 |
| Appearance and Odor: Colorless liquid, combustible, sweet ether odor |
| Flash Point: 79° C / 174°F |

Volatile Organic Compound

| |
|----------------------------|
| *Paint 80%: .92 |
| **Reducer 20% : .61 |
| Combined VOC: 1.53 |

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
| Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible! |
| Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat |

REACTIVITY DATA

| |
|---|
| Stability: (X) Stable () Unstable Conditions to avoid: extreme temperatures, open flames |
|---|

| |
|---|
| Incompatibility (materials to avoid) : strong oxidizers, strong acids |
| Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. |
| Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: None |

HEALTH INFORMATION

| | | | |
|--|-----------------|-------------------|-----------------|
| Primary Route of Exposure: | | | |
| Inhalation: | Skin: X | Ingestion: | Eyes: |
| Carcinogen: | IARC: no | NTP: no | OSHA: no |
| Signs and Symptoms of Exposure: none found | | | |
| Medical Conditions Generally Aggravated by Exposure: none found | | | |
| Emergency and First Aid Procedures: <u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician. | | | |

SPECIAL PROTECTION DATA

| |
|--|
| Respiratory Protection: Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator. |
| Ventilation: The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment. |
| Protective Gloves: Neoprene or rubber gloves with cuffs |
| Other Protective Clothing: Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking. |

SPILL AND LEAK PROCEDURES

| |
|--|
| Steps to be taken in case of material spill: COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway. |
| Storing/Handling: Store in tightly closed containers in a cool, well-ventilated area. |
| Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations. Other Precautions: None |

MATERIAL SAFETY DATA SHEET

Distributed by:
The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200
Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 6/30/11**

| | |
|--|---------------------|
| IDENTITY: (As used on label) | Synonyms: |
| Auto Air Flash Reducer Fast Dry Item # 4011 | Flash Reducer, 4011 |
| Chemical family: | Formula |
| --- | |

HAZARDOUS INGREDIENTS

| COMPONENT | CAS # | % | OSHA/PEL |
|------------------------|---------------|-------|-----------------|
| Proprietary Ingredient | Not specified | 75-95 | Not established |
| Methoxy 2 | 107-98-2 | <1 | 100 PPM |
| Methoxy 1 | 1589-47-5 | < .05 | 150 PPM |

PHYSICAL/CHEMICAL CHARACTERISTICS

| |
|---|
| Boiling /melting point: 408°F (209° C) |
| Solubility in water: Appreciable (>20%) |
| Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C |
| Vapor density: (Air=1) 6.6 |
| Specific Gravity (H₂O-1): (Water=1) 0.972 |
| Evaporation Rate: (BuAct=1): .07 |
| Appearance and Odor: Colorless liquid, combustible, sweet ether odor |
| Flash Point: 79° C / 174°F |

TESTED TO MEET ASTM D-4236 STANDARDS. HAS AP SEAL OF APPROVAL**Volatile Organic Compound**

| |
|----------------------------|
| *Paint 80%: .92 |
| **Reducer 20% : .61 |
| Combined VOC: 1.53 |

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

| |
|--|
| Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam |
| Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible! |
| Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat |

REACTIVITY DATA

| | |
|--|---|
| Stability: (X) Stable () Unstable | Conditions to avoid: extreme temperatures, open flames |
|--|---|

| |
|---|
| Incompatibility (materials to avoid) : strong oxidizers, strong acids |
| Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced. |
| Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: None |

HEALTH INFORMATION

| | | | |
|--|-----------------|-------------------|-----------------|
| Primary Route of Exposure: | | | |
| Inhalation: | Skin: X | Ingestion: | Eyes: |
| Carcinogen: | IARC: no | NTP: no | OSHA: no |
| Signs and Symptoms of Exposure: none found | | | |
| Medical Conditions Generally Aggravated by Exposure: none found | | | |
| Emergency and First Aid Procedures: <u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician. | | | |

SPECIAL PROTECTION DATA

| |
|--|
| Respiratory Protection: Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator. |
| Ventilation: The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment. |
| Protective Gloves: Neoprene or rubber gloves with cuffs |
| Other Protective Clothing: Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking. |

SPILL AND LEAK PROCEDURES

| |
|--|
| Steps to be taken in case of material spill: COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway. |
| Storing/Handling: Store in tightly closed containers in a cool, well-ventilated area. |
| Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations. |
| Other Precautions: None |