Material Safety Data Sheet

Chrome Part B

SECTION 1

Manufactured for:	The Easthill Group dba/ The Eastwood Company
Address:	263 Shoemaker Road
City, State, and Zip:	
	7/2004
24 Hour Emergency Number:- CHEMTREC	(800)424-9300
Information Phone:	USA & Canada: 800-345-1178, Outside USÀ: 610-323-2200
CECTION O	

SECTION 2

Hazard Rating: Health 3, Flammability 1, Reactivity 0

(Scale: 4 –Extreme, 3-High, 2–Moderate, 1-Slight, 0-Insignificant)

TSCA Status: All components that make up this product are on TSCA inventory.

Silver Diammine Complex 25%-30% (wt %)

ACGIH TLV: .01 mg/m³ **CAS NO.:** 23606-32-8

Ammonium Hydroxide 10%-15% (wt %)

ACGIH TLV: 35 mg/m³ **CAS NO.:** 1336-21-6

Water 65%-55% (wt %)

CAS NO.: 1336-21-6

SECTION 3

PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point: Between 83C-86C Specific Gravity (water=1): 1.185 Vapor Pressure (mm Hg): N/A Vapor Density (Air=1): 5.8

Solubility in Water: Complete Reactivity in Water: None

Appearance and Odor: Blue liquid-Ammonia odor.

Melting Point: N/A

SECTION 4: FIRE & EXPLOSION DATA

Flash Point: N/A Method Used: Not Flammable

Flammable Limits in Air% by Volume: LEL 16% UEL 25%

Auto-Ignition Temperatures: N/A

Extinguisher Media: Water fog.

Special Fire Fighting Procedures: Mixture will not burn, but ammonia gas escaping can burn in range of 16-25% in air. Water will extinguish the flame. Wear full protective clothing and self contained breathing apparatus in the pressure demand mode. Vapors in the range of 16-25% ammonia in air can explode in a confined space on contact with sources of ignition.

Unusual Fire and Explosive Hazards: Can form explosive if mixed with concentrated caustic material. When heated, material will give off ammonia gas, a strong irritant to eye, exposed to extreme heat may develop pressure. Combustion of released ammonia may form nitrogen oxides.

SECTION 5

PHYSICAL HAZARDS (REACTIVITY DATA)

Stability: Stable

Conditions to Avoid: Excessive temperatures, light.

Incompatibility (Materials to Avoid): Organic compounds, combustible materials, strong reducing agents, strong bases, alkalis, halides, strong acids; Chlorine, bromine, mercury, and hypochlorite (bleach) react with the ammonia to form explosive compounds. Avoid using metal containing copper or zinc.

Hazardous Decomposition Products: Oxides of Nitrogen, heating and contact of vapors with very hot surfaces may form hydrogen.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Do not mix concentrated silver solution with concentrated activator solution-may

explode!

SECTION 6

HEALTH HAZARDS

Toxicity: Oral mouse LD50 for silver nitrate 50 mg/kg Intraperitoneal mouse LD50 for silver nitrate 22 mg/kg

Acute: Silver/ammonia solution is a strong base and reacts corrosively with all body tissue.

Chronic: Inhalation of extremely high concentrations may cause bronchitis and/or pneumonia with some reduction in pulmonary function. Repeated inhalation may cause lung disease.

Signs and Symptoms of Exposure: Skin darkening and irritation, strong ammonia odor.

Medical Conditions Generally Aggravated by Exposure:

- 1. Inhalation: The gas can be suffocating and is irritating to the mucus membranes and lung tissues. Repeated or prolonged exposure to concentrations greater that 500 ppm IDLH level for Ammonia can cause permanent injury or death. Less exposure may cause irritation, headache, coughing, severe lung congestion, breathing difficulty, convulsions, shock.
- 2. Eyes: Severely irritation from liquid and fumes. May cause burns. Eye problems may cause greater susceptibility to effects of exposure. Burns may lead to blindness.
- 3. Skin: Silver Compounds can be absorbed into the circulation through breaks in the skin. Local irritation, burns, and blister form from contact.
- 4. Ingestion: Burning pain in mouth, throat, stomach, thorax, constriction of throat, coughing, followed by vomiting or diarrhea. Portable lethal ingestion dose is 3-4ml (1ounce).

Chemical Listed as Carcinogen or Potential Carcinogen:

National Toxicology Program: No

I.A.R.C. Monographs: No

OSHA: No

Emergency and First Aid Procedures:

Ingestion: If conscious, give salt water and/or milk to drink, induce vomiting. Highly toxic via oral route. Call physician. Inhalation: Remove to fresh air. If breathing has stopped or is difficult, administer artificial respiration or oxygen as needed. Seek medical aid. Skin: Immediately flush skin with water for 15 minutes. Remove contaminated clothing. Once deposited (at sight of injury) through breaks in skin, there is no known method by which the silver can be eliminated. The pigment is permanent Handle with care. Eye contact: Immediately flush with water for 15 minutes.

SECTION 7

SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES.

Precautions to be Taken in Handling and Storage: Store in dark, dry place. Keep container closed. Store away from incompatible materials, flammables and combustibles.

Other Precautions:

Steps to be Taken in Case Material is Released or Spilled: Soak up solution, place in plastic bag or bottle. Flush area with water.

Waste Disposal Methods: (Consult federal, state, and local regulations):

Send to refinery for silver recovery.

SECTION 8

SPECIAL PROTECTION INFORMATION/CONTROL MEASURES

Respiratory Protection (specify type): Approved by NOISH/MSHA respirator with ammonia filter. Must be used when exposure limits are exceeded.

Ventilation: Local exhaust, to meet TLV requirements.

Protective Gloves: Rubber or neoprene.

Eye Protection: Chemical safety splash goggles to prevent eye contact. Contact lenses should not be

worn.

Other Protective Clothing or Equipment: Rubber apron or protective coveralls.

Work/Hygienic Practices: Wash after handling-have shower and eye bath available. Do not get on clothing.

SECTION 9

TRANSPORTATION

Proper Shipping Name: Ammonia Hydroxide (Aqua Ammonia) Corrosive Material UN-2672

Hazard Class: 8, Corrosive Material.

Label: Corrosive UN-2672

Identification No.: UN-2672, Corrosive, PG III

Other Requirements: Under the Comprehensive Environmental Response, Compensation, and Liability Act of 1980 any environmental release of this chemical equal to or over the reportable quantity of 100 lbs. must be reported promptly to the National Response Center, Washington, D.C. (1-800-424-8802). Any consumer product containing 5% or more ammonia requires a POISON label under FSHA (16 CFR 1500.129(1)).

SECTION 10 DISCLAIMER

The above information in this M.S.D.S. was obtained from sources which we believe are reliable and correct, but does not purport to be inclusive and shall be used only as a guide. The information is provided without any representation or warranty expressed or implied regarding accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, Peacock Laboratories, Inc. and its employees do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use or disposal of the product.