



DO THE JOB RIGHT.®

SELF-ETCHING WELD-THRU GRAY PRIMER



- Combines the Benefits of a Weld-Thru Primer with Etching Capabilities
- Prevents Corrosion
- Enhances Adhesion/Durability of Top Coats

DANGER: EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SERIOUS EYE IRRITATION. CAUSES SKIN IRRITATION. READ CAUTIONS ON BACK PANEL.

Net Wt. 16.1 oz. / 454 grams

12899Z

EASTWOOD SELF ETCHING WELD-THRU PRIMER combines the benefits of a weld-thru and the capabilities of a traditional Self Etching Primer. This unique formula has organic binders that replace conductive heavy metals such as copper and zinc. These organic binders will burn off during the welding process leaving a corrosion resistant etching primer. The etching primer will enhance adhesion and durability and is compatible with most top coats. Compatible with MIG, TIG and Arc welding.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

1. Read all directions and warnings for safe and proper application.
2. Use in a well ventilated area, away from open flames. Always wear eye, skin and respiratory protection when painting and welding.
3. Clean surface with Eastwood's PRE, ensuring the area is clean and free of greases and oils.
4. Apply 2 medium wet coats, allowing 5 minutes flash time between each coat. Allow to cure at least 20 minutes prior to welding.

12899Z SELF-ETCHING WELD-THRU GRAY PRIMER

CONTAINS (CAS No.): acetone (67-64-1), petroleum gases, liquefied, sweetened (68476-86-8), methyl acetate (79-20-9), toluene (108-88-3), xylene (1330-20-7), quartz (SiO2) (14808-60-7), titanium dioxide (13463-67-7), mica (12001-26-2), talc(14807-96-6), ethylbenzene (100-41-4), 3-ethyl-2-methyl-2-(3-methylbutyl)-1,3-oxazolidine (143860-04-2), stoddard solvent (8052-41-3).

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Keep aerosol container away from welding heat sources and sparks. Causes serious eye irritation. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. May cause damage to organs. May cause drowsiness or dizziness.

PRECAUTIONS: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames or hot surfaces. No smoking.

Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Do not breathe dust, fume, gas, mist, vapors, spray. Wear protective gloves. Wear eye and face protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

RESPONSE: If exposed or concerned: Get medical advice or attention. Get medical advice or attention if you feel unwell. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash before reuse. Specific treatment (see on this label). If eye irritation persists: Get medical advice or attention. **IF ON SKIN:** Wash with plenty of soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice or attention.

STORAGE: Store locked up. Keep cool. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C - 122°F.

DISPOSAL: Dispose of contents and container in accordance with local, regional, national, and international regulations.

Safety data sheet available on request. KEEP OUT OF REACH OF CHILDREN.



WARNING:
Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night:
1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464
1-800-343-9353 www.eastwood.com

© Copyright 2018 Easthill Group, Inc. Manufactured in the USA

