



**DO THE JOB RIGHT.**

## SAFETY DATA SHEET

### SECTION 1 / Identification

**IDENTITY: PREMIUM BUFFING COMPOUND**  
**PRODUCT CODE: 13132A - 13194A GREASELESS**

**Manufacturer/Distributor:** Eastwood Company  
**Address:** 263 Shoemaker Road  
Pottstown, PA 19464  
**Telephone No:** 800-343-9353  
**Emergency Telephone No:** 800-424-9300  
**Date:** Chemtrec  
6/1/2015

### SECTION 2: Hazard(s) Identifications

Buffing compounds as shipped do not present a hazard.

Buffing operations may cause lint and abrasives to become airborne. Proper ventilation and respirator recommended.

**Signal Word:**

**Warning**



### SECTION 3: Composition/information on ingredients

Substance:	CAS No.	%
Metal Oxides	1309-37-1	less than 15 %
Silica Abrasive	1317-65-3	less than 30%
Aluminum Oxide	1344-28-1	less than 70%
Hyde Glue	9000-70-0	less than 10%

## SECTION 4: First Aid Measures

**Ingestion:** If swallowed - seek medical attention  
**Inhalation:** Move to a fresh air environment  
**Eye Contact:** Flush thoroughly with water and call physician  
**Skin Contact:** Remove dust from skin with warm water and soap

## SECTION 5: Firefighting measures

**Flash Point (method used):** 350° F ( CoC )  
**LEL:** N/A  
**Extinguishing Media:** CO<sub>2</sub> Dry Chemical  
**Special Fire Fighting Instructions:** Use Air Pack - Treat as Grease Fire  
**Unusual Fire and Explosion Haz:** Dense smoke  
**Flammable Limits:** No Data  
**UEL:** N/A

## SECTION 6: Accidental release measures

If material is spilled or released - sweep up with broom and dispose. Follow normal clean up procedures per State and local laws - Care taken to prevent dust from becoming airborne.

## SECTION 7: Handling and Storage

Do not store near direct heat sources - Store in a cool dry area  
No other precautions apply

## SECTION 8: Exposure controls/personal protection

Hazardous Guidelines:

Hazardous Component	OSHA PEL	ACGIH / TLV
Metal Oxides	5 mg ./m <sup>3</sup>	5 mg ./m <sup>3</sup>
Silica Abrasive	.1 mg ./m <sup>3</sup>	.1 mg ./m <sup>3</sup>
Aluminum Oxide	15 mg ./m <sup>3</sup>	10 mg ./m <sup>3</sup>
Hyde Glue	N/A	N/A

**Special:** None  
**Mechanical ( General ):** To maintain employee below permissible limits.  
**Respiratory Protection:** OSHA/MOHA approved dust mask / respirator  
**Gloves:** Yes  
**Eye Protection:** Safety Glasses  
**Other:** Long sleeve protective clothing

**SECTION 9: Physical and chemical properties****Boiling Point:** > 450°F**Vapor Pressure (mm Hg):** N/A**Vapor Density:** N/A**Solubility in Water:** Insoluble**Appearance & Odor:** Red ,Green, Brown, Blue, Orange-packed in plastic bag / low odor**Specific Gravity:** 1.9 to 2.6**Melting Point:** 130°F**Evaporation Rate:** N/A**( Butyl Acetate=1)****SECTION 10: Stability and Reactivity****Stability:** Yes**Incompatibility:** N/A**Hazardous Decomposition of By-Products:** N/A**Hazardous Polymerization:** Will not occur**Conditions to Avoid:** N/A**SECTION 11: Toxicological Information****Route(s) of Entry :**      **Inhalation:** Yes      **Skin:** No      **Ingestion:** No**Health Hazards ( Acute and Chronic ):** Coughing and sneezing. Buffing operations may cause lint and abrasives to become airborne. Respirator and ventilation is recommended.**Effects of overexposure:** N/A**Carcinogenicity:** N/A**NTP:** N/A**IARC Monographs:** No**OSHA Regulated:** No**SECTION 12: Ecological information ( Non-Mandatory )****ECOTICITY :** None**SECTION 13: Disposal considerations ( Non-Mandatory )****Per State and Local Law****SECTION 14: Transport Information ( Non-Mandatory )****Not regulated as dangerous goods****SECTION 15: Regulatory Information ( Non-Mandatory )****None****SECTION 16: Other Information ( Non-Mandatory )****Revision Date:** 05/12/2017**Revision Summary:****Update all sections per GHS compliance****Revised by:** A. Battle



