

SAFETY DATA SHEET

Part No. 13445Z Aerosol

 Print Date: 04/19/2017
 Revision Date: 04/19/2017
 Version: 2.0 (EN)
 Page 1 of 9

Aerosol Injected Lubricator

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : *Aerosol Injected Lubricator*
 Manufacturer Product Number : *13445Z*
 Supplier Product Numbers : *13445Z*

1.2 Other Means Of Identification

Other Identifiers : *Not Available*

1.3 Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against

Recommended Use : *Automotive injection lubricator*
 Restrictions On Use : *None Identified*

1.4 Supplier Details

Company Name
 Address
 Phone Number
 Fax Number
 Email
 Website

Supplier Details

The Easthill Group, Inc./The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464 -
United States
610-705-5422
610-323-6268

1.5 24 Hr Emergency Phone Number

Emergency Number : *800-424-9300 (Chem-Trec)*

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification Of The Substance Or Mixture

Flammable Aerosols, Category 1 : *Extremely flammable aerosol*
 Gases Under Pressure : Compressed Gas : *Contains gas under pressure; may explode if heated*
 Aspiration Hazard, Category 1 : *May be fatal if swallowed and enters airways*

2.2 Label Elements

Hazard Pictograms :



GHS02



GHS04



GHS08

Signal Word :

Danger

Hazard Statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Precautionary Statements :

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. If swallowed: Immediately call POISON CENTER. Do NOT induce vomiting. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to local regulations.

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : *None Identified.*

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 2 of 9

Aerosol Injected Lubricator

2.4 Unknown Acute Toxicity

26.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

26.8% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

21% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance

Not Applicable

3.2 Mixture

Ingredient	Cas Number	%	Classification*
Hydrotreated Light Naphthenic Distillate	64742-53-6	30 - 60	Asp. Tox. 1, H304
Hydrotreated Light Petroleum Distillate	64742-47-8	10 - 30	Asp. Tox. 1, H304
Propane	74-98-6	10 - 30	Flam. Gas 1, H220 Press. Gas (Diss.), H280
Solvent-Dewaxed Heavy Paraffinic Petroleum Distillate	64742-65-0	1 - 10	Asp. Tox. 1, H304
Solvent-Refined Residual Oil	64742-01-4	1 - 5	Not classified
Hydrotreated Heavy Naphthenic Distillate	64742-52-5	1 - 5	Asp. Tox. 1, H304
Carbon Dioxide	124-38-9	0.1 - 1	Press. Gas (Comp.), H280

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4 - FIRST-AID MEASURES

4.1 Description Of First-Aid Measures

General Measures	: Call a physician immediately.
Eye Contact	: Rinse eyes with water as a precaution.
Skin Contact	: Wash skin with plenty of water.
Ingestion	: Do not induce vomiting. Call a physician immediately.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms And Effects, Both Acute And Delayed

Eye Contact	: Liquid contact may cause pain along with moderate eye irritation.
Skin Contact	: Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking skin. May cause more severe response if confined to skin.
Ingestion	: Risk of lung oedema.
Inhalation	: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.

4.3 Indication Of Immediate Medical Attention And Special Treatment

Notes To Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Immediate Medical Attention	: No Information Available.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
---------------------	-----------------------------------------------------------------------------

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 3 of 9

Aerosol Injected Lubricator

Unsuitable Media : Water jet.

5.2 Specific Hazards Arising From The Chemical Or Mixture

- Decomposition Products** : Decomposition products may include: oxides of carbon, smoke, vapors.
- Hazards From The Product** : Extremely flammable. Contents under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to ignition an source.

5.3 Special Protective Actions For Fire-Fighters

- Protective Actions** : Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
- Protective Equipment** : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment And Emergency Procedures

- For Non-Emergency Personnel** : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
- For Emergency Responders** : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

- Precautions** : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

6.3 Methods And Materials For Containment And Cleaning Up

- Containment Procedures** : Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
- Cleanup Procedures** : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions For Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions For Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.
- NFPA 30B Classification** : This product is classified as a Level 3 Aerosol per NFPA 30B.

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 4 of 9

Aerosol Injected Lubricator

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Propane (74-98-6)		
OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m ³)	1800 mg/m ³
California	California PEL (TWA) (ppm)	1000 ppm
Carbon Dioxide (124-38-9)		
ACGIH	ACGIH TWA (ppm)	5000 ppm
ACGIH	ACGIH STEL (ppm)	30000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
NIOSH	US IDLH (ppm)	40000 ppm
NIOSH	NIOSH REL (TWA) (ppm)	5000 ppm
NIOSH	NIOSH REL (STEL) (ppm)	30000 ppm
California	California PEL (TWA) (mg/m ³)	9000 mg/m ³
California	California PEL (TWA) (ppm)	5000 ppm
California	California PEL (STEL) (mg/m ³)	54000 mg/m ³
California	California PEL (STEL) (ppm)	30000 ppm
Hydrotreated Light Naphthenic Distillate (64742-53-6)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ Oil Mist
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Oil Mist
California	California PEL (TWA) (mg/m ³)	5 mg/m ³
Hydrotreated Light Petroleum Distillate (64742-47-8)		
California	California PEL (TWA) (mg/m ³)	5 mg/m ³
Not applicable		
Solvent-Dewaxed Heavy Paraffinic Petroleum Distillate (64742-65-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ Oil Mist
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Oil Mist
California	California PEL (TWA) (mg/m ³)	5 mg/m ³
Hydrotreated Heavy Naphthenic Distillate (64742-52-5)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ Oil Mist
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Oil Mist
California	California PEL (TWA) (mg/m ³)	5 mg/m ³
Solvent-Refined Residual Oil (64742-01-4)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ Oil Mist
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Oil Mist
California	California PEL (TWA) (mg/m ³)	5 mg/m ³

8.2 Exposure Controls

Engineering Measures

: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 5 of 9

Aerosol Injected Lubricator

Respiratory Protection	: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.
Skin Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
Eye/Face Protection	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
Other Protective Equipment	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 0.00 °C	Melting / Freezing Point	> 0.00 °C
Flash Point, Liquid	> 40.00 °C	Flash Point, Propellant	-104.40 °C
Explosive Limits	LEL: 0.00 UEL: 10.00 vol %	Autoignition Temperature, Liquid	255.00 °C
Flammability	Extremely Flammable Aerosol	Density	0.806 g/cm ³
Molecular Weight	Not Available	Weight	6.726 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	Not Available	Partition Coefficient	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical Form	Pressurized Product	Heat Of Combustion	16068.36 BTU/lb
Odor	Characteristic	Water Solubility	Not Available
Appearance / Color	Clear, Colorless	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	23.80 % wt	VOC Regulatory	100.28 g/L (0.84 lbs/gal)
Percent VOC	10.80 % wt	VOC Actual	87.05 g/L (0.73 lbs/gal)
Percent HAP	0.00 % wt	HAP Content	0.00 g/L (0.00 lbs/gal)
Global Warming Potential	0.36 GWP	Maximum Incremental Reactivity	0.2890 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity	: No specific test data related to reactivity is available for this products or its ingredients.
------------	--------------------------------------------------------------------------------------------------

10.2 Chemical Stability

Stability	: This product is stable.
-----------	---------------------------

10.3 Possibility Of Hazardous Reactions

Reactions	: Under normal conditions of storage and use, hazardous reactions are not expected to occur.
-----------	----------------------------------------------------------------------------------------------

10.4 Conditions To Avoid

Conditions	: Other Ignition Sources, Heat, Flames, Sparks.
------------	-------------------------------------------------

10.5 Incompatible Materials

Incompatibilities	: Strong Oxidizing Agents.
-------------------	----------------------------

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 6 of 9

Aerosol Injected Lubricator

10.6 Hazardous Decomposition Products

Products : None identified.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1.1 Information On Toxicological Effects

Propane (74-98-6)

LC50 Inhalation (Rat) 658 mg/l/4h (Lit.)

Hydrotreated Light Naphthenic Distillate (64742-53-6)

LD50 Oral (Rat) > 5000 mg/kg (ChemInfo)

LD50 Dermal (Rabbit) > 2000 mg/kg (ChemInfo)

LC50 Inhalation (Rat) 2180 ml/m³ (RTECS)

Hydrotreated Light Petroleum Distillate (64742-47-8)

LD50 Oral (Rat) > 5000 mg/kg (ExxonMobil SDS)

LD50 Dermal (Rabbit) > 5000 mg/kg (ExxonMobil SDS)

LC50 Inhalation (Rat) > 5000 mg/kg (ExxonMobil SDS)

Solvent-Dewaxed Heavy Paraffinic Petroleum Distillate (64742-65-0)

LD50 Oral (Rat) > 5000 mg/kg (ChemInfo)

LD50 Dermal (Rabbit) > 5000 mg/kg (ChemInfo)

Hydrotreated Heavy Naphthenic Distillate (64742-52-5)

LD50 Oral (Rat) > 5000 mg/kg (ChemInfo)

LD50 Dermal (Rabbit) > 2000 mg/kg (ChemInfo)

LC50 Inhalation (Rat) 2180 ml/m³

Solvent-Refined Residual Oil (64742-01-4)

LD50 Oral (Rat) > 5000 mg/kg (ChemInfo)

LD50 Dermal (Rabbit) > 2000 mg/kg (ChemInfo)

11.1.2 Health Hazard Classification

Skin Corrosion/Irritation : Not classified

Eye Damage/Irritation : Not classified

Respiratory Or Skin Sensitization : Not classified

Germ Cell Mutagenicity : Not classified

Reproductive Toxicity : Not classified

Stot-Single Exposure : Not classified

Stot-Repeated Exposure : Not classified

Aspiration Hazard : May be fatal if swallowed and enters airways.

Carcinogen Data : None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

11.1.3 Information On The Likely Routes Of Exposure

Routes Of Exposure : Eye Contact, Skin Contact, Inhalation.

11.1.4 Symptoms Related To The Physical, Chemical And Toxicological Characteristics

Symptoms of Exposure : Confusion, Dizziness.

11.1.5 Delayed And Immediate Effects And Also Chronic Effects From Short And Long Term Exposure

Delayed Effects : No known delayed effects.

Immediate Effects : Asphyxia.

Chronic Effects : No chronic effects identified.

Target Organs : Cardiovascular System, Central Nervous System, Respiratory System.

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 7 of 9

Aerosol Injected Lubricator

Medical Conditions Aggravated

: None identified.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hydrotreated Light Naphthenic Distillate (64742-53-6)

LC50 fish 1	> 5000 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	> 1000 mg/l Water Flea - 48hr

Solvent-Dewaxed Heavy Paraffinic Petroleum Distillate (64742-65-0)

LC50 fish 1	> 5000 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	> 1000 mg/l Water Flea - 48hr

Hydrotreated Heavy Naphthenic Distillate (64742-52-5)

LC50 fish 1	> 5000 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	> 1000 mg/l Water Flea - 48hr

Solvent-Refined Residual Oil (64742-01-4)

LC50 fish 1	> 5000 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	> 1000 mg/l Water Flea - 48hr

12.2 Ecological Properties

Propane (74-98-6)

Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
BCF fish 1	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Carbon Dioxide (124-38-9)

Log Pow	0.83
---------	------

Hydrotreated Light Naphthenic Distillate (64742-53-6)

Persistence and degradability	Biodegradability in water: no data available.
Log Pow	> 6.5
Bioaccumulative potential	No bioaccumulation data available.

Hydrotreated Light Petroleum Distillate (64742-47-8)

Persistence and degradability	Biodegradability 88% / 28 days.
Log Pow	6

Solvent-Dewaxed Heavy Paraffinic Petroleum Distillate (64742-65-0)

Persistence and degradability	Biodegradability in water: no data available.
Log Pow	> 6.5
Bioaccumulative potential	No bioaccumulation data available.

Hydrotreated Heavy Naphthenic Distillate (64742-52-5)

Persistence and degradability	Biodegradability in water: no data available.
Log Pow	> 6.5
Bioaccumulative potential	No bioaccumulation data available.

Solvent-Refined Residual Oil (64742-01-4)

Persistence and degradability	Biodegradability in water: no data available.
Log Pow	> 6.5
Bioaccumulative potential	No bioaccumulation data available.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal

: Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 8 of 9

Aerosol Injected Lubricator

Waste Disposal Of Packaging

in compliance with the respective national, federal, state, and/or local regulations.

: In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.





Landfill Precautions

: Not Available.

Incineration Precautions

: Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information	Ground Transportation (DOT)	Air Transportation (IATA)	Ocean Transportation (IMDG)
Identification Number	UN1950	UN1950	UN1950
Proper Shipping Name	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
Hazard Class(es)	2.1	2.1	2.1
Packaging Group	None	None	None
Limited Quantity	Yes 	Yes 	Yes 
Marine Pollutant	No	No	No
Hazard Labels		2.1 - Flammable gas 	

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

TSCA Inventory

: All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

SARA 313 Reporting

: This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Applicable Federal Regulations

: To the best of our knowledge none of the ingredients appear in any applicable Federal regulation.

15.2 State Regulations

California Proposition 65

: This product does not contain any substance known to the State of California to cause cancer, developmental and/or reproductive harm.

State Right-to-Know Lists

: The following ingredients appear on one or more state Right-to-Know lists.

Propane (74-98-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

Carbon Dioxide (124-38-9)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 - OTHER INFORMATION

SAFETY DATA SHEET

Part No. 13445Z Aerosol

Print Date: 04/19/2017

Revision Date: 04/19/2017

Version: 2.0 (EN)

Page 9 of 9

Aerosol Injected Lubricator

SDS Compliance

: This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department .

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

Disclaimer Of Liability

: The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Full text of H-statements

H Code	H Phrase
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways