

**PRODUCT: EW13524 FLEXIBLE STRIP CAULK BLACK****SECTION 01: Chemical product and company identification**

Product name..... EW13524 FLEXIBLE STRIP CAULK BLACK
 Manufactured for..... The Eastwood Company
 263 Shoemaker Road
 Pottstown, PA 19464
 Tel (800) 343 - 9353
 24 hour emergency number:..... IN THE UNITED STATES CALL CHEMTREC (800) 424-9300.
 Material use..... Automotive. This product should not be used for any other purpose other than the ones described in this section.
 Chemical family..... Mixture.
 Preparation date..... March 7, 2015.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 1 Reactivity: 0.
 HMIS..... H: 2 F: 1 R: 0.

SECTION 02: Hazards identification

Signal Word..... WARNING.
 Hazard Classification..... Carcinogen 2.
 Hazard Description..... H351 This product contains ingredients that are suspected of causing cancer.
 Precautionary Statements..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P280 Wear protective gloves and eye protection.
 Response P308 + P313 If exposed or concerned, get medical advice/attention.
 Storage..... P405 Store locked up.
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	WT. %
CELLULOSE FIBERS	9004-34-6	1-5
CARBON BLACK	1333-86-4	0.1-1.0

SECTION 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
 Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
 Inhalation..... If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
 Ingestion..... If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
 Additional information..... Treat victims symptomatically. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

PRODUCT: EW13524 FLEXIBLE STRIP CAULK BLACK**SECTION 05: Fire fighting measures**

Extinguishing media..... "Alcohol" foam, CO₂, dry chemical.
 Hazardous combustion products..... Oxides of carbon (CO, CO₂).
 Special fire fighting procedures..... Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Solvent vapours may be heavier than air and may build up and travel along the ground to an ignition source, which may result in a flash back to the source of the vapours. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture.

SECTION 06: Accidental release measures

Leak/spill..... Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).

SECTION 07: Handling and storage

Handling procedures..... Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
 Storage needs..... Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: Exposure controls / personal protection

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
CELLULOSE FIBERS	Not established 15 mg/m ³	Not established	Not established	Not established	Not established
CARBON BLACK	3.5 mg/m ³	Not established	3.5 mg/m ³	Not established	3.5 mg/m ³
Clothing/type.....	Wear adequate protective clothes.				
Eye/type.....	Liquid chemical goggles.				
Footwear/type.....	Safety boots per local regulations.				
Gloves/ type.....	Chemical resistant gloves.				
Other/type.....	Emergency showers and eye wash stations should be available.				
Protective equipment					
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Ventilation requirements.....	Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. .				
Exposure limits					

SECTION 09: Physical and chemical properties

Physical state..... Paste.
 Colour..... Black.
 Odour..... Faint.
 Odour threshold (ppm)..... No data.
 Vapour pressure (mm Hg)..... No data.
 Vapour density (air=1)..... Not available.
 pH..... Not applicable.
 Density..... 14.77 lb/usg - 1.77 g/mL.
 Specific gravity..... 1.77.
 Freezing point (deg C)..... No data.
 Solubility..... Little or none.
 Boiling point (deg C)..... Not available.
 Evaporation rate..... No data.
 Flash point (deg C), method..... 260°C Closed Cup.

PRODUCT: EW13524 FLEXIBLE STRIP CAULK BLACK**SECTION 09: Physical and chemical properties**

Auto ignition temperature (deg C)..... Not tested.
 Upper flammable limit (% vol)..... Not applicable.
 Lower flammable limit (% vol)..... Not applicable.
 Coefficient of water/oil distribution..... No data.
 VOC..... Non volatile.
 Viscosity..... No data.

SECTION 10: Stability and reactivity

Stability..... Stable at normal temperatures and pressures.
 Reactivity conditions..... Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
 Incompatibility..... Incompatible with strong oxidizers.
 Hazardous products of decomposition..... Oxides of carbon (CO,CO2).
 Hazardous polymerization..... Will not occur under normal temperature and pressure.

SECTION 11: Toxicological information

INGREDIENTS	LC50	LD50
CELLULOSE FIBERS	NOT AVAILABLE	NOT AVAILABLE
CARBON BLACK	No data	>8,000 mg/kg oral (rat)
Route of entry	Eye contact. Skin contact. Inhalation.	
Effects of acute exposure.....	May cause skin or eye irritation after repeated or prolonged contact.	
Effects of chronic exposure.....	Not available.	
Skin contact.....	Prolonged or repeated contact may cause irritation.	
Skin absorption.....	No evidence of adverse effects from available information.	
Eye contact.....	May cause eye irritation.	
Inhalation (acute).....	No evidence of adverse effects from available information.	
Ingestion.....	Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. May be harmful or fatal if swallowed.	
Carcinogenicity of material.....	Carbon black is known to the State of California to cause cancer and developmental effects.	
Reproductive effects.....	None.	
Toxicological Data		

SECTION 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

SECTION 13: Disposal considerations

Waste disposal..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

SECTION 14: Transport information

TDG Classification..... Not regulated.
 DOT Classification (Road)..... Not regulated.
 IATA Classification (Air)..... Not regulated.
 IMDG Classification (Marine)..... Not regulated.
 Marine Pollutant..... This component of the product is not regulated. See part B for transport regulatory information.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

SECTION 15: Regulatory information

WHMIS classification..... D2A.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health.
 Section 313..... None.

PRODUCT: EW13524 FLEXIBLE STRIP CAULK BLACK**SECTION 15: Regulatory information**

EPA hazardous air pollutants (HAPS) None.
40CFR63
TSCA inventory status..... All components are listed.
California Proposition 65..... This product contains Carbon Black known to the State of California to cause cancer.

SECTION 16: Other information

Prepared by: REGULATORY AFFAIRS.
Telephone number:..... (800) 387-7981.
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
Preparation date: MAR07/15