



\*Estimate  
N/A-Not Applicable  
N/R-Not Restricted  
N/E-Not Established

## MATERIAL SAFETY DATA SHEET

<b>NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.</b>					
<b>IDENTITY</b> (As shown on Label or package) LIQUID TAPE SPRAY			<b>PART NO.</b> IF APPLICABLE		
<b>SECTION I</b>					
<b>MANUFACTURER'S NAME</b> Plasti Dip International Inc.			<b>EMERGENCY PHONE No.</b> Chem-Trec USA only: 1-800-424-9300 INT'L: 703-527-3887		
<b>ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)</b> 3920 Pheasant Ridge Drive			<b>REVISION #</b> 0001		
Blaine, MN 55449			<b>MANUFACTURER'S PHONE</b> No. FOR INFORMATION 1-763-785-2156		
			<b>DATE MSDS</b> WAS PREPARED May 18, 2009		
<b>SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all carcinogens if 0.1% of the composition or greater.</b>					
<b>HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)</b>	<b>% Wt. (OPTIONAL)</b>	<b>CAS NO.</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>OTHER LIMITS RECOMMEND</b>
Propane	20 - 30	74-98-6	1000 ppm	1000 ppm	None
VM&P Naphtha	15 - 20	64742-89-8	300 ppm	300 ppm	None
Xylene	10 - 15	1330-20-7	100 ppm	100 ppm	None
Heptane	10 - 15	426260-76-6	500 ppm	400 ppm	None
N-Butane	10 - 15	106-97-8	800 ppm	800 ppm	None
Ethylbenzene	1 - 5	100-41-4	100 ppm	100 ppm	None
Methyl n-Amyl Ketone	1 - 5	110-43-0	100 ppm	50 ppm	None
<b>SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS</b>					
<b>BOILING POINT</b> <0 - 285 °F	<b>SPECIFIC GRAVITY (H<sub>2</sub>O =1)</b> 0.67		<b>APPROXIMATE WEIGHT PER GALLON (LBS)</b> 5.59		
<b>VAPOR PRESSURE</b> 760 mm Hg @ 20 °C	<b>VAPOR DENSITY (AIR = 1)</b> Heavier than Air		<b>EVAPORATION RATE (BUTYL ACETATE =1)</b> >1.0		
<b>SOLUBILITY IN WATER</b> N/A	% VOLATILE 87% VOC 4.89 Lbs/Gal		<b>OTHER (IF ANY)</b>		
<b>APPEARANCE AND ODOR</b> Various colors, syrupy liquid, with solvent odor					
<b>SECTION IV-FIRE AND EXPLOSION HAZARD DATA</b>					
<b>FLASH POINT</b> Propellant < -25 °F	<b>FLAMMABLE LIMITS</b>		<b>LEL</b> 0.9	<b>UEL</b> 9.5	
<b>EXTINGUISHING MEDIA</b> Carbon Dioxide, Dry Chemical, or Foam					
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.					
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b> This material is flammable and may be ignited by heat, sparks, flame or static electricity. Level 3 aerosol (NFPA 30B). Contents under pressure if heated over 120°F aerosol can could explode, even when empty.					
<b>HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION</b> Carbon Dioxide and/or Carbon Monoxide					
<b>EXPLOSIVE LIMITS (% BY VOLUME IN AIR)</b> 0.9 - 9.5					
<b>SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION</b>					
<b>HAZARD RATING</b> 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT **SEE SECTION IV			<b>National Fire Protection Association (NFPA)</b>  <b>FIRE</b> <u>4</u> <b>REACTIVITY</b> <u>0</u>  <b>HEALTH</b> <u>2</u> <b>SPECIAL HAZARDS</b> <u>NONE</u>		

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.

<b>SECTION VI - REACTIVITY AND STABILITY DATA</b>			
<b>STABILITY</b>		UNSTABLE      STABLE X	
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide and/or Carbon Dioxide			
<b>HAZARDOUS POLYMERIZATION</b>		MAY OCCUR WILL NOT OCCUR X	<b>CONDITIONS TO AVOID</b> Avoid contact with heat, sparks, and open flame. Product may explode if heated.
<b>SECTION VII - HEALTH HAZARD DATA</b>			
<b>ROUTES OF ENTRY</b>		INHALATION? YES	SKIN? YES      INGESTION? YES      EYES? YES
<b>HEALTH HAZARDS</b>	ACUTE	X	
	CHRONIC	X	
CARCINOGENICITY: IARC 2B			
<b>SIGNS AND SYMPTOMS OF EXPOSURE</b>		Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.	
<b>MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE</b>			
<b>EMERGENCY AND FIRST AID PROCEDURES</b>		Ingestion: Contact Physician or Poison Control Immediately. Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary. Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician. Skin: Wash with soap and water.	
<b>SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE</b>			
<b>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED</b>		Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers. Eliminate all sources of ignition. Ventilate to maintain exposure below PELs.	
<b>WASTE DISPOSAL METHODS</b> Dispose of product in accordance with local, county, state and federal regulations.			
<b>PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE</b>		Keep away from sparks, flames, and heat sources. Do Not store above 120°F Level 3 aerosol (NFPA 30B).	
<b>OTHER PRECAUTIONS</b>		Keep Container Closed When Not In Use. Store this product with adequate ventilation in cool areas. Never place aerosol in flame or fire, Even when Empty.	
<b>SECTION IX - CONTROL MEASURES</b>			
<b>RESPIRATORY PROTECTION</b> (SPECIFY TYPE) Depending on the Airborne concentration, use a Respirator with appropriate NIOSH approved cartridge or supplied air equipment.		<b>PROTECTIVE GLOVES</b> Impervious Gloves	
<b>VENTILATION</b>	LOCAL EXHAUST	Supplemental (if needed)	<b>SPECIAL</b> None
	MECHANICAL (GENERAL) To maintain exposure below PELs		<b>OTHER</b> None
<b>EYE PROTECTION</b> Chemical splash goggles, or approved eye protection.		<b>OTHER PROTECTIVE CLOTHING OR EQUIPMENT</b> Chemical Apron/Eye bath/Safety Shower	
<b>WORK HYGIENIC PRACTICES</b> Wash thoroughly after handling.			
<b>SECTION X - TRANSPORTATION INFORMATION</b>			
<b>DOT PROPER SHIPPING NAME</b> Aerosols		<b>DOT HAZARD CLASS</b> 2.1	
<b>DOT UN NUMBER</b> UN 1950		<b>DOT PACKING GROUP</b> N/A	
<b>IATA PROPER SHIPPING NAME</b> Aerosols, flammable		<b>IATA HAZARD CLASS</b> 2.1	
<b>IATA UN NUMBER</b> UN 1950		<b>IATA PACKING GROUP</b> N/A	
<b>SECTION XI - 313 SUPPLIER NOTIFICATION</b>			
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight). Xylene and Ethylbenzene			
<b>WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.</b>			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Michael N. Hindin