

according to 1907/2006/EC, Article 31

Page 1/9 Printing date 03-08-2016 Revision: 03-08-2016 Version number 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: AUTOSOL® Stainless Steel Polish (75 ml Tube)
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Polishing agent/ Burnishing compound
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Autosol LLC P.O. Box 340358 Austin, Texas 78734 USA

Tel.: +1-512-804-9337 Fax: +1-512-266-6518

www.autosol.com info@autosol.com

· Further information obtainable from:

Abteilung Produktsicherheit

msds@autosol.com

- · 1.4 Emergency telephone number:
- +1-512-804-9337 Main or 1-800-314-5545 Toll Free US and Canada

8.00 - 16.00 h

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



Signal word Warning

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Page 2/9 Printing date 03-08-2016

> Revision: 03-08-2016 Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 1)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection. P273 Avoid release to the environment.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

· Additional information: Keep out of reach of children.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	10-25%		
EINECS: 265-151-9 Reg.nr.: 01-2119473851-33-xxxx	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336			
EC number: 919-164-8 Reg.nr.: 701-2119473977-17-XXXX	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, Aromatics (2-25%)	1-10%		
	♦ Asp. Tox. 1, H304; Aquatic Chronic 3, H412			
CAS: 100-37-8	2-diethylaminoethanol	1-10%		
EINECS: 202-845-2	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 3, H311; Acute Tox. 3, H331; ♦ Skin Corr. 1B, H314; ♠ Acute Tox. 4, H302; STOT SE 3, H335			
CAS: 64-17-5	ethanol	1-10%		
EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319			

· Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Page 3/9
Printing date 03-08-2016
Revision: 03-08-2016
Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 12
- · 7.3 Specific end use(s) No further relevant information available.

GB —



according to 1907/2006/EC, Article 31

Page 4/9

Printing date 03-08-2016 Revision: 03-08-2016 Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device when high concentrations are present. Filter A/P2

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Natural rubber, NR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)




according to 1907/2006/EC, Article 31

Page 5/9
Printing date 03-08-2016
Revision: 03-08-2016
Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 4)

· Eye protection:



SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties				
General Information				
· Appearance: Form:	Pasty			
Colour:	White			
· Odour:	Characteristic			
· Odour threshold:	Not determined.			
· pH-value at 20 °C:	9.2			
· Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	90 °C			
· Flash point:	Not applicable.			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:				
Decomposition temperature:	Not determined.			
· Self-igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
· Vapour pressure:	Not determined.			
· Density at 20 °C:	1.04 g/cm ³			
Relative density	Not determined.			
· Vapour density	Not determined.			
· Evaporation rate	Not determined.			
· Solubility in / Miscibility with				
water:	Not miscible or difficult to mix.			
· Partition coefficient (n-octanol/water	· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity:				
Dynamic:	Not determined.			
Kinematic at 40 °C:	> 21 mm²/s			

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Page 6/9
Printing date 03-08-2016
Revision: 03-08-2016
Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:				
64742-49-	64742-49-0 Naphtha (petroleum), hydrotreated light				
Oral	LD50	5000 mg/kg (rat)			
Dermal	LD50	2800 mg/kg (rabbit)			
Inhalative	LC50 (4 h)	>23.3 mg/l (rat)			
Hydrocarl Aromatics	,	C13, n-alkanes, iso-alkanes, cyclenes,			
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>2920 mg/kg (rabbit)			
Inhalative	LC50 (4 h)	>13.1 mg/l (rat)			
100-37-8 2	100-37-8 2-diethylaminoethanol				
Oral	LD50	1300 mg/kg (rat)			
Inhalative	LC50 (4 h)	5 mg/l (mouse)			
64-17-5 et	64-17-5 ethanol				
Oral	LD50	7060 mg/kg (rat)			
	LC50 (4 h)	20000 mg/l (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Page 7/9

Printing date 03-08-2016 Revision: 03-08-2016 Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 6)

- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclenes, Aromatics (2-25%)

LC50 10-100 mg/l (Oncorhynchus mykiss)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Page 8/9
Printing date 03-08-2016
Revision: 03-08-2016
Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 7

		(Contd. of page /
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Anr Marpol and the IBC Code	nex II of Not applicable.	
· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing MSDS:

Autosol LLC

P.O. Box 340358 Austin, Texas 78734

Abteilung F&E / Produktsicherheit

(Contd. on page 9)



according to 1907/2006/EC, Article 31

Page 9/9

Printing date 03-08-2016 Revision: 03-08-2016 Version number 1

Trade name: AUTOSOL® Stainless Steel Polish

(Contd. of page 8)

· Contact: msds@autosol.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4
Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3