

according to 1907/2006/EC, Article 31

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- [·] Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish
- \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against \cdot Sector of Use
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Application of the substance / the mixture Polishing agent/ Burnishing compound
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Autosol, LLC P.O. Box 340358 Austin, TX 78734

Tel.: 1-512-804-9337

www.autosol.com

• Further information obtainable from: msds@autosol.com

• **1.4 Emergency telephone number:** 1-512-804-9337 or 1-800-314-5545 Toll Free US and Canada

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



R36: Irritating to eyes.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Page 1/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1



according to 1907/2006/EC, Article 31

Page 2/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Oxiran, 2-Methyl-, Polymere with Oxiran, mono(2-Propylheptyl) ether

- · Hazard statements
- H318 Causes serious eye damage.

· Precautionary statements

P102 Keep out of reach of children.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P310 Immediately call a POISON CENTER/doctor.
- · Additional information: Keep out of reach of children.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 67-63-0	propan-2-ol	1-10%	
EINECS: 200-661-7	🗙 Xi R36; 👩 F R11		
	R67		
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336		
CAS: 166736-08-9	Oxiran, 2-Methyl-, Polymere with Oxiran, mono(2-Propylheptyl) ether	1-10%	
	🗙 Xn R22; 🗙 Xi R41		
	📀 Eye Dam. 1, H318; 🚯 Acute Tox. 4, H302		
CAS: 166736-08-9	Oxiran, 2-Methyl-, Polymer mit Oxiran, mono(2-Propylheptyl) ether	1-10%	
	🗙 Xn R22; 🗙 Xi R41		
	😔 Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302		
Additional information: For the wording of the listed risk phrases refer to section 16.			

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.

(Contd. of page 1)



according to 1907/2006/EC, Article 31

Page 3/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

(Contd. of page 2)

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

· After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 10
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)



according to 1907/2006/EC, Article 31

Page 4/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- · Respiratory protection:

Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)



according to 1907/2006/EC, Article 31

Page 5/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

3.1 information on basic physical a	and chemical properties	
· General Information		
· Appearance:	-	
Form:	Pasty	
Colour: · Odour:	Beige	
· Odour: · Odour threshold:	Characteristic Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
· Flash point:	49 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure at 20 °C:	23 hPa	
· Density:	Not determined.	
 Relative density 	Not determined.	
 Vapour density 	Not determined.	
· Evaporation rate	Not determined.	
 Solubility in / Miscibility with 		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wat	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	

(Contd. of page 4)

GB —



according to 1907/2006/EC, Article 31

Page 6/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

9.2 Other information

No further relevant information available.

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:

67-63-0 pi	ropan-2-ol		
Oral	LD50	5045 mg/kg (rat)	
Dermal	LD50	12800 mg/kg (rabbit)	
Inhalative	LC50 (4 h)	30 mg/l (rat)	
166736-08-9 Oxiran, 2-Methyl-, Polymere with Oxiran, mono(2-Propylheptyl) ether			
Oral	LD50	300-2000 mg/kg (rat)	
166736-08	166736-08-9 Oxiran, 2-Methyl-, Polymer mit Oxiran, mono(2-Propylheptyl) ether		
Oral	LD50	500 mg/kg (rat)	
· Primary in	ritant effec	t:	

- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, disziness, etc.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Page 7/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

(Contd. of page 6)

SECTION 12: Ecological information				
· 12.1 Toxicit	ey (
· Aquatic toxicity:				
67-63-0 propan-2-ol				
LC50	> 100 mg/l (daphnia)			
LC50 (96 h)	> 100 mg/l (fish)			
166736-08-9 Oxiran, 2-Methyl-, Polymere with Oxiran, mono(2-Propylheptyl) ether				
LC50 (48 h)	10-100 mg/l (daphnia)			
LC50 (96 h)	10-100 mg/l (fish)			
166736-08-9 Oxiran, 2-Methyl-, Polymer mit Oxiran, mono(2-Propylheptyl) ether				
LC50 (48 h)	1-10 mg/l (daphnia)			
LC50 (96 h)	10-100 mg/l (fish)			
	tence and degradability No further relevant information available.			

• 12.3 Bioaccumulative potential No further relevant information available.

 \cdot 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	ation	
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
 · 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA 	Void	
		(Contd. on page 8)



Page 8/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

	(Contd. of page	ge 7)
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
Class	Void	
· 14.4 Packing group		
· ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	
 14.6 Special precautions for user 	Not applicable.	
· 14.7 Transport in bulk according to Annex I	ll of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN "Model Regulation":	-	

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

- H302 Harmful if swallowed.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- R11 Highly flammable.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R41 Risk of serious damage to eyes.
- R67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS:

Autosol, LLC P.O. Box 340358 Austin, TX 78734

· Contact: msds@autosol.com

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)



according to 1907/2006/EC, Article 31

Page 9/9 Printing date 02-13-2016 Revision: 02-13-2016 Version number 1

Trade name: 01 001920 AUTOSOL® Anodized Aluminium Polish

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 2: Flammable liquids, Hazard Category 2 Acute Tox. 4: Acute toxicity, Hazard Category 4 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 (Contd. of page 8)