



# Material Safety Data Sheet

NFPA	HMIS / WHMIS	PPE	Transport Symbol

Revision Date 05-Dec-2012

Revision Number 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** Kawasaki Green Powder  
**Product Code(s)** 14118A  
**Product Type** Polyester TGIC  
**Manufactured by:** The Eastwood Company  
 263 Shoemaker Road  
 Pottstown, PA 19464  
**Emergency Contact Number** 800-345-1178  
 (610)-323-2200  
**Telephone for Information** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Emergency Overview

May cause skin and eye irritation

**Appearance** Powder**Physical State** Solid/Powder**Odor** Odorless
**OSHA Regulatory Status**

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

**Potential Health Effects**
**Acute Toxicity**

## PAGE FOOTER

<b>Eyes</b>	No known effect based on information supplied
<b>Skin</b>	No known effect based on information supplied
<b>Inhalation</b>	No known effect based on information supplied
<b>Ingestion</b>	No known effect based on information supplied

**Chronic Effects**

No known effect

**Aggravated Medical Conditions** None known**Environmental Hazard** See Section 12 for additional Ecological Information

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Hazardous Components**

Components	CAS-No	Weight %
C.I. Pigment Yellow 53	8007-18-9	10-30%
Barium sulfate	7727-43-7	10-30%
Titanium Dioxide	13463-67-7	1-10%
TGIC/1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(oxiranylmethyl)-	2451-62-9	1-10%

### 4. FIRST AID MEASURES

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes
<b>Skin Contact</b>	Wash skin with soap and water
<b>Inhalation</b>	Move to fresh air
<b>Ingestion</b>	Never give anything by mouth to an unconscious person
<b>Notes to Physician</b>	Treat symptomatically

### 5. FIRE-FIGHTING MEASURES

<b>Flammable Properties</b>	Powdered material may form explosive dust-air mixtures
<b>Suitable Extinguishing Media</b>	Water spray, dry chemical, carbon dioxide (CO <sub>2</sub> ), or foam
<b>Hazardous Combustion Products</b>	Carbon oxides

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

<b>NFPA</b>	<b>Health Hazard</b> 0	<b>Flammability</b> 1	<b>Stability</b> 0	<b>Physical and Chemical Hazards</b> N/A
-------------	------------------------	-----------------------	--------------------	--

### PAGE FOOTER

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Wear protective gloves/clothing and eye/face protection
<b>Methods for Containment</b>	Prevent further leakage or spillage if safe to do so
<b>Methods for Cleaning Up</b>	Pick up and transfer to properly labeled containers

## 7. HANDLING AND STORAGE

<b>Handling</b>	Handle in accordance with good industrial hygiene and safety practice
<b>Storage</b>	Store in a dry, air conditioned place below 80F

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Exposure Guidelines</b>	This product, as supplied, contains the following materials with occupational exposure limits established by the region specific regulatory bodies
----------------------------	--

Components	ACGIH TLV	OSHA PEL	NIOSH IDLH
C.I. Pigment Yellow 53		TWA: 0.5 mg/m <sup>3</sup> (vacated) TWA: 0.5 mg/m <sup>3</sup>	IDLH: 10 mg/m <sup>3</sup> except Nickel carbonyl IDLH: 50 mg/m <sup>3</sup> TWA: 0.015 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup>
Barium sulfate	TWA: 10 mg/m <sup>3</sup>	(vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
Titanium Dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 10 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup>
TGIC/1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(oxiranylmethyl)-	TWA: 0.05 mg/m <sup>3</sup>		

<b>Engineering Measures</b>	Showers Eyewash stations Ventilation systems
-----------------------------	--

### Personal Protective Equipment

<b>Eye/Face Protection</b>	Eye protection
<b>Skin and Body Protection</b>	Wear protective gloves/clothing
<b>Respiratory Protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn

<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice
-------------------------	---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Powder	<b>Odor</b>	Odorless
<b>Physical State</b>	Solid/Powder	<b>pH</b>	Approximately neutral
<b>Flash Point</b>	Not applicable	<b>Autoignition Temperature</b>	Not applicable
<b>Boiling Point/Range</b>	Not applicable	<b>Melting Point/Range</b>	Melting Point/Range 50-70 °C
<b>Freezing point</b>	Not applicable	<b>Flammability Limits in Air</b>	No information available
<b>Explosion Limits</b>	30-70 g/m <sup>3</sup>		

## PAGE FOOTER

<b>Specific Gravity</b>	1.2-1.8	<b>VOC Content</b>	None
<b>HAPS data</b>	Not applicable		

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	Stable under recommended storage conditions
<b>Incompatible Products</b>	None known based on information supplied
<b>Conditions to Avoid</b>	None known based on information supplied
<b>Hazardous Decomposition Products</b>	May emit toxic fumes under fire conditions - carbon monoxide, carbon dioxide, nitrogen oxides, and hydrogen chloride
<b>Hazardous Reactions</b>	Hazardous polymerization does not occur

## 11. TOXICOLOGICAL INFORMATION

### Acute Toxicity

<b>Product Information</b>	Substances which cause concern for man owing to possible mutagenic effects but for which the available information is not adequate for making a satisfactory assessment.
<b>Irritation</b>	Repeated or prolonged exposure may cause irritation of eyes and skin

Components	LD50 Oral	LD50 Dermal	LC50 Inhalation
Titanium Dioxide	10000 mg/kg ( Rat )		
TGIC/1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(oxiranylmethyl)-	188 mg/kg ( Rat )		

### Chronic Toxicity

<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen
------------------------	---

Components	ACGIH	IARC	NTP	OSHA
C.I. Pigment Yellow 53		Group 1	Known	x
Titanium Dioxide		Group 2B		X

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

The environmental impact of this product has not been fully investigated

## 13. DISPOSAL CONSIDERATIONS

### PAGE FOOTER

**Waste Disposal Method** Dispose of contents/container in accordance with local regulation

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

**TDG** Not regulated

**MEX** Not regulated

**IATA** Not regulated

**IMDG/IMO** Not regulated

## 15. REGULATORY INFORMATION

### International Inventories

<b>TSCA</b>	Complies
<b>DSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Does not Comply
<b>IECSC</b>	Complies
<b>KECL</b>	Does not Comply
<b>PICCS</b>	Does not Comply
<b>AICS</b>	Complies

### U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains the following chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Components	CAS-No	Weight %	SARA 313 - Threshold Values %
C.I. Pigment Yellow 53	8007-18-9	10-30%	0.1

#### **SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	No
<b>Chronic Health Hazard</b>	No
<b>Fire Hazard</b>	No
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

#### **Clean Water Act**

## PAGE FOOTER

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990

#### CERCLA

This material, as supplied, contains the following substance(s) regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

#### U.S. State Regulations

##### California Proposition 65

This product contains the following Proposition 65 chemicals

#### U.S. State Right-to-Know Regulations

Components	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
C.I. Pigment Yellow 53		X	X	X	X
Barium sulfate	X	X	X		X
Titanium Dioxide	X	X	X		X
TGIC/1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris(oxiranylmethyl)-		X			

#### International Regulations

Components	Carcinogen Status	Exposure Limits
C.I. Pigment Yellow 53		Mexico: TWA= 0.5 mg/m <sup>3</sup>
Barium sulfate		Mexico: TWA= 0.5 mg/m <sup>3</sup>
Titanium Dioxide		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### WHMIS Hazard Class

Not determined

## 16. OTHER INFORMATION

Revision Date

05-Dec-2012

## PAGE FOOTER

---

**Disclaimer**

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of MSDS**