


SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Norton Weatherstrip Adhesive Amber 5 oz Tube
Product Code: 14130Z
Distributed By: The Easthill Group
 dba/ The Eastwood Company
 263 Shoemaker Road
 Pottstown, PA 19464
Address:
General Phone Number: USA & Canada: 800-345-1178
 Outside USA: 610-323-2200
Emergency Phone Number: Chemtrec: 1 800 424-9300
MSDS Creation Date: August 09, 2010
MSDS Revision Date: December 15, 2010



HMIS	
Health Hazard	2
Fire Hazard	3
Reactivity	0
Personal Protection	1

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Ethyl Acetate	141-78-6	3 - 7 by weight	
Petroleum Naphtha	64742-95-6	15 - 40 by weight	
Toluene	108-88-3	10 - 30 by weight	
Acetone	67-64-1	15 - 40 by weight	606-001-00-8

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: DANGER! Flammable.. Irritant.
Route of Exposure: Eyes. Skin. Inhalation. Ingestion.
Potential Health Effects:
Eye: May cause irritation.
Skin: May cause irritation.
Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion: Harmful if swallowed. Ingestion can cause nausea, vomiting, diarrhea and gastrointestinal irritation.
Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.
Target Organs: Eyes. Skin. Respiratory system. Digestive system. Central nervous system. Kidney.

SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact: Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: < 0 deg F
 < -18 deg C

EW #14130Z - Norton Weatherstrip Adhesive Amber 5 oz Tube

Flash Point Method:	Tag Closed Cup
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	1.2
Upper Flammable/Explosive Limit:	12.0
Fire Fighting Instructions:	Extremely flammable. Conditions to avoid: Ignition sources, excessive heat, open flame, sparks and electrostatic charge.
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.
Protective Equipment:	As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	Flammable liquid. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back.
Universal Fire And Explosion Hazards:	Toxic gases may be formed. Emits flammable vapours which, when mixed with air, can burn or become explosive.

NFPA Ratings:

NFPA Health:	2
NFPA Flammability:	3
NFPA Reactivity:	0

Notes : HAZARD RATING SOURCE:
HMIS:
HEALTH: 2
FLAMMABILITY: 3
REACTIVITY: 0

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	Use proper personal protective equipment as listed in section 8.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Spill Cleanup Measures:	Remove all sources of ignition. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal.

SECTION 7 - HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper grounding procedures.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use.
Work Practices:	To reduce potential for static discharge, bond and ground containers when transferring material.
Special Handling Procedures:	Provide appropriate ventilation/respiratory protection against decomposition products (see Section 10) during welding/flame cutting operations and to protect against dust during sanding/grinding of cured product.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

EW #14130Z - Norton Weatherstrip Adhesive Amber 5 oz Tube

EXPOSURE GUIDELINES

Ethyl Acetate :

Guideline ACGIH: TLV-TWA: 400 ppm

Guideline OSHA: PEL-TWA: 400 ppm

Toluene :

Acetone :

Guideline ACGIH: 500 ppm
TLV-STEL: 750 ppm
TLV-TWA: 500 ppm

Guideline OSHA: 1000 ppm
PEL-TWA: 1000 ppm

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	liquid
Color:	Light amber
Odor:	Mild aromatic odour.
Boiling Point:	56 deg C
Specific Gravity:	H2O=1: 0.86
Solubility:	Not soluble in water
Vapor Density:	(Air = 1.0): Heavier than air
Percent Volatile:	74% +/- 2
Evaporation Rate:	Slower than ether
Flash Point:	< 0 deg F < -18 deg C
Flash Point Method:	Tag Closed Cup
Auto Ignition Temperature:	Not determined.
VOC Content:	248 g/l 2.1 lbs/gal

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Heat, flames, ignition sources, and sparks. Incompatible materials. Freezing or temperatures below 32 deg. F. Temperatures above 120 °F.
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.
Special Decomposition Products:	May emit fumes at decomposition including chlorine, hydrogen chloride, carbon monoxide and carbon dioxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acetone :

Eye:	Eye - Human Standard Draize test.: 500 ppm Eye - Rabbit Standard Draize test.: 20 mg/24H Eye - Rabbit Standard Draize test.: 10 uL Eye - Human Standard Draize test.: 186300 ppm Eye - Rabbit Standard Draize test.: 20 mg
Skin:	Oral - Rat LD50: 5800 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50: 5800 mg/kg [Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor] Intravenous. - Rat LD50: 5500 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50: 3 gm/kg [Details of toxic effects not reported other than lethal dose value] Intraperitoneal. - Mouse LD50: 1297 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rabbit LD50: 5340 mg/kg [Details of toxic effects not reported other than lethal dose value] Administration onto the skin - Guinea pig LD50: >9400 uL/kg [Details of toxic effects not reported other than lethal dose value] Administration onto the skin - Rabbit Open irritation test: 395 mg
Inhalation:	Inhalation - Rat LC50: 50100 mg/m3 [Details of toxic effects not reported other than lethal dose value] Inhalation - Rat LC50: 50100 mg/m3/8H [Details of toxic effects not reported other than lethal dose value] Inhalation - Mouse LC50: 44 gm/m3/4H [Details of toxic effects not reported other than lethal dose value]
Ingestion:	Oral - Rat LD50: 5800 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Rat LD50: 5800 mg/kg [Behavioral - Altered sleep time (including change in righting reflex) Behavioral - Tremor] Oral - Mouse LD50: 3 gm/kg [Details of toxic effects not reported other than lethal dose value]

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity:	No ecotoxicity data was found for the product.
Environmental Fate:	No environmental information found for this product.
Notes :	CHEMICAL FATE: Not Applicable

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:	Remove all sources of ignition. Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
-----------------	---

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name:	Flammable liquid, n.o.s
DOT UN Number:	Non regulated.

SECTION 15 - REGULATORY INFORMATION

Ethyl Acetate :

TSCA Inventory Status:	Listed
EINECS Number:	205-500-4
Canada DSL:	Listed

Toluene :

Section 313:	(*) This substance is regulated under section 313 of the Emergency Planning and Community Right - to - Know Act of 1986.
Canada WHMIS:	(*) This substance is regulated under the Canadian National Pollution Reduction Initiative(NPRI).

Acetone :

TSCA Inventory Status:	Listed
Massachusetts:	Listed: Massachusetts Oil and Hazardous List
Pennsylvania:	Listed
Canada DSL:	Listed
EC Number:	606-001-00-8

SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard:	2
HMIS Fire Hazard:	3
HMIS Reactivity:	0
HMIS Personal Protection:	1
MSDS Creation Date:	August 09, 2010
MSDS Revision Date:	December 15, 2010
Notes :	KEY TO ABBREVIATIONS: EQ = Equal LT = Less Than GT = Greater Than AP = Approximately TR = TRace ND = No Data available

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.