

IMPORTANT! READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

WARNING! This product contains isocyanates and requires the use of a respirator. Serious injury can occur without proper respiratory protection. This is a 2-Component catalyzed paint system, once activated you have 48 hours to use the entire contents of this can.

1. Shake can for at least 2 minutes. This ensures the solids are distributed evenly.
2. Remove the red button from the cap. Do NOT remove cap, keep in place.
3. Put can on hard surface such as a sturdy table, work bench or floor. Turn can up-side-down and place red button on valve on bottom of the can. Push down on red button to pierce the inside activator chamber.
4. Shake can thoroughly for at least 2 minutes to mix the two components. Now the paint is activated.
5. Once activated, the pot life is about 48 hours, it may be a good idea to note the time the product was originally activated.
6. Apply to clean surface using side to side strokes 10 to 12 inches from the substrate. You can adjust the spray pattern by turning the nozzle in 90° increments.
7. This coating is a 2-Component Catalyzed System and will cure relatively fast in most conditions. Ideal application conditions are 70-85°F at 50% humidity or less.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. Suspected of



causing cancer. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.

PRECAUTIONS: Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Avoid breathing dust, fume, gas, mist, vapors and spray. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with local, regional, national and international regulations.

FIRST AID: If exposed or concerned: Get medical advice. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or doctor. **CONTAINS:** dimethyl ether 115-10-6; acetone 67-64-1; n-butyl acetate 123-86-4; Hexamethylene diisocyanate oligomers 28182-81-2; Solvent naphtha (petroleum), light arom. 64742-95-6; 2-methoxy-1-methylethyl acetate 108-65-6; Naphta (petroleum)y hydrotreated heavy 64742-48-9.

EPA Coating Category: NFP Limit 1.40 O₃/g product.

CARB Aerosol Rule Coating Category (01/17) TCC PWR Limit 1.20 O₃/g product.



WARNING: Cancer – www.P65Warnings.ca.gov

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call
Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464

1-800-343-9353 www.eastwood.com © Copyright 2019 Easthill Group, Inc. Made in Germany



DO THE JOB RIGHT.®

2K AEROSPRAY[®] CHASSIS BLACK[®]

SATIN BLACK FINISH



- 2-Component Catalyzed Technology
- Most Durable Aerosol Paint Available
- Sprays Like a Paint Gun

DANGER:

CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE.
Harmful if Swallowed. Irritating To The Skin and Eyes.
Vapor Harmful. Read Precautions On Rear Panel Before Use.

Net wt. 11.9 oz. / 338 grams

14146Z