

IMPORTANT! READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

This is a 2-Component catalyzed paint system. Once activated, you have 48 hours to use the entire contents of this can.

1. Shake can for at least 2 minutes. This ensures the particles are separated and distributed evenly.
2. Remove the red button from the cap. Do NOT remove cap, keep in place.
3. Put can on hard surface such as a sturdy table, work bench or floor. Turn can up-side-down and place red button on to valve on bottom of the can. Push down on red button to pierce the inside activator chamber.
4. Shake can thoroughly for at least 2 minutes to mix the two components. Now the paint is activated.
5. Once activated, the pot life is about 48 hours, it may be a good idea to note the time the product was originally activated.
6. Apply to clean surface using side to side strokes 10 to 12 inches from the substrate. You can adjust the angle of the spray pattern by turning the nozzle tip in 90° increments. For best results, apply with can in vertical position.
7. This coating is a 2-Component Catalyzed System and will cure relatively fast in most conditions. Ideal application conditions are 70-85°F at 50% humidity or less.

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.



Suspected of causing cancer. Suspected of damaging the unborn child. May cause damage to organs (hearing organs) through prolonged or repeated exposure. May displace oxygen and cause rapid suffocation.

PRECAUTIONS: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

CONTENTS: Dimethyl ether 115-10-6, Acetone 67-64-1, Bisphenol A-epichlorohydrin polymer 25068-38-6, Titanium dioxide 13463-67-7, Xylenes (o-, m-, p- isomers) 1330-20-7, Methyl isoamyl ketone 110-12-3, Solvent naphtha, petroleum, heavy aromatic 64742-94-5, n-Butyl acetate 123-86-4, Ethylbenzene 100-41-4, Propylene glycol monomethyl ether acetate 108-65-6. EPA Coating Category: ABP PWR Limit 1.55 O₃/g product.

CARB Aerosol Rule Coating Category (01/07) ABP PWR Limit 0.95 O₃/g



WARNING: This product can expose you to Ethylbenzene and Titanium dioxide, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7166

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
1-800-343-9353 www.eastwood.com © Copyright 2024 Eastwood Automotive Group LLC Made in Germany



DO THE JOB RIGHT.®

2K AERO-SPRAY EPOXY PRIMER

GRAY FINISH



- 2-Component Catalyzed Technology
- Most Durable Aerosol Epoxy Primer Available
- Sprays Like a Paint Gun

DANGER: CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. HARMFUL IF SWALLOWED. IRRITATING TO THE SKIN AND EYES. VAPOR HARMFUL. Read Precautions On Rear Panel Before Use.

Net wt. 12.5 oz. / 353 grams

14149Z

