



DO THE JOB RIGHT.

DATE ISSUED :	1/25/2016
Version No:	1415860-2

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Eastwood Urethane Reducer

PRODUCT CODE: 14158ZP Fast (Low-Temp), 14159ZP Medium (Mid-Temp), 14160ZP Slow (High-Temp)

PRODUCT USE: FOR PROFESSIONAL USE ONLY

MANUFACTURED FOR:

The Easthill Group
dba The Eastwood Company
263 Shoemaker Road,
Pottstown, PA 19464
USA: 1-800-345-1178 or (610) 323-2200 CANADA: 1-800-820-9042

24 HR. EMERGENCY TELEPHONE NUMBER:

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure
Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CLASSIFICATION:

FLAMMABLE LIQUIDS - Category 2
ACUTE TOXICITY: Inhalation - Category 4
ASPIRATION HAZARD: Category 1
CARCINOGENICITY: Category 1B
GERM MUTAGENICITY: Category 1B
REPRODUCTIVE TOXICITY: Category 1B
SKIN IRRITATION: Category 2
EYE IRRITATION: Category 2A
SPECIFIC TARGET ORGAN TOXICITY: SINGLE EXPOSURE - Category 3 (Respiratory, Central nervous system)
SPECIFIC TARGET ORGAN TOXICITY: REPEATED EXPOSURE - Category 2 (Auditory system, eyes)

GHS label elements

PICTOGRAMS



SIGNAL WORD: Danger

HAZARD STATEMENTS: Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin, causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness. May cause genetic defects. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS:

PREVENTION: Read all warning statements on all labels for this and any other products to be mixed with it prior to use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Use personal protective equipment as required, (see Section 8). Wear protective gloves, protective clothing, eye/face protection. Wear an appropriate, properly fitted fresh air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated in Section 8. If medical advice is needed, have product container or label at hand. Avoid release to the environment, if spilled contain material with inert absorbent. Keep out of reach of children and pets at all times.

RESPONSE: IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with plenty of water/shower. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If continued difficulty breathing is experienced, seek immediate medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do, continue rinsing then seek immediate medical attention. If exposed or concerned: Get Medical attention. Call a POISON CENTER, doctor or physician if you feel unwell.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction, do not use water, see Section 5.

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

DISPOSAL: Dispose of unused amounts and empty container with an approved waste disposal facility, in compliance with all local, regional, national and international regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range % by Wt
ACETONE	67-64-1	20 – 50 %
*AROMATIC NAPHTHA	64742-94-5	20 – 50 %
PM ACETATE	108-65-6	20 – 50 %
*METHYL ISOBUTYL KETONE	108-10-1	20 – 50 %
*TOLUENE	108-88-3	< 20 %
VM&P NAPHTHA	64742-89-8	< 20 %

* Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

4. FIRST AID MEASURES

EYES: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, check for and remove contact lenses. Seek immediate medical attention.

SKIN: Remove contaminated clothing. Immediately flush exposed area with large amounts of water. If symptoms occur or persist, seek medical attention. Wash clothing separately and clean shoes before reuse.

INGESTION: Seek immediate medical attention, contact physician or poison control center. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

INHALATION: Seek immediate medical attention. Remove from exposure to fresh air. If not breathing or if breathing is irregular, provide artificial respiration or oxygen by trained personnel; rescuers should put on appropriate protective gear. To prevent aspiration, keep head below knees.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED: Vapor and spray mist harmful. May be harmful or fatal if swallowed, aspiration hazard. Exposure may cause lung damage, allergic reaction and respiratory reaction. May cause eye, skin, nose, throat and respiratory irritation. May affect the central nervous system causing dizziness, headache, or nausea. May cause skin dryness or cracking.

EFFECTS: Repeated and prolonged overexposure to solvents may lead to permanent brain and nervous system damage causing dizziness, headache, or nausea and may cause adverse liver and kidney effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. Individuals with chronic respiratory problems should neither use this product nor be exposed to its vapors or spray mist.

NOTES TO PHYSICIAN: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Symptoms of poisoning may appear several hours later.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Alcohol-resistant Foam. Do not use water, material will float and may ignite on surface of water.

FIRE FIGHTING PROCEDURES: Fight as volatile liquid fire. Wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Eliminate all sources of ignition. Evacuate unnecessary personnel. Use water spray to cool containers with caution, avoid spreading burning liquid. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

UNUSUAL FIRE AND EXPLOSION HAZARD: Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Vapors/dust may cause flash fire or explosion. This material may be ignited by heat, sparks, flame or static electricity. Closed containers may explode when exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

6. ACCIDENTAL RELEASE MEASURES

ENVIRONMENTAL PRECAUTIONS: Avoid runoff and contact with soil, drains, sewers and waterways. Contact appropriate authority if spill is in excess of reportable quantity, in compliance with local/regional/national regulations.

PERSONAL PRECAUTIONS: Eliminate all ignition sources. No smoking, do not use flares. Contact emergency personnel. Evacuate the spill area and keep unnecessary, unprotected personnel away. Do not breathe vapors, use suitable personal protective equipment. Do not touch or walk through spilled material. Prevent additional discharge of material if able to do so safely. Ventilate spill area.

METHOD OF CLEANING UP: For small spills, add absorbent, (dry sand or soil may be used in the absence of other non-combustible suitable materials), and use a non-sparking or explosion-proof means to transfer material to an appropriate container for disposal. For large spills, dike spilled material, or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal using non-sparking tools.

Dispose of spilled material and contaminated absorbent material in compliance with local and national regulations, use a licensed waste disposal contractor, see Section 13.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Use only in a well ventilated area, with appropriate personal protective equipment, (see section 8). Do not eat, drink or smoke when handling this material. Wash hands and face before eating, drinking or smoking. Do not breathe vapor, fumes or mist. Do not get in eyes, or on skin, or clothing.

Always open containers slowly to allow any excess pressure to vent. Containers should be grounded when pouring. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-proof tools and explosion proof equipment.

Read the Safety Data Sheet(s) for all components before mixing, as the mixture will have the hazards of all of its parts. Empty containers retain product residue and can be hazardous. Do not reuse container.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES: Store in accordance with local regulations. Store locked up. Keep container closed when not in use. Isolate from heat, flame, sparks, pilot lights, smoking materials and other sources of ignition. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated, explosion proof area. Protect from direct sunlight. KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES.

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

Components	CAS	Exposure Limits
ACETONE	67-64-1	ACGIH TWA 500 PPM OSHA PEL TWA 1,000 PPM
AROMATIC NAPHTHA	64742-94-5	Data not available
METHYL ISOBUTYL KETONE	108-10-1	ACGIH TWA 20 PPM OSHA PEL TWA 100 PPM
PM ACETATE	108-65-6	Data not available
TOLUENE	108-88-3	OSHA PEL TWA 200 PPM ACGIH TWA 20 PPM
VM&P NAPHTHA	64742-89-8	Data not available

ENGINEERING CONTROLS: Provide explosion proof exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

SKIN: Wear impervious gloves to prevent contact with the skin. Where contact is likely, wear chemical resistant gloves, a chemical suit, long sleeves, rubber boots, and chemical safety goggles plus a face shield.

RESPIRATORY: Wear an appropriate, properly fitted fresh-air supplied respirator, (NIOSH-approved TC-19C or equivalent), during and after application, until all organic vapors and spray mists are exhausted or any time airborne contaminate levels exceed exposure limits. Follow respirator manufacturer's directions and observe OSHA regulations for respirator use (29 cfr 1910.134).

WORK HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Clear liquid

ODOR: Typical

ODOR THRESHOLD: Not available**pH:** Not available**MELTING POINT:** Not applicable**EVAPORATION RATE:** Not available**FLAMMABILITY (Solid/Gas):** Not applicable**VAPOR PRESSURE:** Not available**VAPOR DENSITY:** Heavier than air**% SOLUBILITY IN WATER:** Not available**OCTANOL/WATER PARTITION COEFFICIENT:** Not available**AUTO-IGNITION TEMPERATURE:** Not available**DECOMPOSITION TEMPERATURE:** Not available

	14158ZP Fast (Low-temp)	14159ZP Medium (Mid-temp)	14160ZP Slow (High-temp)
BOILING POINT:	133°F	194.0 °F	243.0 °F
FLAS FLAMMABLE LIMITS:	.8 TO 13	.8 TO 8	1 TO 8
FLASH POINT - METHOD:	-4 °F TCC	40 °F TCC	61 °F TCC
DENSITY lb/gal:	7.0	7.1	7.7
SPECIFIC GRAVITY:	0.84	0.85	0.927
VOLATILE WEIGHT:	100	100	100
VOLATILE VOLUME:	100	100	100
EXEMPT V.O.C. WT %:	47.99	0.00	0.00
EXEMPT V.O.C. VOL %:	51.0	0.00	0.00
REGULATORY V.O.C. g/l:	890.61	850.06	925.26
ACTUAL V.O.C. g/l:	436.40	850.06	925.26

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Under normal conditions of storage and use, hazardous polymerization will not occur.

CONDITIONS TO AVOID: Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke, extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, tools, appliances and any other possible sources of ignition prior to spray application, during use and until all vapors are exhausted from the area.

CHEMICAL STABILITY: The product is stable. Avoid heat, open flame, sparks, static electricity, freezing.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and possible oxides of nitrogen

INCOMPATIBLE MATERIALS: Alkaline materials, strong acids and oxidizing materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Under normal conditions of use and storage, hazardous reactions will not occur.

11. TOXICOLOGICAL INFORMATION

This product has not been tested as a whole, individual component data, (where available), is listed below:

ACETONE(67-64-1)

Acute Dermal Toxicity	LD50: >7,426 mg/kg	May cause skin irritation.
Acute Inhalation Toxicity	LC50: 76.0 mg/l 4hrs (rat)	
Acute Oral Toxicity	LD50: 5,800 mg/kg (rat)	
Aspiration Toxicity	May be fatal if swallowed and enters airways	
Target Organ, Single Exposure	Central Nervous System	Category 3 May cause drowsiness or dizziness.
Eye Irritation		Category 2A Causes serious eye irritation.
Symptoms of Overexposure	Headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV may cause narcotic effects. Solvents may degrease the skin.	
Carcinogenicity Classification	No ingredient in this component is present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC, NTP or OSHA.	

PM ACETATE(108-65-6)

Acute Dermal Toxicity	LD50: >5,000 mg/kg (rabbit)	
Acute Oral Toxicity	LD50: 8,532 mg/kg (rat)	
Reproductive Toxicity	Category 1B	May damage fertility or the unborn child.

TOLUENE(108-88-3)

Acute Dermal Toxicity	LD50: >5,000 mg/kg (rabbit)	Irritating to skin.
Acute Inhalation Toxicity	LC50: 28.1mg/l 4hrs (rat)	
Acute Oral Toxicity	LD50: >5,580 mg/kg (rat)	
Aspiration Toxicity	Category 1	May be fatal if swallowed and enters airways
Target Organ, Single Exposure	Central Nervous System	Category 3 May cause drowsiness or dizziness.
Target Organ, Repeated Exposure	Auditory system, Eyes, Inhalation	Category 2 May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye Irritation	Category 2A	Causes serious eye irritation.
Skin Irritation	Category 2	Cause skin irritation.
Reproductive Toxicity	Category 2	Suspected of damaging fertility or the unborn child.

Carcinogenicity Classification	No ingredient in this component is present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC, NTP or OSHA.	
<u>VM&P NAPHTHA(64742-89-8)</u>		
Acute Dermal Toxicity	LD50: >2,000 mg/kg (rabbit)	Irritating to skin.
Acute Oral Toxicity	LD50: >5,000 mg/kg (rat)	
Aspiration Toxicity	Category 1	May be fatal if swallowed and enters airways.
Target Organ, Single Exposure	Central Nervous System	Category 3 May cause drowsiness or dizziness.
Eye Irritation	Category 2A	Causes serious eye irritation.
Skin Irritation	Category 2	Causes skin irritation.
Germ Cell Mutagenicity	Category 1B	May cause genetic defects.
Carcinogenicity Classification	IARC Group 2B	Contains ethylbenzene (CAS No. 100-41-4), which is classified as possibly carcinogenic to humans.
Symptoms of Overexposure	Headache, dizziness, tiredness, nausea and vomiting.	

<u>AROMATIC NAPHTHA(64742-94-5)</u>		
Acute Dermal Toxicity	LD50: >2,000 mg/kg (rabbit)	Irritating to skin.
Acute Inhalation Toxicity	No data available	
Acute Oral Toxicity	LD50: >5,000 mg/kg (rat)	
Aspiration Toxicity	Category 1	May be fatal if swallowed and enters airways.
Eye Irritation	Category 2A	Causes serious eye irritation.
Skin irritation	Category 2	Causes skin irritation.
Carcinogenicity Classification	IARC Group 2B	Contains Naphthalene, (CAS No. 91-20-3), which is classified as possibly carcinogenic to humans.

<u>METHYL ISOBUTYL KETONE(108-10-1)</u>		
Acute Dermal Toxicity	LD50: >2,000 mg/kg (rat)	May cause skin irritation.
Acute Inhalation Toxicity	LC50: 8.2 - 16.4 mg/l 4hrs (rat)	Category 4 Harmful if inhaled.
Acute Oral Toxicity	LD50: 2,080 mg/kg (rat)	
Target Organ, Single Exposure	Respiratory System	Category 3 May cause respiratory irritation.
Eye Irritation	Category 2A	Causes serious eye irritation. May cause irreversible eye damage.
Carcinogenicity Classification	IARC Group 2B	Possibly carcinogenic to humans.

12. ECOLOGICAL INFORMATION

This product has not been tested as a whole, individual component data, (where available), is listed below:

<u>ACETONE(67-64-1)</u>			
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 6,100 mg/l 48hrs	
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 7,630 mg/l 48hrs	
Toxicity to algae	No data available	No data available	
Persistence and degradability	Biodegradability	Readily	
Bioaccumulative potential	N/A	Negative	
<u>PM ACETATE(108-65-6)</u>			
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 100 mg/l 96hrs	
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 500 mg/l 48hrs	
Toxicity to algae	Selenastrum capricornutum (green algae)	EC50: >1,000 mg/l 96hrs	
Persistence and degradability	Biodegradability	Readily	
Bioaccumulative potential	Partition coefficient: n-octanol/water	Log Pow: 0.43	
<u>TOLUENE(108-88-3)</u>			
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 5.5 mg/l 96hrs	
Toxicity to daphnia and other aquatic invertebrate	Ceriodaphnia dubia	EC50: 3.78 mg/l 48hrs	
Toxicity to algae	Chlorella vulgaris (Fresh water algae)	EC50: 134 mg/l 3hrs	
Toxicity to bacteria	Bacteria	IC50: 84 mg/l 24hrs	
Ecotoxicology Assessment	Acute aquatic toxicity	Toxic to aquatic life	
Ecotoxicology Assessment	Chronic aquatic toxicity	Toxic to aquatic life with long lasting effects	
Persistence and degradability	Biodegradability	Readily	
Bioaccumulative potential	Partition coefficient: n-octanol/water	Log Pow: 2.73	
<u>VM&P NAPHTHA(64742-89-8)</u>			
Toxicity to fish	Oncorhynchus mykiss (rainbow trout)	LC50: 8.2 mg/l 96hrs	
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: 4.5 mg/l 48hrs	
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EC50: 3.7 96hrs	
Persistence and degradability	Biodegradability	Readily	
Bioaccumulative potential	Bioaccumulation	No data available	
<u>METHYL ISOBUTYL KETONE(108-10-1)</u>			
Toxicity to fish	Danio rerio (zebra fish)	LC50: >179 mg/l 96hrs	
Toxicity to daphnia and other aquatic invertebrate	Daphnia magna (Water flea)	EC50: >200 mg/l 48hrs	
Toxicity to algae	Pseudokirchneriella subcapitata (green algae)	EC50: 400 mg/l 96hrs	
Persistence and degradability	Biodegradability	Readily	
Bioaccumulative potential	Bioaccumulation	Bioaccumulation is unlikely	
Bioaccumulation	Partition coefficient: n-octanol/water	Pow: 24 - log Pow: Calculated 1.9	

13. DISPOSAL CONSIDERATIONS

RECOMMENDATIONS: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection, waste disposal legislation and any regional local authority requirements. Empty containers should be disposed of through an approved waste management facility. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, ensure conformity to all applicable hazardous waste regulations, consult your local or regional authorities.

14. TRANSPORT INFORMATION

UN NUMBER: UN1263

UN PROPER SHIPPING NAME: PAINT

TRANSPORT HAZARD CLASS: 3**PACKING GROUP : II**

SPECIAL PRECAUTIONS: The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the shipper and the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Local Government regulations and rules should prevail.

15. REGULATORY INFORMATION**UNITED STATES FEDERAL REGULATIONS:****OSHA:** OSHA Hazard Communication Standard 29 CFR 1910.1200

A component(s) of this product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA RQ - 40 CFR302.4 (a)****List of Hazardous Substances and Reportable Quantities (RQ)**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>RQ</u>
ACETONE	67-64-1	5,000 lbs.
TOLUENE	108-88-3	1,000 lbs.
METHYL ISOBUTYL KETONE	108-10-1	5,000 lbs.
AROMATIC NAPHTHA	64742-94-5	
Contains: Naphthalene	91-20-3	100 lbs.

SARA 313 Components - 40 CFR 372.65

This product contains the following substances subject to the reporting requirements of Section 313 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and 40 CFR 372:

<u>Chemical Name</u>	<u>CAS Number</u>
TOLUENE	108-88-3
METHYL ISOBUTYL KETONE	108-10-1
AROMATIC NAPHTHA	64742-94-5
Contains: Naphthalene	91-20-3
1,2,4-Trimethylbenzene	95-63-6

SARA Section 311/312 Hazard Category - 40 CFR 370.2

This product is considered, under applicable definitions, to meet the following categories:

(X) Fire Hazard (X) Acute Health Hazard (X) Chronic Health Hazard

STATE REGULATIONS:**California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
TOLUENE	108-88-3
VM&P NAPHTHA	64742-89-8
METHYL ISOBUTYL KETONE	108-10-1
AROMATIC NAPHTHA	64742-94-5
Contains: Naphthalene	91-20-3
1,2,4-Trimethylbenzene	95-63-6

New Jersey Right-To-Know Component Information

<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
TOLUENE	108-88-3
PM ACETATE	108-65-6
VM&P NAPHTHA	64742-89-8
METHYL ISOBUTYL KETONE	108-10-1
AROMATIC NAPHTHA	64742-94-5
Contains: Naphthalene	91-20-3
1,2,4-Trimethylbenzene	95-63-6

Pennsylvania Right-To-Know Component Information


<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
TOLUENE	108-88-3
PM ACETATE	108-65-6
VM&P NAPHTHA	64742-89-8
METHYL ISOBUTYL KETONE	108-10-1
AROMATIC NAPHTHA	64742-94-5
Contains: Naphthalene	91-20-3
1,2,4-Trimethylbenzene	95-63-6

Massachusetts Right-To-Know Component Information

<u>Chemical Name</u>	<u>CAS Number</u>
ACETONE	67-64-1
TOLUENE	108-88-3
VM&P NAPHTHA	64742-89-8
METHYL ISOBUTYL KETONE	108-10-1
AROMATIC NAPHTHA	64742-94-5
Contains: Naphthalene	91-20-3
1,2,4-Trimethylbenzene	95-63-6

16. OTHER INFORMATION

HMIS RATING	
Health:	3
Flammability:	3
Personal Hazard:	1
Personal Protection:	J

NFPA CODES

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, * = Chronic

DISCLAIMER: The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date. The Eastwood Company makes no representation, warranty or guarantee as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

DATE ISSUED: 1/25/2016
Version No.: 1415860-2