

Distributed by:


The Easthill Group Dba/The Eastwood Company 263 Shoemaker Road Pottstown,PA 19464

> USA & Canada: 800-345-1178 Outside USA: 610-323-2200

Emergengy contact: Chem-Trec: 800-424-9300

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PE	RMITTED.	IF ANY ITE	M IS	NOT APPLICABLE, TH	E SPACE MUS	T BE MARI	KED TO INDICATE THAT.	
IDENTITY	PART NO.							
(As shown on Label or package)						IF APPLICABLE		
PDS GLOSSIFIER-METALLICIZER-PEARLIZER AEROSOL								
SECTION I								
MANUFACTURER'S					EMERGENCY PHONE No.			
NAME Plasti Dip Internatio					USA only: 1-800-424-9300 INT'L: 703-527-3887			
ADDRESS (NUMBER, STREET, CITY,	STATE AN	D ZIP CODE)		REVISION#			
3920 Pheasant Ridge Drive								
n					MANUFACTURER'S PHONE			
Blaine, MN 55449					No. FOR INFORMATION 1-763-785-2156			
·					DATE MSDS WAS PREPARED November 20, 2012			
OF COVERY AND SAME AN	NITIO INTEG	DATATION	4 11 TY.	-141. YY11-1				
SECTION II - HAZARDOUS INGREDIE		RMATION.	All He	alth Hazards which com	prise 1% or gre	ater of the co	omposition and all	
carcinogens if 0.1% of the composition or		0/ 3374		CAGNO	OCITA	ACGIH	OTHER LIMITS	
HAZARDOUS COMPONENTS CHEMI		% Wt. (OPTIONA	411	CAS NO.	OSHA PEL	TLV	RECOMMEND	
IDENTITY AND COMMON NAMI	7 (9)	40 - 51	1L)	64742-89-8	300 ppm	300 ppm		
VM & P Naphtha		20 - 26		74-98-6	1000 ppm	1800 ppm	None	
Propane N Butane	,,,,,,,	10 - 16		106-97-8	800 ppm	800 ppm		
		5 - 8		78-93-3	200 ppm	200 ppm		
Methyl Ethyl Ketone		3 - 5		110-43-0	100 ppm	50 ppm	None	
Methyl Amyl Ketone		3 - 5		1330-20-7	100 ppm	100 ppm		
Xylene Ethylbenzene		1 - 3		100-41-4	100 ppm	100 ppm		
	CILADAC			100-41-4	1 100 ppin	100 ppin	Table	
SECTION III - PHYSICAL / CHEMICA			/TT 0	1)	ADDROVIM	AND MARKON	TE DED CALLON (LDC)	
BOILING	SPECIFIC	C GRAVITY		=1)	APPROXIMATE WEIGHT PER GALLON (LBS) N/A			
POINT < 0°F to 350°F	XII DOD Y	N/A			EVAPORATION RATE			
VAPOR PRESSURE		VAPOR DENSITY (AIR = 1) N/A			(BUTYL ACETATE = 1) 4.6			
5585.20 mmHg @ 20°C SOLUBILITY IN WATER					OTHER			
1 11	% VOLA	% VOLATILE				None		
Insoluble (IF ANY) None APPEARANCE								
AND ODOR Aerosol, Mild Solvent Od	or						•	
SECTION IV-FIRE AND EXPLOSION H		ΔΤΔ		1	1			
FLASH POINT	INDIXIO D	(112)	FIA	MMABLE LIMITS	LEL		UEL	
<0°F			FLA	MIMIADDE LIMITS	No Data (r	nixture)	No Data (mixture)	
EXTINGUISHING					Tio Data (I	111111111111111111111111111111111111111	110 2 414 (1111141)	
MEDIA Carbon Dioxide, Dry Chemical, or Foam								
SPECIAL FIRE								
FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.								
UNUSUAL FIRE AND This material is flammable and may be ignited by heat, sparks, flame or static electricity.								
EXPLOSION HAZARDS Level 3 aerosol (NFPA 30B). Contents under pressure if heated over 120°F aerosol can could explode, even when empty.								
HAZARDOUS PRODUCTS FORMED BY								
FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide								
EXPLOSIVE LIMITS								
(% BY VOLUME IN AIR) No Data								
SECTION V - OPTIONAL HAZARD RA	TINGS IDI	ENTIFICATION	ON					
HAZARD RATING				National Fire Protection Association (NFPA)				
4-EXTREME								
3-HIGH				FIRE 4 REACTIVITY 0.				
2-MODERATE								
1-SLIGHT				HEALTH 2 ODECTAL HAZADDO No.				
0-INSIGNIFICANT **SEE SECTION IV				HEALTH 2 SPECIAL HAZARDS None				
DEE DECTION IY								
						` `		





CTCTTCTTT DT.	ohvy rymy r i s r		DAY AMAL AND I				
SECTION VI - REA	at et al conservation that the territories are the territories and the territories are the territories and the territories are	and the second second second		, , , , , , , , , , , , , , , , , , ,			
STABILITY	UNSTA		STABLE X				
) Strong oxidizing agents				
HAZARDOUS DECOMPOSITION OR BY PRODUCTS							
Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.							
HAZARDOUS MAY OCCUR CONDITIONS TO AVOID							
POLYMERIZATION WILL NOT OCCUR X Avoid contact with heat, sparks, and open flame. Product may explode if heated.							
SECTION VII - HEA		D DAT					
ROUTES OF ENTRY	<i>?</i>	INH	ALATION? Yes SKIN? Y		ON? Yes EYES? Yes		
HEALTH	ACUTE	X	See Signs and Symptoms of Expo	osure below.			
HAZARDS	CHRONIC	X Brain and Nervous System Damage (Referred to as solvents or painters syndrome). Drying or Cracking skin.					
CARCINOGENICIT	Y: IARC 2B						
SIGNS AND					· ·		
SYMPTOMS OF					Irregular Heartbeat, Skin and Eye Irritation.		
EXPOSURE		Targe	et Organs: CNS, CVS, PNS, Liver	, Kidneys, Lungs, Re	idneys, Lungs, Respiratory System, Skin.		
1							
MEDICAL CONDIT	ONS GENER	ALLY	AGGRAVATED BY EXPOSUR	E Pre-existing Hear	t, Liver, Kidney and Lung disorders.		
EMERGENCY AND		Inges	tion: Contact Physician or Poison	Control Immediately	,		
FIRST AID		Inhal	ation: Remove to fresh air. Admir	nister Oxygen or Arti	ficial Respiration if Necessary.		
PROCEDURES		Eye (Contact: Flush with large amounts	of water. If irritation	n persists, contact Physician.		
,		Skin:	Wash with soap and water.				
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE							
	19500-1- W. doo'd discourse			Acceptable 14			
STEPS TO BE TAKE	:N	Wine	up with floor absorbent. Transfer	to hood. Prevent rur	n-off to sewers.		
IN CASE MATERIAL			inate all sources of ignition. Ventil				
RELEASED OR	2.15			<u> </u>			
SPILLED							
WASTE DISPOSAL	METHODS	Dieno	se of product in accordance with le	ocal county state an	d federal regulations		
TITION IN DIST COLLE	IL THOUS	Вюрс	do of product in accordance (inter-	,,,	- Tadorai 108		
PRECAUTIONS TO	RE	Keen	away from sparks, flame and heat	sources. Do not stor	e above 120°F		
TAKEN IN HANDLI			3 aerosol (NFPA 30B).	Dourous, Do not bro.			
AND STORAGE		LOVO	5 LEI 050. (111 11 50 2).				
ANDSTORAGE							
OTHER		Keen	Container Closed When Not In Us	e. Store this product	with adequate ventilation in cool areas. Never place		
OTHER Keep Container Closed When Not In Use. Store this product with adequate ventilation in cool areas. Never place PRECAUTIONS aerosol container in flame or fire, even when empty.							
SECTION IX - CONTROL MEASURES							
			(CDYADE) D. C		DDOTECTIVE CLOVES		
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the airborne of					PROTECTIVE GLOVES Impervious Gloves		
use a respirator with appropriate NIOSH approved cartridge or supplied air equipme				oment.			
VENTILATION	VENTILATION LOCAL EXHAUST Supplememental (if needed)			halam DET a	BI BERIE TORE		
MECHANICAL (GENERAL) To maintain exposure bel			ENERAL) To maintain exposure	below PELS	OTHER None OTHER PROTECTIVE CLOTHING OR EQUIPMENT		
EYE PROTECTION			445				
Chemical splash goggles, or approved eye protection. Chemical Apron/Eye bath/Safety Shower							
WORK HYGIENIC PRACTICES Wash thoroughly after handling.							
SECTION X - TRANSPORTATION INFORMATION (Optional)							
DOT PROPER SHIPPING NAME Aerosols			ols		DOT HAZARD CLASS 2.1		
				DOT PACKIN	DOT PACKING GROUP N/A		
DOT EXCEPTIONS Ground shipment of limited or excepted quantities of aerosols in containers of 1 quart or less may ship as CONSUMER COMMODITY, ORM-D							
Ground shipment of lin	nited or excepte	d quan	tities of aerosols in containers of 1	quart or less may shi	p as CONSUMER COMMODITY, ORM-D		
					G REQUIREMENTS OF SECTION 313 OF THE		
	INING AND C	OMM	UNITY RIGHT -TO-KNOW AC	T OF 1986, 40 CFF	R 372, (see table on page 1 for CAS # and percent by weight)		
Xylene, Ethylbenzene							
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS,					ALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS,		
OR OTHER REPRODUCTIVE HARM.							

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By:	Mark Kenow	