

*Auto Air
EW# 14762*

MATERIAL SAFETY DATA SHEET

3/14/2013

MANUFACTURER OR DISTRIBUTOR: **Color Craft, Ltd./Createx Colors**
14 Airport Park Road
East Granby, Connecticut 06026

INFORMATION TELEPHONE NUMBER:
EMERGENCY TELEPHONE NUMBER: **800-243-2712**

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: **AUTO AIR COLORS 4012 HIGH PERFORMANCE REDUCER** PRODUCT NUMBER: **4012-HPR**
PRODUCT SIZES: **2 OZ, 4 OZ, 16 OZ, & 32 OZ** BRAND NAME: **AUTO AIR COLORS 4012 HIGH PERFORMANCE REDUCER**
PRODUCT CLASS: **SOLVENTS**

SECTION II - POTENTIAL HEALTH EFFECTS

PERMISSIBLE EXPOSURE LEVEL: SEE SECTION III FOR COMPONENT PEL/TLVs
PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, EYE, SKIN

EFFECTS AND SYMPTOMS OF ACUTE EXPOSURE: EYE IRRITANT. MAY BE HARMFUL IF SWALLOWED, BY SKIN CONTACT OR BY BREATHING VAPORS.
CONTACT MAY RESULT IN REDNESS OR PAIN OF THE EYES.

EFFECTS AND SYMPTOMS OF CHRONIC EXPOSURE: EXPOSURE MAY RESULT IN FATIGUE.

CARCINOGEN LISTING: NTP: **NO** IARC: **NO** OSHA: **NO**

SEE SECTION III FOR COMPONENTS AFFECTED

MEDICAL CONDITIONS USUALLY AGGRAVATED BY OVER EXPOSURE TO THIS PRODUCT: LIVER DISEASE.

SECTION III - HAZARDOUS INGREDIENTS

<u>Ingredient</u>	<u>CAS #</u>	<u>PEL/TLV (MG/M3)</u>	<u>Max % Weight</u>	<u>NTP</u>	<u>IARC</u>
2-BUTOXY ETHANOL	111-76-2	97.00	24.75000	N	N

SECTION IV - FIRST AID

FIRST AID MEASURES: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care.

SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): N/A AUTOIGNITION TEMPERATURE: N/A
EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
UNUSUAL FIRE & EXPLOSION HAZARDS: NOT COMBUSTIBLE

SECTION VI - SPILL AND LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

SECTION VIII - EXPOSURE CONTROLS

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use only with adequate ventilation.
OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED
WORK/HYGIENE PRACTICES: Keep away from eyes.
ENGINEERING CONTROLS: KEEP OUT OF REACH OF CHILDREN.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A	MELTING POINT: N/A
VAPOR PRESSURE: N/A	
SPECIFIC VAPOR DENSITY (AIR=1): N/A	SPECIFIC GRAVITY: N/A
SOLUBILITY IN WATER: N/A	REACTIVITY IN WATER: NON-REACTIVE

SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: NONE
STABILITY: STABLE CONDITIONS TO AVOID: NONE
INCOMPATIBILITY (MATERIALS TO AVOID): NONE
HAZARDOUS DECOMPOSITION PRODUCTS: NONE

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: EYE IRRITANT. MAY BE HARMFUL IF SWALLOWED, BY SKIN CONTACT OR BY BREATHING VAPORS.
CONTACT MAY RESULT IN REDNESS OR PAIN OF THE EYES.
The summated LD50 is 4969.7 mg/kg.
This product is/is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

SECTION XII - ECOLOGICAL INFORMATION

NO HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

COMPANY: Color Craft, Ltd./Createx Colors

3/14/2013

PRODUCT: 4012-HPR

BRAND NAME: AUTO AIR COLORS 4012 HIGH PERFORMANCE REDUCER

U.S. DOT (49 CFR 172.101): THIS IS NOT A HAZARDOUS MATERIAL AS CLASSIFIED BY CFR 172.101.

SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS MSDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS

NONE

SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):

NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):

NONE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:

ETHYLENE GLYCOL MONOBUTYL ETHER

SUPPLEMENTAL STATE COMPLIANCE INFORMATION:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED IN THE STATE OF CALIFORNIA UNDER THEIR SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986 (PROPOSITION 65) AS BEING KNOWN TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM:

NONE

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) LISTED UNDER NEW JERSEY'S RIGHT TO KNOW PROGRAM:

2-BUTOXY ETHANOL

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRING NOTIFICATION TO THE STATE OF WASHINGTON UNDER THEIR CHILDREN'S SAFE PRODUCTS ACT:

NONE

SECTION XVI - OTHER INFORMATION

THIS INFORMATION SHEET IS FOR CONSUMER USE ONLY.

COMPANY: Color Craft, Ltd./Createx Colors

3/14/2013

PRODUCT: 4012-HPR

BRAND NAME: AUTO AIR COLORS 4012 HIGH PERFORMANCE REDUCER

BRAND NAMES

THIS MSDS APPLIES TO THE FOLLOWING BRAND NAMES

<u>Brand Name</u>	<u>SKU</u>
AUTO AIR COLORS 4012 HIGH PERFORMANCE REDUCER	
WICKED COLORS W500 HIGH PERFORMANCE REDUCER	

A handwritten signature in black ink, appearing to read 'Woodhall Stopford', is written over a faint, dotted background that includes the word 'DUNKER'.

Woodhall Stopford, MD, MSPH
Signed on 03/14/2013
Durham, NC

Woodhall Stopford, MD, MSPH

3/14/2013