

**IMPORTANT! READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!**

**WARNING!** This product contains isocyanates and requires the use of a respirator. Serious injury can occur without proper respiratory protection. This is a 2-Component catalyzed paint system, once activated you have 48 hours to use the entire contents of this can.

1. Shake can for at least 2 minutes. This ensures the solids are distributed evenly.
2. Remove the red button from the cap. Do NOT remove cap, keep in place.
3. Put can on hard surface such as a sturdy table, work bench or floor. Turn can up-side-down and place red button on to valve on bottom of the can. Push down on red button to pierce the inside activator chamber.
4. Shake can thoroughly for at least 2 minutes to mix the two components. Now the paint is activated.
5. Once activated, the pot life is about 48 hours; it may be a good idea to note the time the product was originally activated.
6. Apply to clean surface using side to side strokes 10 to 12 inches from the substrate. You can adjust the spray pattern by turning the nozzle in 90° increments. For best results, apply with can in vertical position.
7. This coating is a 2-Component Catalyzed System and will cure relatively fast in most conditions. Ideal application conditions are 70-85°F at 50% humidity or less.

**DANGER:** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.



**PRECAUTIONS:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands, forearms and face thoroughly after handling. Wear eye protection, face protection, protective clothing, protective gloves. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

**FIRST AID:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

**CONTENTS:** dimethyl ether 115-10-6; acetone 67-64-1; n-butyl acetate 123-86-4; titanium dioxide 13463-67-7; trizinc bis (orthophosphate) 7779-90-0; xylene 1330-20-7; hexane 1,6-diisocyanato- homopolymer 28182-81-2; methoxy-1-methylethyl acetat 108-65-6; Low boiling point naphta; Talc (Mg3H2/SiO3)4 14807-96-6; ethylbenzene 100-41-4; carbon black 1333-86-4.

**KEEP OUT OF REACH OF CHILDREN**

EPA Coating category: ABP Limit 1.55 O<sub>3</sub>/g product  
CARB aerosol Rule Coating Category (01/17) TCC PWR Limit 1.20. O<sub>3</sub>/g product



**WARNING: Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call  
Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464  
1-800-343-9353 [www.eastwood.com](http://www.eastwood.com) © Copyright 2019 Easthill Group, Inc. Made in Germany



**DO THE JOB RIGHT.™**

# 2K AEROSPRAY™ HIGH-BUILD URETHANE PRIMER – GRAY



- 2-Component Catalyzed Technology
- Most Durable Aerosol Urethane Primer Available
- Sprays Like a Paint Gun

**DANGER:**

**CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE.**  
Harmful if Swallowed. Irritating To The Skin and Eyes.  
Vapor Harmful. Read Precautions On Rear Panel Before Use.

Net wt. 13.6 oz. / 385 grams

**14794Z**